```
//Class: ActionEvent & Interface: ActionListener
import java.awt.*;
import java.awt.event.*;
class ActionEventDemo extends Frame implements ActionListener
{
      Button b1,b2;
      Label L1;
      ActionEventDemo()
      {
            FlowLayout f1=new FlowLayout();
            setLayout(f1);
            b1=new Button("OK");
            b2=new Button("CANCEL");
            L1=new Label("                                                  ");
            add(b1);
            add(b2);
            add(L1);
            b1.addActionListener(this);
            b2.addActionListener(this);
      }
      public void actionPerformed(ActionEvent ae)
      {
            //String str=ae.getActionCommand();
            //if(str.equals("OK"))
            if(ae.getSource()==b1)
            {
                  L1.setText("Ok Button pressed");
            }
            else
            {
                  L1.setText("Cancel Button pressed");
            }
      }
      public static void main(String args[])
      {
            ActionEventDemo a1=new ActionEventDemo();
            a1.setVisible(true);
            a1.setSize(500,500);
            a1.setTitle("VJTech Frame");
      }
}
```

```
//Class: ComponentEvent & Interface: ComponentListener
import java.awt.*;
import java.awt.event.*;
class ComponentDemo extends Frame implements ComponentListener
{
	ComponentDemo()
	{
		addComponentListener(this);
	}
	public void componentMoved(ComponentEvent ce)
	{
		System.out.println("Component moved...!!!");
	}
	public void componentResized(ComponentEvent ce)
	{
		System.out.println("Component resized...!!!");
	}
	public void componentShown(ComponentEvent ce)
	{
		System.out.println("Component shown...!!!");
	}
	public void componentHidden(ComponentEvent ce)
	{
		System.out.println("Component hidden...!!!");
	}
	public static void main(String args[])
	{
		ComponentDemo f1=new ComponentDemo();
		f1.setVisible(true);
		f1.setSize(500,500);
		f1.setTitle("VJTech Frame");
	}
}
```

```
//Class: ContainerEvent & Interface: ContainerListener
import java.awt.*;
import java.awt.event.*;
class ContainerEventDemo extends Frame implements ContainerListener
{
	ContainerEventDemo()
	{
		addContainerListener(this);
		setLayout(new FlowLayout());
		Button b1=new Button("OK");
		add(b1);
		remove(b1);
	}
	public void componentAdded(ContainerEvent ce)
	{
		System.out.println("Component added...!!!");
	}
	public void componentRemoved(ContainerEvent ce)
	{
		System.out.println("Component removed...!!!");
	}
	public static void main(String args[])
	{
		ContainerEventDemo f1=new ContainerEventDemo();
		f1.setVisible(true);
		f1.setSize(500,500);
		f1.setTitle("VJTech Frame");
	}
}
```

```
//Class: ItemEvent & Interface: ItemListener
import java.awt.*;
import java.awt.event.*;
class ItemEventDemo extends Frame implements ItemListener
{
      Checkbox c1;
      Label L1;
      ItemEventDemo()
      {
            FlowLayout f1=new FlowLayout();
            setLayout(f1);
            c1=new Checkbox("India");
            L1=new Label("
");
            add(c1);
            add(L1);
            c1.addItemListener(this);
      }
      public void itemStateChanged(ItemEvent ie)
      {
            L1.setText("You have selected India Checkbox");
      }
      public static void main(String args[])
      {
            ItemEventDemo f1=new ItemEventDemo();
            f1.setVisible(true);
            f1.setSize(500,500);
            f1.setTitle("VJTech Frame");
      }
}
```

```
//Class: KeyEvent & Interface: KeyListener
import java.awt.*;
import java.awt.event.*;
class KeyEventDemo extends Frame implements KeyListener
{
	KeyEventDemo()
	{
		setLayout(new FlowLayout());
		TextField tf1=new TextField(40);
		add(tf1);
		tf1.addKeyListener(this);
	}
	public void keyPressed(KeyEvent ke)
	{
		System.out.println("Key Pressed...!!!");
	}
	public void keyTyped(KeyEvent ke)
	{
		System.out.println("Key keyTyped...!!!");
	}
	public void keyReleased(KeyEvent ke)
	{
		System.out.println("Key keyReleased...!!!");
	}
	public static void main(String args[])
	{
		KeyEventDemo f1=new KeyEventDemo();
		f1.setVisible(true);
		f1.setSize(500,500);
		f1.setTitle("VJTech Frame");
	}
}
```

```
import java.awt.*;
import java.awt.event.*;
import java.applet.*;
public class LineDemo extends Applet
{
      int x1=0,y1=0;
      int flag=1;
      public void init()
      {
            addMouseListener(new InnerClicked());
            addMouseMotionListener(new InnerMoved());
      }
      class InnerClicked extends MouseAdapter
      {
            public void mouseClicked(MouseEvent me)
            {
                  if(flag==1)
                  {
                        x1=me.getX();
                        y1=me.getY();
                        flag=2;
                  }
            }
      }
      class InnerMoved extends MouseMotionAdapter
      {
            public void mouseMoved(MouseEvent me)
            {
                  int x=me.getX();
                  int y=me.getY();
                  Graphics g=getGraphics();
                  if(flag==2)
                  {
                        g.setColor(Color.red);
                        g.drawLine(x,y,x1,y1);
                        x1=x;
                        y1=y;
                  }
            }
      }
}
/*
<applet code="LineDemo.class" width="500" height="500">
</applet>
*/
```

```
//class:MouseEvent & Listener: MouseListener
import java.awt.*;
import java.awt.event.*;
class MouseEventDemo extends Frame     implements
MouseListener,MouseMotionListener
{
      MouseEventDemo()
      {
            setLayout(new FlowLayout());
            TextField tf1=new TextField(30);
            add(tf1);
            tf1.addMouseListener(this);
            tf1.addMouseMotionListener(this);
      }
      public void mouseEntered(MouseEvent me)
      {
            System.out.println("Mouse Entered Event Occurred...!!!");
      }
      public void mouseExited(MouseEvent me)
      {
            System.out.println("Mouse Exited Event Occurred...!!!");
      }
      public void mouseReleased(MouseEvent me)
      {
            System.out.println("Mouse Released Event Occurred...!!!");
      }
      public void mousePressed(MouseEvent me)
      {
            System.out.println("Mouse Pressed Event Occurred...!!!");
      }
      public void mouseClicked(MouseEvent me)
      {
            System.out.println("Mouse Clicked Event Occurred...!!!");
      }
      public void mouseDragged(MouseEvent me)
      {
            System.out.println("Mouse Dragged Event Occurred...!!!");
      }
      public void mouseMoved(MouseEvent me)
      {
            System.out.println("Mouse Moved Event Occurred...!!!");
      }
      public static void main(String args[])
      {
            MouseEventDemo m1=new MouseEventDemo();
            m1.setVisible(true);
            m1.setSize(500,500);
            m1.setTitle("VJTech Frame");
      }
}
```

```
import java.awt.*;
import java.awt.event.*;
class PasswordDemo extends Frame implements ActionListener
{
      Label L1;
      Button b1;
      TextField tf1;
      PasswordDemo()
      {
            setLayout(new FlowLayout());
            L1=new Label("Enter Password:");
            tf1=new TextField(30);
            b1=new Button("Show Password");
            tf1.setEchoChar('*');
            add(L1);
            add(tf1);
            add(b1);
            b1.addActionListener(this);
      }
      public void actionPerformed(ActionEvent ae)
      {
            String str=ae.getActionCommand();
            if(str.equals("Show Password"))
            {
                  b1.setLabel("Hide Password");
                  tf1.setEchoChar('\0');
            }
            else
            {
                  b1.setLabel("Show Password");
                  tf1.setEchoChar('*');
            }
      }
      public static void main(String args[])
      {
            PasswordDemo p1=new PasswordDemo();
            p1.setVisible(true);
            p1.setSize(500,500);
            p1.setTitle("VJTech Frame");
      }
}
```

```
import java.awt.*;
import java.awt.event.*;
class SquareCalcEventDemo extends Frame implements ActionListener,
MouseListener
{
      Label L1,L2;
      TextField tf1,tf2;
      Button b1;
      SquareCalcEventDemo()
      {
            setLayout(new FlowLayout());
            L1=new Label("Enter Number:");
            L2=new Label("Result:");
            tf1=new TextField(30);
            tf2=new TextField(30);
            b1=new Button("Calculate Square");
            add(L1);add(tf1);
            add(L2);add(tf2);
            add(b1);
            b1.addActionListener(this);
            tf1.addMouseListener(this);
            tf2.addMouseListener(this);
      }
      public void actionPerformed(ActionEvent ae)
      {
            int no=Integer.parseInt(tf1.getText());
            int result=no*no;
            tf2.setText(result+"");
      }
      public void mouseEntered(MouseEvent me)
      {
            tf1.setText(null);
            tf2.setText(null);
      }
      public void mouseExited(MouseEvent me){}
      public void mousePressed(MouseEvent me){}
      public void mouseReleased(MouseEvent me){}
      public void mouseClicked(MouseEvent me){}
      public static void main(String args[])
      {
            SquareCalcEventDemo s1=new SquareCalcEventDemo();
            s1.setVisible(true);
            s1.setTitle("VJTech Frame");
            s1.setSize(500,500);
      }
}
```

```
//class:TextEvent & Listener: TextListener
import java.awt.*;
import java.awt.event.*;
class TextEventDemo extends Frame implements TextListener
{
      Label L1;
      TextEventDemo()
      {
            setLayout(new FlowLayout());
            TextField tf1=new TextField(30);
            L1=new Label("
");
            add(tf1);
            add(L1);
            tf1.addTextListener(this);
      }
      public void textValueChanged(TextEvent te)
      {
            L1.setText("TextEvent occurred");
      }
      public static void main(String args[])
      {
            TextEventDemo m1=new TextEventDemo();
            m1.setVisible(true);
            m1.setSize(500,500);
            m1.setTitle("VJTech Frame");
      }
}
```

```
import java.awt.*;
import java.awt.event.*;
class WindowEventDemo extends Frame implements WindowListener
{
      WindowEventDemo()
      {
            addWindowListener(this);
      }
      public void windowClosing(WindowEvent we)
      {
            System.out.println("window closing");
            dispose();
      }
      public void windowClosed(WindowEvent we){
            System.out.println("window closed");
      }
      public void windowOpened(WindowEvent we){
            System.out.println("window opened");
      }
      public void windowIconified(WindowEvent we){
            System.out.println("window Iconified");
      }
      public void windowDeiconified(WindowEvent we){
            System.out.println("window Deiconified");
      }
      public void windowActivated(WindowEvent we){
            System.out.println("window Activated");
      }
      public void windowDeactivated(WindowEvent we){
            System.out.println("window Deactivated");
      }
      public void windowLostFocus(WindowEvent we){
            System.out.println("window Lost Focus");
      }
      public void windowGainFocus(WindowEvent we){
            System.out.println("window Gain Focus");
      }
      public static void main(String args[])
      {
            WindowEventDemo w1=new WindowEventDemo();
            w1.setVisible(true);
            w1.setTitle("Window Frame");
            w1.setSize(500,500);
      }
}
```