



Turnitin Originality Report

ABS by Chandni Suresh

From Paper (CSE Papers)

Processed on 11-Nov-2014 1:08 PM

SGT

ID: 476233263

Word Count: 4345

Similarity Index

5%

Similarity by Source

Internet Sources:	4%
Publications:	2%
Student Papers:	5%

sources:

1

2% match (Internet from 28-Oct-2013)

<http://www.howstuffworks.com/auto-parts/brakes/brake-types/anti-lock-brake1.htm>

2

2% match (Internet from 04-Sep-2010)

http://www.boschindia.com/content/language1/downloads/Jan_7_2010_Bosch_first_to_manufacture_ABS_in_India

3

2% match (student papers from 15-Sep-2012)

[Submitted to UNITEC Institute of Technology on 2012-09-15](#)

paper text:

Investigation on Life Rescue Technologies on road- Airbags and Anti-lock braking system (ABS) *1Janani N, *2Shriram K Vasudevan, *3Chandni Suresh, *4Srivathsan S, *5ShivaJegan RD, *6Arunagiri J *Department of Computer Science and Engineering, Amrita School of Engineering, Amrita Vishwa Vidyapeetham, India. India. E-mail: 1mailme.janani6@gmail.com, 2kv_shriram@cb.amrita.edu, 3chand.cns@gmail.com, 4vathsan1993@gmail.com, 5s.jegan@live.com, 6jarunagiri5@gmail.com. Abstract- This paper is mainly inclined towards understanding why there is a necessity for Airbags and ABS in vehicles. A survey is been presented in this paper on whether the use of airbags and ABS is beneficial to help curb road accidents. Accidents are prevailing world- wide due to the increased number of vehicles. These unexpected happenings lead to terrific consequences like causing damage to the vehicle, and the people travelling in it. Damage to the vehicle can be passed over but if a human is being killed because of an accident, then it is pathetic. Hence AIRBAGS and ABS can be implemented, so that even if a massive accident happens, the victim is left with considerable injuries rather than having his life at stake. We mainly forward through this paper, an analysis of how a human life a can be saved by implementing these technologies. The working of airbags and ABS; also how they can be more efficient is also projected in this paper. Keywords- ABS, Air Bags, Accident safety, Seatbelt. INTRODUCTION ? Why air bags? Air bags that will be folded and kept inside the vehicle at all possible places to reduce the life risk of travellers during accidents. When a massive disturbance happens around the air bags, it automatically opens up, and air gets filled in it and becomes like a pillow. It is designed in a fashion that, once when it is opened, air surrounding it will enter the bag and enlarge its size. Hence this fills in the gap between the person on the seat to the hard surface on which is he is about to hit. Provided the traveller has passed on his seat belt, then it is anticipated that he will go and fall on the air bag, which will not harm him. Assume, if there is a massive accident on the road, where two cars, having no air bags, hit each other head-on-head, then it is guaranteed that, the lives of people travelling in both the cars are under high danger. Due to this sudden jolt, the cars will try force stop because of the terrible hit. And as we know from the Newton's second law, the inertia of motion, people travelling in the car, will naturally stride front with the force with which the two cars collided. That is, people sitting inside the car will go and forcefully hit on the object that is in front of them, getting hurt badly. If there are air bags in both the cars placed at appropriate places, then, if this head-on- head collision occurs, as per inertia of motion people travelling in it will go and hit the air bags, which will get opened due to the heavy force applied around it. Once the bag is opened it will be filled by air and due to this the folded air bag will become like a pillow. All these will happen within fraction

of a second so that people sitting inside, instead of going and hitting on a solid surface, will go and rest on an air pillow which will avoid them from getting hurt badly. **MATERIALS AND METHODS ?** How airbags work? There is a crash sensor that connects the auto-mobile and the air bag. This is the most indispensable part of an air bag system, which senses or anticipates sudden crash or forced stopping or braggings of the vehicle, after a tremendous hit over an object. The most widely deployed sensor is, electro-magnetic sensors, which contains a tube or filament like feature, and to its one is a circuit, and on the rear side there will be a spherical ball like object attached with a small magnet. When a massive disturbance occurs to around this sensor, the magnet frees the ball, which travels through the tube and hits the other end, where the circuit switching happens. This signal from the circuit inflates the air bag. Usually the inflator will have a chemical set up that produces explosion of nitrogen gas which will get filled in up the air bag. This ensteering wheel scene happens with in fraction of a fraction of a second which can be approximated to 25 or 25 milliseconds. This air bags demands reasonable force to be applied upon it to get it opened. Also, air bags once opened are difficult to be refolded and replaced. Only professionals can do it properly (Marshall Brain, 2000). A driver side air bag costs between \$400-800. passenger side air bags costs around \$1000. Curtain side air bags are comparatively cheaper to the previously discussed two. An informative picture showing its components is shown in Fig (1). Fig (1) Contents and working of airbags Image Courtesy: wikipedia ? Is it a life saver or a killer? Air bags are targeted and designed to reduce the life risk of people travelling in an auto mobile. But if the traveller did not pass on his seat belts, then it is not sure that he will land on the air bag and get less hurt. If seat belts are not laid, then the traveller is expected to fall along the direction in which the car strikes the opposite object (Richard W. Kent, 2003). In this case, the air bag will further push the passenger towards some other direction. Also air bags hold very well for adults, provided that air bags are complimented with seat belts. But what if a child travels in it or a physically challenged person travels in it. One cannot fix the air bags according to their heights, because one cannot guarantee that no adult will travel in it. Also when the airbags get open at the time, when it is actually not needed, it may even kill the person sitting before because the force in which it opens will be inordinate. ? Can it be placed more efficiently? Air bags now serve only for a targeted purpose to save adults who have their seat belts on. To make it more efficient, one can try for a bigger size air bag which will rescue adult, children and pregnant women. Air bag can be placed more efficiently by anticipating a place which can predict the height of the traveller, be it a child or an adult and then accordingly open in that height so that it can actually rescue the passenger. Some people like a relaxed driving or may not be that comfortable in using a seat belt. In those cases, air bags can do an additional work that is when it opens it must surround the passenger by falling off in the rear sides. Considering a case where the vehicle somersaults and goes top down. It is obvious that in this case the travellers will go and hardly get hit on the roof of the car due to the gravity. If an airbag is placed at the top off the car, then the risk of injury can be reduced to a reasonable extent. Also the inflated roof air bag must not exceed a certain height that it can hide the mirror that helps the driver see the surrounding. Most of the accidents are caused because of the improper maintenance of the vehicle (Donald E, 2005). Small intricate details like brake oil level, brake shoes condition, wheel pressure and battery condition are not frequently checked by the user regularly. So these can be consistently monitored at regular intervals by keeping these records maintained in the cloud which may help in avoiding accidents. ? Detriments of air bags Air Bags attempt to save the life of people travelling in a four-wheeler. But it does not care or address to two-wheeler riders, since it is impossible to find a proper place to keep air bag in a two-wheeler. This is because the designer cannot guarantee saying that, in case of an accident the rider will fall only on the front, or on any particular side. Also, it must care for the person who sits in the pillion. So implementing air bag in a two-wheeler is still a night mare. Air bags once opened cannot be easily folded. It demands professional skills to fold it and replace it. Usually air bags are folded by automated machines where the folding will be so accurate and perfect so that it can open very easily in case of emergency. Air bags are expected to get into action within milliseconds when accidents happen. But if the folding is not done properly, it is of no use. The air bag will open only when the air bag is hit around its peripherals. If the vehicle is hit hard at the back, then the airbag will not open for rescue, where having it is of no use. ? Some companies like Nissan, Renault, Skoda does not mandate seat belt which may not ensure the proper working of the air bag. As airbags work well only when seat 4 belts are on. No No 0% 2,893 0 ? Since airbags cost high, people Yes No 48% 0 0 don't prefer using it. ? Adjustable steering: Now-a-days

Total lives saved 6,540 steering is adjustable in most of the vehicles, it can't cover drivers face. ? Anti Lock Braking System (ABS) In India, airbags are seen more as a luxury than as a necessity and a safety feature. Whatever the vehicle may be, be it a two But outside India, it is not so. Airbags are wheeler or a four wheeler; stopping it considered the mandatory feature that any safely is one of the most important car manufacturer is concerned about. Even functions of a motor vehicle. If it fails, for the smallest cars to the heavy vehicles, then the consequences may be damage to airbags are a must. Let's look at a survey. vehicle, personal injury or death even According to latest government data, the (Karim Nice, 2000). Hence to improve the accidents in India climbed up to 138,258 working of the brake systems, ABS was in 2012 from 84,674; about a decade back. proposed and being implemented in The executives of Nissan and Suzuki say leading automobile companies. This that not many Indians were willing to pay extra for the airbags, even if it was at most prevents a vehicle's brake from locking up necessary in a country like India. Safety and skidding during hard stops on wet icy standards in India are around 10 years out roads. dated from the western countries and, since most of the accidents happen by ? What is ABS? vehicles colliding with each other, airbags An antilock brake system (ABS) is a can save many lives. Table 1 shows a secure and an effective braking system. survey of accidents that happened, and the number of lives saved due to the use of ABS allows the driver to maintain Airbags and seatbelts. directional stability, control over steering capability and in some situations, to reduce Table 1 National Centre for Statistics stopping distances during emergency and Analysis NHTSA, Survey of 2000 braking situation, mainly on wet and shows that, slippery road surface (Dr. Nader Sadegh, 2005). ABS has become as important as a Belt Air Effectiven Fataliti Live Use Bag ess Of es s seatbelt or an airbag these days, and if the d in Restrained save driver usually likes to takes risks by Vehic Use d by performing dangerous driving stunts or le belts rather, is unaware of the braking system and which is purely more than just stomping air on the brake pedal, then ABS is worth bags Yes Yes 53.72% 3,565 4,13 every penny spent on. Fig (2) shows the 8 symbol of ABS. No Yes 14% 3,364 548 Yes Yes 48% 0 0 No Yes 0% 1 0 Yes No 48% 2,008 185 ? Four-channel, four-sensor ABS ? Three-channel, four-sensor ABS ? Three-channel, three-sensor ABS ? Two-channel, four sensor ABS ? One-channel, one-sensor ABS Fig (2) Symbol of ABS Following, let's see a survey in Table 2, based on Indian road traffic which shows the count of accidents that have occurred without the use of ABS. Table 2 A Survey on number of accidents in the absence of ABS. Population Accidents caused by Dense Cities not using ABS Lucknow 600 last year Delhi 2110 last year Kolkata 7290 (2013 – 2014 till date) Chennai 9663 last year Mumbai 25000 (2012 JAN-2014 JAN) Amritsar 6513 last year Trivandrum 5657 last year Cherapunjee 400-600 st year ? ABS – More technical approach As you have already had an introduction to what an ABS system is, let's closer look at it; technically. Types of breaks: Anti-lock braking systems use different ways depending on the type of brakes. They can be differentiated by the number of channels and that are individually controlled and the number of speed sensors ? Components of ABS: SPEED SENSOR: A speed sensor's role is to determine the acceleration or deceleration of the wheel. These sensors use a magnet and a coil of wire to generate a signal. The rotation of the wheel induces a magnetic field around the sensor. The fluctuations of this magnetic field generate a voltage in the sensor. Since the voltage induced in the sensor is a result of the rotating wheel, this sensor can become incorrect at slower speeds. The slower rotations of the wheel causes incorrect fluctuations in the magnetic field and thus present with incorrect readings to the controller.

1 Valves: There is a valve in the brake line of each brake controlled by the ABS. On some systems, the valve has three positions: • In position one, the valve is open; pressure from the master cylinder is passed right through in to the brake. • In position two, the valve blocks the line, isolating that brake from the master cylinder. This prevents the pressure from rising further; should the driver push the brake pedal harder. • In position three, the valve releases some of the pressure from the brakes. The

majority of problems with the valve system occur; when they get clogged. When a valve is clogged, it is

unable to open, close, or change position. An inoperable valve will prevent the system from modulating the valves and controlling pressure supplied to the brakes. Pump The pump in the ABS is used to restore the pressure to the hydraulic brakes after the valves have released it. A signal from the controller will discharge the valve at the detection of a wheel slip. After a valve release the pressure supplied from the user, the pump is used to restore a desired amount of pressure to the braking system. The controller will adjust the pumps status in order to provide the preferred quantity of strain and trim down slipping.

Controller: The controller is an ECU (Engine Control Unit) type unit in the car which receives information from each individual wheel speed sensor, in turn if a wheel loses traction the signal is sent to the controller, the controller will then limit the brake force (EBD) and activate the ABS modulator which actuates the braking valves on and off. Working of ABS Without using an ABS what happens is that when you are travelling at say 80km/hr, you will keep moving in that pace, unless you interrupt and brake. So when you try to brake quickly, you are putting so much pressure on the brakes, which forces your steering wheel to decelerate from 80km/hr to 0km/hr. This has to happen instantaneously and so it is very hard to make the steering wheels stop at such a fast rate (Ken Gilbert, 2003). Naturally due to the pressure applied on the brakes, and the less friction on the road it is travelling, the steering wheel gets locked. It becomes difficult for the steering wheel to take control of its motion and changing its trajectory. When such a situation arises steering control gets lost and cars can only be stopped after driving for longer distances. While using an ABS in the vehicle, the speed sensors on the steering wheels realize that we are decelerating from 80km/hr to 0km/hr. Braking at this limit is called "threshold braking", (Kalton C. Lahue, 2012) and is the fastest and safest way to stop a car. When it senses that action, it will try to reduce the pressure on the brake pad so that once again the steering wheels can accelerate to a moderate level, and stay in motion. This pressure is released by the Hydraulic Control Unit. If the steering wheels are on the verge of getting locked, the process repeats and the pressure is adjusted. This pressure maintenance is often experienced like pulsing or jerking of the vehicle; where we feel we are losing grip on the steering wheels, but nothing actually happens as such. ABS takes control and allows the steering wheels to constantly rotate. This makes it comfortable for the driver to stop at a safe distance, maneuver the track or miss an obstacle coming on the way. Below from Fig (3) you can relate on how ABS is used in the car. Fig (3) Situation clearly describing motion of car with and without ABS. Internal Description – detailed working of the system Now coming to the more detailed description on how ABS works internally in the car. The major components are brake pedal, master cylinder, wheel speed sensors, Electronic Control Unit (ECU) and Hydraulic control unit (AA Aly, 2012). The wheel speed sensor consists of a rotor that rotates when the wheel turns. As the wheel turns, the rotation induces a voltage to the sensor which is picked up and sent to the ECU. As and when the driver wishes to apply brakes, the rotation of the wheel is no longer in its normal pattern and it changes. This change is notified to the ECU again. The important part is that, in case the ECU feels the wheels might lock while applying brakes, it sends a quick message to the hydraulic control unit (Fletcher, 2011). In a three-tier channel system, the hydraulic unit controls the braking system using three solenoid valves. The valves are in sync with brake master cylinder, hence preventing. Each of them operates on each front wheels and one of them operates for the rear wheels. During the start of the journey, the ABS assures itself in working mode. When the journey starts it will be working, else a signal is given to the driver. For now, if we see the braking systems in foreign cars like Toyota, Mitsubishi, Nissan etc., the braking system along with ABS, comprises of EBD (Electronic Brake force Distribution), Emergency Brake Assist and Electronic Stability Control. The major usage of this system being that, it can help curb a whole lot of accidents by increasing the rear braking force either with full or low load and provide vehicle balance torque. If we take a look at its implementation in India, without specifying "Bosch" we cannot advance this survey. Bosch is a German multinational engineering and Electronics Company, which is

2the world's leading supplier of automotive technology.

It

2is the first company to manufacture antilock braking systems in

Indian vehicles. It

2has established a new manufacturing facility for its ABS antilock braking system at the Chakan plant in Pune, Maharashtra, India.

Bosch is the only automotive supplier to manufacture ABS in India for passenger cars and light commercial vehicles. ? Why the need for an ABS system? Consider a situation, suppose in the highway, there might be an instance when people suddenly tempt to cross the road without prior notice to the incoming vehicles. That time when the driver tries to brake, he uses so much force on the wheels and the wheels will get locked up. This results in either skidding of the vehicle or inability for the driver to take control of the vehicle's course. Here is where ABS helps. The braking system provides the correct force needed to control the vehicle by preventing the wheel to lock itself. ABS is a new age braking system for better road safety. So by using such a system, a lot many accidents can be avoided. All we have to do is, when a situation arrives to quickly brake, just keep on pressing on the brakes firmly without releasing and steer away from the obstacle. Also remember to maintain a moderate distance from the car in the front, as braking is an involuntary action A point to be noted is that, in a

2survey of 594 car owners in Delhi, Mumbai, Bangalore, Chennai, Hyderabad, and Kolkata

2considered ABS more important than the airbag, and second only to the seatbelt. While the awareness of Indian motorists is high, today's availability of ABS in the market is limited. ? Current situation India

currently has one of the worst road accident rates worldwide. Government statistics show that 1.35 lakh people died in 2010 in road accidents across India, which increased to 1.42 lakh in 2011. Around 31% of the incidents involve commercial vehicles like trucks, buses and tractors. To install this ABS package, cost is expected to vary between 20,000 and 50,000 depending on the size and class of commercial vehicle. Once mandated by the roads ministry, it would be an effective mechanism to improve passenger safety. We can assure this by the fact that; majority of heavy buses sold in India would be now installed with this system. Nearly 45,000 passenger buses and 1.6 lakh trucks would be covered by the new provision in the Indian market, where around three lakh units. RESULTS AND DISCUSSION ? Advantages of ABS The main benefits of an anti-lock brake system (ABS) are: • Stops on ice flooring. ABS prevents lock-ups and skidding, even in slippery conditions. Anti-lock brakes have been proven to save lives in some situation. • Insurance cost is low. Since it is carefully tested safety device with a track record of success, insurers give clients specific discounts for having an ABS system on their vehicle. • Resale value is higher. As a feature on a car or truck, an ABS can raise the market value of the vehicle. Where ever ABS technology has become usual on many vehicles, it could result in a lower price for resale. • Grip control. ABS shares some of the infrastructure of a grip control systems, new technology helps to ensure that each wheel has grip on the road. That makes it easy for manufacturers to install both of these features at the factory. • ABS works well with alloy wheel. ? Disadvantages of ABS

3Anti-lock brakes have are proven to be a reliable safety feature in most situations, and insurers consider them to substantially considerably lower risk for

a vehicle. However, **not all drivers are sold on this option for a car or truck.** Here are some **of the**

downward that driver find in this kind of brake system. • Unpredictable stop times. Anti- lock brakes are made to provide for fine or good braking in slippery conditions. Some drivers report that they find stopping distances for regular conditions are lengthened by their ABS, because there may be errors in the system, or because of noise of the ABS may contribute to the driver not braking at the same rate. • Maintenance cost. An ABS can be expensive to maintain. Expensive sensors on each wheel can cost hundreds of dollars. To fix if they get out of collaboration or accident or it can develop other problems. This is a big reason to reject an ABS in a vehicle. •

3Delicate systems. It's easy to cause a problem in an ABS by messing around with **the brakes. Problems include** confusion **of the ABS, where a compensating brake sensor causes the vehicle to shudder, make loud** noise **or generally brake worse.**

? Advantages of airbags The benefit of airbags are various. Under here are some of it. ? Air bags are created for injury reduction for body, particularly the torso (Rhett Allain, 2012). ? Designed with convenience for the passenger, a feel that it is invisible but is rightfully present to protect the passenger. ? Insurance is lower for cars with airbags. Disadvantages of airbags ? Air bags may be helpful and protective; but in some situations it could be injurious also. ? It could deploy very strongly and may hit small passengers like children. It can hurt their chest. ? Adults can sit atleast 10 to 12 inches away from airbags; by using seatbelts it can curb the potential damage that can occur due to air bags. CONCLUSION ABS ensures that the minimum stopping distance is achieved, and it is still important to drive at a safe speed for the conditions and leave a gap of at least 2 seconds between yourself and the vehicle in front in order to reduce the chances of needing to make use of the ABS. Wherein, air bags comes to the rescue after an accident occurs. It saves the lives of the passengers by providing an air pillow like object between the hard surface and the traveler. Both these techniques provide low risk on road. REFERENCES AA Aly, 2012 (ABS) Control - Scientific Research Publishing. www.scirp.org/journal/PaperDownload.aspx?paperID=6667 Fletcher, 2011 ABS Control System.doc - 123SeminarsOnly. 123seminarsonly.com/Seminar-Reports/043/43496215-ABS-Control.doc Kalton C. Lahue, 2012 Automotive Brakes and Antilock Braking Systems. Ken Gilbert, 2003 Anti-lock Brake System (ABS). Karim Nice, 2000 How Anti-Lock Brakes Work. <http://auto.howstuffworks.com/auto-parts/brakes/brake-types/anti-lock-brake.htm> Donald E, 2005 Struble Advances in Side Airbag Systems. Rhett Allain, 2012 What Happens When You Put a Book on an Air Bag? <http://www.wired.com/2012/01/what-happens-when-you-put-a-book-on-an-airbag/> Richard W. Kent, 2003 Air Bag Development and Performance. <http://books.sae.org/pt-88/> Marshall Brain, 2000 How Airbags Work. <http://auto.howstuffworks.com/car-driving-safety/safety-regulatory-devices/airbag.htm> Dr. Nader Sadegh, 2005 ABS Braking Systems Georgia Institute of Technology George W. Woodruff School of Technology. Shivajegan RD, et al, 2014 Cloud Computing: A Technical Gawk, International Journal of Applied Engineering Research. ISSN 0973-4562 Volume (Number 14(2014)) pp.2539-2554. Acknowledgements We thank the Computer Science Department of Amrita School Of Engineering, Amrita Vishwa Vidyapeetham for providing us with immense support, motivation and suggestions during the making of this paper. We also want to thank our friends, who encouraged us to go ahead with this idea. Without them, this process would have been very monotonous.