

# GreenLeaf SunMax 400 Solar Panel - Product Guide

GreenLeaf Energy manufactures the SunMax 400, a residential solar panel built around monocrystalline silicon cells.

The SunMax 400 has a rated power output of 400 watts and a module efficiency of 21.5 percent.

Each panel weighs 21 kilograms and measures 1.7 meters by 1.0 meters.

The SunMax 400 operates reliably across a temperature range of minus 40 degrees Celsius to 85 degrees Celsius.

GreenLeaf backs the SunMax 400 with a 25 year performance warranty.

The panel is designed to pair directly with the GreenLeaf PowerCell 10 home battery for whole-home backup.

Mechanical mounting uses a standard 35 millimetre frame with four grounding points. The junction box is IP68 rated and the cable leads are 1.2 metres of 4 millimetre-squared PV wire with MC4 connectors. Bypass diodes protect the module under partial shade.

Certified to IEC 61215 and IEC 61730. The nameplate lists a maximum system voltage of 1000 volts DC. Do not confuse this 400 watt module with the lower-output SunMax 370, which has a shorter warranty and a different cell architecture; the two SKUs are not interchangeable for array stringing without a redesign of the inverter setpoints.

Recommended array tilt follows local latitude. Annual degradation is specified at 0.45 percent per year after the first year. Shipping pallets hold 30 modules. Installers must torque rail clamps to 16 newton-metres and observe the fire classification on the label.