

 Home  Java  Programs  OOps  String Exception  Multithreading

 [SCROLL TO TOP](#)

Java Lambda Expressions

Lambda expression is a new and important feature of Java which was included in Java SE 8. It provides a clear and concise way to represent one method interface using an expression. It is very useful in collection library. It helps to iterate, filter and extract data from collection.

The Lambda expression is used to provide the implementation of an interface which has functional interface. It saves a lot of code. In case of lambda expression, we don't need to define the method again for providing the implementation. Here, we just write the implementation code.

Java lambda expression is treated as a function, so compiler does not create .class file.

Functional Interface

Lambda expression provides implementation of *functional interface*. An interface which has only one abstract method is called functional interface. Java provides an annotation `@FunctionalInterface`, which is used to declare an interface as functional interface.

Why use Lambda Expression

1. To provide the implementation of Functional interface.
2. Less coding.

Java Lambda Expression Syntax

↑ SCROLL TO TOP

{body}

Java lambda expression is consisted of three components.

- 1) Argument-list:** It can be empty or non-empty as well.
- 2) Arrow-token:** It is used to link arguments-list and body of expression.
- 3) Body:** It contains expressions and statements for lambda expression.

No Parameter Syntax

```
() -> {  
    //Body of no parameter lambda  
}
```

One Parameter Syntax

```
(p1) -> {  
    //Body of single parameter lambda  
}
```

Two Parameter Syntax

```
(p1,p2) -> {  
    //Body of multiple parameter lambda  
}
```

Let's see a scenario where we are not implementing Java lambda expression. Here, we are implementing an interface without using lambda expression.

Without Lambda Expression

```
interface Drawable{
    public void draw();
}

public class LambdaExpressionExample {
    public static void main(String[] args) {
        int width=10;

        //without lambda, Drawable implementation using anonymous class
        Drawable d=new Drawable(){
            public void draw(){System.out.println("Drawing "+width);}
        };
        d.draw();
    }
}
```

Test it Now

Output:

```
Drawing 10
```

Java Lambda Expression Example

Now, we are going to implement the above example with the help of Java lambda expression.

```
@FunctionalInterface //It is optional
interface Drawable{
    public void draw();
}

public class LambdaExpressionExample2 {
    public static void main(String[] args) {
```

↑ SCROLL TO TOP

```
//with lambda
Drawable d2=()->{
    System.out.println("Drawing "+width);
};
d2.draw();
}
```

Test it Now

Output:

```
Drawing 10
```

A lambda expression can have zero or any number of arguments. Let's see the examples:

Java Lambda Expression Example: No Parameter

```
interface Sayable{
    public String say();
}

public class LambdaExpressionExample3{
    public static void main(String[] args) {
        Sayable s=()->{
            return "I have nothing to say.";
        };
        System.out.println(s.say());
    }
}
```

Test it Now

Output:

↑ SCROLL TO TOP

I have nothing to say.

Java Lambda Expression Example: Single Parameter

```
interface Sayable{
    public String say(String name);
}

public class LambdaExpressionExample4{
    public static void main(String[] args) {

        // Lambda expression with single parameter.
        Sayable s1=(name)->{
            return "Hello, "+name;
        };
        System.out.println(s1.say("Sonoo"));

        // You can omit function parentheses
        Sayable s2= name ->{
            return "Hello, "+name;
        };
        System.out.println(s2.say("Sonoo"));
    }
}
```

Test it Now

Output:

```
Hello, Sonoo
Hello, Sonoo
```

Java Lambda Expression Example: Multiple Parameters

↑ SCROLL TO TOP

```
interface Addable{  
    int add(int a,int b);  
}  
  
public class LambdaExpressionExample5{  
    public static void main(String[] args) {  
  
        // Multiple parameters in lambda expression  
        Addable ad1=(a,b)->(a+b);  
        System.out.println(ad1.add(10,20));  
  
        // Multiple parameters with data type in lambda expression  
        Addable ad2=(int a,int b)->(a+b);  
        System.out.println(ad2.add(100,200));  
    }  
}
```

Test it Now

Output:

```
30  
300
```

Java Lambda Expression Example: with or without return keyword

In Java lambda expression, if there is only one statement, you may or may not use return keyword. You must use return keyword when lambda expression contains multiple statements.

```
}

public class LambdaExpressionExample6 {
    public static void main(String[] args) {

        // Lambda expression without return keyword.
        Addable ad1=(a,b)->(a+b);
        System.out.println(ad1.add(10,20));

        // Lambda expression with return keyword.
        Addable ad2=(int a,int b)->{
            return (a+b);
        };
        System.out.println(ad2.add(100,200));
    }
}
```

Test it Now

Output:

```
30
300
```

Java Lambda Expression Example: Foreach Loop

```
import java.util.*;

public class LambdaExpressionExample7{
    public static void main(String[] args) {

        List<String> list=new ArrayList<String>();
        list.add("ankit");
        list.add("mayank");
        // ...
    }
}
```

↑ SCROLL TO TOP


```
list.forEach(  
    (n)->System.out.println(n)  
);  
}  
}
```

Test it Now

Output:

```
ankit  
mayank  
irfan  
jai
```

Java Lambda Expression Example: Multiple Statements

```
@FunctionalInterface  
interface Sayable{  
    String say(String message);  
}  
  
public class LambdaExpressionExample8{  
    public static void main(String[] args) {  
  
        // You can pass multiple statements in lambda expression  
        Sayable person = (message)-> {  
            String str1 = "I would like to say, ";  
            String str2 = str1 + message;  
            return str2;  
        };  
        System.out.println(person.say("time is precious."));  
    }  
}
```

↑ SCROLL TO TOP

Test it Now

Output:

```
I would like to say, time is precious.
```

Java Lambda Expression Example: Creating Thread

You can use lambda expression to run thread. In the following example, we are implementing run method by using lambda expression.

```
public class LambdaExpressionExample9{
    public static void main(String[] args) {

        //Thread Example without lambda
        Runnable r1=new Runnable(){
            public void run(){
                System.out.println("Thread1 is running...");
            }
        };
        Thread t1=new Thread(r1);
        t1.start();

        //Thread Example with lambda
        Runnable r2=()->{
            System.out.println("Thread2 is running...");
        };
        Thread t2=new Thread(r2);
        t2.start();
    }
}
```

Test it Now

Output:

↑ SCROLL TO TOP

```
Thread1 is running...  
Thread2 is running...
```

Java lambda expression can be used in the collection framework. It provides efficient and concise way to iterate, filter and fetch data. Following are some lambda and collection examples provided.

Java Lambda Expression Example: Comparator

```
import java.util.ArrayList;  
import java.util.Collections;  
import java.util.List;  
class Product{  
    int id;  
    String name;  
    float price;  
    public Product(int id, String name, float price) {  
        super();  
        this.id = id;  
        this.name = name;  
        this.price = price;  
    }  
}  
  
public class LambdaExpressionExample10{  
    public static void main(String[] args) {  
        List<Product> list=new ArrayList<Product>();  
  
        //Adding Products  
        list.add(new Product(1,"HP Laptop",25000f));  
        list.add(new Product(3,"Keyboard",300f));  
        list.add(new Product(2,"Dell Mouse",150f));
```

↑ SCROLL TO TOP `rtln("Sorting on the basis of name...");`

```
// implementing lambda expression
Collections.sort(list,(p1,p2)->{
    return p1.name.compareTo(p2.name);
});
for(Product p:list){
    System.out.println(p.id+" "+p.name+" "+p.price);
}

}
```

Test it Now

Output:

```
Sorting on the basis of name...
2 Dell Mouse 150.0
1 HP Laptop 25000.0
3 Keyboard 300.0
```

Java Lambda Expression Example: Filter Collection Data

```
import java.util.ArrayList;
import java.util.List;
import java.util.stream.Stream;
class Product{
    int id;
    String name;
    float price;
    public Product(int id, String name, float price) {
        super();
        this.id = id;
        this.name = name;
        this.price = price;
    }
}
```

↑ SCROLL TO TOP

```

    }
}

public class LambdaExpressionExample11{
    public static void main(String[] args) {
        List<Product> list=new ArrayList<Product>();
        list.add(new Product(1,"Samsung A5",17000f));
        list.add(new Product(3,"Iphone 6S",65000f));
        list.add(new Product(2,"Sony Xperia",25000f));
        list.add(new Product(4,"Nokia Lumia",15000f));
        list.add(new Product(5,"Redmi4 ",26000f));
        list.add(new Product(6,"Lenevo Vibe",19000f));

        // using lambda to filter data
        Stream<Product> filtered_data = list.stream().filter(p -> p.price > 20000);

        // using lambda to iterate through collection
        filtered_data.forEach(
            product -> System.out.println(product.name+": "+product.price)
        );
    }
}

```

Test it Now

Output:

```

Iphone 6S: 65000.0
Sony Xperia: 25000.0
Redmi4 : 26000.0

```

Java Lambda Expression Example: Event Listener

```

import javax.swing.JButton;
import javax.swing.JFrame;
import javax.swing.JTextField;

```

↑ SCROLL TO TOP

```
public class LambdaEventListenerExample {  
    public static void main(String[] args) {  
        JTextField tf=new JTextField();  
        tf.setBounds(50, 50,150,20);  
        JButton b=new JButton("click");  
        b.setBounds(80,100,70,30);  
  
        // lambda expression implementing here.  
        b.addActionListener(e-> {tf.setText("hello swing");});  
  
        JFrame f=new JFrame();  
        f.add(tf);f.add(b);  
        f.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);  
        f.setLayout(null);  
        f.setSize(300, 200);  
        f.setVisible(true);  
    }  
}
```

Output:

[< Prev](#)[Next >](#)

 [For Videos Join Our Youtube Channel: Join Now](#)

Feedback

- Send your Feedback to feedback@javatpoint.com


Help Others, Please Share




[↑ SCROLL TO TOP](#)





Learn Latest Tutorials


 Splunk tutorial
Splunk


 SPSS tutorial
SPSS

 Swagger
tutorial
Swagger

 T-SQL tutorial
Transact-SQL


 Tumblr tutorial
Tumblr

 React tutorial
ReactJS

 Regex tutorial
Regex

 Reinforcement
learning tutorial
Reinforcement
Learning


 R Programming
tutorial
R Programming

 RxJS tutorial
RxJS

 React Native
tutorial
React Native

 Python Design
Patterns
Python Design
Patterns

 Python Pillow
tutorial
Python Pillow

 Python Turtle
tutorial
Python Turtle

 Keras tutorial
Keras

↑ SCROLL TO TOP

Preparation



Aptitude



Logical
Reasoning
Reasoning



Verbal Ability
Verbal Ability



Interview
Questions
Interview Questions



Company
Interview
Questions
Company Questions

Trending Technologies



Artificial
Intelligence
Tutorial
Artificial
Intelligence



AWS Tutorial
AWS



Selenium
tutorial
Selenium



Cloud
Computing
tutorial
Cloud Computing



Hadoop tutorial
Hadoop



ReactJS
Tutorial
ReactJS



Data Science
Tutorial
Data Science



Angular 7
Tutorial
Angular 7



Blockchain
Tutorial
Blockchain



Git Tutorial
Git




Machine
Learning Tutorial
Machine Learning





DevOps
Tutorial
DevOps


B.Tech / MCA

 DBMS tutorial
DBMS


 Data Structures
tutorial
Data Structures


 DAA tutorial
DAA

 Operating
System tutorial
Operating System


 Computer
Network tutorial
Computer Network

 Compiler
Design tutorial
Compiler Design


 Computer
Organization and
Architecture
Computer
Organization

 Discrete
Mathematics
Tutorial
Discrete
Mathematics

 Ethical Hacking
Tutorial
Ethical Hacking


 Computer
Graphics Tutorial
Computer Graphics


 Software
Engineering
Tutorial
Software
Engineering


 html tutorial
Web Technology


 Cyber Security
tutorial
Cyber Security


 Automata
Tutorial
Automata


 C Language
tutorial
C Programming

 C++ tutorial
C++

 Java tutorial
Java

 .Net
Framework
tutorial
.Net

 Python tutorial
Python

 List of
Programs
Programs

↑ SCROLL TO TOP



Control
Systems tutorial

Control System



Data Mining
Tutorial

Data Mining



Data
Warehouse
Tutorial

Data Warehouse

↑ SCROLL TO TOP