

# Uninformed Search I

---

*PROF. LIM KWAN HUI*

50.021 Artificial Intelligence

*The following notes are compiled from various sources such as textbooks, lecture materials, Web resources and are shared for academic purposes only, intended for use by students registered for a specific course. In the interest of brevity, every source is not cited. The compiler of these notes gratefully acknowledges all such sources.*



# Outline & Objectives

---

- Learn about five different uninformed search algorithms
  - Breadth-First Search
  - Uniform-cost search
  - Depth-First Search
  - Depth-limited search
  - Iterative deepening search
- Understand the trade-offs in properties between these algorithms
- Being able to use these algorithms to solve a search problem



# Recap: Types of Search

---

- Uninformed Search
  - No additional information about states beyond that in the problem definition (AKA blind search)
- Informed Search
  - Uses problem-specific knowledge beyond the definition of the problem itself
- Adversarial Search
  - Used in multi-agent environment where the agent needs to consider the actions of other agents and how they affect its own performance.



# Recap: Search Strategies

- The **Expand** function **creates new nodes** (and their various fields)
  - using the Actions and Transition Model to create the corresponding states
- A **search strategy** is defined by picking the *order of node expansion*

**Expand step:**  
**Determines**  
**our search**  
**strategy**

```
function TREE-SEARCH(problem) returns a solution, or failure
  initialize the frontier using the initial state of problem
  loop do
    if the frontier is empty then return failure
    choose a leaf node and remove it from the frontier
    if the node contains a goal state then return the corresponding solution
    expand the chosen node, adding the resulting nodes to the frontier
```



# Recap: Search Strategies


---


- Strategies are evaluated along the following dimensions:
  - **Completeness** - does it always find a solution if one exists?
  - **Optimality** - does it always find a least-cost solution?
  - **Time complexity** - number of nodes generated/expanded
  - **Space complexity** - maximum number of nodes in memory



# Recap: Search Strategies

- Time and space complexity are measured in terms of
  - $b$  - maximum branching factor of the search tree
  - $d$  - depth of the least-cost solution
  - $m$  - maximum depth of the state space (may be infinite)



 Least-cost solution



# Recap: Graph vs Tree Search

**function** TREE-SEARCH(*problem*) **returns** a solution, or failure

initialize the frontier using the initial state of *problem*

**loop do**

if the frontier is empty **then return** failure

choose a leaf node and remove it from the frontier

if the node contains a goal state **then return** the corresponding solution

expand the chosen node, adding the resulting nodes to the frontier

---

**function** GRAPH-SEARCH(*problem*) **returns** a solution, or failure

initialize the frontier using the initial state of *problem*

*initialize the explored set to be empty*

**loop do**

if the frontier is empty **then return** failure

choose a leaf node and remove it from the frontier

if the node contains a goal state **then return** the corresponding solution

*add the node to the explored set*

expand the chosen node, adding the resulting nodes to the frontier

*only if not in the frontier or explored set*



# Types of Uninformed Search

---

- Breadth-First Search
- Uniform-cost search
- Depth-First Search
- Depth-limited search
- Iterative deepening search





# Search Strategies

- A **search strategy** is defined by picking the *order of node expansion*
- How do we implement this?

**Expand step:**  
**Determines**  
**our search**  
**strategy**

```
function GRAPH-SEARCH(problem) returns a solution, or failure
  initialize the frontier using the initial state of problem
  initialize the explored set to be empty
  loop do
    if the frontier is empty then return failure
    choose a leaf node and remove it from the frontier
    if the node contains a goal state then return the corresponding solution
    add the node to the explored set
    expand the chosen node, adding the resulting nodes to the frontier
    only if not in the frontier or explored set
```



# Search Strategies

- A **search strategy** is defined by picking the *order of node expansion*
- How do we implement this?
  - Using different types of queue structures to represent the frontier

**Expand step:**  
**Determines**  
**our search**  
**strategy**

```
function GRAPH-SEARCH(problem) returns a solution, or failure
  initialize the frontier using the initial state of problem
  initialize the explored set to be empty
  loop do
    if the frontier is empty then return failure
    choose a leaf node and remove it from the frontier
    if the node contains a goal state then return the corresponding solution
    add the node to the explored set
    expand the chosen node, adding the resulting nodes to the frontier
    only if not in the frontier or explored set
```



# Search Strategies

- A **search strategy** is defined by picking the *order of node expansion*
- How do we implement this?
  - Using different types of queue structures to represent the frontier
  - *Order of node expansion = Adding/removal sequence in queue*

**Expand step:**  
**Determines**  
**our search**  
**strategy**


```
function GRAPH-SEARCH(problem) returns a solution, or failure
  initialize the frontier using the initial state of problem
  initialize the explored set to be empty
  loop do
    if the frontier is empty then return failure
    choose a leaf node and remove it from the frontier
    if the node contains a goal state then return the corresponding solution
    add the node to the explored set
    expand the chosen node, adding the resulting nodes to the frontier
    only if not in the frontier or explored set
```



# Breadth-First Search

---

- General idea: Expand the *shallowest* unexpanded node
- Implementation: Using a *First-In First-Out (FIFO)* queue




# Breadth-First Search

- General idea: Expand the *shallowest* unexpanded node
- Implementation: Using a *First-In First-Out (FIFO)* queue

*Initialize frontier*

*Queue:*




# Breadth-First Search

- General idea: Expand the *shallowest* unexpanded node
- Implementation: Using a *First-In First-Out (FIFO)* queue

***Check node for goal state***


Queue:  $\emptyset$



# Breadth-First Search

- General idea: Expand the *shallowest* unexpanded node
- Implementation: Using a *First-In First-Out (FIFO)* queue


***Not goal? Expand nodes based on strategy***



# Breadth-First Search

- General idea: Expand the *shallowest* unexpanded node
- Implementation: Using a *First-In First-Out (FIFO)* queue

**Check next node  
for goal state**






# Breadth-First Search

- General idea: Expand the *shallowest* unexpanded node
- Implementation: Using a *First-In First-Out (FIFO)* queue


**Not goal again?  
Continue  
expanding nodes**



# Breadth-First Search

- General idea: Expand the *shallowest* unexpanded node
- Implementation: Using a *First-In First-Out (FIFO)* queue

**Check next node  
(again!) for goal  
state**




Queue: ~~a~~, ~~ab~~, ~~ac~~, abd, abe



# Breadth-First Search

- General idea: Expand the *shallowest* unexpanded node
- Implementation: Using a *First-In First-Out (FIFO)* queue


**Check next node  
(again!) for goal  
state and again**



# Breadth-First Search

- General idea: Expand the *shallowest* unexpanded node
- Implementation: Using a *First-In First-Out (FIFO)* queue

**Check next node  
(again!) for goal  
state and again  
and again**



# Breadth-First Search

---

```
function BREADTH-FIRST-SEARCH(problem) returns a solution, or failure
  node  $\leftarrow$  a node with STATE = problem.INITIAL-STATE, PATH-COST = 0
  if problem.GOAL-TEST(node.STATE) then return SOLUTION(node)
  frontier  $\leftarrow$  a FIFO queue with node as the only element
  explored  $\leftarrow$  an empty set
  loop do
    if EMPTY?(frontier) then return failure
    node  $\leftarrow$  POP(frontier) /* chooses the shallowest node in frontier */
    add node.STATE to explored
    for each action in problem.ACTIONS(node.STATE) do
      child  $\leftarrow$  CHILD-NODE(problem, node, action)
      if child.STATE is not in explored or frontier then
        if problem.GOAL-TEST(child.STATE) then return SOLUTION(child)
        frontier  $\leftarrow$  INSERT(child, frontier)
```



# Properties of Breadth-First Search

---

- Completeness: Yes (if  $b$  is finite)
- Optimality: Yes (if  $cost=1$  per step)  
(Not optimal in general)
- Time complexity:
- Space complexity:



# Properties of Breadth-First Search

---

- Completeness: Yes (if  $b$  is finite)
- Optimality: Yes (if  $cost=1$  per step)  
(Not optimal in general)
- Time complexity:  $1+b+b^2+b^3+\dots +b^d = O(b^d)$
- Space complexity:  $O(b^d)$   
(keeps every node in memory)



# Two Issues with BFS

- Memory requirements are a bigger problem for Breadth-First Search than is the execution time
- Exponential-complexity search problems cannot be solved by uninformed methods for any but the smallest instances

Depth	Nodes	Time	Memory
2	$10^2$	0.11 milliseconds	107 kilobytes
4	$10^4$	11 milliseconds	10.6 megabytes
6	$10^6$	1.1 seconds	1 gigabytes
8	$10^8$	2 minutes	103 gigabytes
10	$10^{10}$	3 hours	10 terabytes
12	$10^{12}$	13 days	1 petabytes
14	$10^{14}$	3.5 years	99 petabytes
16	$10^{14}$	350 years	10 exabytes

*Assuming branching factor  $b=10$ ; 1 million nodes/second; 1000 bytes/node*






# Properties of Breadth-First Search

- Completeness: Yes (if  $b$  is finite)
- Optimality: Yes (if  $cost=1$  per step)  
(Not optimal in general)  
*What if step cost  $\neq 1$  or is non-uniform?*
- Time complexity:  $1+b+b^2+b^3+\dots +b^d = O(b^d)$
- Space complexity:  $O(b^d)$   
(keeps every node in memory)



# Uniform Cost Search

- General idea: Expand unexpanded node  $n$  with the *lowest path cost  $g(n)$*
- Implementation: Using a *priority* queue ordered by *path cost  $g$*




# Uniform Cost Search

```
function UNIFORM-COST-SEARCH(problem) returns a solution, or failure
  node  $\leftarrow$  a node with STATE = problem.INITIAL-STATE, PATH-COST = 0
  frontier  $\leftarrow$  a priority queue ordered by PATH-COST, with node as the only element
  explored  $\leftarrow$  an empty set
  loop do
    if EMPTY?(frontier) then return failure
    node  $\leftarrow$  POP(frontier) /* chooses the lowest-cost node in frontier */
    if problem.GOAL-TEST(node.STATE) then return SOLUTION(node)
    add node.STATE to explored
    for each action in problem.ACTIONS(node.STATE) do
      child  $\leftarrow$  CHILD-NODE(problem, node, action)
      if child.STATE is not in explored or frontier then
        frontier  $\leftarrow$  INSERT(child, frontier)
      else if child.STATE is in frontier with higher PATH-COST then
        replace that frontier node with child
```




# Uniform Cost Search



```
function UNIFORM-COST-SEARCH(problem) returns a solution, or failure  
  node  $\leftarrow$  a node with STATE = problem.INITIAL-STATE, PATH-COST = 0  
  frontier  $\leftarrow$  a priority queue ordered by PATH-COST, with node as the only element  
  explored  $\leftarrow$  an empty set  
  loop do  
    if EMPTY?(frontier) then return failure  
    node  $\leftarrow$  POP(frontier) /* chooses the lowest-cost node in frontier */  
    if problem.GOAL-TEST(node.STATE) then return SOLUTION(node)  
    add node.STATE to explored  
    for each action in problem.ACTIONS(node.STATE) do  
      child  $\leftarrow$  CHILD-NODE(problem, node, action)  
      if child.STATE is not in explored or frontier then  
        frontier  $\leftarrow$  INSERT(child, frontier)  
      else if child.STATE is in frontier with higher PATH-COST then  
        replace that frontier node with child
```



# Uniform Cost Search



**function** UNIFORM-COST-SEARCH(*problem*) **returns** a solution, or failure

*node*  $\leftarrow$  a node with STATE = *problem*.INITIAL-STATE, PATH-COST = 0

*frontier*  $\leftarrow$  a priority queue ordered by PATH-COST, with *node* as the only element

*explored*  $\leftarrow$  an empty set

**loop do**

**if** EMPTY?(*frontier*) **then return** failure

*node*  $\leftarrow$  POP(*frontier*) /\* chooses the lowest-cost node in *frontier* \*/

**if** *problem*.GOAL-TEST(*node*.STATE) **then return** SOLUTION(*node*)

    add *node*.STATE to *explored*

**for each** *action* **in** *problem*.ACTIONS(*node*.STATE) **do**

*child*  $\leftarrow$  CHILD-NODE(*problem*, *node*, *action*)

**if** *child*.STATE is not in *explored* or *frontier* **then**

*frontier*  $\leftarrow$  INSERT(*child*, *frontier*)

**else if** *child*.STATE is in *frontier* with higher PATH-COST **then**

            replace that *frontier* node with *child*



# Properties of Uniform Cost Search

---

- Completeness: Yes  
(if *step cost*  $> \epsilon$ , some positive constant)
- Optimality: Yes
- Time complexity:
- Space complexity:



# Properties of Uniform Cost Search

---

- Completeness: Yes  
(if *step cost*  $> \epsilon$ , some positive constant)
- Optimality: Yes
- Time complexity:  $O(b^{C^*/\epsilon})$   
Given  $C^*$  = cost of optimal solution
- Space complexity:  $O(b^{C^*/\epsilon})$



# Summary: Uninformed Search

---

- Breadth-First Search
- Uniform-cost search
- Depth-First Search
- Depth-limited search
- Iterative deepening search

