localhost:8888/notebooks/Untitled12.ipynb

Summarize Chat

jupyter Untitled12 Last Checkpoint: 7 minutes ago

File Edit View Run Kernel Settings Help Trusted

Code JupyterLab Python 3 (ipykernel)

[1]:
```
my_list = [10, 3.5, "hello", True]
print("List:", my_list)
print("Type of list:", type(my_list))
for item in my_list:
    print(f"Value: {item}, Type: {type(item)}")
```

```
List: [10, 3.5, 'hello', True]
Type of list: <class 'list'>
Value: 10, Type: <class 'int'>
Value: 3.5, Type: <class 'float'>
Value: hello, Type: <class 'str'>
Value: True, Type: <class 'bool'>
```

[2]:
```
a = [1, 2, 3]
b = [4, 5, 6]
concat = a + b
print("Concatenation:", concat)
repeat = a * 3
print("Repetition:", repeat)
print("Is 2 in list a?", 2 in a)
print("Length of list a:", len(a))
print("Length of list b:", len(b))
```

localhost:8888/notebooks/Untitled12.ipynb

Summarize Chat

jupyter Untitled12 Last Checkpoint: 7 minutes ago

File Edit View Run Kernel Settings Help Trusted

Code JupyterLab Python 3 (ipykernel)

```
Concatenation: [1, 2, 3, 4, 5, 6]
Repetition: [1, 2, 3, 1, 2, 3, 1, 2, 3]
Is 2 in list a? True
Length of list a: 3
Length of list b: 3
```

[4]:
```
nums = [10, 5, 20, 8, 15]
print("Maximum value:", max(nums))
print("Minimum value:", min(nums))
print("Sum of elements:", sum(nums))
ascending = sorted(nums)
print("Ascending order:", ascending)
descending = sorted(nums, reverse=True)
print("Descending order:", descending)
print("Index of 8:", nums.index(8))
```

```
Maximum value: 20
Minimum value: 5
Sum of elements: 58
Ascending order: [5, 8, 10, 15, 20]
Descending order: [20, 15, 10, 8, 5]
Index of 8: 3
```

localhost:8888/notebooks/Untitled12.ipynb

jupyter Untitled12 Last Checkpoint: 7 minutes ago

Trusted

File Edit View Run Kernel Settings Help

JupyterLab Python 3 (ipykernel)

Code

[5]:
```
nums = [10, 20, 30]
print("Original list:", nums)
nums.append(40)
print("After append:", nums)
nums.insert(1, 15)
print("After insert:", nums)
nums.remove(20)
print("After remove:", nums)
nums.pop()
print("After pop:", nums)
nums.reverse()
print("After reverse:", nums)
```

```
Original list: [10, 20, 30]
After append: [10, 20, 30, 40]
After insert: [10, 15, 20, 30, 40]
After remove: [10, 15, 30, 40]
After pop: [10, 15, 30]
After reverse: [30, 15, 10]
```

[7]:
```
nums = list(map(int, input("Enter numbers separated by space: ").split()))
even_nums = [n for n in nums if n % 2 == 0]
print("Even numbers:", even_nums)
```

localhost:8888/notebooks/Untitled12.ipynb

jupyter Untitled12 Last Checkpoint: 8 minutes ago

File Edit View Run Kernel Settings Help

Trusted

Code

JupyterLab Python 3 (ipykernel)

```
After pop: [10, 15, 30]
After reverse: [30, 15, 10]
```

[7]:
```
nums = list(map(int, input("Enter numbers separated by space: ").split()))
even_nums = [n for n in nums if n % 2 == 0]
print("Even numbers:", even_nums)
odd_nums = [n for n in nums if n % 2 != 0]
print("Odd numbers:", odd_nums)
print("Largest number:", max(nums))
print("Smallest number:", min(nums))
unique_nums = list(set(nums))
print("List without duplicates:", unique_nums)
```

```
Enter numbers separated by space:  10 20 30
Even numbers: [10, 20, 30]
Odd numbers: []
Largest number: 30
Smallest number: 10
List without duplicates: [10, 20, 30]
```

[ ]: