DATA-260 Homework 7

DATA-260 Homework 7

GitHub repository: https://github.com/shrustishetty-2401/data260-9004

Student and Configuration

- Student: Shrusti Shetty
- SID4: 9004
- Port base: 8004
- Prefix: `s9004`
- Domain ID: 4
- Seed: 9004
- Verify seed: 269004
- Hardware: MacBook Pro, Apple Silicon
- Local model: `qwen3:8b`
- Branch: `hw7`
- Final branch/tag: `hw7`
- Final implementation commit: `2b816ca`
- Final branch and tag were verified with `git ls-remote`.

Part 1: JWT Authentication, Roles, and Linting

Implemented JWT authentication with MySQL-backed users.

Test users:

- `reader` / `data260`
- `writer` / `data260`
- `moderator` / `data260`

Verified:

- Valid login returns HTTP 200 and a JWT.
- Invalid login returns HTTP 401.
- Missing token returns HTTP 401.
- Invalid token returns HTTP 401.
- Reader package creation returns HTTP 403.
- Writer package creation returns HTTP 201.
- Writer package deletion returns HTTP 403.

- Moderator package deletion returns HTTP 200.
- Authenticated list/read request returns HTTP 200.
- Ruff and pre-commit checks pass.

Login Evidence




Login success and invalid login

Authentication Failure Evidence




Missing and invalid token responses

Create Permission Evidence




Reader 403 and writer 201 responses

Delete Permission Evidence




Writer 403 and moderator 200 responses

Authenticated Read Evidence



Authenticated list request

Linting Evidence



Ruff and pre-commit evidence

Part 2: Tool-Using Agent

Implemented a tool-using agent with:

- `search_vulnerabilities`
- `vulnerability_detail`
- `vulnerability_aggregate`

The agent supports:

- Multiple tool calls.
- Tool-role messages.


- Input validation.
- Malformed-argument repair.
- Unknown-tool blocking.
- Maximum-step limits.
- Safe handling of nonexistent vulnerability IDs.

Verification Tasks

Task A searched for a seeded vulnerability and retrieved the first result.

Task B retrieved an aggregate summary and searched for a supporting package example.


Task C searched for `package-0` and retrieved details for vulnerability IDs `10002` and `9752`.



Tasks A, B, and C

Error Recovery

The nonexistent-ID test used vulnerability ID `999999999`. The tool returned `vulnerability not found`, and the agent responded without crashing.



Nonexistent ID recovery

Evidence:

- `raw/agent_reliability.json`


- `RUN_LOG.txt`

Part 3: Reflexion and Bounded Self-Correction

Implemented:

- Deterministic verification.
- Reflection after failed attempts.
- Revised strategies.
- Maximum two retries.
- Tool and token budgets.
- Stored reflection evidence.

Metric	Original loop	Reflexion loop
Task success	2	3
Retry rate	0.000	0.333
Tool calls	5	7
Estimated tokens	2278	3506
Latency	41793.48 ms	61113.38 ms
Verifier false rejections	0	0



Reflexion comparison

The verifier recorded zero false rejections. The stored reflections contain concise failure evidence and revised strategies without hidden chain-of-thought.

Evidence:

- `raw/reflexion_comparison.json`
- `raw/reflections.json`

Part 4: Citi Bike ReAct/MRKL Application

Implemented a React/Vite Citi Bike decision application with the following tools:

1. `csv_sql`

2. `policy_retriever`
3. `calculator`


The application displays:

- Uploaded CSV filename.
- Tool execution timeline.
- Weekly member/casual comparison.
- Membership or pay-per-use decision.
- Pricing source.
- Pricing capture time.
- Pricing snapshot SHA-256 hash.
- Calculator output.
- Membership cost.
- Pay-per-use cost.
- Break-even point.
- Step count.
- Total execution time.
- Completion stop reason.

Dataset Results

Dataset	Rows	Member rides	Casual rides	Result
`bikeshare_membership_wins.csv`	800	700	100	Membership is stronger
`bikeshare_pay_per_use_wins.csv`	800	100	700	Pay-per-use is stronger


Membership-Win Scenario



Membership-win scenario

The membership-win dataset contains 700 member rides and 100 casual rides. The application selected `Buy Monthly Membership` because member usage was dominant.

Pay-Per-Use-Win Scenario



Pay-per-use-win scenario

The pay-per-use-win dataset contains 100 member rides and 700 casual rides. The application selected `Pay Per Ride/Minute` because casual usage was dominant.

Pricing evidence:

- `raw/pricing_snapshot.txt`
- `raw/pricing_snapshot.sha256`

Part 5: Prompt-Injection Defense

Threat Model

The threat model covers:

- Recommendation override: an attacker attempts to force an incorrect plan recommendation.
- Non-read-only tool misuse: an attacker attempts to make the SQL tool modify data.
- Data exfiltration: an attacker attempts to include restricted uploaded content in the final answer.

The hostile fixture is stored at:


- `raw/hostile_pricing_fixture.html`

Tested attacks:

- Instruction override.
- Unauthorized tool abuse.
- CSV-based prompt injection.

Results:

- Attack cases: 3
- Defended cases: 3
- Defense success rate: 100%



Prompt-injection defense

Retrieved text is treated as untrusted data. Tool-boundary enforcement is stronger than prompt-only defense because the tool itself rejects unsafe operations even if an input attempts to bypass the instructions.

Before-and-After Defense Results

Attack	Before defense	After defense	Result
Instruction override	Input attempted to replace trusted instructions and expose restricted information.	Trusted policy remained active and the request was blocked.	Defended
Unauthorized tool abuse	Input attempted to use an approved tool for arbitrary Python execution and environment-variable access.	Tool use was restricted to approved read-only operations.	Defended
CSV prompt injection	Uploaded text attempted to override the pricing recommendation.	Uploaded content was treated as untrusted data and the attack was blocked.	Defended

Overall defense result: 3 of 3 attacks were blocked successfully.

Evidence:

- `raw/prompt_injection_results.json`
- `raw/hostile_pricing_fixture.html`

Part 6: File Tools and Safety Gate

Implemented:

- `read_file`
- `write_file`
- `edit_file`
- `glob_files`
- `search_in_files`
- `bash`

The safety gate includes:


- `SAFE_PREFIXES`
- `is_destructive`
- `confirm_bash`
- Explicit confirmation for destructive commands.
- Path traversal protection.
- Unconfirmed write protection.

The integration test performed:

`glob -> search -> read`

The safety suite tested ten commands. Five safe commands were allowed and five destructive or restricted commands were blocked.

The results confirmed that file listing, file search, file reading, unconfirmed-write blocking, path-traversal blocking, and destructive-command confirmation all work as intended.



File tools and safety evidence

Evidence:

- `raw/file_tools_results.json`

Reproducibility Evidence

- `RUN_LOG.txt`
- `METRICS.md`
- `AI_USE.md`
- `verification.json`
- `raw/agent_reliability.json`
- `raw/reflexion_comparison.json`
- `raw/reflections.json`
- `raw/prompt_injection_results.json`
- `raw/file_tools_results.json`
- `raw/pricing_snapshot.txt`
- `raw/pricing_snapshot.sha256`
- `raw/hostile_pricing_fixture.html`
- `raw/bikeshare_membership_wins.csv`
- `raw/bikeshare_pay_per_use_wins.csv`

Final Verification

The following checks passed:

- Python compilation.
- Ruff check.
- Pre-commit hooks.
- Backend API startup.
- JWT authentication tests.
- Invalid-login test.
- Missing-token test.
- Role-permission tests.
- Authenticated read test.
- Agent tests.
- Tool tests.
- Reliability experiment.
- Reflexion experiment.
- Bike-share API test.
- React production build.
- Prompt-injection tests.
- File-safety tests.

The final branch and tag are both named `hw7` and were verified with:

```
git ls-remote --heads origin hw7
git ls-remote --tags origin hw7
```

Both references pointed to the same final commit at submission time.

Submission Files

The final submission PDF is:

`reports/hw07/Shetty_HW7.pdf`

The report includes screenshots for Parts 1 through 6, machine-readable experiment outputs, verification results, and reproducibility evidence.