

1.

 **SIMATS**
ENGINEERING

SIMATS Online Programming Lab
C++ PROGRAMMING

SHRUTHI SREE
192421129RC

QUESTIONS 19 / 19 completed

()

()

Write a C++ program to overload the () operator to call a function with arguments.

PROGRAM EDITOR C++ Run Save

INPUT

4 5

2.



SIMATS Online Programming Lab

C++ PROGRAMMING

SHRUTHI SREE R
192421129RC

QUESTIONS 19 / 19 completed

(-)

(-)

Write a C++ program to overload the - operator to subtract two complex numbers.

PROGRAM EDITOR

C++

Run

Save

```
1 #include <iostream>
2 using namespace std;
3
4 class Complex {
5     float real;
6     float imag;
7
8 public:
9     Complex(float r = 0, float i = 0) {
10         real = r;
11         imag = i;
12     }
13
14     // Overloading - operator to subtract two complex numbers
15     Complex operator-(const Complex& obj) {
16         Complex temp;
17         temp.real = real - obj.real;
18         temp.imag = imag - obj.imag;
19         return temp;
20     }
21 }
```

INPUT

5.5 4.3
2.1 1.2

3.



SIMATS
ENGINEERING

SIMATS Online Programming Lab
C++ PROGRAMMING

 **SHRUTHI SREE R**
192421129RC

QUESTIONS 19 / 19 completed

Plus Equal ▾

PLUS EQUAL

Write a C++ program to overload the += operator to add two objects of a user-defined class.

PROGRAM EDITOR C++ ▾ **Run** **Save**

```
1 #include <iostream>
2 using namespace std;
3
4 class Number {
5     int value;
6
7 public:
8     Number(int v = 0) {
9         value = v;
10    }
11
12    // Overloading += operator
13    Number& operator+=(const Number& obj) {
14        this->value += obj.value;
15        return *this;
16    }
17
18    void display() {
19        cout << value << endl;
20    }
21 };
```

INPUT
15 25

4.



SIMATS
ENGINEERING

SIMATS Online Programming Lab

C++ PROGRAMMING

 **SHRUTHI SREE R**
192421129RC

QUESTIONS 19 / 19 completed

Add

ADD

Write a C++ program to overload a function to add two integer numbers and two floating-point numbers separately.

PROGRAM EDITOR

C++

Run

Save

```
1 #include <iostream>
2 using namespace std;
3
4 // Function to add two integers
5 int add(int a, int b) {
6     return a + b;
7 }
8
9 // Overloaded function to add two floating-point numbers
10 double add(double a, double b) {
11     return a + b;
12 }
13
14 int main() {
15     int i1, i2;
16     double d1, d2;
17
18     cin >> i1 >> i2;
19     cin >> d1 >> d2;
20
21 }
```

INPUT

10 20
12.5 7.3

5.



SIMATS
ENGINEERING

SIMATS Online Programming Lab

C++ PROGRAMMING

SHRUTHI SREE R
192421129RC

QUESTIONS 19 / 19 completed

Maximum

MAXIMUM

Write a C++ program to overload a function to find the maximum value from two integer numbers, two floating-point numbers, and two characters separately.

PROGRAM EDITOR

C++

Run

Save

INPUT

10 20
5.5 2.3
a z