

Constructor and Destructor

1.Student

main.cpp	Output
<pre>1 #include <iostream> 2 using namespace std; 3 4 class Student { 5 public: 6 Student() { 7 cout << "Student Constructor called" << endl; 8 } 9 10 ~Student() { 11 cout << "Student Destructor called" << endl; 12 } 13 }; 14 15 int main() { 16 Student s; 17 return 0; 18 }</pre>	<pre>Student Constructor called Student Destructor called === Code Execution Successful ===</pre>

2.Book

main.cpp	Output
<pre>1 #include <iostream> 2 using namespace std; 3 4 class Book { 5 public: 6 Book() { 7 cout << "Book is created" << endl; 8 } 9 10 ~Book() { 11 cout << "Book is destroyed" << endl; 12 } 13 }; 14 15 int main() { 16 Book b; 17 return 0; 18 }</pre>	<pre>Book is created Book is destroyed === Code Execution Successful ===</pre>

3.Rectangle

main.cpp	Output
<pre>1 #include <iostream> 2 using namespace std; 3 4 class Rectangle { 5 public: 6 Rectangle() { 7 cout << "Rectangle created" << endl; 8 } 9 10 ~Rectangle() { 11 cout << "Rectangle destroyed" << endl; 12 } 13 }; 14 15 int main() { 16 Rectangle r; 17 return 0; 18 }</pre>	<pre>Rectangle created Rectangle destroyed === Code Execution Successful ===</pre>

4.Car

main.cpp	Output
<pre>1 #include <iostream> 2 using namespace std; 3 4 class Car { 5 public: 6 Car() { 7 cout << "Car started" << endl; 8 } 9 10 ~Car() { 11 cout << "Car stopped" << endl; 12 } 13 }; 14 15 int main() { 16 Car c; 17 return 0; 18 }</pre>	<pre>Car started Car stopped === Code Execution Successful ===</pre>

5.Bank

main.cpp		Run	Output
<pre>1 #include <iostream> 2 using namespace std; 3 4 class Bank { 5 public: 6 Bank() { 7 cout << "Bank account opened" << endl; 8 } 9 10 ~Bank() { 11 cout << "Bank account closed" << endl; 12 } 13 }; 14 15 int main() { 16 Bank b; 17 return 0; 18 }</pre>			Bank account opened Bank account closed === Code Execution Successful ===