

# Presenting: 'Cryptographic primitives based on hard learning problems: Blum, Furst, Kearns, Lipton'

Vishvas Vasuki

April 19, 2009

# Outline

- 1 Outline
- 2 Introduction to Learning Theory
- 3 Hardness of learning as a cryptographic assumption
  - What do we really mean?
  - A problem in hardness definition
  - A new definition for hardness of learning
- 4 Pseudorandom generator from Hard to learn set of functions
- 5 Conclusion

# What to look out for?

# What to look out for?

- A **new definition** for hardness of learning.

# What to look out for?

- A **new definition** for hardness of learning.
- A **pseudorandom bit generator** using hard to learn class of functions.

# Outline

- 1 Outline
- 2 Introduction to Learning Theory
- 3 Hardness of learning as a cryptographic assumption
  - What do we really mean?
  - A problem in hardness definition
  - A new definition for hardness of learning
- 4 Pseudorandom generator from Hard to learn set of functions
- 5 Conclusion

# The binary classification problem

# The binary classification problem

- Teach the computer difference between male face and female face by giving examples.






# The binary classification problem

- Teach the computer difference between male face and female face by giving examples.



- Ask computer: Is  a female face?

# The binary classification problem

- Teach the computer difference between male face and female face by giving examples.



- Ask computer: Is a female face?
- Computer wins if it succeeds with good probability.

# The binary classification problem formalized

# The binary classification problem formalized

- Known set of  $n$  features. Eg: Hairstyle, facial hair, moustache




# The binary classification problem formalized

- Known set of  $n$  features. Eg: Hairstyle, facial hair, moustache



- Unknown classification function (concept)




# The binary classification problem formalized

- Known set of  $n$  features. Eg: Hairstyle, facial hair, moustache



- Unknown classification function (concept)




- $c$  belongs to a known set of functions,  $C_n$ . Eg: Polynomial sized DNF over  $n$  variables, Halfspaces etc..

# The binary classification problem formalized

- Known set of  $n$  features. Eg: Hairstyle, facial hair, moustache



- Unknown classification function (concept)




- $c$  belongs to a known set of functions,  $C_n$ . Eg: Polynomial sized DNF over  $n$  variables, Halfspaces etc..
- See  $m(n)$  examples:  $\{(s_1, c(s_1)), (s_2, c(s_2)).. \} = (S, c(S))$ .

# The binary classification problem formalized

- Known set of  $n$  features. Eg: Hairstyle, facial hair, moustache



- Unknown classification function (concept)



- $c$  belongs to a known set of functions,  $C_n$ . Eg: Polynomial sized DNF over  $n$  variables, Halfspaces etc..
- See  $m(n)$  examples:  $\{(s_1, c(s_1)), (s_2, c(s_2)).. \} = (S, c(S))$ .
- Now, classify test set:  $\{s'_1, s'_2, ..\}$ .





# Some notation

# Some notation

- $C_n$ : a set of classification functions  $\{0, 1\}^n \rightarrow \{0, 1\}$ . Their ensemble  $C = \{C_n\}$ .

# Some notation

- $C_n$ : a set of classification functions  $\{0, 1\}^n \rightarrow \{0, 1\}$ . Their ensemble  $C = \{C_n\}$ .
- $D_n$ : A distribution over inputs:  $\{0, 1\}^n$ . Their ensemble:  $D = \{D_i\}$ .



# $L$ learns a set of functions $C$ wrt $D$

# L learns a set of functions $C$ wrt $D$

- Fix some  $c \in C_n$ .



# L learns a set of functions $C$ wrt $D$

- Fix some  $c \in C_n$ .



- Pick  $S \sim D_n^{m(n)}$ .



# L learns a set of functions $C$ wrt $D$

- Fix some  $c \in C_n$ .



- Pick  $S \sim D_n^{m(n)}$ .



- Alg  $L$ , upon studying  $(S, c(S))$  in time  $\text{poly}(n, \frac{1}{\epsilon})$ , classifies new examples with  $\leq \epsilon$  error rate.

# L learns a set of functions $C$ wrt $D$

- Fix some  $c \in C_n$ .



- Pick  $S \sim D_n^{m(n)}$ .



- Alg  $L$ , upon studying  $(S, c(S))$  in time  $\text{poly}(n, \frac{1}{\epsilon})$ , classifies new examples with  $\leq \epsilon$  error rate.

- 


$$\Pr_{S \sim D_n^{m(n)}, x \sim D_n} (L(S, c(S), x) = c(x)) \geq 1 - \epsilon$$

in time  $\text{poly}(n, \frac{1}{\epsilon})$ .





# L learns a set of functions $C$ wrt $D$


- Fix some  $c \in C_n$ . 

- Pick  $S \sim D_n^{m(n)}$ . 

- Alg  $L$ , upon studying  $(S, c(S))$  in time  $\text{poly}(n, \frac{1}{\epsilon})$ , classifies new examples with  $\leq \epsilon$  error rate.


•

$$\Pr_{S \sim D_n^{m(n)}, x \sim D_n} (L(S, c(S), x) = c(x)) \geq 1 - \epsilon$$

in time  $\text{poly}(n, \frac{1}{\epsilon})$ . 

- $L$  learns  $C$  if you can say this  $\forall c \in C_n, D_n, \forall n$ .

# L learns a set of functions $C$ wrt $D$


- Fix some  $c \in C_n$ . 

- Pick  $S \sim D_n^{m(n)}$ . 

- Alg  $L$ , upon studying  $(S, c(S))$  in time  $\text{poly}(n, \frac{1}{\epsilon})$ , classifies new examples with  $\leq \epsilon$  error rate.

•

$$\Pr_{S \sim D_n^{m(n)}, x \sim D_n} (L(S, c(S), x) = c(x)) \geq 1 - \epsilon$$

in time  $\text{poly}(n, \frac{1}{\epsilon})$ . 

- $L$  learns  $C$  if you can say this  $\forall c \in C_n, D_n, \forall n$ .
- Else hard to learn.

# About computational learning theory

# About computational learning theory

- Can you learn it in polynomial time?

# About computational learning theory

- Can you learn it in polynomial time?
- Is it hard to learn it in polynomial time?

# Outline

- 1 Outline
- 2 Introduction to Learning Theory
- 3 Hardness of learning as a cryptographic assumption
  - What do we really mean?
  - A problem in hardness definition
  - A new definition for hardness of learning
- 4 Pseudorandom generator from Hard to learn set of functions
- 5 Conclusion

# Outline

- 1 Outline
- 2 Introduction to Learning Theory
- 3 Hardness of learning as a cryptographic assumption
  - What do we really mean?
  - A problem in hardness definition
  - A new definition for hardness of learning
- 4 Pseudorandom generator from Hard to learn set of functions
- 5 Conclusion

# Some notation



# Some notation

- $C_n$ : a set of classification functions  $\{0, 1\}^n \rightarrow \{0, 1\}$ .

# Some notation

- $C_n$ : a set of classification functions  $\{0, 1\}^n \rightarrow \{0, 1\}$ .
- $P_n$ : A distribution over  $C_n$ . Their ensemble:  $P = \{P_n\}$ .



# Some notation

- $C_n$ : a set of classification functions  $\{0, 1\}^n \rightarrow \{0, 1\}$ .
- $P_n$ : A distribution over  $C_n$ . Their ensemble:  $P = \{P_n\}$ .



- $D_n$ : A distribution over inputs:  $\{0, 1\}^n$ . Their ensemble:  $D = \{D_i\}$ .



# Hardness of learning as a cryptographic assumption

# Hardness of learning as a cryptographic assumption

- Want 'C is hard to learn' to be a cryptographic assumption.

# Hardness of learning as a cryptographic assumption

- Want 'C is hard to learn' to be a cryptographic assumption.
- Any alg L should learn C only with negligible probability.

# Hardness of learning as a cryptographic assumption

- Want 'C is hard to learn' to be a cryptographic assumption.
- Any alg L should learn C only with negligible probability.
- Take  $(P_n, D_n)$ . Pick classifier  $c$  using  $P_n$ . Pick many examples using  $D_n$ . Your alg cannot match  $c(x)$  with non negligible

probability.



# Outline


- 1 Outline
- 2 Introduction to Learning Theory
- 3 Hardness of learning as a cryptographic assumption
  - What do we really mean?
  - A problem in hardness definition
  - A new definition for hardness of learning
- 4 Pseudorandom generator from Hard to learn set of functions
- 5 Conclusion



# Problem in hardness definition


# Problem in hardness definition

- Even if you have efficient alg L to learn all but a tiny scattered subset of C, it is no good. C is 'hard to learn'.



# Problem in hardness definition

- Even if you have efficient alg L to learn all but a tiny scattered subset of C, it is no good. C is 'hard to learn'.



- If 'Learning C is hard' were a cryptographic assumption, any proof of security built on this assumption would be **worthless**. L is strong enough to break this assumption, by cryptographic standards.

# Outline

- 1 Outline
- 2 Introduction to Learning Theory
- 3 Hardness of learning as a cryptographic assumption
  - What do we really mean?
  - A problem in hardness definition
  - A new definition for hardness of learning
- 4 Pseudorandom generator from Hard to learn set of functions
- 5 Conclusion


# Learning a concept class $C$ wrt $(P, D)$

# Learning a concept class $C$ wrt $(P, D)$

- So, weaken hardness of learning defn or strengthen learnability defn.

# Learning a concept class $C$ wrt $(P, D)$

- So, weaken hardness of learning defn or strengthen learnability defn.
- Pick  $D_n \in D, P_n \in P, c \in P_n$ .



# Learning a concept class $C$ wrt $(P, D)$

- So, weaken hardness of learning defn or strengthen learnability defn.
- Pick  $D_n \in D, P_n \in P, c \in P_n$ .




- Alg  $L$ , upon studying  $S$ ,  $c(S)$  in time  $\text{poly}(n, \frac{1}{\epsilon})$ , classifies new examples with  $\leq \epsilon$  error rate.



# Learning a concept class $C$ wrt $(P, D)$

- So, weaken hardness of learning defn or strengthen learnability defn.
- Pick  $D_n \in D, P_n \in P, c \in P_n$ .




- Alg  $L$ , upon studying  $S$ ,  $c(S)$  in time  $\text{poly}(n, \frac{1}{\epsilon})$ , classifies new examples with  $\leq \epsilon$  error rate.
- 

$$\Pr_{S \sim D_n^{m(n)}, x \sim D_n, c \in P_n} (L(S, c(S), x) = c(x)) \geq 1 - \epsilon$$



# Learning a concept class $C$ wrt $(P, D)$

- So, weaken hardness of learning defn or strengthen learnability defn.
- Pick  $D_n \in D, P_n \in P, c \in P_n$ .



- Alg L, upon studying  $S$ ,  $c(S)$  in time  $\text{poly}(n, \frac{1}{\epsilon})$ , classifies new examples with  $\leq \epsilon$  error rate.
- 

$$\Pr_{S \sim D_n^{m(n)}, x \sim D_n, c \in P_n} (L(S, c(S), x) = c(x)) \geq 1 - \epsilon$$



- L learns  $C$  if you can say this  $\forall P_n, D_n$ .

# Learning a concept class $C$ wrt $(P, D)$

- So, weaken hardness of learning defn or strengthen learnability defn.
- Pick  $D_n \in D, P_n \in P, c \in P_n$ .



- Alg L, upon studying  $S$ ,  $c(S)$  in time  $\text{poly}(n, \frac{1}{\epsilon})$ , classifies new examples with  $\leq \epsilon$  error rate.
- 

$$\Pr_{S \sim D_n^{m(n)}, x \sim D_n, c \in P_n} (L(S, c(S), x) = c(x)) \geq 1 - \epsilon$$



- L learns  $C$  if you can say this  $\forall P_n, D_n$ .
- Else hard to learn.

# The new definition, pictorially



'Hard to learn':

$$P_n \times D_n^m$$



'Learnable':

$$P_n \times D_n^m$$

# Outline

- 1 Outline
- 2 Introduction to Learning Theory
- 3 Hardness of learning as a cryptographic assumption
  - What do we really mean?
  - A problem in hardness definition
  - A new definition for hardness of learning
- 4 Pseudorandom generator from Hard to learn set of functions
- 5 Conclusion

# Pseudorandom bit generator (PRBG)

# Pseudorandom bit generator (PRBG)

- $G_n$  takes  $n$  bits input, makes  $g(n) > n$  bits output.

# Pseudorandom bit generator (PRBG)

- $G_n$  takes  $n$  bits input, makes  $g(n) > n$  bits output.
- Any polynomial time alg  $T$  does not behave noticeably differently on  $y \sim U(\{0, 1\}^{g(n)})$  and  $g(x)|_x \sim U(\{0, 1\}^n)$ .




# Pseudorandom bit generator (PRBG)

- $G_n$  takes  $n$  bits input, makes  $g(n) > n$  bits output.
- Any polynomial time alg  $T$  does not behave noticeably differently on  $y \sim U(\{0, 1\}^{g(n)})$  and  $g(x)|_x \sim U(\{0, 1\}^n)$ .
- $G = \{G_n\}$ .


# Pseudorandom bit generator (PRBG)

- $G_n$  takes  $n$  bits input, makes  $g(n) > n$  bits output.
- Any polynomial time alg  $T$  does not behave noticeably differently on  $y \sim U(\{0, 1\}^{g(n)})$  and  $g(x)|_x \sim U(\{0, 1\}^n)$ .
- $G = \{G_n\}$ .
- Now, construct a PRBG.

# Construct PRBG from hard to learn $P_n$ over $C_n$



# Construct PRBG from hard to learn $P_n$ over $C_n$



- Proof by contradiction: If you could break this PRBG,  $C_n$  not hard to learn wrt  $(P_n, U(\{0, 1\}^n))$ .
- 1110011100111100001011001... 'Can I predict the next bit?'

# Outline

- 1 Outline
- 2 Introduction to Learning Theory
- 3 Hardness of learning as a cryptographic assumption
  - What do we really mean?
  - A problem in hardness definition
  - A new definition for hardness of learning
- 4 Pseudorandom generator from Hard to learn set of functions
- 5 Conclusion

# Some other results in the paper: Skip

## Some other results in the paper: Skip

- Things you can make from hard to learn set of functions: One way functions, A private key cryptosystem.

## Some other results in the paper: Skip


- Things you can make from hard to learn set of functions: One way functions, A private key cryptosystem.
- A pseudo random generator based on hardness of learning parity functions in the presence of noise.




## Some other results in the paper: Skip

- Things you can make from hard to learn set of functions: One way functions, A private key cryptosystem.
- A pseudo random generator based on hardness of learning parity functions in the presence of noise.
- They take more pains to relate the circuit size and depth required to evaluate functions in hard to learn  $C_n$  with the circuit depth and size of the primitives generated.

# The take home message




## The take home message



- Can use hardness of learning, properly defined, as a cryptographic assumption.

# The take home message



- Can use hardness of learning, properly defined, as a cryptographic assumption.
- Can generically make pseudorandom bit generator from hard to learn but easy to evaluate classes of functions.

# Bye!

