

Nelskraft Refractory Pvt.ltd

"BUILDING DURABILITY,
ENABLING SUSTAINABLITY"

ABOUT US

Nelskraft Refractory Pvt.ltd

"BUILDING DURABILITY,
ENABLING SUSTAINABLITY"

Nelskraft Refractory Pvt Ltd is a professionally managed legal entity focused on customer-centric objectives that involve understanding client needs and preferences while delivering exceptional service. Our mission is to create value for our customers and earn recognition both domestically and internationally as a unique company with distinct qualities, products, and services. Our business plan and operations are led by a team of experienced professionals in the various product areas we offer. Our advisory team includes experts in refractory industries, ceramic engineering, biofuels, boiler design and maintenance, geology, logistics, and strategic management.

The range of products we provide includes:

1. Refractory Products
2. Biomass Pellets
3. Ball Clay
4. Silica Sand

With a robust supply chain network, strict quality control measures, a process-oriented approach, and a dedicated customer relationship manager, we ensure timely management information system (MIS) reports to help our clients make evidence-based decisions. This, in turn, adds value and provides a comprehensive solution to all their needs.

HIGH ALUMINA BRICK POWDER



Application: Refractory Bricks, Mortar, Welding Flux, and Nozzle Mouth (for Iron Filter manufacturing)

- **Size: 0 - 5 mm**
- **Al_2O_3 Content: 70%**
- **Mesh size : 60 (fines)**
- **Temperature: 1700°C**

REFRACTORIES BOILER BED MATERIAL IS-8 GEADE



Utilization CFB Boiler Usage

- **Size: 0.85mm- 2.36mm**
- **Al_2O_3 Content: 35-40%**
- **SiO_2 Content: 45-55%**
- **Bulk Density: 1000-1100 m^3**
- **Operating Temperature: 1400°C**



REFRACTORIES MORTAR

Utilization: Fire and Air Setting Mortar - Furnace Construction and Brick Lining Works

- **Size: 0 - 1 mm**
- **Mesh: 60 & 100 (Fines)**
- **Al_2O_3 Content: 50% - 70%**
- **Temperature: 1600°C**



REFRACTORIES CASTABLE

Utilization: Furnace Construction

- **Size: 0 - 1mm,1-3mm& 3-5 mm**
- **Al_2O_3 Content: 50% - 70%**
- **Temperature:**
  - **1400°C - 50% (Al_2O_3)**
  - **1500°C - 60% (Al_2O_3)**
  - **1600°C - 70% (Al_2O_3)**
  -

Size and chemical percentage and be customized according to coustomer preferances



FIRECLAY

Utilization: Tasks related to furnace construction and brick lining

- **Mesh: 60 &100 (Fines)**
- **Al_2O_3 Content: 30% - 50%**
- **Temperature: 1400°C - 1600°C**

CAT - 9 CEMENT



Utilization: Cement Applications in Turbine Power Units

- **Mesh Size: 60 mesh**
- **Temperature: 1600°C**



REFRACTORIES BRICK POWDER IS-8 GREAD

Application: Refractory Bricks, Mortar, Welding Flux, and Nozzle Mouth (for Iron Filter manufacturing)

- **Size: 0 -1 mm, 1-3mm & 3-5mm**
- **Al_2O_3 Content: 40-70%**
- **Temperature: 1400-1700°C**



Size and chemical percentage and be customized according to coustomer preferances

IS - 6 BRICKS



- Al_2O_3 Content: 30%
- Temperatura: 1400 °C

IS-8 BRICKS



- Al2O3 Content: 40%
- Temperatura: 1500 °C

Biomass Pellets

Our high-quality biomass pellets are a reliable and eco-friendly alternative to coal, designed for efficient combustion in industrial applications.

Key Features:

GrossCalorific Value (GCV):
3200-3700

Sizes Available: 8mm,16mm and as per customer requirement

Moisture: 4%-6%

Sustainable & Cost-Effective: Reduces carbon footprint and fuel costs.

Consistent Support: Reliable year-round availability.







De-oiled Cashew Nut Shell Cake



Cashew De-Oiled Cake, also known as Bio Shell Cake, is an eco-friendly biomass fuel derived from cashew nut shells after the extraction of Cashew Nut Shell Liquid (CNSL). This fuel offers a high calorific value and burns cleanly with minimal ash production, making it a viable replacement for coal in industrial boilers, kilns, and furnaces.

Key Features:

GrossCalorific Value (GCV): 4200-4600
Moisture: 10%



BALL CLAY





Ball clay's exceptional plasticity makes it essential in ceramic manufacturing, allowing easy shaping for intricate designs. Its high green strength prevents cracks during handling, while superior bonding enhances durability, making it ideal for high-quality ceramics.

Physical Properties

- Water of Plasticity - 42%
- Residue 350# - <1%
- Dry MOR - 30 kg/cm² (Extruded Bar)
- Soluble Salts - <600 ppm

Chemistry XRF Method

- SiO_2 - 47,2%
- Al_2O_3 - 35,1%
- Fe_2O_3 - 0,85%
- TiO_2 - 1,50%
- K_2O - 0,10%
- NaO - 0,00%
- CaO - 0,05%
- MgO - 0,01%
- L.O.I - 14,4%

Fired properties (1205°C lab furnace)

- Colour L value - >90
- Fired Shrinkage - 12%
- Fired MOR - >300 kg/cm²
- Water Absorption - <14%

SILICA SAND



Silica sand is a high-purity industrial mineral primarily composed of silicon dioxide (SiO_2). It is widely used in various industries for its chemical stability, durability, and high-temperature resistance. The material is available in different grades to meet the requirements of diverse applications.





Chemical Properties

Property	weight %
Loss on ignition	1.00 - 5.00
Silica (SiO_2)	84.00 - 93.00
Iron (Fe_2O_3)	0.30 - 1.80
Alumina (Al_2O_3)	2.00 - 8.00
Calcium (CaO)	0.30 - 3.00
Magnesium (MgO)	0.30 - 4.00
Sulphur (SO_3)	0.44 - 2.00
Sodium (Na_2O)	0.03 - 0.07

Thank you!

Let’s Build Durability Together
Partner with Nelskraft Refractory Pvt Ltd
for Sustainable and Efficient Solutions

Contact us today to explore how we can
meet your industrial needs

PHONE : +91 7020309001

EMAIL : INFO@NELSKRAFT.COM

WEBSITE : WWW.NELSKRAFT.COM

R.O : S.NO 315/1, GRACE VILLA, WAGHERE COLONY-1,
PIMPRI GAON,PIMPRI,PUNE,
MAHARASHTRA,INDIA. -411017

GST NO : 27AAJCN8508Q1ZM

CIN NO : U23990PN2024PTC233992