

Finding time complexity of algorithms

Problem 1: Finding Complexity using Counter Method

Question 1 | Correct Mark 1.00 out of 1.00 [Flag question](#)

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;

    int s =1;

    while(s <= n)
    {
        i++;
        s += i;
    }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 v int main(){
3     int n;
4     scanf("%d",&n);
5     int i = 1;
6     int s = 1;
7     int c = 0;
8 v     while (s<=n){
9         c++;
10        i++;
11        c++;
12        s += i;
13        c++;
14    }
15    c++;
16    printf("%d",c+2);
17    return 0;
18 }
```

	Input	Expected	Got	
✓	9	12	12	✓
✓	4	9	9	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Problem 2: Finding Complexity using Counter method

Question 1 | Correct. Mark 1.00 out of 1.00 [Flag question](#)

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
        printf("*");
    }
    else
    {
        for(int i=1; i<=n; i++)
        {
            for(int j=1; j<=n; j++)
            {
                printf("*");
                printf("*");
                break;
            }
        }
    }
}
```

Note: No need of counter increment for declarations and `scanf()` and `count` variable `printf()` statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 void func(int n)
3 {
4     int c=0;
5     if(n==1)
6     {
7         c++;
8         //printf("*");
9         c++;
10    }
11    else
12    {
13        c++;
14        for(int i=1; i<=n; i++)
15        {
16            c++;
17            for(int j=1; j<=n; j++)
18            {
19                c++;
20                //printf("*");
21                c++;
22                c++;
23            }
24            printf("%d",c);
25        }
26    int main(){
27        int n;
28        scanf("%d",&n);
29        func(n);
30    }
```

	Input	Expected	Got	
✓	2	12	12	✓
✓	1000	5002	5002	✓
✓	143	717	717	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Problem 3: Finding Complexity using Counter Method

Question 1 | Correct Mark 1.00 out of 1.00 [Flag question](#)

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {  
    for (i = 1; i <= num; ++i)  
    {  
        if (num % i == 0)  
        {  
            printf("%d ", i);  
        }  
    }  
}
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```
1 #include <stdio.h>
2 void Factor(int num)
3 {
4     int c = 0,i;
5     for ( i = 1; i <= num; ++i){
6         c++;
7
8         if (num % i== 0)
9         {
10            //printf("%d ", i);
11            c++;
12            }c++;
13        }c++;
14    printf("%d",c);
15 }
16
17
18 int main(){
19     int num;
20     scanf("%d",&num);
21     Factor(num);
22 }
```

	Input	Expected	Got	
✓	12	31	31	✓
✓	25	54	54	✓
✓	4	12	12	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Problem 4: Finding Complexity using Counter Method

Question 1 | Correct Mark 1.00 out of 1.00 [Flag question](#)

Convert the following algorithm into a program and find its time complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and `scanf()` and `count` variable `printf()` statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```
1 #include <stdio.h>
2 void function(int n)
3 {
4     int c=0;
5     c++;
6     for(int i=n/2;i<n;i++){
7         c++;
8         for(int j=1;j<n;j=2*j){
9             c++;
10            for(int k=1;k<n;k=k*2){
11                c++;
12                c++;
13                }c++;
14            }c++;
15        }c++;
16        printf("%d",c);
17    }
18 int main(){
19     int n;
20     scanf("%d",&n);
21     function(n);
22 }
```

	Input	Expected	Got	
✓	4	30	30	✓
✓	10	212	212	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Problem 5: Finding Complexity using counter method

Question 1 | Correct Mark 1.00 out of 1.00 [Flag question](#)

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
    int rev = 0, remainder;
    while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
    print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```
1 #include <stdio.h>
2 void reverse(int n)
3 {
4     int c=0;
5     int rev = 0, remainder;
6     c++;
7     while (n != 0)
8     {
9         c++;
10        remainder = n % 10;
11        c++;
12        rev = rev * 10 + remainder;
13        c++;
14        n/= 10;
15        c++;
16    }
17    //printf(rev);
18    printf("%d",c);
19 }
20 int main(){
21     int n;
22     scanf("%d",&n);
23     reverse(n);
24 }
```

	Input	Expected	Got	
✓	12	11	11	✓
✓	1234	19	19	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.