```
Practical No-5
Aim:
Data Analytics II
1. Implement logistic regression using Python/R to perform
classification on
Social_Network_Ads.csv dataset.
2. Compute Confusion matrix to find TP, FP, TN, FN, Accuracy, Error
rate, Precision, Recall
on the given dataset.

import numpy as np
import matplotlib.pyplot as plt
import pandas as pd

dataset = pd.read_csv(r"C:\Users\System21\Desktop\diabetes.csv")

dataset
```

	Pregnancies	Glucose	BloodPressure	SkinThickness	Insulin	BMI
0	6	148	72	35	0	33.6
1	1	85	66	29	0	26.6
2	8	183	64	0	0	23.3
3	1	89	66	23	94	28.1
4	0	137	40	35	168	43.1
..	...	...	...	...	...	...
763	10	101	76	48	180	32.9
764	2	122	70	27	0	36.8
765	5	121	72	23	112	26.2
766	1	126	60	0	0	30.1
767	1	93	70	31	0	30.4

	DiabetesPedigreeFunction	Age	Outcome
0	0.627	50	1
1	0.351	31	0
2	0.672	32	1
3	0.167	21	0
4	2.288	33	1
..	...	...	...
763	0.171	63	0

```
764                      0.340   27        0
765                      0.245   30        0
766                      0.349   47        1
767                      0.315   23        0

[768 rows x 9 columns]
```

```
dataset.describe()
```

```
       Pregnancies     Glucose  BloodPressure  SkinThickness
Insulin  \
count   768.000000  768.000000     768.000000     768.000000
768.000000
mean      3.845052  120.894531      69.105469      20.536458
79.799479
std       3.369578   31.972618      19.355807      15.952218
115.244002
min       0.000000    0.000000       0.000000       0.000000
0.000000
25%       1.000000   99.000000      62.000000       0.000000
0.000000
50%       3.000000  117.000000      72.000000      23.000000
30.500000
75%       6.000000  140.250000      80.000000      32.000000
127.250000
max      17.000000  199.000000     122.000000      99.000000
846.000000
```

```
              BMI  DiabetesPedigreeFunction          Age     Outcome
count  768.000000                768.000000  768.000000  768.000000
mean    31.992578                  0.471876   33.240885    0.348958
std      7.884160                  0.331329   11.760232    0.476951
min      0.000000                  0.078000   21.000000    0.000000
25%     27.300000                  0.243750   24.000000    0.000000
50%     32.000000                  0.372500   29.000000    0.000000
75%     36.600000                  0.626250   41.000000    1.000000
max     67.100000                  2.420000   81.000000    1.000000
```

```
import numpy as np
import matplotlib.pyplot as plt
from sklearn.linear_model import LinearRegression
def sigmoid(z):
    return 1/(1 + np.exp(-z))
X_linear = np.array([1, 2, 3, 4, 5]).reshape(-1, 1)
y_linear = np.array([2, 4, 6, 8, 10])
linear_model = LinearRegression()
linear_model.fit(X_linear, y_linear)
y_pred_linear = linear_model.predict(X_linear)
X_logistic = np.linspace(-6, 6, 100)
y_logistic = sigmoid(X_logistic)
```

```
plt.figure(figsize=(12, 5))
plt.subplot(1, 2, 1)
plt.scatter(X_linear, y_linear, color='blue', label="Actual Data")
plt.plot(X_linear, y_pred_linear, color='red', label="Linear
Regression")
plt.title("Linear Regression: y = b0 + b1 * x")
plt.xlabel("X values")
plt.ylabel("y values")
plt.legend()
plt.grid()
plt.subplot(1, 2, 2)
plt.plot(X_logistic, y_logistic, color='green', label="Sigmoid Curve")
plt.title("Logistic Regression: a(z) = 1 / (1 + e^-z)")
plt.xlabel("x values")
plt.ylabel("Probability (0 to 1)")
plt.legend()
plt.grid()
plt.show()
```




```
import pandas as pd
import numpy as np
import warnings
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import confusion_matrix, classification_report
from tabulate import tabulate

# Ignore future warnings
warnings.simplefilter(action='ignore', category=FutureWarning)
```

```
# Load the dataset
dataset = pd.read_csv("Social_Network_Ads.csv")

# Preview the dataset
print("\nDataset Preview: \n")
print(tabulate(dataset.head(), headers='keys', tablefmt='grid'))

# Prepare features and target
X = dataset[['Age', 'EstimatedSalary']].values
y = dataset['Purchased'].values

# Split the dataset into training and test sets
X_train, X_test, y_train, y_test = train_test_split(X, y,
test_size=0.25, random_state=42)

# Scale the features
scaler = StandardScaler()
X_train = scaler.fit_transform(X_train)
X_test = scaler.transform(X_test)

# Initialize and train the logistic regression model
multi_logistic = LogisticRegression(solver='lbfgs')
multi_logistic.fit(X_train, y_train)

# Make predictions on the test set
y_pred_multi = multi_logistic.predict(X_test)
print("\nLogistic Regression Predictions: \n", y_pred_multi)

# Create and display the confusion matrix
cm = confusion_matrix(y_test, y_pred_multi)
cm_df = pd.DataFrame(cm, index=["Actual 0", "Actual 1"],
columns=["Predicted 0", "Predicted 1"])
print("\nConfusion Matrix:\n")
print(tabulate(cm_df, headers='keys', tablefmt='grid'))

# Generate and display the classification report
report_df = pd.DataFrame(classification_report(y_test, y_pred_multi,
output_dict=True)).transpose()
print("\nClassification Report:\n")
print(tabulate(report_df, headers='keys', tablefmt='grid'))
```

```
Dataset Preview:

+----+-----------+----------+-------+------------------+-------------
+
|    |   User ID | Gender   |   Age |   EstimatedSalary |   Purchased
|
+====+===========+==========+=======+==================+=============
+
```

```
|  0 |  15624510 | Male     |    19 |              19000 |           0
|
+----+-----------+----------+-------+--------------------+-------------
+
|  1 |  15810944 | Male     |    35 |              20000 |           0
|
+----+-----------+----------+-------+--------------------+-------------
+
|  2 |  15668575 | Female   |    26 |              43000 |           0
|
+----+-----------+----------+-------+--------------------+-------------
+
|  3 |  15603246 | Female   |    27 |              57000 |           0
|
+----+-----------+----------+-------+--------------------+-------------
+
|  4 |  15804002 | Male     |    19 |              76000 |           0
|
+----+-----------+----------+-------+--------------------+-------------
+

Logistic Regression Predictions:
 [0 1 0 1 0 0 1 0 0 0 0 1 0 0 0 0 1 1 0 1 0 0 0 1 0 0 1 0 1 0 0 0 1 0
1 0 0
 0 0 0 0 0 0 0 0 1 0 0 0 0 0 1 0 0 0 0 1 0 0 0 0 0 1 0 0 0 1 1 0 0 1 0
0 0
 0 0 1 1 0 0 0 0 1 0 1 0 0 1 0 0 1 0 0 0 0 0 1 0 1 0]

Confusion Matrix:

+----------+---------------+---------------+
|          |   Predicted 0 |   Predicted 1 |
+==========+===============+===============+
| Actual 0 |            61 |             2 |
+----------+---------------+---------------+
| Actual 1 |            12 |            25 |
+----------+---------------+---------------+

Classification Report:

+--------------+-------------+----------+------------+-----------+
|              |   precision |   recall |   f1-score |   support |
+==============+=============+==========+============+===========+
| 0            |    0.835616 | 0.968254 |   0.897059 |     63    |
+--------------+-------------+----------+------------+-----------+
| 1            |    0.925926 | 0.675676 |   0.78125  |     37    |
+--------------+-------------+----------+------------+-----------+
| accuracy     |    0.86     | 0.86     |   0.86     |      0.86 |
+--------------+-------------+----------+------------+-----------+
| macro avg    |    0.880771 | 0.821965 |   0.839154 |    100    |
```

```
+--------------+-------------+----------+------------+-----------+
| weighted avg |    0.869031 | 0.86     |   0.85421  |    100    |
+--------------+-------------+----------+------------+-----------+
```

```
import pandas as pd
import numpy as np
import seaborn as sns
import matplotlib.pyplot as plt
import warnings
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import confusion_matrix
warnings.simplefilter(action='ignore', category=FutureWarning)
dataset = pd.read_csv("Social_Network_Ads.csv")
X = dataset[['Age', 'EstimatedSalary']].values
y = dataset['Purchased'].values
X_train, X_test, y_train, y_test = train_test_split(X, y,
test_size=0.25, random_state=42)
scaler = StandardScaler()
X_train = scaler.fit_transform(X_train)
X_test = scaler.transform(X_test)
logistic_model = LogisticRegression(solver='lbfgs')
logistic_model.fit(X_train, y_train)
y_pred = logistic_model.predict(X_test)
cm = confusion_matrix(y_test, y_pred)
plt.figure(figsize=(5, 4))
sns.heatmap(cm, annot=True, fmt='d', cmap='Blues',
xticklabels=["Predicted 0", "Predicted 1"], yticklabels=["Actual 0",
"Actual 1"])
plt.xlabel("Predicted", fontsize=12, color="purple")
plt.ylabel("Actual", fontsize=12, color="purple")
plt.title("Confusion Matrix", fontsize=14, color="blue")
plt.show()
```




```
import numpy as np
import matplotlib.pyplot as plt

def sigmoid(z):
    return 1/(1 + np.exp(-z))

z = np.linspace(-10, 10, 100)
plt.plot(z, sigmoid(z))
plt.title("Sigmoid Function")
plt.xlabel("z")
plt.ylabel("a(z)")
plt.grid()
plt.show()
```




```
13229 Shruti Manwar
```