


Stanford CS224W: Node Embeddings

CS224W: Machine Learning with Graphs
Jure Leskovec, Stanford University
<http://cs224w.stanford.edu>




Recap: Traditional ML for Graphs

Given an input graph, extract node, link and graph-level features, learn a model (SVM, neural network, etc.) that maps features to labels.




Graph Representation Learning

Graph Representation Learning alleviates the need to do feature engineering **every single time**.





Graph Representation Learning

Goal: Efficient task-independent feature learning for machine learning with graphs!



Why Embedding?

- **Task: Map nodes into an embedding space**
 - Similarity of embeddings between nodes indicates their similarity in the network. For example:
 - Both nodes are close to each other (connected by an edge)
 - Encode network information
 - Potentially used for many downstream predictions



Tasks

- Node classification
- Link prediction
- Graph classification
- Anomalous node detection
- Clustering
-

Example Node Embedding

- 2D embedding of nodes of the Zachary's Karate Club network:





Image from: [Perozzi et al.](#) DeepWalk: Online Learning of Social Representations. *KDD 2014*.


Stanford CS224W: Node Embeddings: Encoder and Decoder

CS224W: Machine Learning with Graphs
Jure Leskovec, Stanford University
<http://cs224w.stanford.edu>



"Shallow" Encoding

Simplest encoding approach: **encoder is just an embedding-lookup**



“Shallow” Encoding

Simplest encoding approach: **Encoder is just an embedding-lookup**

**Each node is assigned a unique
embedding vector**

(i.e., we directly optimize
the embedding of each node)


Many methods: DeepWalk, node2vec

Note on Node Embeddings


- This is **unsupervised/self-supervised** way of learning node embeddings.
 - We are **not** utilizing node labels
 - We are **not** utilizing node features
 - The goal is to directly estimate a set of coordinates (i.e., the embedding) of a node so that some aspect of the network structure (captured by DEC) is preserved.
- These embeddings are **task independent**
 - They are not trained for a specific task but can be used for any task.

Stanford CS224W: Random Walk Approaches for Node Embeddings

CS224W: Machine Learning with Graphs
Jure Leskovec, Stanford University
<http://cs224w.stanford.edu>




Random Walk




Given a *graph* and a *starting point*, we **select a neighbor** of it at **random**, and move to this neighbor; then we select a neighbor of this point at random, and move to it, etc. The (random) sequence of points visited this way is a **random walk on the graph**.

Random-Walk Embeddings

1. Estimate probability of visiting node v on a random walk starting from node u using some random walk strategy R



2. Optimize embeddings to encode these random walk statistics:



Similarity in embedding space (Here: dot product = $\cos(\theta)$) encodes random walk “similarity”

Unsupervised Feature Learning

- **Intuition:** Find embedding of nodes in d -dimensional space that preserves similarity
- **Idea:** Learn node embedding such that **nearby** nodes are close together in the network
- **Given a node u , how do we define nearby nodes?**
 - $N_R(u)$... neighbourhood of u obtained by some **random walk strategy R**



Random Walks: Summary

1. Run **short fixed-length** random walks starting from each node on the graph
2. For each node u collect $N_R(u)$, the multiset of nodes visited on random walks starting from u .
3. Optimize embeddings using Stochastic Gradient Descent:

$$\mathcal{L} = \sum_{u \in V} \sum_{v \in N_R(u)} -\log(P(v|\mathbf{z}_u))$$

We can efficiently approximate this using
negative sampling!

Node2vec = Random walks + Word2vec



Summary so far

- **Core idea:** Embed nodes so that distances in embedding space reflect node similarities in the original network.
- **Different notions of node similarity:**
 - Naïve: similar if two nodes are connected
 - Neighborhood overlap (covered in Lecture 2)
 - Random walk approaches (**covered today**)


Stanford CS224W: Embedding Entire Graphs

CS224W: Machine Learning with Graphs
Jure Leskovec, Stanford University
<http://cs224w.stanford.edu>



Embedding Entire Graphs

- **Goal:** Want to embed a subgraph or an entire graph G . Graph embedding: \mathbf{z}_G .



- **Tasks:**
 - Classifying toxic vs. non-toxic molecules
 - Identifying anomalous graphs

Simple (but effective) approach 1:

- Run a standard graph embedding technique *on* the (sub)graph G .
- Then just sum (or average) the node embeddings in the (sub)graph G .

$$\mathbf{z}_G = \sum_{v \in G} \mathbf{z}_v$$

- Used by [Duvenaud et al., 2016](#) to classify molecules based on their graph structure

How to Use Embeddings

- **How to use embeddings \mathbf{z}_i of nodes:**
 - **Clustering/community detection:** Cluster points \mathbf{z}_i
 - **Node classification:** Predict label of node i based on \mathbf{z}_i
 - **Link prediction:** Predict edge (i, j) based on $(\mathbf{z}_i, \mathbf{z}_j)$
 - Where we can: concatenate, avg, product, or take a difference between the embeddings:
 - Concatenate: $f(\mathbf{z}_i, \mathbf{z}_j) = g([\mathbf{z}_i, \mathbf{z}_j])$
 - Hadamard: $f(\mathbf{z}_i, \mathbf{z}_j) = g(\mathbf{z}_i * \mathbf{z}_j)$ (per coordinate product)
 - Sum/Avg: $f(\mathbf{z}_i, \mathbf{z}_j) = g(\mathbf{z}_i + \mathbf{z}_j)$
 - Distance: $f(\mathbf{z}_i, \mathbf{z}_j) = g(\|\mathbf{z}_i - \mathbf{z}_j\|_2)$
 - **Graph classification:** Graph embedding \mathbf{z}_G via aggregating node embeddings or anonymous random walks. Predict label based on graph embedding \mathbf{z}_G .