

# CSE 220

## Data Structures

### Lecture 01: Introduction to Time and Space Complexity

Anwarul Bashir Shuaib [ABS]  
Lecturer  
Department of Computer Science and Engineering  
BRAC University



# Topics to Review

- 1D Arrays:
  - Declaration, initialization, and traversal.
  - Insertion, deletion, and updating elements.
  - Searching (Linear Search).
  - Sorting (Bubble Sort, Selection Sort, Insertion Sort).
- 2D Arrays:
  - Declaration, initialization, and traversal.
  - Row-major and column-major storage.
  - Common operations (matrix addition, multiplication, transpose).
- Pointers (Optional but Useful) – Understanding array-pointer relationship for dynamic memory allocation.



# Why Is Complexity Important?

- Efficiency Matters:
  - As input size grows, some algorithms become too slow or use too much memory.



# Why Is Complexity Important?

- Efficiency Matters:
  - As input size grows, some algorithms become too slow or use too much memory.
  - Complexity helps us predict how an algorithm will perform as input scales.



# Why Is Complexity Important?

- Efficiency Matters:
  - As input size grows, some algorithms become too slow or use too much memory.
  - Complexity helps us predict how an algorithm will perform as input scales.
- Real-World Problems:
  - Computers are fast, but real-world problems can be huge (e.g., multiplying giant matrices or searching through millions of records).



# Why Is Complexity Important?

- Efficiency Matters:
  - As input size grows, some algorithms become too slow or use too much memory.
  - Complexity helps us predict how an algorithm will perform as input scales.
- Real-World Problems:
  - Computers are fast, but real-world problems can be huge (e.g., multiplying giant matrices or searching through millions of records).
  - Even with powerful computers, inefficient programs can take too long or use too much memory.



# Which Code Runs Faster?

```
public static int findSum(int[] arr) {  
    int total = 0;  
    for (int num : arr) {  
        total += num;  
    }  
    return total;  
}
```

```
public static List<int[]> findPairs(int[] arr) {  
    List<int[]> pairs = new ArrayList<>();  
    for (int i : arr) {  
        for (int j : arr) {  
            pairs.add(new int[]{i, j});  
        }  
    }  
    return pairs;  
}
```

# Which Code Runs Faster?



```
public static int findSum(int[] arr) {  
    int total = 0;  
    for (int num : arr) {  
        total += num;  
    }  
    return total;  
}
```

$O(n)$

```
public static List<int[]> findPairs(int[] arr) {  
    List<int[]> pairs = new ArrayList<>();  
    for (int i : arr) {  
        for (int j : arr) {  
            pairs.add(new int[]{i, j});  
        }  
    }  
    return pairs;  
}
```

$O(n^2)$



# What is Big-O? (Simplified!)

- Big-O is like a "*speedometer*" for your code.



# What is Big-O? (Simplified!)

- Big-O is like a "*speedometer*" for your code.
  - It tells you **how fast your code runs** or **how much memory it uses** as the input grows.



# What is Big-O? (Simplified!)

- Big-O is like a "*speedometer*" for your code.
  - It tells you **how fast your code runs** or **how much memory it uses** as the input grows.
  - **It's Not Exact:** Big-O doesn't count every single step. Instead, it gives you a general idea of **how your code scales**.



# What is Big-O? (Simplified!)

- Big-O is like a "*speedometer*" for your code.
  - It tells you **how fast your code runs** or **how much memory it uses** as the input grows.
  - **It's Not Exact:** Big-O doesn't count every single step. Instead, it gives you a general idea of **how your code scales**.
- Example:
  - If your code takes  $3n^2 + 2n + 1$  steps, Big-O simplifies it to  $O(n^2)$



# What is Big-O? (Simplified!)

- Big-O is like a "*speedometer*" for your code.
  - It tells you **how fast your code runs** or **how much memory it uses** as the input grows.
  - **It's Not Exact:** Big-O doesn't count every single step. Instead, it gives you a general idea of **how your code scales**.
- Example:
  - If your code takes  $3n^2 + 2n + 1$  steps, Big-O simplifies it to  $O(n^2)$
  - Why? Because as  $n$  gets really big, the  $n^2$  part dominates the others



# How do we find the complexity?

```
public static int addNums(int a, int b, int c) {  
    int sum = a + b + c;  
    return sum;  
}
```



# How do we find the complexity?

```
public static int addNums(int a, int b, int c) {  
    int sum = a + b + c;  
    return sum;  
}
```

Exact run time complexity:  $c + c = 2c$



# How do we find the complexity?

```
public static int findSum(int[] arr) {  
    int total = 0;  
    for (int num : arr) {  
        total += num;  
    }  
    return total;  
}
```

Exact run time complexity:  $c + nc + c = c(n + 2)$



# How do we find the complexity?

```
public static int[] findElementAndSum(int[] arr, int target) {  
    int element = -1; // assuming -1 for simplicity  
    int sum = 0;  
    for (int i : arr) {  
        if (i == target) element = i;  
    }  
    for (int i : arr) {  
        sum += i;  
    }  
    return new int[]{element, sum};  
}
```

Exact run time complexity:  $c + c + n \cdot (c + c) + nc + c = 3c(n + 1)$

# How do we find the complexity?

```
public static int[] findElementAndSum(int[] arr, int target) {  
    int element = -1; // assuming -1 for simplicity  
    int sum = 0;  
    for (int i : arr) {  
        if (i == target) element = i;  
    }  
    for (int i : arr) {  
        sum += i;  
    }  
    return new int[]{element, sum};  
}
```

We only consider the worst-case scenario

Exact run time complexity:  $c + c + n \cdot (c + c) + nc + c = 3c(n + 1)$

# How do we find the complexity?

```
public static List<int[]> findPairs(int[] arr) {  
    List<int[]> pairs = new ArrayList<>();  
    for (int i : arr) {  
        for (int j : arr) {  
            pairs.add(new int[]{i, j});  
        }  
    }  
    return pairs;  
}
```

Exact run time complexity:  $c + n \cdot n \cdot c + c = c(n^2 + 2)$

# How do we find the complexity?

```
public static List<int[]> findPairs(int[] arr) {  
    List<int[]> pairs = new ArrayList<>();  
    for (int i : arr) {  
        for (int j : arr) {  
            pairs.add(new int[]{i, j});  
        }  
    }  
    return pairs;  
}
```

Exact run time complexity:  $c + n \cdot n \cdot c + c = c(n^2 + 2)$

**Think:** Why  $n \cdot n$  instead of  $n + n$ ?

# What Is *Asymptotic* Complexity?

- Big-O focuses on how an algorithm's performance scales as the input size ( $n$ ) grows.



# What Is *Asymptotic* Complexity?

- Big-O focuses on how an algorithm's performance scales as the input size ( $n$ ) grows.
- We **ignore constant factors and lower-order terms** because they become insignificant for large inputs.




# What Is *Asymptotic* Complexity?

- Big-O focuses on how an algorithm's performance scales as the input size ( $n$ ) grows.
- We **ignore constant factors and lower-order terms** because they become insignificant for large inputs.
- This Big-O notation is sometimes called the “**Order of Growth**”



# What Is Asymptotic Complexity?




\*Axes have been scaled to logarithmic for better visualization


powered by  
desmos



# What Is Asymptotic Complexity?



# What Is Asymptotic Complexity?



# How do we find the order of growth?

```
public static int addNums(int a, int b, int c) {  
    int sum = a + b + c;  
    return sum;  
}
```

Exact run time complexity:  $c + c = 2c$



# How do we find the order of growth?

```
public static int addNums(int a, int b, int c) {  
    int sum = a + b + c;  
    return sum;  
}
```

Exact run time complexity:  $c + c = 2c$

Asymptotic complexity:  $O(1)$



# How do we find the order of growth?

```
public static int addNums(int a, int b, int c) {  
    int sum = a + b + c;  
    return sum;  
}
```

Exact run time complexity:  $c + c = 2c$

Asymptotic complexity:  $O(1)$  → Constant Time



# How do we find the order of growth?

```
public static int findSum(int[] arr) {  
    int total = 0;  
    for (int num : arr) {  
        total += num;  
    }  
    return total;  
}
```

Exact run time complexity:  $c + nc + c = c(n + 2)$

# How do we find the order of growth?

```
public static int findSum(int[] arr) {  
    int total = 0;  
    for (int num : arr) {  
        total += num;  
    }  
    return total;  
}
```

Exact run time complexity:  $c + nc + c = c(n + 2)$

Asymptotic complexity:  $O(n)$  → Linear Time

# How do we find the order of growth?

```
public static int[] findElementAndSum(int[] arr, int target) {  
    int element = -1; // assuming -1 for simplicity  
    int sum = 0;  
    for (int i : arr) {  
        if (i == target) element = i;  
    }  
    for (int i : arr) {  
        sum += i;  
    }  
    return new int[]{element, sum};  
}
```

Exact run time complexity:  $c + c + n \cdot (c + c) + nc + c = 3c(n + 1)$



# How do we find the order of growth?

```
public static int[] findElementAndSum(int[] arr, int target) {  
    int element = -1; // assuming -1 for simplicity  
    int sum = 0;  
    for (int i : arr) {  
        if (i == target) element = i;  
    }  
    for (int i : arr) {  
        sum += i;  
    }  
    return new int[]{element, sum};  
}
```

Exact run time complexity:  $c + c + n \cdot (c + c) + nc + c = 3c(n + 1)$

Asymptotic complexity:  $O(n)$  → Linear Time

# How do we find the order of growth?

```
public static List<int[]> findPairs(int[] arr) {  
    List<int[]> pairs = new ArrayList<>();  
    for (int i : arr) {  
        for (int j : arr) {  
            pairs.add(new int[]{i, j});  
        }  
    }  
    return pairs;  
}
```

Exact run time complexity:  $c + n \cdot n \cdot c + c = c(n^2 + 2)$

# How do we find the order of growth?


```
public static List<int[]> findPairs(int[] arr) {  
    List<int[]> pairs = new ArrayList<>();  
    for (int i : arr) {  
        for (int j : arr) {  
            pairs.add(new int[]{i, j});  
        }  
    }  
    return pairs;  
}
```

Exact run time complexity:  $c + n \cdot n \cdot c + c = c(n^2 + 2)$

Asymptotic complexity:  $O(n^2) \rightarrow$  Quadratic Time



# So...What Should We Prefer?



jwcarroll  
@jwcarroll

Alternative Big O notation:

$O(1) = O(\text{yeah})$   
 $O(\log n) = O(\text{nice})$   
 $O(n) = O(\text{ok})$   
 $O(n^2) = O(\text{my})$   
 $O(2^n) = O(\text{no})$   
 $O(n!) = O(\text{mg!})$

8:10 PM · 06 Apr 19 · [Twitter for Android](#)

# Practice

- How would we perform a linear search in an array? What would be its time complexity (the order of growth)?



# Practice

- How would we perform a linear search in an array? What would be its time complexity (the order of growth)?

```
public static int linearSearch(int[] arr, int target) {  
    for (int i : arr) {  
        if (i == target)  
            return i;  
    }  
    return -1;  
}
```

# Practice

- How would we perform a linear search in an array? What would be its time complexity (the order of growth)?

```
public static int linearSearch(int[] arr, int target) {  
    for (int i : arr) {  
        if (i == target)  
            return i;  
    }  
    return -1;  
}
```

Time complexity:  $O(n)$

# Practice

- How would we perform a linear search in an array? What would be its time complexity (the order of growth)?

```
public static int linearSearch(int[] arr, int target) {  
    for (int i : arr) {  
        if (i == target)  
            return i;  
    }  
    return -1;  
}
```

Time complexity:  $O(n)$

**Think:** Why  $O(n)$ ? Why not  $O(1)$  when the target is at `arr[0]`? 40



# Practice

- Can we improve it? What if the array is sorted beforehand?



# Practice

- Can we improve it? What if the array is sorted beforehand?

```
public static int binarySearch(int[] arr, int target) {  
    int left = 0;  
    int right = arr.length - 1;  
    while (left <= right) {  
        int mid = (left + right) / 2;  
        if(arr[mid] == target) return mid;  
        else if (arr[mid] > target) right = mid - 1;  
        else left = mid + 1;  
    }  
    return -1;  
}
```

See a nice demo [here](#)



# Practice

- Can we improve it? What if the array is sorted beforehand?

```
public static int binarySearch(int[] arr, int target) {  
    int left = 0;  
    int right = arr.length - 1;  
    while (left <= right) {  
        int mid = (left + right) / 2;  
        if(arr[mid] == target) return mid;  
        else if (arr[mid] > target) right = mid - 1;  
        else left = mid + 1;  
    }  
    return -1;  
}
```

See a nice demo [here](#)

Time complexity:  $O(\log n)$   $\Rightarrow$  Logarithmic time




# Seeing the Impact!



powered by  
desmos

# Seeing the Impact!



# Practice

- What about 2D matrix multiplication?

```
public static int[][] matMul(int[][] matA, int[][] matB) {  
    int m = matA.length;        // Rows in matA  
    int n = matA[0].length;      // Columns in matA  
    int r = matB.length;        // Rows in matB  
    int p = matB[0].length;      // Columns in matB  
    if (n != r) {  
        System.out.println("Dimension mismatch");  
        return null;  
    }  
    int[][] result = new int[m][p];  
    for (int i = 0; i < m; i++) {  
        for (int j = 0; j < p; j++) {  
            for (int k = 0; k < n; k++) {  
                result[i][j] += matA[i][k] * matB[k][j];  
            }  
        }  
    }  
    return result;  
}
```



# Practice

- What about 2D matrix multiplication?

```
public static int[][] matMul(int[][] matA, int[][] matB) {
    int m = matA.length;        // Rows in matA
    int n = matA[0].length;      // Columns in matA
    int r = matB.length;        // Rows in matB
    int p = matB[0].length;      // Columns in matB
    if (n != r) {
        System.out.println("Dimension mismatch");
        return null;
    }
    int[][] result = new int[m][p];
    for (int i = 0; i < m; i++) {
        for (int j = 0; j < p; j++) {
            for (int k = 0; k < n; k++) {
                result[i][j] += matA[i][k] * matB[k][j];
            }
        }
    }
    return result;
}
```

Time complexity:  $O(n^3)$



# The Power of Efficient Algorithms

- Converting an  $O(n^3)$  algorithm to  $O(n^2)$  can make the difference between impossible and practical.





# The Power of Efficient Algorithms

- Converting an  $O(n^3)$  algorithm to  $O(n^2)$  can make the difference between impossible and practical.
- Say,  $n=1000000$ , 2GHz CPU ( $2 \times 10^9$  operations / second)
  - With  $O(n^3) \Rightarrow$
  - With  $O(n^2) \Rightarrow$



# The Power of Efficient Algorithms

- Converting an  $O(n^3)$  algorithm to  $O(n^2)$  can make the difference between impossible and practical.
- Say,  $n=1000000$ , 2GHz CPU ( $2 \times 10^9$  operations / second)
  - With  $O(n^3) \Rightarrow 10^{18}$  operations
  - With  $O(n^2) \Rightarrow 10^{12}$  operations



# The Power of Efficient Algorithms

- Converting an  $O(n^3)$  algorithm to  $O(n^2)$  can make the difference between impossible and practical.
- Say,  $n=1000000$ , 2GHz CPU ( $2 \times 10^9$  operations / second)
  - With  $O(n^3) \Rightarrow 10^{18}$  operations  $\Rightarrow$  approx 16 years!
  - With  $O(n^2) \Rightarrow 10^{12}$  operations  $\Rightarrow$  8.3 minutes!



# Space Complexity

- Same type of analysis goes for memory consumption as well



# Space Complexity

- Same type of analysis goes for memory consumption as well
  - Space complexity measures how much memory an algorithm uses as the input size ( $n$ ) grows.

-----



# Space Complexity

- Same type of analysis goes for memory consumption as well
  - Space complexity measures how much memory an algorithm uses as the input size ( $n$ ) grows.
  - Memory is valuable!
  - 1D array
  - 2D array




# Space Complexity

- Same type of analysis goes for memory consumption as well
  - Space complexity measures how much memory an algorithm uses as the input size ( $n$ ) grows.
  - Memory is valuable!
  - 1D array  $\Rightarrow O(n)$  space complexity
  - 2D array  $\Rightarrow O(n^2)$  space complexity



# Time Complexity vs Space Complexity

- **Time Complexity:**
  - Measures how fast an algorithm runs.
- **Space Complexity:**
  - Measures how much memory an algorithm uses.
- **Trade-Off:**
  - Sometimes, you can save time by using more memory, or save memory by using more time.





# Examples

```
public static int sumNumbers(int a, int b) { no usages
    return a + b; // O(1) space
}

public static int[] create1DArray(int size) { no usages
    return new int[size]; // O(n) space
}

public static int[][] create2DArray(int rows, int cols) { no usages
    return new int[rows][cols]; // O(n^2) space
}
```

Doesn't matter if we are using a loop to initialize the array or not

# Pitfall

String concatenation may not be constant as we might think!

```
public static String badStringConcat(int n) { no usages
    String s = "";
    for (int i = 0; i < n; i++) {
        s += "a";
    }
    return s;
}
```



# Pitfall

String concatenation may not be constant as we might think!

```
public static String badStringConcat(int n) { no usages
    String s = "";
    for (int i = 0; i < n; i++) { // O(n) loop
        s += "a"; // O(n) operation, not constant!
    }
    return s;
}
```



# Some Common Order of Growth Functions

order of growth	name	typical code framework	description	example
1	<b>constant</b>	<code>a = b + c;</code>	statement	add two numbers
$\log N$	<b>logarithmic</b>	<pre>while (N &gt; 1) {   N = N / 2; ... }</pre>	divide in half	binary search
$N$	<b>linear</b>	<pre>for (int i = 0; i &lt; N; i++) {   ... }</pre>	loop	find the maximum
$N \log N$	<b>linearithmic</b>	[see mergesort lecture]	divide and conquer	mergesort
$N^2$	<b>quadratic</b>	<pre>for (int i = 0; i &lt; N; i++)   for (int j = 0; j &lt; N; j++)   {     ...   }</pre>	double loop	check all pairs
$N^3$	<b>cubic</b>	<pre>for (int i = 0; i &lt; N; i++)   for (int j = 0; j &lt; N; j++)     for (int k = 0; k &lt; N; k++)     {       ...     }</pre>	triple loop	check all triples
$2^N$	<b>exponential</b>	[see combinatorial search lecture]	exhaustive search	check all subsets

# Things Can Get Complicated 🤪

```
def sum_array(arr, i = 0):
    if i == len(arr):
        return 0
    return arr[i] + sum_array(arr, i + 1)
```

O(n)

```
def binary_search(arr, target, low = 0, high = None):
    if high is None:
        high = len(arr) - 1
    if low > high:
        return -1
    mid = (low + high) // 2
    if arr[mid] == target:
        return mid
    elif arr[mid] < target:
        return binary_search(arr, target, mid + 1, high)
    else:
        return binary_search(arr, target, low, mid - 1)
```

O(logn)


```
def fib(n):
    if n <= 1:
        return n
    return fib(n-1) + fib(n-2)
```

O(2^n)



# Conclusion: Efficiency Beats Raw Power

- A supercomputer can perform trillions of calculations per second.
- But if it runs an inefficient algorithm (e.g.,  $O(n^3)$  or  $O(n^2)$  ) it can still struggle with large inputs.
- A normal computer running an efficient algorithm (e.g.,  $O(n)$  or  $O(n \log n)$  ) can outperform a supercomputer running an inefficient one.



# Homework

- You have an n-bit secret integer. What would be the time complexity of an algorithm that tries to guess this integer?
- Find the space complexity of storing all possible permutations of a given string.
- Find the time complexity of generating all possible subsets of a given set.
  - Hint:  $\{1,2,3\} \Rightarrow \{ \{\}, \{1\}, \{2\}, \{3\}, \{1,2\}, \{2,3\}, \{3,1\}, \{1,2,3\} \}$



# Homework

- You have a list of integers. Find pairs of integers (a,b) such that  $a+b = 0$ 
  - $O(n^2)$  time  $\Rightarrow$  Brute force
  - $O(n \log n)$  time  $\Rightarrow$  Sorting + Binary search
  - $O(n)$  time  $\Rightarrow$  Hashmap (Will study later in this course)
  - Try to figure out the space complexity for each approach!



# Reading Materials

- <https://medium.com/@hlfdev/algorithms-discover-the-power-of-big-o-notation-17a367bd62a>



