


# Learning Distributed Representations of Symbolic Structure Using Binding and Unbinding Operations

Shuai Tang, Paul Smolensky, Virginia R. de Sa



UC San Diego  
Cognitive Science





Shuai Tang  
Cognitive Science  
UC San Diego



Paul Smolensky  
Cognitive Science  
Johns Hopkins University  
Microsoft Research AI



Virginia R. de Sa  
Cognitive Science  
UC San Diego

# Outline

- Motivations
- Our Proposed Recurrent Unit
- Experiments
- Conclusions

# Outline

- Motivations
- Our Proposed Recurrent Unit
- Experiments
- Conclusions

## Distributed Representations

- Inducing structure in data
- Considerable power in statistical inference
- Encoding word knowledge
- Efficient usage of representation space

## Symbolic Computing Systems

- Symbol ---- Substructure
  - Representations maintain the structure of data explicitly
  - Each substructure can be retrieved with no loss
- Inducing implicit structure from data
  - unique symbol ---- potential substructure

## Distributed Representations + Symbolic Computing Systems

- Inducing structure in data
- Considerable power in statistical inference
- Encoding word knowledge
- Efficient usage of representation space

- Symbol ---- Substructure
  - Representations maintain the structure of data explicitly
  - Each substructure can be retrieved with no loss
- Inducing implicit structure from data
  - unique symbol ---- potential substructure

Learning Structured  
Distributed Representations

# Tensor Product Representations (TPRs)

$$\mathbf{S} = \sum_{i=1}^N \mathbf{r}_i \otimes \mathbf{f}_i = \sum_{i=1}^N \mathbf{r}_i \mathbf{f}_i^\top = \mathbf{R} \mathbf{F}^\top$$

- Binding Operation


$$\mathbf{r}_i \otimes \mathbf{f}_i$$

- Unbinding Operation

$$\mathbf{f}_i = \mathbf{u}_i^\top \mathbf{S}$$

$$\mathbf{u}_i^\top \mathbf{r}_j = \delta_{ij}$$

# Tensor Product Representations (TPRs)

$$S = \sum_{i=1}^N \mathbf{r}_i \otimes \mathbf{f}_i = \sum_{i=1}^N \mathbf{r}_i \mathbf{f}_i^\top = \mathbf{R} \mathbf{F}^\top$$


Symbols

- Binding Operation
- Unbinding Operation

$$\mathbf{r}_i \otimes \mathbf{f}_i$$

$$\mathbf{f}_i = \mathbf{u}_i^\top \mathbf{S}$$

$$\mathbf{u}_i^\top \mathbf{r}_j = \delta_{ij}$$

Positions in a string

Part-of-speech tags

Context



# Tensor Product Representations (TPRs)

$$S = \sum_{i=1}^N \mathbf{r}_i \otimes \mathbf{f}_i = \sum_{i=1}^N \mathbf{r}_i \mathbf{f}_i^\top = \mathbf{R} \mathbf{F}^\top$$

- Binding Operation

$$\mathbf{r}_i \otimes \mathbf{f}_i$$

- Unbinding Operation

$$\mathbf{f}_i = \mathbf{u}_i^\top \mathbf{S}$$

$$\mathbf{u}_i^\top \mathbf{r}_j = \delta_{ij}$$

## Vector Representations

$$\mathbf{b} = \mathbf{R} \mathbf{f} \quad \text{and} \quad \mathbf{f} = \mathbf{U}^\top \mathbf{b}$$

# Tensor Product Representations (TPRs)

$$S = \sum_{i=1}^N \mathbf{r}_i \otimes \mathbf{f}_i = \sum_{i=1}^N \mathbf{r}_i \mathbf{f}_i^\top = \mathbf{R} \mathbf{F}^\top$$

- Binding Operation
- Unbinding Operation

$$\mathbf{r}_i \otimes \mathbf{f}_i$$

$$\mathbf{f}_i = \mathbf{u}_i^\top \mathbf{S}$$

$$\mathbf{u}_i^\top \mathbf{r}_j = \delta_{ij}$$

simplify

Vector Representations

simplify

$$\mathbf{b} = \mathbf{R} \mathbf{f}$$

and

$$\mathbf{f} = \mathbf{U}^\top \mathbf{b}$$

# Tensor Product Representations (TPRs)

$$S = \sum_{i=1}^N r_i \otimes f_i = \sum_{i=1}^N r_i f_i^\top = RF^\top$$

- Binding Operation

$$r_i \otimes f_i$$

- Unbinding Operation

$$f_i = u_i^\top S$$

$$u_i^\top r_j = \delta_{ij}$$

## Vector Representations

$$b = Rf$$

and

$$f = U^\top b$$

binding complex

binding complex

# Tensor Product Representations (TPRs)

$$S = \sum_{i=1}^N \mathbf{r}_i \otimes \mathbf{f}_i = \sum_{i=1}^N \mathbf{r}_i \mathbf{f}_i^\top = \mathbf{R} \mathbf{F}^\top$$

- Binding Operation

$$\mathbf{r}_i \otimes \mathbf{f}_i$$

- Unbinding Operation

$$\mathbf{f}_i = \mathbf{u}_i^\top \mathbf{S}$$

$$\mathbf{u}_i^\top \mathbf{r}_j = \delta_{ij}$$

Vector Representations

$$\mathbf{b} = \mathbf{R} \mathbf{f} \quad \text{and} \quad \mathbf{f} = \mathbf{U}^\top \mathbf{b}$$


learned





# Outline

- Motivations
- **Our Proposed Recurrent Unit**
- Experiments
- Conclusions


## TPRU – Recurrent Unit



# TPRU – Recurrent Unit



## TPRU – Recurrent Unit



- Unbinding operation  $\mathbf{f}_{b,t} = \mathbf{U}^\top \mathbf{b}_{t-1} \in \mathbb{R}^{N \times 1}, \quad \mathbf{f}_{x,t} = \mathbf{U}^\top \mathbf{W} \mathbf{x}_t \in \mathbb{R}^{N \times 1}$

$$(\tilde{\mathbf{f}}_{b,t})_n = \text{ReLU}((\mathbf{f}_{b,t})_n + b_b), \quad (\tilde{\mathbf{f}}_{x,t})_n = \text{ReLU}((\mathbf{f}_{x,t})_n + b_x)$$

$$(f_t)_n = \frac{\left((\tilde{\mathbf{f}}_{b,t})_n + (\tilde{\mathbf{f}}_{x,t})_n\right)^2}{\sum_{m=1}^N \left((\tilde{\mathbf{f}}_{b,t})_m + (\tilde{\mathbf{f}}_{x,t})_m\right)^2}$$

- Binding operation

$$\tilde{\mathbf{b}}_t = \mathbf{R} \mathbf{f}_t$$

- Input Gate

$$\mathbf{b}_t = \mathbf{g}_t \circ \tanh(\tilde{\mathbf{b}}_t) + (1 - \mathbf{g}_t) \circ \mathbf{b}_{t-1}$$

$$\mathbf{g}_t = \sigma(\mathbf{W}_b \mathbf{b}_{t-1} + \mathbf{W}_x \mathbf{x}_t)$$



# TPRU – Unbinding Vectors

$$U = W_u V$$

$$R = W_r V$$

- Unbinding operation

$$f_{b,t} = U^T b_{t-1} \in \mathbb{R}^{N \times 1}, \quad f_{x,t} = U^T W x_t \in \mathbb{R}^{N \times 1}$$

$$(\tilde{f}_{b,t})_n = \text{ReLU}((f_{b,t})_n - b_n), \quad (\tilde{f}_{x,t})_n = \text{ReLU}((f_{x,t})_n - b_n)$$

$$J(f)_{b,t} = \frac{(\tilde{f}_{b,t})_n + (\tilde{f}_{x,t})_n}{\sum_{n=1}^N ((f_{b,t})_n + (f_{x,t})_n)^2}$$

- Binding operation

$$\tilde{b}_t = R f_t$$

- Input Gate

$$b_t = g_t \circ \tanh(\tilde{b}_t) + (1 - g_t) \circ b_{t-1}$$

$$g_t = \sigma(W_b b_{t-1} + W_g x_t)$$

# TPRU – Binding Vectors

$$U = W_u V$$

$$R = W_r V$$

- Unbinding operation

$$\mathbf{f}_{b,t} = U^T \mathbf{b}_{t-1} \in \mathbb{R}^{N \times 1}, \quad \mathbf{f}_{x,t} = U^T \mathbf{W} \mathbf{x}_t \in \mathbb{R}^{N \times 1}$$

$$(\tilde{f}_{b,t})_n = \text{ReLU}((f_{b,t})_n - b_n), \quad (\tilde{f}_{x,t})_n = \text{ReLU}((f_{x,t})_n - b_n)$$

$$U_{n,k} = \frac{(\tilde{f}_{b,t})_n (\tilde{f}_{x,t})_k}{\sum_{n=1}^N (\tilde{f}_{b,t})_n (\tilde{f}_{x,t})_k}$$

- Binding operation

$$\tilde{\mathbf{b}}_t = R \mathbf{f}_t$$

- Input Gate

$$b_t = g_t \circ \tanh(\tilde{b}_t) + (1 - g_t) \circ b_{t-1}$$

$$g_t = \sigma(W_b b_{t-1} + W_g x_t)$$

## TPRU – Parameters

$$U = W_u V \quad R = W_r V$$

- Unbinding operation  $f_{b,t} = U^\top b_{t-1} \in \mathbb{R}^{N \times 1}, \quad f_{x,t} = U^\top W x_t \in \mathbb{R}^{N \times 1}$

$$(\tilde{f}_{b,t})_n = \text{ReLU}((f_{b,t})_n + b_b), \quad (\tilde{f}_{x,t})_n = \text{ReLU}((f_{x,t})_n + b_x)$$

$$(f_t)_n = \frac{\left((\tilde{f}_{b,t})_n + (\tilde{f}_{x,t})_n\right)^2}{\sum_{m=1}^N \left((\tilde{f}_{b,t})_m + (\tilde{f}_{x,t})_m\right)^2}$$

- Binding operation

$$\tilde{b}_t = R f_t$$

- Input Gate

$$b_t = g_t \circ \tanh(\tilde{b}_t) + (1 - g_t) \circ b_{t-1}$$
$$g_t = \sigma(W_b b_{t-1} + W_x x_t)$$

# Outline

- Motivations
- Our Proposed Recurrent Unit
- **Experiments**
- Conclusions

# Experiments

- Tasks
  - Logical Entailment in Propositional Logic (Evans et al., 2018)
  - Multi-genre Natural Language Inference (Williams et al., 2018)
  - General Purpose Sentence Representations (Conneau & Kiela, 2018)
- Plain & BiDAF architecture
  - BiDAF – Bi-Directional Attention Flow (Seo et al., 2017)

# Logical Entailment in Propositional Logic

- Training set
- Validation set
- Test set
  - easy, big, hard, massive, exam

Connectives matter

Table 4: A truth table for  $A = p \wedge q$  and  $B = q$ .

$p$	$q$	$A$	$B$	
T	T	T (1)	T (1)	(1 = 1)
T	F	F (0)	F (0)	(0 = 0)
F	T	F (0)	T (1)	(0 < 1)
F	F	F (0)	F (0)	(0 = 0)

# Logical Entailment in Propositional Logic

- Training set
- Validation set
- Test set
  - easy, big, hard, massive, exam

A:  $((g > ((xls)l((q \& i) \& o))) \& (s \& ((ilv)lx)))$

B:  $(\sim(((rls)lq)) > (\sim((q \& (ql(sl r)))) > (vlr)))$

Connectives matter

Table 4: A truth table for  $A = p \wedge q$  and  $B = q$ .

$p$	$q$	$A$	$B$	
T	T	T (1)	T (1)	(1 = 1)
T	F	F (0)	F (0)	(0 = 0)
F	T	F (0)	T (1)	(0 < 1)
F	F	F (0)	F (0)	(0 = 0)

# Logical Entailment in Propositional Logic

model	valid	easy	hard	test big	massive	exam	# params
Mean 2 <sup>#Vars</sup>	75.7	81.0	184.4	3310.8	848,570.0	5.8	
Plain (BiDAF) Architecture - dim 64							
LSTM	71.7 (88.5)	71.8 (88.7)	64.1 ( <b>74.5</b> )	64.2 ( <b>73.8</b> )	53.7 ( <b>66.8</b> )	68.3 ( <b>80.0</b> )	65.5k (230.0k)
GRU	75.1 (87.9)	<b>77.1</b> (88.3)	63.7 (72.5)	63.8 (71.3)	54.4 (66.1)	73.7 (78.0)	49.1k (172.4k)
Ours	8	66.8 (86.2)	67.2 (87.1)	59.3 (69.1)	60.9 (68.2)	51.9 (62.5)	40.1k (131.3k)
	32	73.7 (88.4)	73.7 (88.4)	62.7 (71.1)	62.8 (70.1)	53.0 (64.9)	
	128	75.9 (88.5)	76.0 (88.6)	<b>64.9</b> (71.5)	64.0 (69.8)	53.8 (64.1)	
	512	<b>76.8 (88.6)</b>	76.8 ( <b>89.2</b> )	64.4 (72.6)	<b>64.6</b> (71.2)	<b>54.6</b> (64.4)	
Plain (BiDAF) Architecture - dim 128							
LSTM †	64.5 ( <b>88.6</b> )	64.2 ( <b>89.3</b> )	59.7 ( <b>74.7</b> )	62.1 (73.5)	50.9 ( <b>67.4</b> )	65.0 (78.3)	196.6k (917.5k)
GRU ‡	<b>80.8</b> (86.2)	<b>80.3</b> (85.7)	65.9 (69.1)	<b>66.0</b> (69.1)	55.0 (63.1)	77.3 (72.7)	147.5k (688.1k)
Ours	8	63.7 (87.1)	63.4 (87.3)	57.5 (69.4)	59.6 (68.1)	51.3 (62.7)	131.1k (524.3k)
	32	71.5 (88.2)	71.7 (88.5)	62.6 (71.6)	62.4 (70.3)	52.0 (64.4)	
	128	72.8 (88.4)	73.1 (89.0)	63.8 (72.4)	62.8 ( <b>71.5</b> )	52.6 (66.3)	
	512	79.6 ( <b>88.6</b> )	79.6 (89.2)	<b>66.1</b> (72.7)	65.9 (70.8)	<b>55.2</b> (64.9)	





# Multi-genre Natural Language Inference

- 5 genres available in training set
- 10 genres presented in dev and test set

## Both structure and word meaning matter

Now, as children tend their gardens, they have a new appreciation of their relationship to the land, their cultural heritage, and their community.

LETTERS  
**neutral**  
N N N N

All of the children love working in their gardens.

At 8:34, the Boston Center controller received a third transmission from American 11

9/11  
**entailment**  
E E E E

The Boston Center controller got a third transmission from American 11.

In contrast, suppliers that have continued to innovate and expand their use of the four practices, as well as other activities described in previous chapters, keep outperforming the industry as a whole.

OUP  
**contradiction**  
C C C C

The suppliers that continued to innovate in their use of the four practices consistently underperformed in the industry.

# Multi-genre Natural Language Inference

model	MNLI		# params
	dev matched	dev mismatched	
Plain (BiDAF) Architecture - dim 512			
LSTM	72.0 (76.0)	73.2 (75.5)	10.5m (29.4m)
GRU	72.1 (74.2)	72.8 (74.8)	7.9m (22.0m)
Ours	16	72.4 (73.9)	5.8m (15.7m)
	64	73.0 (74.8)	
	256	73.1 (75.9)	
	1024	73.2 (76.2)	
Plain (BiDAF) Architecture - dim 1024			
LSTM	72.5 (75.5)	73.9 (76.6)	25.2m (83.9m)
GRU	72.6 (74.8)	73.6 (75.9)	18.9m (62.9m)
Ours	16	72.9 (73.9)	14.7m (46.1m)
	64	73.4 (75.2)	
	256	73.7 (75.5)	
	1024	74.2 (76.7)	




# General Purpose Sentence Representations

Model	Downstream Tasks in SentEval						
	Binary	SST-5	TREC	SICK-E	STS (Su.)	STS (Un.)	MRPC
Measure	Accuracy				Pearson's $\rho \times 100$		Acc/F1
Plain Architecture - dim 512							
LSTM	87.0	47.5	89.7	84.4	81.8	62.5	<b>77.8</b> / 83.8
GRU	87.0	47.5	<b>91.1</b>	84.8	80.3	62.5	76.9 / 83.4
Ours	16	86.8	47.0	89.5	84.8	80.0	76.3 / 82.8
	64	87.1	46.9	89.9	85.1	80.8	76.8 / 83.3
	256	87.2	47.2	90.1	85.2	81.3	77.4 / <b>84.1</b>
	1024	<b>87.4</b>	<b>48.1</b>	90.5	<b>85.4</b>	<b>82.4</b>	77.1 / 83.9
Plain Architecture - dim 1024							
LSTM	87.6	47.3	<b>92.7</b>	85.0	<b>81.7</b>	63.3	77.0 / 83.6
GRU	87.5	<b>48.9</b>	92.6	85.8	81.2	62.8	<b>77.6</b> / 84.0
Ours	16	87.4	47.5	91.3	85.6	79.6	76.2 / 83.2
	64	87.8	47.8	92.0	85.6	80.7	77.5 / 83.8
	256	87.8	47.9	92.5	<b>86.0</b>	80.6	<b>77.6</b> / 83.9
	1024	<b>87.9</b>	48.5	91.9	85.9	81.5	77.5 / <b>84.4</b>


# Incorporating more role vectors...

$$S = \sum_{i=1}^N r_i \otimes f_i$$


- Faster convergence rate
- Better performance




(a) Training loss on Logical Entailment



(b) Training loss on MNLI dataset



(c) Training accuracy on Logical Entailment



(d) Training accuracy on MNLI dataset

# Outline

- Motivations
- Our Proposed Recurrent Unit
- Experiments
- **Conclusions**

# Conclusions

- A TPRU (Recurrent Unit) is proposed to leverage both
  - Distributed Representations
  - Neural-Symbolic Computing
- Compared to LSTM and GRU
  - symbolic execution
  - reduced total number of parameters
  - comparable or better performance
- Incorporating more role vectors leads to
  - faster convergence rate and better results

# Thank you!

 @Shuai93Tang  shuaitang93@ucsd.edu