



# Object Oriented Programming (OOP) Concepts

Objects, Classes and Encapsulation

JULY,2023

[ expleo ]

# Contents

- Objects
- Classes
- Encapsulation
- Inheritance
- Abstraction
- Polymorphism

# Classes and Objects



## Classes and Objects

### Objects: Recap

- **Object** is the primary unit of Object-Oriented Programming.
- It represents the **real-life entities**. **Example:** pen, chair, table, computer, watch, etc.,
- It can be **physical or logical**.
- An **object** has **three characteristics**:
  1. **State:** represents **data or value** stored in an object.
  2. **Behavior:** represents the **behavior or functionality** of an object. This function is used to manipulate the data and interact with other objects
  3. **Identity:** It gives unique name to an object. **Each object** is identified in Java by **unique memory location**.

## Classes and Objects

### Objects



**State:** colour, size, weight, brand

**Behaviour:** Change channel,  
Manage Volume



**State:** Name, colour, Breed, Type

**Behaviour:** Barking, Fetching,  
Wagging the tail



**State:** Name, black hair, black eyes,  
height

**Behaviour:** eat, study, play, sleep

## Classes and Objects

### Class: Recap

- Class is a **template or blueprint** of the objects.
- It defines the **state** (variables) and **behaviour** (methods) **common to all objects** of a certain kind.
- A class is a **logical entity** and describes the object's **properties** and **behaviours**.
- It is used to **create object instances**.

## Class and Objects

# Object and Class-Recap

### Objects

### Class – Sportsman

#### States

**Name**  
**Sport**  
**Gender**  
**Height**  
**Weight**  
**rank**

#### Behaviors

**Profiling**  
**BMI**



**Name: Cristiano Ronaldo**

**Sport: Football**

**Gender: Male**

**Height: 1.87m**

**Weight: 83kg**

**Rank: 6**

Mr. Cristiano Ronaldo is a Football player with the international rank 6.

BMI is 23.7



**Name: Rafael Nadal**

**Sport: Tennis**

**Gender: Male**

**Height: 1.85m**

**Weight: 85kg**

**Rank: 4**

Mr. Rafael Nadal is a Tennis player with the international rank 4.

BMI is 24.6



**Name: Mirabai Chanu**

**Sport: Weightlifting**

**Gender: Female**

**Height: 1.50m**

**Weight: 49kg**

**Rank: 2**

Ms. Mirabai Chanu is a Weightlifting player with the international rank 2.

BMI is 21.8

( expleo )

## Class and Objects

### Object – Instance of a class: Recap



**Name: Cristiano Ronaldo**  
**Sport: Football**  
**Gender: Male**  
**Height: 1.87m**  
**Weight: 83kg**  
**Rank: 6**



**Name: Rafael Nadal**  
**Sport: Tennis**  
**Gender: Male**  
**Height: 1.85m**  
**Weight: 85kg**  
**Rank: 4**



**Name: Mirabai Chanu**  
**Sport: Weightlifting**  
**Gender: Female**  
**Height: 1.50m**  
**Weight: 49kg**  
**Rank: 2**

#### Instances of Sportsman class

Sports person 1

Sports person 2

Sports person 3

#### States

**Name**  
**Sport**  
**Gender**  
**Height**  
**Weight**  
**rank**

#### Behaviors

**Profiling()**  
**BMI()**

**Sportsman**

( expleo )



## Classes and Objects

# Class Declaration

### Syntax:

**Keyword**

```
Access specifier class Class_name{  
    Fields  
    +  
    Behaviours  
}
```

### Example:

**Class Declaration**

```
public class Theatre {
```

```
    int theatreId = 4523;
```

```
    String theatreName = "INOX";
```

```
    String theatreLocation = "Kochi";
```

**Fields/  
Properties / Attributes/  
States**

```
    public void displayTheatre() {
```

```
        System.out.println("Theatre ID : "+theatreId);
```

```
        System.out.println("Theatre Name : "+theatreName);
```

```
        System.out.println("Theatre Location : "+theatreLocation);
```

**Operations/  
Behaviours/  
Methods**

```
    }
```

```
}
```

## Classes and Objects

### Access Specifiers

- **Access specifiers** defines the **scope and accessibility** of **data and method** in class.
- There are **three** Java access modifiers:
  1. **public**: accessible in all class in your application.
  2. **protected**: accessible within the class in which it is defined and in its subclass(es).
  3. **private**: accessible only within the class in which it is defined.
  4. **default** (declared/defined **without using any modifier**) : accessible within **same class** and package within which its class is defined.

#### Note:

- For **classes** and **interface**, you can use either **public or default**
- For **attributes**, **methods** and **constructors**, you can use the one of the following: **Private, Protected, Public**

## Classes and Objects

### Access specifiers : In a Nutshell

Access Modifier	Within Class	Within Package	Outside package by subclass only	Outside package
Public	Yes	Yes	Yes	Yes
Private	Yes	No	No	No
Protected	Yes	Yes	Yes	No
Default	Yes	Yes	No	No

## Classes and Objects

### Object Creation

- When an object of a class is created, the class is said to be **instantiated**. All the instances can have the same attributes and the functions of the class.
- The memory allocation of **each object is unique** , which means the **value initialized to each object is distinct**.
- A single class may have any number of instances.

#### Syntax:

```
ClassName objectName = new ClassName();
```

- The new keyword **creates (instantiates) a new instance**. It instantiates a class by allocating **memory for a new object**.

## Classes and Objects

# Object Creation

```
/* This Example demonstrates how to create the Object for Theatre
class */
public class Theatre {
    int theatreId = 4523;
    String theatreName = "INOX";
    int totalTheatreScreens = 12;
    String theatreLocation = "Kochi";
    public void getTheatreDetails(){           //Displaying Theatre
details
        System.out.println("Theatre ID : "+theatreId);
        System.out.println("Theatre Name : "+theatreName);
        System.out.println("Total Theatre Screens : "+totalTheatreScreens);
        System.out.println("Theatre Location : "+theatreLocation);
    }
```

```
public static void main(String[] args) {
    //Declare and instantiate
    Theatre T1 = new Theatre();
    //Declare the reference
    Theatre T2;
    //Then instantiate
    T2 = new Theatre();
}
```

### Note:

- A **declaration** only create **reference variable**.
- Allocate **memory** to object only at that **time of instantiation**.

## Classes and Objects

# Accessing Class Members

- After creation of object to access class members using **dot operator (.)**

```
/* This Example demonstrates how to create the Object for Theatre
class */
public class Theatre {
    int theatreId = 4523;
    String theatreName = "INOX";
    int totalTheatreScreens;
    String theatreLocation = "Kochi";
    public void getTheatreDetails(){           //Displaying Theatre
details
        System.out.println("Theatre ID : "+theatreId);
        System.out.println("Theatre Name : "+theatreName);
        System.out.println("Theatre Location : "+theatreLocation);
    }
}
```

```
public static void main(String[] args) {
    //Declare and instantiate
    Theatre T1 = new Theatre();
    //Fields are accessed
    T1.totalTheatreScreens=12;
    //Methods are called
    T1.getTheatreDetails();
}
}
```

## Classes and Objects

### Accessing Class Members: Example #1

```
/**This Example demonstrates how to access class members using object. */  
public class Employee { //Create Employee class  
    int empId;  
    String empName;  
  
    void setEmployeeDetail(int id,String name) {  
        empId = id;  
        empName = name;  
    }  
    void getEmployeeDetail () {  
        System.out.println("Employee id : "+empId);  
        System.out.println("Employee name : "+empName);  
    }  
}
```

## Classes and Objects

### Accessing Class Members: Example #1

```
public class EmployeeMain {  
    public static void main(String[] args) {  
        Employee Emp1 = new Employee();    //First Object Creation  
        Employee Emp2 = new Employee();    //Second Object Creation  
        Emp1.setEmployeeDetail(1001, "RAM");  
        Emp2.setEmployeeDetail(1002, "RAJ");  
        Emp1.getEmployeeDetail();  
        Emp2.getEmployeeDetail();  
    }  
}
```

#### Output

```
Employee id : 1001  
Employee name : RAM  
Employee id : 1002  
Employee name : RAJ
```



## Classes and Objects

### Accessing Class Members: Example#2

```
/* This Example demonstrates how to access class members of Theatre Class*/  
public class Theatre {  
    int theatreId;  
    String theatreName;  
    int totalTheatreScreens;  
    String theatreLocation;  
  
    public void setTheatreDetails(int id, String name, int count,String address) {  
        theatreId = id;  
        theatreName = name;  
        totalTheatreScreens = count;  
        theatreLocation = address;  
    }  
}
```

## Classes and Objects

### Accessing Class Members: Example#2

```
public void getTheatreDetails(){
    System.out.println("-----Theatre Detail-----");
    System.out.println("Theatre ID : "+theatreId);
    System.out.println("Theatre Name : "+theatreName);
    System.out.println("Total Theatre Halls : "+totalTheatreScreens);
    System.out.println("Theatre Location : "+theatreLocation);
    System.out.println("-----");
}

public static void main(String[] args) {
    Theatre T = new Theatre();
    T.setTheatreDetails(4523, "INOX", 10, "Kochi");
    T.getTheatreDetails();
}
```

#### Output

```
-----Theatre Detail-----
Theatre ID : 4523
Theatre Name : INOX
Total Theatre Halls : 10
Theatre Location : Kochi
-----
```

## Classes and Objects

# Object Creation: More Details

### Multiple Object Creation

- To create multiple objects like multiple variable, declare in the same declaration.
- **Example:** Theatre T1 = new Theatre(), Theatre T = new Theatre(); **//two objects in single creation**

### Anonymous object

- It means **nameless object**. An object which has **no reference** is known as an **anonymous object**.
- It can be used **at the time of object creation** only. If you have to use an **object only once**, an **anonymous object** is a **good approach**.
- **Syntax:** new className().methodName()
- **Example:** new Theatre().setTheatreDetails(1001,"INOX",10,"Kochi");

## Classes and Objects

# Object Creation: More Details

### Array of Objects:

- Like array of primitive types, the **array of objects** to store the **location of reference variables** of the object.
- **Syntax:** `Class obj[] = new Class[array_length]`
- **Example:** `Theatre obj[] = new Theatre[10];` //Create 10 Objects

## Classes and Objects

### Array of Objects: Example #1

```
/** This example demonstrates the array of objects. */  
public class EmployeeArrayObject {  
    int empld;  
    String empName;  
    void setEmployeeDetail(int id,String name){  
        empld = id;  
        empName = name;  
    }  
    void getEmployeeDetail (){  
        System.out.println("Employee id : "+empld);  
        System.out.println("Employee name : "+empName);  
    }  
}
```

## Classes and Objects

### Array of Objects: Example #1

```
public class EmployeeArrayObject {  
    public static void main(String[] args) {  
        Employee Emp[] = new Employee[2];  
        for(int i=0;i<2;i++) {  
            Emp[i] = new Employee();  
        }  
        System.out.println("-----Employee 1 Detail-----");  
        Emp[0].setEmployeeDetail(1001, "AMUDHAN");  
        Emp[0].getEmployeeDetail();  
        System.out.println("-----Employee 2 Detail-----");  
        Emp[1].setEmployeeDetail(1002, "RAJ");  
        Emp[1].getEmployeeDetail();  
    }  
}
```

#### Output

```
-----Employee 1 Detail-----  
Employee id : 1001  
Employee name : AMUDHAN  
-----Employee 2 Detail-----  
Employee id : 1002  
Employee name : RAJ
```

## Classes and Objects

# Constructors

- In Java, **Constructor** is a special method that is **executed automatically** whenever an **instance of object** is created. It is used **to initialize the object** and **give initial values** for object attributes.

### Rules for Constructor:

- Constructor has **same name** as **class name**.
- Constructor **do not have return value** but can take **arguments**.
- Constructor cannot be **abstract, static, final, and synchronized**. (Will discuss Later)

## Classes and Objects

# Constructors

- There are **two types** of constructors in Java:
  1. No-argument/default constructor
  2. Parameterized constructor

## Default Constructor

- A **constructor** that has **no parameters** is known as **default constructor**. It is either **user defined** or **compiler defined constructor**.
- If we don't create any constructor in a class, then **compiler creates default constructor** for the class and **assign default values** to attributes .
- The **user defined** default constructor provides user given initial values to attributes of the class for **each instantiation**.



## Classes and Objects

### Default Constructor: Example #1

```
/**
 * This example demonstrates compiler defined default constructor.
 */

class Employee { //define Employee class
    int empId;
    String empName;

    void getEmployeeDetails () {
        System.out.println("The default Initial value of employee id is: "+empId);
        System.out.println("The default Initial value of employee name is: "+empName);
    }
}
```

## Classes and Objects

### Default Constructor: Example #1

```
class EmployeeMain {      //Main Class
    public static void main (String[] args)
    {
        Employee emp= new Employee();
        // Default constructor initialize default values to the objects
        emp.getEmployeeDetails();
    }
}
```

#### Output

The default Initial value of employee id is: 0

The default Initial value of employee name is: null

## Classes and Objects

### Default Constructor: Example #2

```
/**
 * This example demonstrates user defined default constructor.
 */

class Employee {    //define Employee class
    int empId;
    String empName;
    //User defined default constructor

    Employee() {
        empId=1111; //Initial value of employee id
        empName="AAA-BBB"; //Initial value of employee name
    }
}
```

## Classes and Objects

### Default Constructor: Example #2

```
void getEmployeeDetails () {  
    System.out.println("The Initial value of employee id is: "+empId);  
    System.out.println("The Initial value of employee name is: "+empName);  
}  
  
class EmployeeMain { //Main Class  
    public static void main (String[] args) {  
        // this invoke compiler defined default constructor.  
        Employee emp= new Employee();  
        // Display assigned initial values  
        emp.display();  
    }  
}
```

#### Output

The Initial value of employee id is: 111  
The Initial value of employee name is: AAA-BBB

## Classes and Objects

### Parameterized Constructor

- A **constructor** that accepts arguments are known as **parameterized constructor**. It is use to **initialize with your own values**.
- In **parameterized constructor**, we must provide **initial values** of objects **as arguments** to the constructors.

## Classes and Objects

### Parameterized Constructor: Example #1

```
/**
 * This example demonstrates parameterized constructor.
 */

class Employee { //define Employee class
    int empId;
    String empName;

    //Parameterized constructor
    Employee(int id, String name){
        empId=id; //Assign Initial employee id
        empName=name; //Assign Initial employee name
    }
}
```

## Classes and Objects

### Parameterized Constructor: Example#1

```
void getEmployeeDetails (){\n    System.out.println("User given initial employee id is: "+empId);\n    System.out.println("User given initial employee name is: "+empName);\n}\n\nclass EmployeeMain { //Main Class\n    public static void main (String[] args) {\n        // Pass arguments to the constructor\n        Employee emp= new Employee(1003,"Peter");\n        //Display employee initial values\n        emp.display();\n    }\n}
```

#### Output

User given Initial value of employee id is: 103

User given Initial value of employee name is: Peter

## Classes and Objects

### Constructor Overloading

- **Constructor overloading: More than one constructor** with different parameter lists depending on the application. Each constructors functions in its **own distinct way**.
- **Example:**

```
Employee() { ....} //Default Constructor
```

```
Employee(int empId) {.....} //One Parameter Constructor
```

```
Employee(String name, String designation) {...} // Two parameter Constructor
```

- They are differentiated by the Java compiler by the **number of arguments, order of arguments** listed and the **types of each arguments**.



## Classes and Objects

# Constructor Overloading: Example #1

```
/**
 * This example demonstrates the constructor overloading */
class Employee { //define Employee class
    int empId;
    String empName;
    Employee(){ //Default Constructor
        empId=0;
        empName="AAA-BBB";
    }
    Employee(int id, String name){ //Parameterized constructor
        empId=1111; //Assign Initial employee id
        empName=name; //Assign Initial employee name
    }
}
```

## Classes and Objects

### Constructor Overloading: Example #1

```
void getEmployeeDetails (){
    System.out.println("Employee id is: "+empId);
    System.out.println("Employee name is:"+empName);
}
}

class EmployeeMain { //Main Class
    public static void main (String[] args) {
        Employee emp0=new Employee(); //Default Constructor
        Employee emp1= new Employee(1001,"Ram Kumar"); //Parameterized Constructor
        //Display employee initial values
        emp0.getEmployeeDetails();
        emp1.getEmployeeedisplay();
    }
}
```

#### Output

```
Employee id : 1002
Employee name :Guru
Employee id : 1003
Employee name :Peter
```

## Classes and Objects

### 'this' Keyword

- **'this'** is a reference variable that refers to the **current object**.

#### Usage of 'this' Keyword

- It can be used **to refer instance variable** of current class and return the current class instance.
- It can be used **to invoke or initiate** current class **constructor**. It means **constructor chaining** is possible. **For example**, Call default constructor from parameterized

#### Note:

- this keyword cannot be used outside a class

## Classes and Objects

### 'this' Keyword :Example #1

```
/**
 * This example illustrates the problem
 * if we dont use 'this' keyword.
 */

public class Employee {
    int empId;    // instance variable
    String empName; //instance variable
    Employee(String empName, int empId ) {
        empName = empName;
        empId = empId;
    }
    void display() {
        System.out.println(name+ " \t"+ empId);
    }
}
```

Both local  
and instance  
variables are  
same

#### Note:

- 'this' keyword resolves the ambiguity between instance and local variable.
- This example illustrates the problem, if we don't use 'this' keyword.

## Classes and Objects

### 'this' Keyword :Example #1

```
//Main Class
class EmployeeMain {
    public static void main (String[] args) {
        Employee emp = new Employee("Manas Kumar",29);
        emp.display();
    }
}
```

## Classes and Objects

### 'this' Keyword :Example #2

```
/**
 * This program illustrates the use of 'this' keyword.
 */
public class Employee {
    int empld;
    String empName;
    Employee(String empName, int empld ) {
        this.empName = empName;
        this.empld = empld;
    }
    void display() {
        System.out.println(name+ " \t"+ empld);
    }
}
```

Here this.empld  
and empName are  
instance variables

#### Note:

- 'this' keyword resolves the ambiguity between instance and local variables.

## Classes and Objects

### 'this' Keyword :Example #2

```
//Main Class
class EmployeeMain {
    public static void main (String[] args) {
        Employee emp = new Employee("Manas Kumar",29);
        emp.display();
    }
}
```

#### Output

Employee id : 29

Employee name : Manas Kumar

## Classes and Objects

### Static Members

- The **static** keyword in Java is used for **managing memory efficiently** with the class instances.
- We can apply **static** keyword with **variables, methods, blocks** and **nested classes**.
- The **static** keyword belongs to the class rather than each instance of the class. The **static member** is common to the class and it is **same for all the instances** created for that class. For **example**, the company name of employees, college name of students, bank name of account holders, etc.
- **Static members** can be accessed with objects of a class.
- Static members can be **accessed before any objects** of its class are created.



## Classes and Objects

# Static Block and Static Variables

### Static Block

- **Static block** mainly used for to **initialize the static variables**.
- It is **executed** at the time of **class is loaded** in the memory.
- In case of **multiple static blocks**, which will execute in the **same order**.

### Static Variable

- **Static variable** also called as **class variable**.
- It is **common to all the instance** of the class.
- **Memory allocation** for static variables are **happens when the class is loaded** in the memory.

## Classes and Objects

# Static Members : Static Block

```
/**
 * This example demonstrates static block */
class Employee{ //Main Class
    static int empld;
    static String empName;
    static{
        System.out.println("Static Block 1");
        empld = 1001;
        empName = "Alex";
    }
    static{
        System.out.println("Static Block 2");
        empld = 1002;
        empName = "Peter";
    }
}
```

## Classes and Objects

# Static Members : Static Block

```
public static void main(String args[])
{
    System.out.println("Employee Id : "+empId);
    System.out.println("Employee Name : "+empName);
}
}
```

### Note:

- **'static block'** is used to initialize the static data member.
- It is executed only once when the class gets loaded.

### Output

Static Block 1

Static Block 2

Employee Id : 1002

Employee Name : Peter

## Classes and Objects

# Static Members : Static Variable

```
/**
 * This example demonstrates static variable.
 */

class Employee { //define Employee class
    int empld;
    String empName;
    static String companyName="ABC Solutions"; //static variable
    //Parameterized constructor
    Employee(int id, String name) {
        empld=id; //Assign Initial employee id
        empName=name; //Assign Initial employee name
    }
}
```

## Classes and Objects

# Static Members : Static Variable

```
void display (){ //Employee Details
    System.out.println("Company Name : "+companyName); //common to all employee
    System.out.println("Employee Id : "+empId);
    System.out.println("Employee Name : "+empName);
}
}

class EmployeeMain { //Main Class
    public static void main (String[] args) {
        // Pass arguments to the constructor
        Employee emp1= new Employee(1001,"Ram Kumar");
        Employee emp2= new Employee(1002,"Raj Kumar");
        //Display employee details
        emp1.display();
        emp2.display();
    }
}
```

### Note:

- Here, companyName Static variable is common for all objects created for that class.
  - All instances of the class share the same static variable.
- static block** and **static variables** are executed in order they are present in the program

## Classes and Objects

# Static Members : Static Variable

### Output

Company Name : ABC Solutions

Employee Id : 1001

Employee Name : Ram Kumar

Company Name : ABC Solutions

Employee Id : 1002

Employee Name : Raj Kumar

## Classes and Objects

### Static Methods

- A **static method** belongs to the **class and common for all the object** of a class.
- It can be invoked **without object** of class or using **class name**.

#### Restrictions:

- Can access only other static methods and variables.
- Cannot refer to **this or super** keyword.

## Classes and Objects

# Static Methods : Example

```
/**
 * This example demonstrates static method.
 */

class Employee { //define Employee class
    int empId;
    String empName;
    static String companyName = "ABC Solutions"; //static variable
    //Parameterized constructor
    Employee(int id, String name){
        empId = id; //Assign Initial employee id
        empName = name; //Assign Initial employee name
    }
}
```



## Classes and Objects

# Static Methods : Example

```
//Change company name
static void getCompany(){
    companyName = "XYZ Private Ltd"; //Access static data
}
//Display Employee Details
void display (){
    System.out.println("Company Name : "+companyName); //common to all employee
    System.out.println("Employee Id : "+empId);
    System.out.println("Employee Name : "+empName);
}
}
```

## Classes and Objects

# Static Methods : Example

```
class EmployeeMain { //Main Class
    public static void main (String[] args) {
        // Pass arguments to the constructor
        Employee emp1= new Employee(1001,"Ram Kumar");
        Employee emp2= new Employee(1002,"Raj Kumar");
        //Display employee details
        emp1.display();
        emp2.display();
        Employee.getCompany(); //Access static method
        //Display employee details after change company
        emp1.display();
        emp2.display();
    }
}
```

### Output

```
Company Name : ABC Solutions
Employee Id : 1001
Employee Name : Ram Kumar
Company Name : ABC Solutions
Employee Id : 1002
Employee Name : Raj Kumar
Company Name : XYZ Private Ltd
Employee Id : 1001
Employee Name : Ram Kumar
Company Name : XYZ Private Ltd
Employee Id : 1002
Employee Name : Raj Kumar
```

## Classes and Objects

# Static Members : Static Method

```
/* This example demonstrates static members created for the Theatre Screen class */  
public class TheatreScreen {  
    private static int totalseats = 20 ;    //static variable  
    TheatreScreen() {  
        System.out.println("Current Seat Availability : "+totalseats);  
    }  
    public void DisplayTheatreScreen() {  
        System.out.println("Current Seat Availability : "+totalseats);  
    }  
    public static void BookTicket(int nooftickets) { // static method  
        System.out.println("No. of Seats Booked : "+nooftickets);  
    }  
}
```

## Classes and Objects

### Static Members : Static Method

```
        totalseats -= nooftickets;
    }
    public static void main(String args[]) {
        System.out.println("Screen Ticket Availability Status:");
        TheatreScreen TS1 = new TheatreScreen();
        TS1.BookTicket(4);
        TheatreScreen TS2 = new TheatreScreen();
        TS2.BookTicket(5);
        TS2.DisplayTheatreScreen();
    }
}
```

#### Output

Screen Ticket Availability Status:  
Current Seat Availability: 20  
No. of Seats Booked : 4  
Current Seat Availability : 16  
No. of Seats Booked : 5  
Current Seat Availability : 11

# Encapsulation



## Encapsulation

### Introduction

- **Encapsulation** is a another important concept of **Object Oriented Programming**.
- It is the process of **binding the data and behaviour** into a single unit called **class**.

#### Need of Encapsulation:

- In this world, many data are **sensitive, confidential and personal**. Hence privacy is an important threat with respect to every data.
- **Data privacy** is achieved with the help of **encapsulation concept** in Java.

## Encapsulation

# Introduction

### Achieve encapsulation in Java:

- Encapsulation can be **achieved** by declaring data in the **class members as private**.
- Provide **public setter and getter methods** to modify and view the private class members.

**(Good Practice)**

### Note:

- Encapsulation **prevents the private class members** being accessed by **external classes and methods**. Therefore, it is also known as **data hiding**.

## Encapsulation

### Setter and getter Methods

**Setter and getter Method:** It is used to **update and retrieve the value of variables**.

#### Rules for setter Method:

- It should be **public**, if it needs to be accessed from outside.
- The **return-type** should be **void**.
- The setter method should be prefixed with **set**.
- It should **take some argument** i.e. it should not be **no-argument** method.

#### Rules for getter Method:

- It should be **public**, if it needs to be accessed from outside
- The **return-type** should **not be void** i.e. according to our requirement we have to give return-type.
- The getter method should be prefixed with **get**.
- It **should not** take **any argument**.



## Encapsulation

### Advantages

- Use only a **setter or getter method**, you implicitly achieve member of the class that becomes **read-only or write-only option**.
- It gives you **command over the data**. **For Example**, You can write the logic inside the setter method if you need to set the value of empId based on some criteria.
- It is a way to **achieve data hiding** in Java because other class will not be able to access the data through the private data members.
- The encapsulate class is **easy to test**. So, it is **better for unit testing**.
- The standard **IDE's** are providing the **facility to generate** the getters and setters method it **helps** to create **encapsulate class easy and fast**.

## Classes and Objects

### Example

```
/**
 * This example demonstrates encapsulation features using getter and setter methods
 */

class Employee {    //define Employee class
    //private data members
    private int _empld;
    private String _empName;
    //public getter and setter methods
    //Set employee id
    public void setId(int id) {
        _empld=id;
    }
}
```

## Classes and Objects

### Example

```
//Set employee name
public void setName(String name) {
    _empName=name;
}

//Get employee id
public int getId() {
    return _empld;
}

//Get employee name
public String getName() {
    return _empName;
}
}
```

## Classes and Objects

### Example

```
class EmployeeMain { //Main Class
    public static void main (String[] args) {
        Employee emp= new Employee(); //create instance of Employee class
        //setting values through setter methods
        emp.setId(1001);
        emp.setName("Ram Kumar");
        //getting values through getter methods
        System.out.println("Employee Id: "+emp.getId());
        System.out.println("Employee Name: "+emp.getName());
    }
}
```

#### Output

Employee Id : 1001

Employee Name Ram Kumar

## OOP Concepts

### Quiz



1. X is a keyword that denotes member variable or method can be accessed, without requiring an instantiation of the class to which it belongs. X is \_\_\_\_

a) This

b) static

c) volatile

d) public

e) None of the above

b) static

## OOP Concepts

### Quiz



2. In case the programmer does not provide a constructor for a class, Java compiler will

a) Throw error

b) Create Default constructor

c) Throw run time exception

d) Create new object

e) None of the above

b) Create Default constructor

## OOP Concepts

### Quiz



3. \_\_\_\_\_ provides objects with the ability to hide their internal characteristics and behaviour.

a) Encapsulation

b) Abstraction

c) Polymorphism

d) Inheritance

e) None of the above

a) Encapsulation

## OOP Concepts

### Quiz



4. In a class, an attribute needs to be accessed from any class in that application. What should be the access specifiers for that attribute

a) protected

b) private

c) public

d) default

e) None of the above

c) public



## OOP Concepts

### Quiz



5. Given a class with the name Trainee. Which of the following instantiates an object for this class?

a) Trainee t;

b) Trainee()

c) Trainee t=new Trainee()

d) All the options

e) None of the above

c) Trainee t=new Trainee()

## OOP Concepts

### Quiz



6. Assume, a class **Person**. Identify the correct signature for the constructor

a) `void Person()`

b) `private void Person()`

c) `public Person()`

d) `public void Person()`

e) None of the above

c) `public Person()`

## OOP Concepts

### Quiz



7. Which of the following keywords acts as a reference variable to the current object?

a) this

b) reference

c) static

d) public

e) None of the above

a) this

## OOP Concepts

### Quiz



8. The keyword used to create a new object in Java is \_\_\_\_.

a) class

b) java

c) new

d) create

e) None of the above

c) new

## OOP Concepts

### Quiz



9. In a .java file, how many numbers of public class allowed?

a) 1

b) 2

c) 3

d) Any number

a) 1

## OOP Concepts

### Quiz



10. How many maximum numbers of objects can be created from a single Class in Java?

a) 32

b) 64

c) 256

d) None of these Above

d) None of these Above