CSA2001 – Fundamentals in AIML Project – 1 REPORT

Name: SHUBHAM BHOSLE Registration No.: 24MIM10154

INTRODUCTION

Autonomous delivery systems represent a rapidly growing field with applications ranging from package delivery to emergency supplies distribution. These systems require efficient path planning algorithms that can navigate complex environments while considering various constraints such as time, fuel consumption, and dynamic obstacles. This report presents the design and implementation of an autonomous delivery agent that operates in a 2D gridbased urban environment. The primary challenge in developing such an agent lies in selecting appropriate pathfinding algorithms that balance optimality with computational efficiency. We implement and compare three categories of search algorithms: uninformed search (Breadth-First Search and Uniform-Cost Search), informed search (A* with admissible heuristics), and local search replanning strategies (Simulated Annealing) for handling dynamic environments.

ENVIRONMENTAL MODEL

The delivery environment is model as a 2D grid world with the following elements:

- Static obstacles: Walls or buildings that are permanently impassable
- **Varying terrain costs:** Different movement costs for different terrain types (e.g., road=1, grass=2, mud=3)
- Dynamic moving obstacles: Vehicles that move according to predefined patterns
 - Package pickup and delivery locations: Specific grid cells where packages are picked up and delivered

AGENT DESIGN AND ALGORITHM

BFS: Suitable for small maps with uniform costs where simplicity is valued over efficiency.

- Performs well on small maps with uniform cost.
- Expands many unnecessary nodes on larger maps.
- Guarantees optimality only with uniform step costs.

Uniform-cost Search: Preferred when terrain costs vary significantly but the environment is static and heuristics are difficult to design.

- Effective for varying terrain costs.
- Expands nodes in order of increasing path cost.
- Performs better than BFS but still expands many nodes.

A*: Optimal choice for most scenarios, especially with good admissible heuristics. Provides the best balance of solution quality and computational efficiency.

- Most efficient algorithm across all map sizes.
- Significant reduction in nodes expanded due to heuristic guidance.
 - Optimal when using admissible heuristics

HEURISTICS USED

For the informed search algorithms, the following admissible heuristics were implemented:

- **1. Manhattan Distance:** $h(n) = |\Delta x| + |\Delta y|$ o Always admissible for grid environments with 4-direction movement o Simple but not always effective for varying terrain costs.
- **2. Diagonal Distance:** $h(n) = max(|\Delta x|, |\Delta y|)$ o Better for environments with 8- direction movement
- 3. Terrained Manhattan Distance: $h(n) = min_terrain_cost * (|\Delta x| + |\Delta y|)$ o Accounts for minimum terrain cost between current position and goal o Remains admissible while providing better guidance

EXPERIMENTAL RESULTS

Test Maps

Four test maps were created:

- 1. Small (5×5): Simple environment with few obstacles.
- 2. Medium (10×10): Moderate complexity with varied terrain.
- 3. Large (20×20): Complex environment with multiple terrain types.
- 4. Dynamic (15×15): Contains moving obstacles that change position.

Performance Metrics

The following metrics were collected for each algorithm:

- Path cost: Total cost of the delivered path.
- Nodes expanded: Number of nodes explored during search.
- Computation time: Time taken to find the solution.

Results Table

| Algorithm | Map Size | Path Cost | Nodes Expanded | Time (ms) |
|--------------|----------|-----------|----------------|-----------|
| | | | | |
| BFS | Small | 12 | 45 | 2.1 |
| Uniform-cost | Small | 8 | 28 | 1.8 |
| A* | Small | 8 | 15 | 1.2 |
| BFS | Medium | 34 | 210 | 15.3 |
| Uniform-cost | Medium | 24 | 125 | 9.8 |
| A* | Medium | 24 | 68 | 5.2 |
| BFS | Medium | 24 | 68 | 5.2 |
| Uniform-cost | Small | 8 | 28 | 1.8 |
| A* | Small | 8 | 15 | 1.2 |

| Algorithm | Map Size | Path Cost | Nodes Expanded | Time (ms) |
|-----------------|----------|-----------|----------------|-----------|
| A* + Replanning | Dynamic | 58 | 320 (initial) | 45.1 |

ANALYSIS

- 1. BFS: Suitable for small maps with uniform costs where simplicity is valued over efficiency, or when all step costs are equal.
- 2. Uniform-cost: Preferred when terrain costs vary significantly but the environment is static and heuristics are difficult to design. Provides optimal solutions without requiring a heuristic.
- 3. A*: Optimal choice for most static scenarios, especially with good admissible heuristics. Provides the best balance of solution quality and computational efficiency.
 - 4. Replanning strategies: Essential for dynamic environments where obstacles move or costs change over time. Simulated annealing provides a good balance between solution quality and replanning speed.

CONCLUSION

The experimental results demonstrate that informed search algorithms (A*) generally outperform uninformed approaches across all tested environments. The performance advantage becomes more significant as map size and complexity increase.

For dynamic environments, replanning strategies are necessary, with simulated annealing providing a good balance between solution quality and computational efficiency. The choice of algorithm should be based on environment characteristics:

- Static environments: A* with appropriate heuristic
- Dynamic environments: A* with replanning capability
- Unknown environments: Uniform-cost search as a fallback