



Technical datasheet

GrapheneBlack™ 3X

Supplied By NANOXPLORE – Last Updated On Mar 11, 2026

GrapheneBlack™ 3X

By NANOXPLORE

Sampling Options



Compare



Description

Benefits

Applications

Compliance

Availability

Properties



GrapheneBlack™ 3X by NanoXplore is a multifunctional additive/ reinforcing agent for thermoplastics and rubbers. This hydroxy and carbonyl modified graphene is an optimal replacement for conventional additives, particularly carbon black, that can improve product cost and enhance product performance even at low-loading concentrations. GrapheneBlack™ 3X improves mechanical & thermal properties, electrical conductivity & shielding, UV protection, oxidation resistance and barrier properties. This versatile and low-cost graphene powder is well suited for use in thermosets.

Product family: **Nanoparticles**

Chemical family: Graphene / Graphene Oxides

Product Type: Additives

CAS Number	1034343-98-0
Chemical Composition:	Hydroxy and carbonyl modified graphene
Color	Black
Appearance	Powder

Benefits

Good Electrical Conductivity | Low Formulation Cost

Compliance



Type a product name, supplier or product family

For Suppliers



Applications

Recommended markets

No data available

Availability

Product Status: COMMERCIAL

GrapheneBlack™ 3X

By [NANOXPLORE](#)

GrapheneBlack™ 3X properties

Other properties

Supplier data

SI units

Imperial units

Properties	Value & unit	Test condition	Test method
Ash Content	< 6 %	Residue on Ignition, , Thermogravimetric Analysis. By Weight	
Carbon Content	> 91 %		
Decomposition Temperature	600 °C		
Density	2.2 g/cm³		
Density, Bulk	0.18 g/cm³		
Impurities	< 2 %		
Melting Point	4500 °C		
Moisture Content	< 0.7 %	Thermogravimetric Analysis. By Weight	
Number of Layers	6 – 10	Up to 90% of flakes	
Oxygen Content	< 7 %		
Particle Size	1 – 2 µm	Statistical TEM Analysis	
Particle Size Distribution, Median	38 µm	Laser Diffraction	
Sulfur Content	< 0.5 %		

Related products

With Samples Available (3)



[See the product](#) →

