

C PROGRAMMING MCQ TEST 2

Question 1 :

```
int a = 1;
if (printf("") && a++)
{
    printf("if block executed");
}
else
{
    printf("else block executed");
}
```

- (a) else block executed
- (b) if block executed
- (c) Compilation error
- (d) No output

Correct Answer: (a) else block executed

Question 2 :

```
int a = 1;
if (printf("hi") && a++)
{
    printf("if block executed");
}
else
{
    printf("else block executed");
}
```

- (a) hiif block executed
- (b) hielse block executed
- (c) if block executed
- (d) else block executed

Correct Answer: (a) hiif block executed

Question 3 :

```
int a = 0;
if (printf("") || a++)
{
    printf("if block executed");
}
else
{
    printf("else block executed");
}
```

- (a) if block executed
- (b) else block executed
- (c) Compilation error
- (d) No output

Correct Answer: (b) else block executed

Question 4 :

```

int a = 0;
if (printf("FBS") || a++)
{
printf("if block executed");
}
else
{
printf("else block executed");
}

```

- (a) FBSif block executed
- (b) FBSelse block executed
- (c) if block executed
- (d) else block executed

Correct Answer: (a) FBSif block executed

Question 5 :

```

int a = 0, b = 5;
if (a++ && ++b)
{
printf("%d %d", a, b);
}
else
{
printf("%d %d", a, b);
}

```

- (a) 1 6
- (b) 1 5
- (c) 0 5
- (d) 1 4

Correct Answer: (b) 1 5

Question 6 :

```

int a = 1, b = 2;
if (a-- && ++b)
{
printf("%d %d", a, b);
}
else
{
printf("%d %d", a, b);
}

```

- (a) 0 2
- (b) 1 3
- (c) 0 3
- (d) 1 2

Correct Answer: (c) 0 3

Question 7 :

```

int x = 0, y = 1;
if (x++ || --y)
{
printf("%d %d", x, y);
}
else

```

```
{  
printf("%d %d", x, y);  
}
```

(a) 1 0

(b) 1 1

(c) 0 0

(d) 1 2

Correct Answer: (a) 1 0

Question 8 :

```
int p = 5, q = 0;  
if (--p && q++)  
{  
printf("%d %d", p, q);  
}  
else  
{  
printf("%d %d", p, q);  
}
```

(a) 5 0

(b) 4 1

(c) 4 0

(d) 5 1

Correct Answer: (c) 4 0

Question 9 :

```
int m = 0, n = 0;  
if (m++ || ++n)  
{  
printf("%d %d", m, n);  
}  
else  
{  
printf("%d %d", m, n);  
}
```

(a) 0 0

(b) 1 1

(c) 1 0

(d) 0 1

Correct Answer: (b) 1 1

Question 10 :

```
int i = 1, j = 2;  
if (--i && j--)  
{  
printf("%d %d", i, j);  
}  
else  
{  
printf("%d %d", i, j);  
}
```

(a) 0 2

(b) 1 2

(c) 0 1

(d) 1 1

Correct Answer: (a) 0 2

Question 11 :

```
int a = 2, b = 3;
if (a-- && ++b)
{
    printf("%d %d", a, b);
}
else
{
    printf("%d %d", ++a, b--);
}
```

(a) 1 4

(b) 2 4

(c) 2 3

(d) 1 3

Correct Answer: (a) 1 4

Question 12 :

```
int x = 0, y = 5;
if (++x || y--)
{
    printf("%d %d", x, y);
}
else
{
    printf("%d %d", --x, ++y);
}
```

(a) 1 4

(b) 1 5

(c) 0 5

(d) 0 6

Correct Answer: (b) 1 5

Question 13 :

```
int p = 0, q = 0;
if (p++ && q++)
{
    printf("%d %d", p, q);
}
else
{
    printf("%d %d", ++p, ++q);
}
```

(a) 1 1

(b) 2 1

(c) 2 2

(d) 1 2

Correct Answer: (c) 2 2

Question 14 :

```
int i = 5, j = 0;
if (--i && ++j)
{
    printf("%d %d", i--, j++);
}
else
{
    printf("%d %d", ++i, --j);
}
```

(a) 5 0

(b) 4 0

(c) 4 1

(d) 5 1

Correct Answer: (c) 4 1

Question 15 :

```
int m = 0, n = 1;
if (m++ || n--)
{
    printf("%d %d", m--, --n);
}
else
{
    printf("%d %d", ++m, ++n);
}
```

(a) 1 0

(b) 1 -1

(c) 0 0

(d) 1 1

Correct Answer: (a) 1 0

Question 16 :

```
int a = 1, b = 0;
if (a && printf("") || b)
{
    printf("Yes");
}
else
{
    printf("No");
}
```

(a) Yes

(b) No

(c) Compilation error

(d) No output

Correct Answer: (b) No

Question 17 :

```
int a = 0, b = 1;
if (a++ || printf("Firstbit"))
```

```
{  
printf(" Solutions");  
}
```

- (a) Firstbit Solutions
- (b) Firstbit
- (c) Solutions
- (d) No output

Correct Answer: (a) Firstbit Solutions

Question 18 :

```
int a = 5;  
if (a = 0)  
{  
printf("Chennai");  
}  
else  
{  
printf("Mumbai");  
}
```

- (a) Chennai
- (b) Mumbai
- (c) Compilation error
- (d) No output

Correct Answer: (b) Mumbai

Question 19 :

```
int a = 5;  
if (a++ && (a = 0))  
{  
printf("Chennai %d",a);  
}  
else  
{  
printf("Mumbai %d",a);  
}
```

- (a) Chennai 0
- (b) Mumbai 0
- (c) Chennai 6
- (d) Mumbai 6

Correct Answer: (a) Chennai 0

Question 20 :

```
int a = 5;  
if (a++ || (a = 0))  
{  
printf("Chennai %d",a);  
}  
else  
{  
printf("Mumbai %d",a);  
}
```

- (a) Chennai 6

(b) Mumbai 6

(c) Chennai 5

(d) Mumbai 0

Correct Answer: (a) Chennai 6

Question 21 :

```
int a = 0;
if (a++ && (a = 5))
{
    printf("Chennai %d",a);
}
else
{
    printf("Mumbai %d",a);
}
```

(a) Chennai 1

(b) Mumbai 1

(c) Chennai 5

(d) Mumbai 5

Correct Answer: (b) Mumbai 1

Question 22 :

```
int a = 3;
if (a > 1)
if (a > 2)
if (a > 3)
    printf("Hi");
else
    printf("Hello");
```

(a) Hi

(b) Hello

(c) No output

(d) Compilation error

Correct Answer: (b) Hello

Question 23 :

```
int x = 2;
if (x == 1)
    printf("One");
else
if (x == 2)
    printf("Two");
else
    printf("Three");
```

(a) One

(b) Two

(c) Three

(d) None

Correct Answer: (b) Two

Question 24 :

```
int a = 10;
if (a > 5)
if (a < 15)
if (a == 10)
printf("Perfect");
else
printf("Almost");
```

- (a) Perfect
- (b) Almost
- (c) Compilation error
- (d) Nothing

Correct Answer: (a) Perfect

Question 25 :

```
int x = 1;
if (x == 1)
if (x == 2)
printf("A");
else
printf("B");
```

- (a) A
- (b) B
- (c) Compilation error
- (d) No output

Correct Answer: (b) B

Question 26 :

```
int x = 6;
if (x % 2 == 0)
if (x % 3 == 0)
printf("Div by 6");
else
printf("Even");
```

- (a) Div by 6
- (b) Even
- (c) Nothing
- (d) Compilation error

Correct Answer: (a) Div by 6

Question 27 :

```
int x = 5;
if (x > 0)
if (x < 3)
printf("Less than 3");
else
printf("Greater than 3");
```

- (a) Less than 3
- (b) Greater than 3
- (c) No output
- (d) Compilation error

Correct Answer: (b) Greater than 3

Question 28 :

```
int a = 4;
if (a % 2 == 0)
if (a % 3 == 0)
printf("Divisible by 6");
else
printf("Even");
else
printf("Odd");
```

- (a) Even
- (b) Odd
- (c) Divisible by 6
- (d) Compilation error

Correct Answer: (a) Even

Question 29 :

```
int a = 3, b = 3;
if (a == b)
if (a + b > 5)
printf("Yes");
else
printf("No");
```

- (a) Yes
- (b) No
- (c) Compilation error
- (d) Nothing

Correct Answer: (a) Yes

Question 30 :

```
int a = 10;
if (a++ == 10)
printf("%d", a);
else
printf("%d", a);
```

- (a) 10
- (b) 11
- (c) 9
- (d) Undefined

Correct Answer: (b) 11