

STRIACO Woden Groove Acoustic Panel

Range	1. MDF – Medium Density Fibre Board [750 kg/cuM] 2. HDMR – High Density Moisture Resistant Fibre Board [850 kg/cuM]
Size	2440 x 128 x 16mm
Front side	Linear Grooving [16mm pitch; 32mm pitch]
Back Side	Perforation 8-10mm Back Side covered with Black Acoustic Fleece
Long Edge	Tongue & Groove system
Installation	With 'U' Aluminium Channel & G.I. side & centre brackets
Area of Application:	Auditorium, Banquet Halls, Seminar Halls, Concert Halls, Studios, Cinema Theatres, Workspaces etc.

Specification

Providing & fixing of 16mm Fibrecrete Striaco in size: 2440 x 128mm made from HDMR pre laminated Fibre boards of approved design & shade of density 850 kg/cuM with linear grooving on front side (pitch 16mm or 32mm), 8-10mm perforation at the back covered with black acoustic fleece and having tongue & groove edges.

Option 1

Fibrecrete Striaco are to be fixed with it's tongue & groove system to G.I. side & centre brackets which will be fixed to Aluminium 'U' channel of 18mm height, 25mm width having flanges of 7mm on both sides. The top surface of the 'U' channel is to be screw fixed to the wall horizontally after levelling. The brackets will be twisted & fixed to the flanges of the 'U' channel.

