

EFFUSIO WOOL

SOUND ABSORPTION WOOL

Material	Color	Application	NRC
Soft Fibre	White	ceiling, walls, partitions, underflooring	0.50 to 0.80

FEATURES

Sound Insulation

Thermal Insulation

Fire Retardant

Non Hazardous

Eco Friendly

Easy to Cut

Easy to Install

Light Weight

Durable

Skin Friendly
[easy to work]

STANDARD DETAILS

Roll Size: 20M x 1.22M = 24.40 Sqm. = 262.50 Sqft

Type	Thickness	Density	NRC
EW1205	12mm	500 GSM	-
EW2505	25mm	500 GSM	0.55
EW2510	25mm	1000 GSM	-
EW5005	50mm	500 GSM	0.65
EW5010	50mm	1000 GSM	0.85



APPLICATION

Used for Infill or Backing in False Ceiling, Wall Panelling, Partitions, Underroof Insulation, Underflooring Insulation.

Places of Usage

- Schools,
- Audio Video Room
- Studios
- Institutes
- Gymnasium
- Cinema Theatre
- Recording rooms
- Music Rooms
- Universities
- Recreational Halls
- Auditorium
- Meeting rooms
- Banquet Halls
- Seminar Halls
- Concert Halls
- Home Theatre
- Conference rooms
- Library
- Exhibition Halls