

**Aim:**

Write a C program to perform optimal merging on a given input array of elements, and print the output as shown in the examples.

**Source Code:**OptimalMerge.c

```
#include <stdio.h>
#include <stdlib.h>

// Function to Sort the files in ascending order, perform optimal file merging and re
return the minimum cost
int optimalMerge(int files[], int n) {
    int totalCost = 0;
    while(n>1) {
        for(int i = 0; i < n-1; i++) {
            for(int j = 0; j < n-i-1; j++) {
                if(files[j] > files[j+1]) {
                    int tmp = files[j];
                    files[j] = files[j+1];
                    files[j+1] = tmp;
                }
            }
        }
        int mergedSize = files[0] + files[1];
        totalCost += mergedSize;
        files[0] = mergedSize;
        for(int i = 1; i < n-1; i++) {
            files[i] = files[i+1];
        }
        n--;
    }
    return totalCost;
}

int main() {
    int n;
    printf("Number of files: ");
    scanf("%d", &n);
    int *files = (int *)malloc(n * sizeof(int));
    printf("Enter the sizes of %d files: ", n);
    for (int i = 0; i < n; i++) {
        scanf("%d", &files[i]);
    }
    int minCost = optimalMerge(files, n);
    printf("Minimum cost of merging is: %d\n", minCost);
    free(files);
    return 0;
}
```

## Execution Results - All test cases have succeeded!

Test Case - 1
User Output
Number of files: 5
Enter the sizes of 5 files: 20 10 5 30 30
Minimum cost of merging is: 205

Test Case - 2
User Output
Number of files: 6
Enter the sizes of 6 files: 8 11 16 18 9 20
Minimum cost of merging is: 208