1. Import Required Libraries

In [1]:
```
import pandas as pd
import numpy as np
```

2. Locate open source data from web

Dataset link : https://www.kaggle.com/c/titanic/data (https://www.kaggle.com/c/titanic/data)

3. Load the dataset into Pandas Dataframe

In [2]:
```
df = pd.read_csv("train.csv")
```

In [3]:
```
df
```

Out[3]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000

Scanned with CamScanner

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500
...	...	...	...	...	...	...	...	...	...	...
886	887	0	2	Montvila, Rev. Juozas	male	27.0	0	0	211536	13.0000
887	888	1	1	Graham, Miss. Margaret Edith	female	19.0	0	0	112053	30.0000
888	889	0	3	Johnston, Miss. Catherine Helen "Carrie"	female	NaN	1	2	W./C. 6607	23.4500
889	890	1	1	Behr, Mr. Karl Howell	male	26.0	0	0	111369	30.0000
				Dooley,						

4. Data Preprocessing

In [4]:
```
# check dimensions of dataframe
df.shape
```

Out[4]:
```
(891, 12)
```

In [5]:
```
# check the columns present
df.columns
```

Out[5]:
```
Index(['PassengerId', 'Survived', 'Pclass', 'Name', 'Sex', 'Age', 'SibSp',
       'Parch', 'Ticket', 'Fare', 'Cabin', 'Embarked'],
      dtype='object')
```

In [6]:
```
# check total size (rows * columns)
df.size
```

Out[6]:
```
10692
```

In [7]:
```
# check datatypes of each column
df.dtypes
```

Out[7]:

Scanned with CamScanner

```
PassengerId      int64
Survived         int64
Pclass           int64
Name            object
Sex             object
```

In [8]:
```
#check for missing values
df.isnull().sum()
```

Out[8]:
```
PassengerId      0
Survived         0
Pclass           0
Name             0
Sex              0
Age            177
SibSp            0
Parch            0
Ticket           0
Fare             0
Cabin          687
Embarked         2
dtype: int64
```

In [9]:
```
# check initial statistics
df.describe()
```

Out[9]:

	PassengerId	Survived	Pclass	Age	SibSp	Parch	Fare
count	891.000000	891.000000	891.000000	714.000000	891.000000	891.000000	891.000000
mean	446.000000	0.383838	2.308642	29.699118	0.523008	0.381594	32.204208
std	257.353842	0.486592	0.836071	14.526497	1.102743	0.806057	49.693429
min	1.000000	0.000000	1.000000	0.420000	0.000000	0.000000	0.000000
25%	223.500000	0.000000	2.000000	20.125000	0.000000	0.000000	7.910400
50%	446.000000	0.000000	3.000000	28.000000	0.000000	0.000000	14.454200
75%	668.500000	1.000000	3.000000	38.000000	1.000000	0.000000	31.000000
max	891.000000	1.000000	3.000000	80.000000	8.000000	6.000000	512.329200

In [10]:
```
# Print information about the dataframe
df.info()
```

Scanned with CamScanner

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 891 entries, 0 to 890
Data columns (total 12 columns):
 #   Column       Non-Null Count  Dtype
---  ------       --------------  -----
 0   PassengerId  891 non-null    int64
 1   Survived     891 non-null    int64
```

5. Data Formatting and Data Normalization

In [11]:
```
# Handling missing values
# 1. fillna() : method which we can use replace null(NaN) values with some oth
# or we can perform forward fill(ffill), backward fill(bfill).

# 2. interpolate() : performs linear interpolation(by default but you can chan
# and replaces the null with the result.

# 3. dropna() : It will drop all the rows that have NaN values. but using this
```

In [12]:
```
df["Cabin"] = df["Cabin"].replace(to_replace=np.nan, value="unknown")
df
```

Out[12]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500
...	...	...	...	...	...	...	...	...	...	...
886	887	0	2	Montvila, Rev. Juozas	male	27.0	0	0	211536	13.0000
887	888	1	1	Graham, Miss. Margaret Edith	female	19.0	0	0	112053	30.0000

Scanned with CamScanner

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
888	889	0	3	Johnston, Miss. Catherine Helen "Carrie"	female	NaN	1	2	W./C. 6607	23.4500
889	890	1	1	Behr, Mr. Karl Howell	male	26.0	0	0	111369	30.0000
890	891	0	3	Dooley, Mr.	male	32.0	0	0	370376	7.7500

In [13]:
```
df["Age"] = df["Age"].interpolate()
df
```

Out[13]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500
...	...	...	...	...	...	...	...	...	...	...
886	887	0	2	Montvila, Rev. Juozas	male	27.0	0	0	211536	13.0000
887	888	1	1	Graham, Miss. Margaret Edith	female	19.0	0	0	112053	30.0000
888	889	0	3	Johnston, Miss. Catherine Helen "Carrie"	female	22.5	1	2	W./C. 6607	23.4500
889	890	1	1	Behr, Mr. Karl Howell	male	26.0	0	0	111369	30.0000

Scanned with CamScanner

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
890	891	0	3	Dooley, Mr.	male	32.0	0	0	370376	7.7500

In [14]:
```
df["Embarked"].fillna(method="ffill",inplace=True)
```

In [15]:
```
df
```

Out[15]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500
...	...	...	...	...	...	...	...	...	...	...
886	887	0	2	Montvila, Rev. Juozas	male	27.0	0	0	211536	13.0000
887	888	1	1	Graham, Miss. Margaret Edith	female	19.0	0	0	112053	30.0000
888	889	0	3	Johnston, Miss. Catherine Helen "Carrie"	female	22.5	1	2	W./C. 6607	23.4500
889	890	1	1	Behr, Mr. Karl Howell	male	26.0	0	0	111369	30.0000
890	891	0	3	Dooley, Mr. Patrick	male	32.0	0	0	370376	7.7500

891 rows × 12 columns

Scanned with CamScanner

In [16]:
```
df.isnull().sum()
```

Out[16]:
```
PassengerId    0
Survived       0
Pclass         0
Name           0
Sex            0
Age            0
SibSp          0
Parch          0
Ticket         0
Fare           0
Cabin          0
Embarked       0
dtype: int64
```

In [17]:
```
# Changing Datatypes
df.dtypes
```

Out[17]:
```
PassengerId      int64
Survived         int64
Pclass           int64
Name            object
Sex             object
Age            float64
SibSp            int64
Parch            int64
Ticket          object
Fare           float64
Cabin           object
Embarked        object
dtype: object
```

In [18]:
```
df["Age"] = df["Age"].astype('int64')
```

In [19]:
```
df.dtypes
```

Out[19]:
```
PassengerId      int64
Survived         int64
Pclass           int64
Name            object
Sex             object
Age              int64
SibSp            int64
Parch            int64
Ticket          object
Fare           float64
Cabin           object
Embarked        object
dtype: object
```

6. Turning categorical variables into quantitive

Scanned with CamScanner

In [20]:
```
quantitative_data = pd.get_dummies(df.Embarked,prefix = 'Embarked')
```

In [21]:
```
quantitative_data
```

Out[21]:

	Embarked_C	Embarked_Q	Embarked_S
0	0	0	1
1	1	0	0
2	0	0	1
3	0	0	1
4	0	0	1
...	...	...	...
886	0	0	1
887	0	0	1
888	0	0	1
889	1	0	0
890	0	1	0

891 rows × 3 columns

In [22]:
```
df = df.join(quantitative_data)
df
```

Out[22]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
0	1	0	3	Braund, Mr. Owen Harris	male	22	1	0	A/5 21171	7.2500
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38	1	0	PC 17599	71.2833
2	3	1	3	Heikkinen, Miss. Laina	female	26	0	0	STON/O2. 3101282	7.9250
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35	1	0	113803	53.1000
4	5	0	3	Allen, Mr. William Henry	male	35	0	0	373450	8.0500
...	...	...	...	...	...	...	...	...	...	...

Scanned with CamScanner

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
886	887	0	2	Montvila, Rev. Juozas	male	27	0	0	211536	13.0000
887	888	1	1	Graham, Miss. Margaret Edith	female	19	0	0	112053	30.0000
888	889	0	3	Johnston, Miss. Catherine Helen "Carrie"	female	22	1	2	W./C. 6607	23.4500
889	890	1	1	Behr, Mr. Karl Howell	male	26	0	0	111369	30.0000
				Dooley,						

In [23]:
```
df.drop(['Embarked'],axis = 1,inplace = True)
df
```

Out[23]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
0	1	0	3	Braund, Mr. Owen Harris	male	22	1	0	A/5 21171	7.2500
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38	1	0	PC 17599	71.2833
2	3	1	3	Heikkinen, Miss. Laina	female	26	0	0	STON/O2. 3101282	7.9250
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35	1	0	113803	53.1000
4	5	0	3	Allen, Mr. William Henry	male	35	0	0	373450	8.0500
...	...	...	...	...	...	...	...	...	...	...
886	887	0	2	Montvila, Rev. Juozas	male	27	0	0	211536	13.0000
887	888	1	1	Graham, Miss. Margaret Edith	female	19	0	0	112053	30.0000

Scanned with CamScanner

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
888	889	0	3	Johnston, Miss. Catherine Helen "Carrie"	female	22	1	2	W./C. 6607	23.4500
889	890	1	1	Behr, Mr. Karl Howell	male	26	0	0	111369	30.0000

In [24]:
```
quantitative_sex = pd.get_dummies(df.Sex,prefix = 'Sex')
quantitative_sex
```

Out[24]:

	Sex_female	Sex_male
0	0	1
1	1	0
2	1	0
3	1	0
4	0	1
...	...	...
886	0	1
887	1	0
888	1	0
889	0	1
890	0	1

891 rows × 2 columns

In [25]:
```
df = df.join(quantitative_sex)
df
```

Out[25]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
0	1	0	3	Braund, Mr. Owen Harris	male	22	1	0	A/5 21171	7.2500
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38	1	0	PC 17599	71.2833
2	3	1	3	Heikkinen, Miss. Laina	female	26	0	0	STON/O2. 3101282	7.9250

Scanned with CamScanner

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35	1	0	113803	53.1000
4	5	0	3	Allen, Mr. William Henry	male	35	0	0	373450	8.0500
...	...	...	...	...	...	...	...	...	...	...
886	887	0	2	Montvila, Rev. Juozas	male	27	0	0	211536	13.0000
887	888	1	1	Graham, Miss. Margaret Edith	female	19	0	0	112053	30.0000
888	889	0	3	Johnston, Miss. Catherine Helen "Carrie"	female	22	1	2	W./C. 6607	23.4500
889	890	1	1	Behr, Mr. Karl owel	male	26	0	0	111369	30.0000

In [26]:
```
df.drop(['Sex'],axis = 1,inplace = True)
df
```

Out[26]:

	PassengerId	Survived	Pclass	Name	Age	SibSp	Parch	Ticket	Fare	Cabin
0	1	0	3	Braund, Mr. Owen Harris	22	1	0	A/5 21171	7.2500	unknown
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	38	1	0	PC 17599	71.2833	C85
2	3	1	3	Heikkinen, Miss. Laina	26	0	0	STON/O2. 3101282	7.9250	unknown
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	35	1	0	113803	53.1000	C123
4	5	0	3	Allen, Mr. William Henry	35	0	0	373450	8.0500	unknown
...	...	...	...	...	...	...	...	...	...	...

Scanned with CamScanner

	PassengerId	Survived	Pclass	Name	Age	SibSp	Parch	Ticket	Fare	Cabin
886	887	0	2	Montvila, Rev. Juozas	27	0	0	211536	13.0000	unknown
887	888	1	1	Graham, Miss. Margaret Edith	19	0	0	112053	30.0000	B42
888	889	0	3	Johnston, Miss. Catherine Helen "Carrie"	22	1	2	W./C. 6607	23.4500	unknown
889	890	1	1	Behr, Mr. Karl Howell	26	0	0	111369	30.0000	C148
				Dooley,						

Scanned with CamScanner

Assignment No 2 : Data Wrangling 2

1. Import Required Libraries

In [1]:
```
import pandas as pd
import numpy as np
```

2. Load the dataset into dataframe

In [2]:
```
df = pd.read_csv('StudentPerformance.csv')
```

In [3]:
```
df
```

Out[3]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
0	71.0	78	65.0	99.0	2018.0	
1	63.0	86	71.0	100.0	NaN	
2	71.0	92	64.0	76.0	2021.0	
3	77.0	95	68.0	84.0	2021.0	
4	63.0	81	70.0	76.0	2021.0	
5	NaN	92	NaN	89.0	2020.0	
6	66.0	75	67.0	93.0	2019.0	
7	50.0	100	68.0	200.0	2015.0	
8	60.0	90	61.0	87.0	2021.0	
9	64.0	89	72.0	80.0	2019.0	
10	63.0	81	62.0	95.0	2021.0	
11	66.0	95	77.0	90.0	2020.0	
12	60.0	88	73.0	91.0	2020.0	
13	72.0	80	69.0	98.0	2021.0	
14	60.0	76	NaN	82.0	2020.0	
15	69.0	83	69.0	NaN	2019.0	
16	72.0	80	20.0	75.0	2021.0	
17	90.0	95	66.0	85.0	2002.0	
18	70.0	89	73.0	90.0	2020.0	

Scanned with CamScanner

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
19	66.0	91	77.0	100.0	2020.0	
20	61.0	75	74.0	76.0	NaN	
21	NaN	77	79.0	82.0	2018.0	
22	65.0	95	60.0	100.0	2021.0	
23	63.0	86	78.0	82.0	2019.0	
24	78.0	95	66.0	NaN	2019.0	
25	71.0	84	72.0	89.0	2018.0	
26	78.0	78	73.0	87.0	2018.0	
27	67.0	79	67.0	89.0	2018.0	

Check the dimensions of dataframe

In [4]:
```
df.shape
```

Out[4]:
```
(30, 6)
```

Check the number of null values in each column

In [5]:
```
df.isnull().sum()
```

Out[5]:
```
math_score              2
reading_score           0
writing_score           3
placement_score         2
club_join_date          2
placement_offer_count   1
dtype: int64
```

In [6]:
```
df.isnull()
```

Out[6]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
0	False	False	False	False	False	
1	False	False	False	False	True	
2	False	False	False	False	False	
3	False	False	False	False	False	
4	False	False	False	False	False	
5	True	False	True	False	False	
6	False	False	False	False	False	
7	False	False	False	False	False	

Scanned with CamScanner

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
8	False	False	False	False	False	
9	False	False	False	False	False	
10	False	False	False	False	False	
11	False	False	False	False	False	
12	False	False	False	False	False	
13	False	False	False	False	False	
14	False	False	True	False	False	
15	False	False	False	True	False	
16	False	False	False	False	False	
17	False	False	False	False	False	
18	False	False	False	False	False	
19	False	False	False	False	False	
20	False	False	False	False	True	
21	True	False	False	False	False	
22	False	False	False	False	False	
23	False	False	False	False	False	
24	False	False	False	True	False	
25	False	False	False	False	False	
26	False	False	False	False	False	
27	False	False	False	False	False	
28	False	False	True	False	False	

Handling missing/null values

In [7]:
```
df['math_score']=df['math_score'].interpolate()
df
```

Out[7]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
0	71.0	78	65.0	99.0	2018.0	
1	63.0	86	71.0	100.0	NaN	
2	71.0	92	64.0	76.0	2021.0	
3	77.0	95	68.0	84.0	2021.0	
4	63.0	81	70.0	76.0	2021.0	
5	64.5	92	NaN	89.0	2020.0	
6	66.0	75	67.0	93.0	2019.0	
7	50.0	100	68.0	200.0	2015.0	

Scanned with CamScanner

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
8	60.0	90	61.0	87.0	2021.0	
9	64.0	89	72.0	80.0	2019.0	
10	63.0	81	62.0	95.0	2021.0	
11	66.0	95	77.0	90.0	2020.0	
12	60.0	88	73.0	91.0	2020.0	
13	72.0	80	69.0	98.0	2021.0	
14	60.0	76	NaN	82.0	2020.0	
15	69.0	83	69.0	NaN	2019.0	
16	72.0	80	20.0	75.0	2021.0	
17	90.0	95	66.0	85.0	2002.0	
18	70.0	89	73.0	90.0	2020.0	
19	66.0	91	77.0	100.0	2020.0	
20	61.0	75	74.0	76.0	NaN	
21	63.0	77	79.0	82.0	2018.0	
22	65.0	95	60.0	100.0	2021.0	
23	63.0	86	78.0	82.0	2019.0	
24	78.0	95	66.0	NaN	2019.0	
25	71.0	84	72.0	89.0	2018.0	
26	78.0	78	73.0	87.0	2018.0	
27	67.0	79	67.0	89.0	2018.0	

In [8]:
```
df.isnull().sum()
```

Out[8]:
```
math_score             0
reading_score          0
writing_score          3
placement_score        2
club_join_date         2
placement_offer_count  1
dtype: int64
```

In [9]:
```
df['writing_score'] = df['writing_score'].fillna(method='ffill')
df
```

Out[9]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
0	71.0	78	65.0	99.0	2018.0	
1	63.0	86	71.0	100.0	NaN	
2	71.0	92	64.0	76.0	2021.0	
3	77.0	95	68.0	84.0	2021.0	
4	63.0	81	70.0	76.0	2021.0	

Scanned with CamScanner

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
5	64.5	92	70.0	89.0	2020.0	
6	66.0	75	67.0	93.0	2019.0	
7	50.0	100	68.0	200.0	2015.0	
8	60.0	90	61.0	87.0	2021.0	
9	64.0	89	72.0	80.0	2019.0	
10	63.0	81	62.0	95.0	2021.0	
11	66.0	95	77.0	90.0	2020.0	
12	60.0	88	73.0	91.0	2020.0	
13	72.0	80	69.0	98.0	2021.0	
14	60.0	76	69.0	82.0	2020.0	
15	69.0	83	69.0	NaN	2019.0	
16	72.0	80	20.0	75.0	2021.0	
17	90.0	95	66.0	85.0	2002.0	
18	70.0	89	73.0	90.0	2020.0	
19	66.0	91	77.0	100.0	2020.0	
20	61.0	75	74.0	76.0	NaN	
21	63.0	77	79.0	82.0	2018.0	
22	65.0	95	60.0	100.0	2021.0	
23	63.0	86	78.0	82.0	2019.0	
24	78.0	95	66.0	NaN	2019.0	
25	71.0	84	72.0	89.0	2018.0	
26	78.0	78	73.0	87.0	2018.0	
27	67.0	79	67.0	89.0	2018.0	
28	75.0	79	67.0	97.0	2020.0	

In [10]:
```
df.isnull().sum()
```

Out[10]:
```
math_score              0
reading_score           0
writing_score           0
placement_score         2
club_join_date          2
placement_offer_count   1
dtype: int64
```

In [11]:
```
df['placement_score'] = df['placement_score'].fillna(method='bfill')
df
```

Out[11]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
0	71.0	78	65.0	99.0	2018.0	
1	63.0	86	71.0	100.0	NaN	

Scanned with CamScanner

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
2	71.0	92	64.0	76.0	2021.0	
3	77.0	95	68.0	84.0	2021.0	
4	63.0	81	70.0	76.0	2021.0	
5	64.5	92	70.0	89.0	2020.0	
6	66.0	75	67.0	93.0	2019.0	
7	50.0	100	68.0	200.0	2015.0	
8	60.0	90	61.0	87.0	2021.0	
9	64.0	89	72.0	80.0	2019.0	
10	63.0	81	62.0	95.0	2021.0	
11	66.0	95	77.0	90.0	2020.0	
12	60.0	88	73.0	91.0	2020.0	
13	72.0	80	69.0	98.0	2021.0	
14	60.0	76	69.0	82.0	2020.0	
15	69.0	83	69.0	75.0	2019.0	
16	72.0	80	20.0	75.0	2021.0	
17	90.0	95	66.0	85.0	2002.0	
18	70.0	89	73.0	90.0	2020.0	
19	66.0	91	77.0	100.0	2020.0	
20	61.0	75	74.0	76.0	NaN	
21	63.0	77	79.0	82.0	2018.0	
22	65.0	95	60.0	100.0	2021.0	
23	63.0	86	78.0	82.0	2019.0	
24	78.0	95	66.0	89.0	2019.0	
25	71.0	84	72.0	89.0	2018.0	
26	78.0	78	73.0	87.0	2018.0	
27	67.0	79	67.0	89.0	2018.0	
28	75.0	79	67.0	97.0	2020.0	

In [12]:
```
df.isnull().sum()
```

Out[12]:
```
math_score              0
reading_score           0
writing_score           0
placement_score         0
club_join_date          2
placement_offer_count   1
dtype: int64
```

In [13]:
```
df['club_join_date'] = df['club_join_date'].replace(to_replace=np.nan,value= 2
df
```

Scanned with CamScanner

Out[13]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
0	71.0	78	65.0	99.0	2018	
1	63.0	86	71.0	100.0	2019	
2	71.0	92	64.0	76.0	2021	
3	77.0	95	68.0	84.0	2021	
4	63.0	81	70.0	76.0	2021	
5	64.5	92	70.0	89.0	2020	
6	66.0	75	67.0	93.0	2019	
7	50.0	100	68.0	200.0	2015	
8	60.0	90	61.0	87.0	2021	
9	64.0	89	72.0	80.0	2019	
10	63.0	81	62.0	95.0	2021	
11	66.0	95	77.0	90.0	2020	
12	60.0	88	73.0	91.0	2020	
13	72.0	80	69.0	98.0	2021	
14	60.0	76	69.0	82.0	2020	
15	69.0	83	69.0	75.0	2019	
16	72.0	80	20.0	75.0	2021	
17	90.0	95	66.0	85.0	2002	
18	70.0	89	73.0	90.0	2020	
19	66.0	91	77.0	100.0	2020	
20	61.0	75	74.0	76.0	2019	
21	63.0	77	79.0	82.0	2018	
22	65.0	95	60.0	100.0	2021	
23	63.0	86	78.0	82.0	2019	
24	78.0	95	66.0	89.0	2019	
25	71.0	84	72.0	89.0	2018	
26	78.0	78	73.0	87.0	2018	
27	67.0	79	67.0	89.0	2018	
28	75.0	79	67.0	97.0	2020	
29	73.0	78	61.0	75.0	2020	

In [14]:
```
df.isnull().sum()
```

Out[14]:

Scanned with CamScanner

```
math_score                0
reading_score             0
```

In [15]:
```
df['placement_offer_count']=df['placement_offer_count'].fillna('1')
df
```

Out[15]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
0	71.0	78	65.0	99.0	2018	
1	63.0	86	71.0	100.0	2019	
2	71.0	92	64.0	76.0	2021	
3	77.0	95	68.0	84.0	2021	
4	63.0	81	70.0	76.0	2021	
5	64.5	92	70.0	89.0	2020	
6	66.0	75	67.0	93.0	2019	
7	50.0	100	68.0	200.0	2015	
8	60.0	90	61.0	87.0	2021	
9	64.0	89	72.0	80.0	2019	
10	63.0	81	62.0	95.0	2021	
11	66.0	95	77.0	90.0	2020	
12	60.0	88	73.0	91.0	2020	
13	72.0	80	69.0	98.0	2021	
14	60.0	76	69.0	82.0	2020	
15	69.0	83	69.0	75.0	2019	
16	72.0	80	20.0	75.0	2021	
17	90.0	95	66.0	85.0	2002	
18	70.0	89	73.0	90.0	2020	
19	66.0	91	77.0	100.0	2020	
20	61.0	75	74.0	76.0	2019	
21	63.0	77	79.0	82.0	2018	
22	65.0	95	60.0	100.0	2021	
23	63.0	86	78.0	82.0	2019	
24	78.0	95	66.0	89.0	2019	
25	71.0	84	72.0	89.0	2018	
26	78.0	78	73.0	87.0	2018	
27	67.0	79	67.0	89.0	2018	
28	75.0	79	67.0	97.0	2020	
29	73.0	78	61.0	75.0	2020	

Scanned with CamScanner

In [16]:
```
df.isnull().sum()
```

Out[16]:
```
math_score               0
reading_score            0
writing_score            0
placement_score          0
club_join_date           0
placement_offer_count    0
dtype: int64
```

Check the data types and convert into appropriate types

In [17]:
```
df.dtypes
```

Out[17]:
```
math_score               float64
reading_score              int64
writing_score            float64
placement_score          float64
club_join_date            object
placement_offer_count     object
dtype: object
```

In [18]:
```
df['math_score']=df['math_score'].astype('int64')
df['reading_score']=df['reading_score'].astype('int64')
df['writing_score']=df['writing_score'].astype('int64')
df['placement_score']=df['placement_score'].astype('int64')
df['club_join_date']=df['club_join_date'].astype('int64')
df['placement_offer_count']=df['placement_offer_count'].astype('int64')
df.dtypes
```

Out[18]:
```
math_score               int64
reading_score            int64
writing_score            int64
placement_score          int64
club_join_date           int64
placement_offer_count    int64
dtype: object
```

Check for outliers

Scanned with CamScanner

In [19]:
```
columns = ['math_score','reading_score','writing_score','placement_score']
df.boxplot(columns)
```

Out[19]: <matplotlib.axes._subplots.AxesSubplot at 0x5d9471ffc8>



In [20]:
```
np.where(df['math_score'] < 60)
```

Out[20]: (array([7], dtype=int64),)

In [21]:
```
np.where(df['math_score'] > 80)
```

Out[21]: (array([17], dtype=int64),)

In [22]:
```
np.where(df['reading_score'] < 75)
```

Out[22]: (array([], dtype=int64),)

In [23]:
```
np.where(df['reading_score'] > 95)
```

Out[23]: (array([7], dtype=int64),)

In [24]:
```
np.where(df['writing_score'] < 60)
```

Out[24]: (array([16], dtype=int64),)

In [25]:
```
np.where(df['writing_score'] > 80)
```

Out[25]: (array([], dtype=int64),)

In [26]:
```
np.where(df['placement_score'] < 75)
```

Out[26]: (array([], dtype=int64),)

In [27]:
```
np.where(df['placement_score'] > 100)
```

Out[27]: (array([7], dtype=int64),)

Scanned with CamScanner

In [28]:
```
np.where((df['placement_score'] < 75) & (df['placement_offer_count'] > 1))
```
Out[28]:
```
(array([], dtype=int64),)
```

In [29]:
```
np.where(((df['placement_score'] > 75) & (df['placement_score'] <= 85))
         & ((df['placement_offer_count'] > 2) | (df['placement_offer_count'] <
```
Out[29]:
```
(array([17, 21], dtype=int64),)
```

In [30]:
```
np.where((df['placement_score'] > 85) & (df['placement_offer_count'] < 3))
```
Out[30]:
```
(array([10, 24], dtype=int64),)
```

In [31]:
```
# The above results gives us the rows with the outliers
# There are different methods that can be used for outlier detection and remov
# 1. Percentile
# 2. Standard Deviation
# 3. Z score
```

Outlier detection

In [32]:
```
df[(df['math_score'] < 60) | (df['math_score'] > 80)]
```
Out[32]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
7	50	100	68	200	2015	
17	90	95	66	85	2002	

In [33]:
```
df[(df['reading_score'] < 75) | (df['reading_score'] > 95)]
```
Out[33]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_c
7	50	100	68	200	2015	

In [34]:
```
df[(df['writing_score'] < 60) | (df['writing_score'] > 80)]
```
Out[34]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
16	72	80	20	75	2021	

In [35]:
```
df[(df['placement_score'] < 75) | (df['placement_score'] > 100)]
```
Out[35]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_c
7	50	100	68	200	2015	

In [36]:
```
df[(df['club_join_date'] < 2018) | (df['club_join_date'] > 2021)]
```
Out[36]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
7	50	100	68	200	2015	

Scanned with CamScanner

In [37]:
```
df[(df['placement_score'] < 75) & (df['placement_offer_count'] > 1)]
```

Out[37]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_co

In [38]:
```
df[((df['placement_score'] > 75) & (df['placement_score'] <= 85))
   & ((df['placement_offer_count'] > 2) | (df['placement_offer_count'] < 2))]
```

Out[38]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
17	90	95	66	85	2002	
21	63	77	79	82	2018	

In [39]:
```
df[((df['placement_score'] > 85) & (df['placement_offer_count'] < 3))]
```

Out[39]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
10	63	81	62	95	2021	
24	78	95	66	89	2019	

Outlier Removal

In [40]:
```
new_df1 = df[
    ((df.math_score >= 60) & (df.math_score <= 80)) &
    ((df.reading_score >= 75) & (df.reading_score <= 95)) &
    ((df.writing_score >= 60) & (df.writing_score <= 80)) &
    ((df.placement_score >= 75) & (df.placement_score <= 100)) &
    ((df.club_join_date >= 2018) & (df.club_join_date <= 2021))]
```

In [41]:
```
new_df1
```

Out[41]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
0	71	78	65	99	2018	
1	63	86	71	100	2019	
2	71	92	64	76	2021	
3	77	95	68	84	2021	
4	63	81	70	76	2021	
5	64	92	70	89	2020	
6	66	75	67	93	2019	
8	60	90	61	87	2021	
9	64	89	72	80	2019	
10	63	81	62	95	2021	
11	66	95	77	90	2020	
12	60	88	73	91	2020	

Scanned with CamScanner

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
13	72	80	69	98	2021	
14	60	76	69	82	2020	
15	69	83	69	75	2019	
18	70	89	73	90	2020	
19	66	91	77	100	2020	
20	61	75	74	76	2019	
21	63	77	79	82	2018	
22	65	95	60	100	2021	
23	63	86	78	82	2019	
24	78	95	66	89	2019	
25	71	84	72	89	2018	
26	78	78	73	87	2018	
27	67	79	67	89	2018	
28	75	79	67	97	2020	

In [42]:
```
new_df1[(new_df1['placement_score'] < 75) & (new_df1['placement_offer_count']
```

Out[42]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_co

In [43]:
```
new_df1[((new_df1['placement_score'] >= 75) & (new_df1['placement_score'] <= 8
   & ((new_df1['placement_offer_count'] > 2) | (new_df1['placement_offer_count
```

Out[43]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
15	69	83	69	75	2019	
21	63	77	79	82	2018	

In [44]:
```
new_df1[((new_df1['placement_score'] > 85) & (new_df1['placement_offer_count']
```

Out[44]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
10	63	81	62	95	2021	
24	78	95	66	89	2019	

In [45]:
```
new_df2 = new_df1[
    ((new_df1.placement_score < 75) & (new_df1.placement_offer_count==1)) |
    (((new_df1.placement_score >= 75) & (new_df1.placement_score <= 85)) & (ne
    ((new_df1.placement_score > 85) & (new_df1.placement_offer_count==3))]
```

In [46]:
```
new_df2
```

Out[46]:

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
0	71	78	65	99	2018	
1	63	86	71	100	2019	

Scanned with CamScanner

	math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_
2	71	92	64	76	2021	
3	77	95	68	84	2021	
4	63	81	70	76	2021	
5	64	92	70	89	2020	
6	66	75	67	93	2019	
8	60	90	61	87	2021	
9	64	89	72	80	2019	
11	66	95	77	90	2020	
12	60	88	73	91	2020	
13	72	80	69	98	2021	
14	60	76	69	82	2020	
18	70	89	73	90	2020	
19	66	91	77	100	2020	
20	61	75	74	76	2019	
22	65	95	60	100	2021	
23	63	86	78	82	2019	
25	71	84	72	89	2018	
26	78	78	73	87	2018	
27	67	79	67	89	2018	
28	75	79	67	97	2020	

In [47]:
```
new_df2.shape
```

Out[47]: (23, 6)

Check if the outliers are completely removed

In [48]:
```
new_df2[(new_df2['math_score'] < 60) | (new_df2['math_score'] > 80)]
```

Out[48]:

math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_co

In [49]:
```
new_df2[(new_df2['reading_score'] < 75) | (new_df2['reading_score'] > 95)]
```

Out[49]:

math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_co

In [50]:
```
new_df2[(new_df2['writing_score'] < 60) | (new_df2['writing_score'] > 80)]
```

Out[50]:

math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_co

Scanned with CamScanner

In [51]:
```
new_df2[(new_df2['placement_score'] < 75) | (new_df2['placement_score'] > 100)
```

Out[51]:

math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_co

In [52]:
```
new_df2[(new_df2['club_join_date'] < 2018) | (new_df2['club_join_date'] > 2021
```

Out[52]:

math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_co

In [53]:
```
new_df2[(new_df2['placement_score'] < 75) & (new_df2['placement_offer_count']
```

Out[53]:

math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_co

In [54]:
```
new_df2[((new_df2['placement_score'] > 75) & (new_df2['placement_score'] <= 85
    & ((new_df2['placement_offer_count'] > 2) | (new_df2['placement_offer_count
```

Out[54]:

math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_co

In [55]:
```
new_df2[((new_df2['placement_score'] > 85) & (new_df2['placement_offer_count']
```

Out[55]:

math_score	reading_score	writing_score	placement_score	club_join_date	placement_offer_co

Data transformation and Normalization

In [56]:
```
from sklearn.preprocessing import MinMaxScaler
scaling = MinMaxScaler()
scaling.fit_transform(new_df2[['math_score','reading_score','writing_score','p
```

Out[56]:
```
array([[0.61111111, 0.15      , 0.27777778, 0.96      ],
       [0.16666667, 0.55      , 0.61111111, 1.        ],
       [0.61111111, 0.85      , 0.22222222, 0.04      ],
       [0.94444444, 1.        , 0.44444444, 0.36      ],
       [0.16666667, 0.3       , 0.55555556, 0.04      ],
       [0.22222222, 0.85      , 0.55555556, 0.56      ],
       [0.33333333, 0.        , 0.38888889, 0.72      ],
       [0.        , 0.75      , 0.05555556, 0.48      ],
       [0.22222222, 0.7       , 0.66666667, 0.2       ],
       [0.33333333, 1.        , 0.94444444, 0.6       ],
       [0.        , 0.65      , 0.72222222, 0.64      ],
       [0.66666667, 0.25      , 0.5       , 0.92      ],
       [0.        , 0.05      , 0.5       , 0.28      ],
       [0.55555556, 0.7       , 0.72222222, 0.6       ],
       [0.33333333, 0.8       , 0.94444444, 1.        ],
       [0.05555556, 0.        , 0.77777778, 0.04      ],
       [0.27777778, 1.        , 0.        , 1.        ],
       [0.16666667, 0.55      , 1.        , 0.28      ],
       [0.61111111, 0.45      , 0.66666667, 0.56      ],
       [1.        , 0.15      , 0.72222222, 0.48      ],
       [0.38888889, 0.2       , 0.38888889, 0.56      ],
       [0.83333333, 0.2       , 0.38888889, 0.88      ],
       [0.72222222, 0.15      , 0.05555556, 0.        ]])
```

Scanned with CamScanner

Assignment No 3 : Descriptive Statistics - Measures of Central Tendency and Variability

Import Required Libraries

In [1]:
```
import pandas as pd
import numpy as np
```

Read csv into Dataframe

In [2]:
```
df = pd.read_csv('iris.csv')
```

In [3]:
```
df
```

Out[3]:

	Id	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm	Species
0	1	5.1	3.5	1.4	0.2	Iris-setosa
1	2	4.9	3.0	1.4	0.2	Iris-setosa
2	3	4.7	3.2	1.3	0.2	Iris-setosa
3	4	4.6	3.1	1.5	0.2	Iris-setosa
4	5	5.0	3.6	1.4	0.2	Iris-setosa
...	...	...	...	...	...	...
145	146	6.7	3.0	5.2	2.3	Iris-virginica
146	147	6.3	2.5	5.0	1.9	Iris-virginica
147	148	6.5	3.0	5.2	2.0	Iris-virginica
148	149	6.2	3.4	5.4	2.3	Iris-virginica
149	150	5.9	3.0	5.1	1.8	Iris-virginica

150 rows × 6 columns

Data Preprocessing

In [4]:
```
df.shape
```

Out[4]:
```
(150, 6)
```

Scanned with CamScanner

In [5]:
```
df.isnull().sum()
```

Out[5]:
```
Id               0
SepalLengthCm    0
SepalWidthCm     0
PetalLengthCm    0
PetalWidthCm     0
Species          0
dtype: int64
```

In [6]:
```
df.dtypes
```

Out[6]:
```
Id                 int64
SepalLengthCm    float64
SepalWidthCm     float64
PetalLengthCm    float64
PetalWidthCm     float64
Species           object
dtype: object
```

In [7]:
```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 150 entries, 0 to 149
Data columns (total 6 columns):
 #   Column         Non-Null Count  Dtype
---  ------         --------------  -----
 0   Id             150 non-null    int64
 1   SepalLengthCm  150 non-null    float64
 2   SepalWidthCm   150 non-null    float64
 3   PetalLengthCm  150 non-null    float64
 4   PetalWidthCm   150 non-null    float64
 5   Species        150 non-null    object
dtypes: float64(4), int64(1), object(1)
memory usage: 7.2+ KB
```

In [8]:
```
df.drop(columns = 'Id', inplace = True)
df
```

Out[8]:

	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm	Species
0	5.1	3.5	1.4	0.2	Iris-setosa
1	4.9	3.0	1.4	0.2	Iris-setosa
2	4.7	3.2	1.3	0.2	Iris-setosa
3	4.6	3.1	1.5	0.2	Iris-setosa
4	5.0	3.6	1.4	0.2	Iris-setosa
...	...	...	...	...	...
145	6.7	3.0	5.2	2.3	Iris-virginica
146	6.3	2.5	5.0	1.9	Iris-virginica
147	6.5	3.0	5.2	2.0	Iris-virginica

Scanned with CamScanner

	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm	Species
148	6.2	3.4	5.4	2.3	Iris-virginica
149	5.9	3.0	5.1	1.8	Iris-virginica

In [9]:
```
df.describe()
```

Out[9]:

	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm
count	150.000000	150.000000	150.000000	150.000000
mean	5.843333	3.054000	3.758667	1.198667
std	0.828066	0.433594	1.764420	0.763161
min	4.300000	2.000000	1.000000	0.100000
25%	5.100000	2.800000	1.600000	0.300000
50%	5.800000	3.000000	4.350000	1.300000
75%	6.400000	3.300000	5.100000	1.800000
max	7.900000	4.400000	6.900000	2.500000

Calculation of Mean for each Feature

In [10]:
```
np.mean(df['SepalLengthCm'])
```

Out[10]: 5.843333333333335

In [11]:
```
np.mean(df['SepalWidthCm'])
```

Out[11]: 3.0540000000000007

In [12]:
```
np.mean(df['PetalLengthCm'])
```

Out[12]: 3.7586666666666693

In [13]:
```
np.mean(df['PetalWidthCm'])
```

Out[13]: 1.1986666666666672

In [14]:
```
np.mean(df)
```

Out[14]:
```
SepalLengthCm    5.843333
SepalWidthCm     3.054000
PetalLengthCm    3.758667
PetalWidthCm     1.198667
dtype: float64
```

Calculation of Standard Deviation for each feature

In [15]:
```
np.std(df)
```

Out[15]:

Scanned with CamScanner

```
SepalLengthCm    0.825301
SepalWidthCm     0.432147
PetalLengthCm    1.758529
PetalWidthCm     0.760613
```

Calculating minimum value

In [16]:
```
np.min(df)
```

Out[16]:
```
SepalLengthCm            4.3
SepalWidthCm               2
PetalLengthCm              1
PetalWidthCm             0.1
Species          Iris-setosa
dtype: object
```

Calculating maximum value

In [17]:
```
np.max(df)
```

Out[17]:
```
SepalLengthCm               7.9
SepalWidthCm                4.4
PetalLengthCm               6.9
PetalWidthCm                2.5
Species          Iris-virginica
dtype: object
```

Calculating 1st quantile (25th percentile)

In [18]:
```
df.quantile(0.25)
```

Out[18]:
```
SepalLengthCm    5.1
SepalWidthCm     2.8
PetalLengthCm    1.6
PetalWidthCm     0.3
Name: 0.25, dtype: float64
```

Calculating 2nd quantile (50th percentile)

In [19]:
```
df.quantile(0.50)
```

Out[19]:
```
SepalLengthCm    5.80
SepalWidthCm     3.00
PetalLengthCm    4.35
PetalWidthCm     1.30
Name: 0.5, dtype: float64
```

Calculating 3rd quantile (75th percentile)

In [20]:
```
df.quantile(0.75)
```

Out[20]:

Scanned with CamScanner

```
SepalLengthCm    6.4
SepalWidthCm     3.3
PetalLengthCm    5.1
PetalWidthCm     1.8
```

Scanned with CamScanner

Assignment No 4 : Data Analytics 1

Reading Required Dataset

In [1]:
```
from sklearn.datasets import load_boston
boston = load_boston()
```

In [2]:
```
print(boston)
```

```
{'data': array([[6.3200e-03, 1.8000e+01, 2.3100e+00, ..., 1.5300e+01, 3.9690
e+02,
        4.9800e+00],
       [2.7310e-02, 0.0000e+00, 7.0700e+00, ..., 1.7800e+01, 3.9690e+02,
        9.1400e+00],
       [2.7290e-02, 0.0000e+00, 7.0700e+00, ..., 1.7800e+01, 3.9283e+02,
        4.0300e+00],

       [6.0760e-02, 0.0000e+00, 1.1930e+01, ..., 2.1000e+01, 3.9690e+02,
        5.6400e+00],
       [1.0959e-01, 0.0000e+00, 1.1930e+01, ..., 2.1000e+01, 3.9345e+02,
        6.4800e+00],
       [4.7410e-02, 0.0000e+00, 1.1930e+01, ..., 2.1000e+01, 3.9690e+02,
        7.8800e+00]]), 'target': array([24. , 21.6, 34.7, 33.4, 36.2, 28.7, 2
2.9, 27.1, 16.5, 18.9, 15. ,
       18.9, 21.7, 20.4, 18.2, 19.9, 23.1, 17.5, 20.2, 18.2, 13.6, 19.6,
       15.2, 14.5, 15.6, 13.9, 16.6, 14.8, 18.4, 21. , 12.7, 14.5, 13.2,
       13.1, 13.5, 18.9, 20. , 21. , 24.7, 30.8, 34.9, 26.6, 25.3, 24.7,
       21.2, 19.3, 20. , 16.6, 14.4, 19.4, 19.7, 20.5, 25. , 23.4, 18.9,
       35.4, 24.7, 31.6, 23.3, 19.6, 18.7, 16. , 22.2, 25. , 33. , 23.5,
       19.4, 22. , 17.4, 20.9, 24.2, 21.7, 22.8, 23.4, 24.1, 21.4, 20. ,
       20.8, 21.2, 20.3, 28. , 23.9, 24.8, 22.9, 23.9, 26.6, 22.5, 22.2,
       23.6, 28.7, 22.6, 22. , 22.9, 25. , 20.6, 28.4, 21.4, 38.7, 43.8,
       33.2, 27.5, 26.5, 18.6, 19.3, 20.1, 19.5, 19.5, 20.4, 19.8, 19.4,
       21.7, 22.8, 18.8, 18.7, 18.5, 18.3, 21.2, 19.2, 20.4, 19.3, 22. ,
       20.3, 20.5, 17.3, 18.8, 21.4, 15.7, 16.2, 18. , 14.3, 19.2, 19.6,
       23. , 18.4, 15.6, 18.1, 17.4, 17.1, 13.3, 17.8, 14. , 14.4, 13.4,
       15.6, 11.8, 13.8, 15.6, 14.6, 17.8, 15.4, 21.5, 19.6, 15.3, 19.4,
       17. , 15.6, 13.1, 41.3, 24.3, 23.3, 27. , 50. , 50. , 50. , 22.7,
       25. , 50. , 23.8, 23.8, 22.3, 17.4, 19.1, 23.1, 23.6, 22.6, 29.4,
       23.2, 24.6, 29.9, 37.2, 39.8, 36.2, 37.9, 32.5, 26.4, 29.6, 50. ,
       32. , 29.8, 34.9, 37. , 30.5, 36.4, 31.1, 29.1, 50. , 33.3, 30.3,
       34.6, 34.9, 32.9, 24.1, 42.3, 48.5, 50. , 22.6, 24.4, 22.5, 24.4,
       20. , 21.7, 19.3, 22.4, 28.1, 23.7, 25. , 23.3, 28.7, 21.5, 23. ,
       26.7, 21.7, 27.5, 30.1, 44.8, 50. , 37.6, 31.6, 46.7, 31.5, 24.3,
       31.7, 41.7, 48.3, 29. , 24. , 25.1, 31.5, 23.7, 23.3, 22. , 20.1,
       22.2, 23.7, 17.6, 18.5, 24.3, 20.5, 24.5, 26.2, 24.4, 24.8, 29.6,
       42.8, 21.9, 20.9, 44. , 50. , 36. , 30.1, 33.8, 43.1, 48.8, 31. ,
       36.5, 22.8, 30.7, 50. , 43.5, 20.7, 21.1, 25.2, 24.4, 35.2, 32.4,
       32. , 33.2, 33.1, 29.1, 35.1, 45.4, 35.4, 46. , 50. , 32.2, 22. ,
       20.1, 23.2, 22.3, 24.8, 28.5, 37.3, 27.9, 23.9, 21.7, 28.6, 27.1,
       20.3, 22.5, 29. , 24.8, 22. , 26.4, 33.1, 36.1, 28.4, 33.4, 28.2,
       22.8, 20.3, 16.1, 22.1, 19.4, 21.6, 23.8, 16.2, 17.8, 19.8, 23.1,
       21. , 23.8, 23.1, 20.4, 18.5, 25. , 24.6, 23. , 22.2, 19.3, 22.6,
```

Scanned with CamScanner

```
19.8, 17.1, 19.4, 22.2, 20.7, 21.1, 19.5, 18.5, 20.6, 19. , 18.7,
32.7, 16.5, 23.9, 31.2, 17.5, 17.2, 23.1, 24.5, 26.6, 22.9, 24.1,
18.6, 30.1, 18.2, 20.6, 17.8, 21.7, 22.7, 22.6, 25. , 19.9, 20.8,
16.8, 21.9, 27.5, 21.9, 23.1, 50. , 50. , 50. , 50. , 50. , 13.8,
13.8, 15. , 13.9, 13.3, 13.1, 10.2, 10.4, 10.9, 11.3, 12.3,  8.8,
 7.2, 10.5,  7.4, 10.2, 11.5, 15.1, 23.2,  9.7, 13.8, 12.7, 13.1,
12.5,  8.5,  5. ,  6.3,  5.6,  7.2, 12.1,  8.3,  8.5,  5. , 11.9,
27.9, 17.2, 27.5, 15. , 17.2, 17.9, 16.3,  7. ,  7.2,  7.5, 10.4,
 8.8,  8.4, 16.7, 14.2, 20.8, 13.4, 11.7,  8.3, 10.2, 10.9, 11. ,
 9.5, 14.5, 14.1, 16.1, 14.3, 11.7, 13.4,  9.6,  8.7,  8.4, 12.8,
10.5, 17.1, 18.4, 15.4, 10.8, 11.8, 14.9, 12.6, 14.1, 13. , 13.4,
15.2, 16.1, 17.8, 14.9, 14.1, 12.7, 13.5, 14.9, 20. , 16.4, 17.7,
19.5, 20.2, 21.4, 19.9, 19. , 19.1, 19.1, 20.1, 19.9, 19.6, 23.2,
29.8, 13.8, 13.3, 16.7, 12. , 14.6, 21.4, 23. , 23.7, 25. , 21.8,
```

Importing Required Libraries

In [3]:
```
import pandas as pd
import numpy as np
from sklearn import linear_model
from sklearn.model_selection import train_test_split
```

Creating Dataframe

In [4]:
```
df_x = pd.DataFrame(boston.data, columns=boston.feature_names)
```

In [5]:
```
df_y = pd.DataFrame(boston.target)
```

In [6]:
```
df_x
```

Out[6]:

	CRIM	ZN	INDUS	CHAS	NOX	RM	AGE	DIS	RAD	TAX	PTRATIO	B	L
0	0.00632	18.0	2.31	0.0	0.538	6.575	65.2	4.0900	1.0	296.0	15.3	396.90	
1	0.02731	0.0	7.07	0.0	0.469	6.421	78.9	4.9671	2.0	242.0	17.8	396.90	
2	0.02729	0.0	7.07	0.0	0.469	7.185	61.1	4.9671	2.0	242.0	17.8	392.83	
3	0.03237	0.0	2.18	0.0	0.458	6.998	45.8	6.0622	3.0	222.0	18.7	394.63	
4	0.06905	0.0	2.18	0.0	0.458	7.147	54.2	6.0622	3.0	222.0	18.7	396.90	
...	...	...	...	...	...	...	...	...	...	...	...	...	
501	0.06263	0.0	11.93	0.0	0.573	6.593	69.1	2.4786	1.0	273.0	21.0	391.99	
502	0.04527	0.0	11.93	0.0	0.573	6.120	76.7	2.2875	1.0	273.0	21.0	396.90	
503	0.06076	0.0	11.93	0.0	0.573	6.976	91.0	2.1675	1.0	273.0	21.0	396.90	
504	0.10959	0.0	11.93	0.0	0.573	6.794	89.3	2.3889	1.0	273.0	21.0	393.45	
505	0.04741	0.0	11.93	0.0	0.573	6.030	80.8	2.5050	1.0	273.0	21.0	396.90	

506 rows × 13 columns

In [8]:
```
df_y
```

Out[8]:

	0
0	24.0

Scanned with CamScanner

	0
502	20.6
503	23.9
504	22.0
505	11.9

In [9]:
```
df_x.describe()
```

Out[9]:

	CRIM	ZN	INDUS	CHAS	NOX	RM	AGE	
count	506.000000	506.000000	506.000000	506.000000	506.000000	506.000000	506.000000	506
mean	3.613524	11.363636	11.136779	0.069170	0.554695	6.284634	68.574901	3
std	8.601545	23.322453	6.860353	0.253994	0.115878	0.702617	28.148861	2
min	0.006320	0.000000	0.460000	0.000000	0.385000	3.561000	2.900000	1
25%	0.082045	0.000000	5.190000	0.000000	0.449000	5.885500	45.025000	2
50%	0.256510	0.000000	9.690000	0.000000	0.538000	6.208500	77.500000	3
75%	3.677083	12.500000	18.100000	0.000000	0.624000	6.623500	94.075000	5
max	88.976200	100.000000	27.740000	1.000000	0.871000	8.780000	100.000000	12

In [10]:
```
df_y.describe()
```

Out[10]:

	0
count	506.000000
mean	22.532806
std	9.197104
min	5.000000
25%	17.025000
50%	21.200000
75%	25.000000
max	50.000000

In [11]:
```
df_x.shape
```

Out[11]:
```
(506, 13)
```

In [12]:
```
df_x.columns
```

Out[12]:
```
Index(['CRIM', 'ZN', 'INDUS', 'CHAS', 'NOX', 'RM', 'AGE', 'DIS', 'RAD', 'TAX
',
       'PTRATIO', 'B', 'LSTAT'],
      dtype='object')
```

Initializing the linear regression Model

Scanned with CamScanner

In [13]:
```
reg = linear_model.LinearRegression()
```

Splitting Data into 70% training and 30% testin

In [14]:
```
x_train, x_test, y_train, y_test = train_test_split(df_x, df_y, test_size=0.3
```

Train the model

In [15]:
```
reg.fit(x_train, y_train)
```

Out[15]:
```
LinearRegression(copy_X=True, fit_intercept=True, n_jobs=None, normalize=Fals
e)
```

In [16]:
```
#print the coefficient/ weights for each feature/column
#f(x) = mx + c =y where m is the coefficient

print(reg.coef_)
```

```
[[-1.33470103e-01  3.58089136e-02  4.95226452e-02  3.11983512e+00
  -1.54170609e+01 4.05719923e+00 -1.08208352e-02 -1.38599824e+00
   2.42727340e-01 -8.70223437e-03 -9.10685208e-01  1.17941159e-02
  -5.47113313e-01]]
```

Prediction

In [17]:
```
#print prediction for model
y_pred = reg.predict(x_test)
print(y_pred)
```

```
[[28.64896005]
 [36.49501384]
 [15.4111932 ]
 [25.40321303]
 [18.85527988]
 [23.14668944]
 [17.3921241 ]
 [14.07859899]
 [23.03692679]
 [20.59943345]
 [24.82286159]
 [18.53057049]
 [-6.86543527]
 [21.80172334]
 [19.22571177]
 [26.19191985]
 [20.27733882]
 [ 5.61596432]
 [40.44887974]
```

In [18]:
```
print(y_test)
```

Scanned with CamScanner

```
        0
173  23.6
274  32.4
491  13.6
72   22.8
452  16.1
..    ...
441  17.1
23   14.5
225  50.0
433  14.3
447  12.6
```

In [21]:
```
#check the model accuracy using mean squared error
print(np.mean((y_pred-y_test)**2))
```

```
0    21.517444
dtype: float64
```

In [20]:
```
from sklearn.metrics import mean_squared_error
print(mean_squared_error(y_test,y_pred))
```

```
21.517444231176995
```

Scanned with CamScanner

Assignment No 5 : Data Analytics 2

Importing Required Libraries

In [1]:
```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline
```

Read csv into dataframe

In [2]:
```
df = pd.read_csv('Social_Network_Ads.csv')
```

In [3]:
```
df
```

Out[3]:

	User ID	Gender	Age	EstimatedSalary	Purchased
0	15624510	Male	19	19000	0
1	15810944	Male	35	20000	0
2	15668575	Female	26	43000	0
3	15603246	Female	27	57000	0
4	15804002	Male	19	76000	0
...	...	...	...	...	...
395	15691863	Female	46	41000	1
396	15706071	Male	51	23000	1
397	15654296	Female	50	20000	1
398	15755018	Male	36	33000	0
399	15594041	Female	49	36000	1

400 rows × 5 columns

Data preprocessing

In [5]:
```
df.shape
```

Out[5]: (400, 5)

Scanned with CamScanner

In [6]:
```
df.columns
```

Out[6]:
```
Index(['User ID', 'Gender', 'Age', 'EstimatedSalary', 'Purchased'], dtype='ob
ject')
```

In [7]:
```
df.dtypes
```

Out[7]:
```
User ID             int64
Gender             object
Age                 int64
EstimatedSalary     int64
Purchased           int64
dtype: object
```

In [8]:
```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 400 entries, 0 to 399
Data columns (total 5 columns):
 #   Column           Non-Null Count  Dtype
---  ------           --------------  -----
 0   User ID          400 non-null    int64
 1   Gender           400 non-null    object
 2   Age              400 non-null    int64
 3   EstimatedSalary  400 non-null    int64
 4   Purchased        400 non-null    int64
dtypes: int64(4), object(1)
memory usage: 15.8+ KB
```

In [9]:
```
df.describe()
```

Out[9]:

	User ID	Age	EstimatedSalary	Purchased
count	4.000000e+02	400.000000	400.000000	400.000000
mean	1.569154e+07	37.655000	69742.500000	0.357500
std	7.165832e+04	10.482877	34096.960282	0.479864
min	1.556669e+07	18.000000	15000.000000	0.000000
25%	1.562676e+07	29.750000	43000.000000	0.000000
50%	1.569434e+07	37.000000	70000.000000	0.000000
75%	1.575036e+07	46.000000	88000.000000	1.000000
max	1.581524e+07	60.000000	150000.000000	1.000000

In [10]:
```
x = df.iloc[:, [2, 3]].values
```

In [11]:
```
x
```

Out[11]:

Scanned with CamScanner

```
array([[    19,  19000],
       [    35,  20000],
       [    26,  43000],
       [    27,  57000],
       [    19,  76000],
       [    27,  58000],
       [    27,  84000],
       [    32, 150000],
       [    25,  33000],
       [    35,  65000],
       [    26,  80000],
       [    26,  52000],
       [    20,  86000],
       [    32,  18000],
```

In [12]:
```
y = df.iloc[:, 4].values
```

In [13]:
```
y
```

Out[13]:
```
array([0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 1,
       1, 1, 1, 1, 1, 1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 1, 0, 0, 0, 1, 0, 0, 0, 1,
       0, 1, 1, 1, 0, 0, 1, 1, 0, 1, 1, 0, 1, 1, 0, 1, 0, 0, 0, 1, 1, 0,
       1, 1, 0, 1, 0, 1, 0, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 1, 0, 1, 1, 0,
       1, 1, 0, 0, 1, 0, 0, 1, 1, 1, 1, 1, 0, 1, 1, 1, 1, 0, 1, 1, 0, 1,
       0, 1, 0, 1, 1, 1, 1, 0, 0, 0, 1, 1, 0, 1, 1, 1, 1, 1, 0, 0, 0, 1,
       1, 0, 0, 1, 0, 1, 0, 1, 1, 0, 1, 0, 1, 1, 0, 1, 1, 0, 0, 0, 1, 1,
       0, 1, 0, 0, 1, 0, 1, 0, 0, 1, 1, 0, 0, 1, 1, 0, 1, 1, 0, 0, 1, 0,
       1, 0, 1, 1, 1, 0, 1, 0, 1, 1, 1, 0, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1,
       0, 1, 0, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 0, 1,
       1, 1, 0, 1], dtype=int64)
```

Spliting Data into 75% training and 25% testing data

In [14]:
```
from sklearn.model_selection import train_test_split
x_train, x_test, y_train, y_test = train_test_split(x, y, test_size = 0.25, ra
```

In [15]:
```
x_train
```

Out[15]:

Scanned with CamScanner

```
array([[    44,  39000],
       [    32, 120000],
       [    38,  50000],
       [    32, 135000],
       [    52,  21000],
       [    53, 104000],
       [    39,  42000],
       [    38,  61000],
       [    36,  50000],
       [    36,  63000],
       [    35,  25000],
       [    35,  50000]
```

In [16]:
```
x_train.shape
```

Out[16]:
```
(300, 2)
```

In [17]:
```
y_train
```

Out[17]:
```
array([0, 1, 0, 1, 1, 1, 0, 0, 0, 0, 0, 0, 1, 1, 1, 0, 1, 0, 0, 1, 0, 1,
       0, 1, 0, 0, 1, 1, 1, 1, 0, 1, 0, 1, 0, 0, 1, 0, 0, 1, 0, 0, 0, 0,
       0, 1, 1, 1, 1, 0, 0, 0, 1, 0, 1, 0, 1, 0, 0, 1, 0, 0, 0, 1, 0, 0,
       0, 1, 1, 0, 0, 1, 0, 1, 1, 1, 0, 0, 1, 1, 0, 0, 1, 1, 0, 1, 0, 0,
       1, 1, 0, 1, 1, 1, 0, 0, 0, 0, 0, 1, 0, 0, 1, 1, 1, 1, 1, 0, 1, 1,
       0, 1, 0, 0, 0, 0, 0, 0, 0, 1, 1, 0, 0, 1, 0, 0, 1, 0, 0, 0, 1, 0,
       1, 1, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 1, 1, 0, 0, 0, 0, 1, 0, 1, 0,
       0, 0, 1, 0, 0, 0, 0, 1, 1, 1, 0, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 0,
       1, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 1, 1, 0, 1, 0, 1, 0, 0, 1,
       0, 0, 0, 1, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 1, 0, 1, 1, 0, 0, 0,
       0, 0, 0, 1, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 1, 0, 1, 0, 0, 0,
       1, 0, 0, 0, 1, 0, 1, 0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 1, 0, 1,
       1, 0, 0, 0, 0, 0, 1, 0, 1, 0, 0, 1, 0, 0, 1, 0, 1, 0, 0, 0, 0, 0,
       0, 1, 1, 1, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0], dtype=int64)
```

In [18]:
```
y_train.shape
```

Out[18]:
```
(300,)
```

In [19]:
```
x_test
```

Out[19]:

Scanned with CamScanner

```
array([[    30,  87000],
       [    38,  50000],
       [    35,  75000],
       [    30,  79000],
       [    35,  50000],
       [    27,  20000],
       [    31,  15000],
       [    36, 144000],
       [    18,  68000],
       [    47,  43000],
       [    30,  49000],
       [    28,  55000],
       [    37,  55000],
       [    39,  77000],
       [    20,  86000],
       [    32, 117000],
       [    37,  77000],
       [    19,  85000],
       [    55, 130000],
       [    35,  22000],
       [    35,  47000],
       [    47, 144000],
       [    41,  51000],
       [    47, 105000],
       [    23,  28000],
       [    49, 141000],
       [    28,  87000],
       [    29,  80000],
       [    37,  62000],
       [    32,  86000],
       [    21,  88000],
       [    37,  79000],
       [    57,  60000],
       [    37,  53000],
       [    24,  58000],
       [    18,  52000],
       [    22,  81000],
       [    34,  43000],
       [    31,  34000],
       [    49,  36000],
       [    27,  88000],
       [    41,  52000],
       [    27,  84000],
       [    35,  20000],
       [    43, 112000],
       [    27,  58000],
       [    37,  80000],
       [    52,  90000],
       [    26,  30000],
       [    49,  86000],
       [    57, 122000],
       [    34,  25000],
       [    35,  57000],
       [    34, 115000],
       [    59,  88000],
       [    45,  32000],
```

Scanned with CamScanner

```
[    29,  83000],
[    26,  80000],
[    49,  28000],
[    23,  20000],
[    32,  18000],
[    60,  42000],
[    19,  76000],
[    36,  99000],
[    19,  26000],
[    60,  83000],
[    24,  89000],
[    27,  58000],
[    40,  47000],
[    42,  70000],
[    32, 150000],
[    35,  77000],
[    22,  63000],
[    45,  22000],
[    27,  89000],
[    18,  82000],
[    42,  79000],
[    40,  60000],
[    53,  34000],
[    47, 107000],
[    58, 144000],
[    59,  83000],
[    24,  55000],
```

In [20]:
```
x_test.shape
```

Out[20]:
```
(100, 2)
```

In [21]:
```
y_test
```

Out[21]:
```
array([0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 1,
       0, 1, 0, 1, 0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0,
       1, 0, 0, 1, 0, 1, 1, 0, 0, 0, 1, 1, 0, 0, 1, 0, 0, 1, 0, 1, 0, 1,
       0, 0, 0, 0, 1, 0, 0, 1, 0, 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 0, 1,
       1, 0, 0, 1, 0, 0, 0, 1, 0, 1, 1, 1], dtype=int64)
```

In [22]:
```
y_test.shape
```

Out[22]:
```
(100,)
```

Data Standardization

In [23]:
```
from sklearn.preprocessing import StandardScaler
sc_x = StandardScaler()
x_train = sc_x.fit_transform(x_train)
x_test = sc_x.fit_transform(x_test)
```

In [24]:
```
x_train
```

Out[24]:

Scanned with CamScanner

```
array([[ 0.58164944, -0.88670699],
       [-0.60673761,  1.46173768],
       [-0.01254409, -0.5677824 ],
       [-0.60673761,  1.89663484],
       [ 1.37390747, -1.40858358],
       [ 1.47293972,  0.99784738],
       [ 0.08648817, -0.79972756],
       [-0.01254409, -0.24885782],
       [-0.21060859, -0.5677824 ],
       [-0.21060859, -0.19087153],
       [-0.30964085, -1.29261101],
       [-0.30964085, -0.5677824 ],
       [ 0.38358493,  0.09905991],
       [ 0.8787462 , -0.59677555],
       [ 2.06713324, -1.17663843],
       [ 1.07681071, -0.13288524],
       [ 0.68068169,  1.78066227],
       [-0.70576986,  0.56295021]
```

In [25]:
```
x_test
```

Out[25]:

Scanned with CamScanner

```
array([[-0.54748976,  0.5130727 ],
       [ 0.15442019, -0.61825566],
       [-0.10879604,  0.14615539],
       [-0.54748976,  0.26846116],
       [-0.10879604, -0.61825566],
       [-0.81070599, -1.53554892],
       [-0.45975102, -1.68843113],
       [-0.0210573 ,  2.25592989],
       [-1.60035469, -0.0678797 ],
       [ 0.94406888, -0.83229075],
       [-0.54748976, -0.6488321 ],
       [-0.72296725, -0.46537345],
       [ 0.06668145, -0.46537345],
       [ 0.24215893,  0.20730828],
       [-1.4248772 ,  0.48249625],
       [-0.37201227,  1.43036596],
       [ 0.06668145,  0.20730828],
       [-1.51261594,  0.45191981],
       [ 1.64597884,  1.8278597 ],
       [-0.10879604, -1.47439603],
       [-0.10879604, -0.70998498],
       [ 0.94406888,  2.25592989],
       [ 0.41763642, -0.58767922],
       [ 0.94406888,  1.06344865],
       [-1.16166097, -1.29093738],
       [ 1.11954637,  2.16420057],
       [-0.72296725,  0.5130727 ],
       [-0.63522851,  0.2990376 ],
       [ 0.06668145, -0.25133835],
       [-0.37201227,  0.48249625],
       [-1.33713846,  0.54364914],
       [ 0.06668145,  0.26846116],
       [ 1.82145632, -0.31249124],
       [ 0.06668145, -0.52652633],
       [-1.07392223, -0.37364412],
       [-1.60035469, -0.55710277],
       [-1.24939971,  0.32961404],
       [-0.19653479, -0.83229075],
       [-0.45975102, -1.10747873],
       [ 1.11954637, -1.04632585],
       [-0.81070599,  0.54364914],
       [ 0.41763642, -0.55710277],
       [-0.81070599,  0.42134337],
       [-0.10879604, -1.53554892],
       [ 0.59311391,  1.27748375],
       [-0.81070599, -0.37364412],
       [ 0.06668145,  0.2990376 ],
       [ 1.3827626 ,  0.60480202],
       [-0.89844474, -1.2297845 ],
       [ 1.11954637,  0.48249625],
       [ 1.82145632,  1.58324817],
       [-0.19653479, -1.38266671],
       [-0.10879604, -0.40422056],
       [-0.19653479,  1.36921307],
       [ 1.99693381,  0.54364914],
       [ 0.7685914 , -1.16863161],
```

Scanned with CamScanner

```
       [-0.63522851,  0.39076693],
       [-0.89844474,  0.2990376 ],
       [ 1.11954637, -1.29093738],
       [-1.16166097, -1.53554892],
       [-0.37201227, -1.5967018 ],
       [ 2.08467255, -0.86286719],
       [-1.51261594,  0.17673183],
       [-0.0210573 ,  0.87999   ],
```

Initializing logistic Regression model and training the model

In [26]:
```
from sklearn.linear_model import LogisticRegression
classifier = LogisticRegression(random_state = 0)
classifier.fit(x_train, y_train)
```

Out[26]:
```
LogisticRegression(C=1.0, class_weight=None, dual=False, fit_intercept=True,
                   intercept_scaling=1, l1_ratio=None, max_iter=100,
                   multi_class='auto', n_jobs=None, penalty='l2',
                   random_state=0, solver='lbfgs', tol=0.0001, verbose=0,
                   warm_start=False)
```

Prediction

In [29]:
```
y_pred = classifier.predict(x_test)
```

In [30]:
```
y_pred
```

Out[30]:
```
array([0, 0, 0, 0, 0, 0, 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 1,
       0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0,
       1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 1,
       0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 1, 0, 1, 1, 1, 1, 0, 0, 1, 1, 0, 1,
       0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 1, 1], dtype=int64)
```

In [31]:
```
y_test
```

Out[31]:
```
array([0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 1,
       0, 1, 0, 1, 0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0,
       1, 0, 0, 1, 0, 1, 1, 0, 0, 0, 1, 1, 0, 0, 1, 0, 0, 1, 0, 1, 0, 1,
       0, 0, 0, 0, 1, 0, 0, 1, 0, 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 0, 1,
       1, 0, 0, 1, 0, 0, 0, 1, 0, 1, 1, 1], dtype=int64)
```

Confusion Matrix

In [32]:
```
from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, y_pred)
cm
```

Out[32]:
```
array([[63,  5],
       [ 8, 24]], dtype=int64)
```

In [ ]:
```
#The confusion matrix tells us that there were 87 correct predictions and 13 i
```

Scanned with CamScanner

Calculating accuracy of model

In [34]:
```
from sklearn.metrics import accuracy_score
accuracy = accuracy_score(y_test, y_pred) * 100
accuracy
```

Out[34]: 87.0

True Positive : Actually True, Predicted True

In [48]:
```
tp = cm[0,[0]]
print('True Positive : ',tp)
```

```
True Positive :  [63]
```

False Positive : Actually False, Predicted True

In [49]:
```
fp = cm[0, [1]]
print('False Positive : ',fp)
```

```
False Positive :  [5]
```

False Negative : Actually True, Predicted False

In [50]:
```
fn = cm[1, [0]]
print('False Negative : ',fn)
```

```
False Negative :  [8]
```

True Negative : Actually False, Predicted False

In [51]:
```
tn = cm[1, [1]]
print('True Negative : ',tn)
```

```
True Negative :  [24]
```

Accuracy

In [47]:
```
accuracy_cm = ((tp + tn)/(tp + fp + fn + tn))
print('Accuracy : ',accuracy_cm*100)
```

```
Accuracy :  [87.]
```

Error Rate

In [54]:
```
error_rate_cm = ((fp + fn)/(tp + fp + fn + tn))
print('Error Rate : ', error_rate_cm*100)
```

```
Error Rate :  [13.]
```

Scanned with CamScanner

Precision

In [56]:
```
precision_cm = (tp / (tp + fp))
print('Precision : ',precision_cm*100)
```

```
Precision :  [92.64705882]
```

Recall

In [59]:
```
#recall is also called sensitivity
recall_cm = (tp / (tp + fn))
print('Sensitivity : ', recall_cm*100)
```

```
Sensitivity :  [88.73239437]
```

Specificity

In [62]:
```
specificity_cm = (tn / (tn + fp))
print('Specificity : ', specificity_cm*100)
```

```
Specificity :  [82.75862069]
```

Scanned with CamScanner

Assignment No 6 : Data Analytics 3

Importing Required Libraries

In [1]:
```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline
import seaborn as sns
```

Reading csv into dataframe

In [2]:
```
df = pd.read_csv('iris.csv')
```

In [3]:
```
df
```

Out[3]:

	Id	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm	Species
0	1	5.1	3.5	1.4	0.2	Iris-setosa
1	2	4.9	3.0	1.4	0.2	Iris-setosa
2	3	4.7	3.2	1.3	0.2	Iris-setosa
3	4	4.6	3.1	1.5	0.2	Iris-setosa
4	5	5.0	3.6	1.4	0.2	Iris-setosa
...	...	...	...	...	...	...
145	146	6.7	3.0	5.2	2.3	Iris-virginica
146	147	6.3	2.5	5.0	1.9	Iris-virginica
147	148	6.5	3.0	5.2	2.0	Iris-virginica
148	149	6.2	3.4	5.4	2.3	Iris-virginica
149	150	5.9	3.0	5.1	1.8	Iris-virginica

150 rows × 6 columns

Data preprocessing

In [4]:
```
df.shape
```

Out[4]:
```
(150, 6)
```

Scanned with CamScanner

In [5]:
```
df.columns
```

Out[5]:
```
Index(['Id', 'SepalLengthCm', 'SepalWidthCm', 'PetalLengthCm', 'PetalWidthCm
',
       'Species'],
      dtype='object')
```

In [6]:
```
df.dtypes
```

Out[6]:
```
Id                 int64
SepalLengthCm    float64
SepalWidthCm     float64
PetalLengthCm    float64
PetalWidthCm     float64
Species           object
dtype: object
```

In [7]:
```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 150 entries, 0 to 149
Data columns (total 6 columns):
 #   Column         Non-Null Count  Dtype
---  ------         --------------  -----
 0   Id             150 non-null    int64
 1   SepalLengthCm  150 non-null    float64
 2   SepalWidthCm   150 non-null    float64
 3   PetalLengthCm  150 non-null    float64
 4   PetalWidthCm   150 non-null    float64
 5   Species        150 non-null    object
dtypes: float64(4), int64(1), object(1)
memory usage: 7.2+ KB
```

In [8]:
```
df.describe()
```

Out[8]:

	Id	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm
count	150.000000	150.000000	150.000000	150.000000	150.000000
mean	75.500000	5.843333	3.054000	3.758667	1.198667
std	43.445368	0.828066	0.433594	1.764420	0.763161
min	1.000000	4.300000	2.000000	1.000000	0.100000
25%	38.250000	5.100000	2.800000	1.600000	0.300000
50%	75.500000	5.800000	3.000000	4.350000	1.300000
75%	112.750000	6.400000	3.300000	5.100000	1.800000
max	150.000000	7.900000	4.400000	6.900000	2.500000

In [9]:
```
df.isnull()
```

Out[9]:

	Id	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm	Species
0	False	False	False	False	False	False

Scanned with CamScanner

	Id	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm	Species
1	False	False	False	False	False	False
2	False	False	False	False	False	False
3	False	False	False	False	False	False
4	False	False	False	False	False	False
...	...	...	...	...	...	...
145	False	False	False	False	False	False
146	False	False	False	False	False	False
147	False	False	False	False	False	False
148	False	False	False	False	False	False
149	False	False	False	False	False	False

In [10]:
```
df.isnull().sum()
```

Out[10]:
```
Id               0
SepalLengthCm    0
SepalWidthCm     0
PetalLengthCm    0
PetalWidthCm     0
Species          0
dtype: int64
```

In [11]:
```
df.drop(columns="Id", inplace=True)
df.head()
```

Out[11]:

	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm	Species
0	5.1	3.5	1.4	0.2	Iris-setosa
1	4.9	3.0	1.4	0.2	Iris-setosa
2	4.7	3.2	1.3	0.2	Iris-setosa
3	4.6	3.1	1.5	0.2	Iris-setosa
4	5.0	3.6	1.4	0.2	Iris-setosa

Data Visualization

Scanned with CamScanner

In [12]:
```
sns.relplot(data = df, x = 'SepalWidthCm', y = 'SepalLengthCm', hue = 'Species
```

Out[12]: <seaborn.axisgrid.FacetGrid at 0x26edcc3cc8>



In [13]:
```
sns.relplot(data = df, x = 'PetalLengthCm', y = 'PetalWidthCm', hue = 'Species
```

Out[13]: <seaborn.axisgrid.FacetGrid at 0x26f0e53ac8>



Scanned with CamScanner

In [14]:
```
sns.pairplot(df, hue = 'Species')
```

Out[14]: <seaborn.axisgrid.PairGrid at 0x26f0ec9248>



Scanned with CamScanner

In [15]:
```
plt.figure(figsize = (15, 10))
plt.subplot(2, 2, 1)
sns.boxplot(data = df, x = 'Species', y = 'PetalLengthCm')

plt.subplot(2, 2, 2)
sns.boxplot(data = df, x = 'Species', y = 'PetalWidthCm')

plt.subplot(2, 2, 3)
sns.boxplot(data = df, x = 'Species', y = 'SepalLengthCm')

plt.subplot(2, 2, 4)
sns.boxplot(data = df, x = 'Species', y = 'SepalWidthCm')
```

Out[15]: <matplotlib.axes._subplots.AxesSubplot at 0x26ef631688>



Scanned with CamScanner

In [16]:
```
sns.boxplot(data = df).set_title("Distribution of Sepal-Length, Sepal-Width, P
```

Out[16]:
```
Text(0.5, 1.0, 'Distribution of Sepal-Length, Sepal-Width, Petal-Length and P
etal-Width for iris-setosa, iris-versicolor and iris-virginica')
```



In [17]:
```
df.corr()
```

Out[17]:

	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm
SepalLengthCm	1.000000	-0.109369	0.871754	0.817954
SepalWidthCm	-0.109369	1.000000	-0.420516	-0.356544
PetalLengthCm	0.871754	-0.420516	1.000000	0.962757
PetalWidthCm	0.817954	-0.356544	0.962757	1.000000

Scanned with CamScanner

In [18]:
```
plt.subplots(figsize = (8,8))
sns.heatmap(df.corr(), annot = True, fmt = "f").set_title("Corelation of attri
```

Out[18]: Text(0.5, 1, 'Corelation of attributes')



In [19]:
```
x = df.iloc[:, 0:4].values
x
```

Out[19]:

Scanned with CamScanner

In [20]:
```
y = df.iloc[:, 4].values
y
```

Out[20]:
```
array(['Iris-setosa', 'Iris-setosa', 'Iris-setosa', 'Iris-setosa',
       '
```

```
y = le.fit_transform(y)
y
```

Out[21]:
```
array([0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,
       1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,
       1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2,
       2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2,
       2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2])
```

Splitting data into 70% training and 30% testin

In [22]:
```
from sklearn.model_selection import train_test_split
x_train, x_test, y_train, y_test = train_test_split(x, y, test_size = 0.3, ran
```

In [23]:
```
x_train
```

Out[23]:

Scanned with CamScanner

```
array([[5. , 2. , 3.5, 1. ],
       [6.5, 3. , 5.5, 1.8],
       [6.7, 3.3, 5.7, 2.5],
       [6. , 2.2, 5. , 1.5],
       [6.7, 2.5, 5.8, 1.8],
       [5.6, 2.5, 3.9, 1.1],
       [7.7, 3. , 6.1, 2.3],
       [6.3, 3.3, 4.7, 1.6],
       [5.5, 2.4, 3.8, 1.1],
       [6.3, 2.7, 4.9, 1.8],
       [6.3, 2.8, 5.1, 1.5],
       [4.9, 2.5, 4.5, 1.7],
       [6.3, 2.5, 5. , 1.9],
       [7. , 3.2, 4.7, 1.4],
       [6.5, 3. , 5.2, 2. ],
       [6. , 3.4, 4.5, 1.6],
       [4.8, 3.1, 1.6, 0.2],
       [5.8, 2.7, 5.1, 1.9],
       [5.6, 2.7, 4.2, 1.3],
       [5.6, 2.9, 3.6, 1.3],
       [5.5, 2.5, 4. , 1.3],
       [6.1, 3. , 4.6, 1.4],
       [7.2, 3.2, 6. , 1.8],
       [5.3, 3.7, 1.5, 0.2],
       [4.3, 3. , 1.1, 0.1],
       [6.4, 2.7, 5.3, 1.9],
       [5.7, 3. , 4.2, 1.2],
       [5.4, 3.4, 1.7, 0.2],
       [5.7, 4.4, 1.5, 0.4],
       [6.9, 3.1, 4.9, 1.5],
       [4.6, 3.1, 1.5, 0.2],
       [5.9, 3. , 5.1, 1.8],
       [5.1, 2.5, 3. , 1.1],
       [4.6, 3.4, 1.4, 0.3],
       [6.2, 2.2, 4.5, 1.5],
       [7.2, 3.6, 6.1, 2.5],
       [5.7, 2.9, 4.2, 1.3],
       [4.8, 3. , 1.4, 0.1],
       [7.1, 3. , 5.9, 2.1],
       [6.9, 3.2, 5.7, 2.3],
       [6.5, 3. , 5.8, 2.2],
       [6.4, 2.8, 5.6, 2.1],
       [5.1, 3.8, 1.6, 0.2],
       [4.8, 3.4, 1.6, 0.2],
       [6.5, 3.2, 5.1, 2. ],
       [6.7, 3.3, 5.7, 2.1],
       [4.5, 2.3, 1.3, 0.3],
       [6.2, 3.4, 5.4, 2.3],
       [4.9, 3. , 1.4, 0.2],
       [5.7, 2.5, 5. , 2. ],
       [6.9, 3.1, 5.4, 2.1],
       [4.4, 3.2, 1.3, 0.2],
       [5. , 3.6, 1.4, 0.2],
       [7.2, 3. , 5.8, 1.6],
       [5.1, 3.5, 1.4, 0.3],
       [4.4, 3. , 1.3, 0.2],
```

Scanned with CamScanner

```
       [5.4, 3.9, 1.7, 0.4],
       [5.5, 2.3, 4. , 1.3],
       [6.8, 3.2, 5.9, 2.3],
       [7.6, 3. , 6.6, 2.1],
       [5.1, 3.5, 1.4, 0.2],
       [4.9, 3.1, 1.5, 0.1],
       [5.2, 3.4, 1.4, 0.2],
       [5.7, 2.8, 4.5, 1.3],
       [6.6, 3. , 4.4, 1.4],
       [5. , 3.2, 1.2, 0.2],
       [5.1, 3.3, 1.7, 0.5],
```

In [24]:
```
x_train.shape
```

Out[24]:
```
(105, 4)
```

In [25]:
```
x_test
```

Out[25]:

Scanned with CamScanner

```
array([[5.8, 2.8, 5.1, 2.4],
       [6. , 2.2, 4. , 1. ],
       [5.5, 4.2, 1.4, 0.2],
       [7.3, 2.9, 6.3, 1.8],
       [5. , 3.4, 1.5, 0.2],
       [6.3, 3.3, 6. , 2.5],
       [5. , 3.5, 1.3, 0.3],
```

In [26]:
```
x_test.shape
```

Out[26]:
```
(45, 4)
```

In [27]:
```
y_train
```

Out[27]:
```
array([1, 2, 2, 2, 2, 1, 2, 1, 1, 2, 2, 2, 2, 1, 2, 1, 0, 2, 1, 1, 1, 1,
       2, 0, 0, 2, 1, 0, 0, 1, 0, 2, 1, 0, 1, 2, 1, 0, 2, 2, 2, 2, 0, 0,
       2, 2, 0, 2, 0, 2, 2, 0, 0, 2, 0, 0, 0, 1, 2, 2, 0, 0, 0, 1, 1, 0,
       0, 1, 0, 2, 1, 2, 1, 0, 2, 0, 2, 0, 0, 2, 0, 2, 1, 1, 1, 2, 2, 1,
       1, 0, 1, 2, 2, 0, 1, 1, 1, 1, 0, 0, 0, 2, 1, 2, 0])
```

In [28]:
```
y_train.shape
```

Out[28]:
```
(105,)
```

In [29]:
```
y_test
```

Out[29]:
```
array([2, 1, 0, 2, 0, 2, 0, 1, 1, 1, 2, 1, 1, 1, 1, 0, 1, 1, 0, 0, 2, 1,
       0, 0, 2, 0, 0, 1, 1, 0, 2, 1, 0, 2, 2, 1, 0, 1, 1, 1, 2, 0, 2, 0,
       0])
```

In [30]:
```
y_test.shape
```

Out[30]:
```
(45,)
```

Initializing Naive Bayes Model and training it

In [31]:
```
from sklearn.naive_bayes import GaussianNB
model = GaussianNB()
model.fit(x_train, y_train)
```

Out[31]:
```
GaussianNB(priors=None, var_smoothing=1e-09)
```

Prediction

In [32]:
```
prediction = model.predict(x_test)
```

In [33]:
```
prediction
```

Out[33]:
```
array([2, 1, 0, 2, 0, 2, 0, 1, 1, 1, 2, 1, 1, 1, 1, 0, 1, 1, 0, 0, 2, 1,
       0, 0, 2, 0, 0, 1, 1, 0, 2, 1, 0, 2, 2, 1, 0, 1, 1, 1, 2, 0, 2, 0,
       0])
```

Scanned with CamScanner

In [34]:
```
y_test
```

Out[34]:
```
array([2, 1, 0, 2, 0, 2, 0, 1, 1, 1, 2, 1, 1, 1, 1, 0, 1, 1, 0, 0, 2, 1,
       0, 0, 2, 0, 0, 1, 1, 0, 2, 1, 0, 2, 2, 1, 0, 1, 1, 1, 2, 0, 2, 0,
       0])
```

Confusion Matrix

In [35]:
```
from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, prediction)
cm
```

Out[35]:
```
array([[16,  0,  0],
       [ 0, 18,  0],
       [ 0,  0, 11]], dtype=int64)
```

Accuarcy

In [36]:
```
from sklearn.metrics import accuracy_score
accuracy = accuracy_score(y_test, prediction) * 100
accuracy
```

Out[36]:
```
100.0
```

Precision

In [43]:
```
from sklearn.metrics import precision_score
precision = precision_score(y_test, prediction, average = 'micro') *100
precision
```

Out[43]:
```
100.0
```

Recall

In [44]:
```
from sklearn.metrics import recall_score
recall = recall_score(y_test, prediction, average = 'micro') * 100
recall
```

Out[44]:
```
100.0
```

Scanned with CamScanner

In [14]:
```
from textblob import TextBlob
import nltk
```

In [4]:
```
b = TextBlob("I havv good spelling")
```

In [5]:
```
b.correct()
```

Out[5]:
```
TextBlob("I have good spelling")
```

In [22]:
```
import nltk
nltk.download('punkt')
b1 = TextBlob("Beautiful is better than ugly."
              "Explicit is better than implicit."
              "Simple is better than complex.")
b1.words
```

```
[nltk_data] Downloading package punkt to
[nltk_data]     C:\Users\ADMIN\AppData\Roaming\nltk_data...
[nltk_data]   Package punkt is already up-to-date!
```

Out[22]:
```
WordList(['Beautiful', 'is', 'better', 'than', 'ugly.Explicit', 'is', 'better
', 'than', 'implicit.Simple', 'is', 'better', 'than', 'complex'])
```

In [23]:
```
b1.sentences
```

Out[23]:
```
[Sentence("Beautiful is better than ugly.Explicit is better than implicit.Sim
ple is better than complex.")]
```

In [24]:
```
sentence = TextBlob("Use 4 spaces per indentation level")
sentence.words
```

Out[24]:
```
WordList(['Use', '4', 'spaces', 'per', 'indentation', 'level'])
```

In [27]:
```
sentence.words[2].singularize()
```

Out[27]:
```
'space'
```

In [28]:
```
sentence.words[5].pluralize()
```

Out[28]:
```
'levels'
```

In [30]:
```
animals = TextBlob("cat dog octopus")
animals.words
```

Out[30]:
```
WordList(['cat', 'dog', 'octopus'])
```

In [31]:
```
animals.words.pluralize()
```

Out[31]:
```
WordList(['cats', 'dogs', 'octopodes'])
```

Scanned with CamScanner

In [32]:
```
sen = TextBlob("We are no longer the knights who say Ni." "We are now the knig
sen.word_counts['ekki']
```

Out[32]:
```
3
```

In [33]:
```
sen.words.count('ekki')
```

Out[33]:
```
3
```

In [34]:
```
sen.words.count('ekki', case_sensitive=True)
```

Out[34]:
```
2
```

In [35]:
```
b = TextBlob("And now for something completely different.")
print(b.parse())
```

```
And/CC/O/O now/RB/B-ADVP/O for/IN/B-PP/B-PNP something/NN/B-NP/I-PNP complete
ly/RB/B-ADJP/O different/JJ/I-ADJP/O ././O/O
```

In [36]:
```
b1[0:19]
TextBlob("Beautiful is better")
```

Out[36]:
```
TextBlob("Beautiful is better")
```

In [37]:
```
b1.upper()
```

Out[37]:
```
TextBlob("BEAUTIFUL IS BETTER THAN UGLY.EXPLICIT IS BETTER THAN IMPLICIT.SIMP
LE IS BETTER THAN COMPLEX.")
```

In [39]:
```
b1.find("Simple")
```

Out[39]:
```
63
```

In [40]:
```
apple_blob = TextBlob('apples')
banana_blob = TextBlob('bananas')
apple_blob < banana_blob
```

Out[40]:
```
True
```

In [41]:
```
blob = TextBlob("Now is better then never.")
blob.ngrams(n=3)
```

Out[41]:
```
[WordList(['Now', 'is', 'better']),
 WordList(['is', 'better', 'then']),
 WordList(['better', 'then', 'never'])]
```

Scanned with CamScanner

In [42]:
```
import nltk
from nltk import tokenize
from nltk.tokenize import sent_tokenize
text = """ Good Day everyone, how are you all today? Its fun learning data ana
text
```

Out[42]:
```
' Good Day everyone, how are you all today? Its fun learning data analysis. H
ope you all are practicing well.'
```

In [43]:
```
tokenized_text = sent_tokenize(text)
```

In [45]:
```
print(tokenized_text)
```

```
[' Good Day everyone, how are you all today?', 'Its fun learning data analysi
s.', 'Hope you all are practicing well.']
```

In [47]:
```
from nltk.tokenize import word_tokenize
tokenizer_word = word_tokenize(text)
print(tokenizer_word)
```

```
['Good', 'Day', 'everyone', ',', 'how', 'are', 'you', 'all', 'today', '?', 'I
ts', 'fun', 'learning', 'data', 'analysis', '.', 'Hope', 'you', 'all', 'are',
'practicing', 'well', '.']
```

In [48]:
```
from nltk.probability import FreqDist
fdist = FreqDist(tokenizer_word)
print(fdist)
```

```
<FreqDist with 19 samples and 23 outcomes>
```

In [49]:
```
fdist.most_common(4)
```

Out[49]:
```
[('are', 2), ('you', 2), ('all', 2), ('.', 2)]
```

Scanned with CamScanner

In [50]:
```
import matplotlib.pyplot as plt
fdist.plot(30,cumulative=False)
plt.show()
```



In [52]:
```
nltk.download('stopwords')
```

```
[nltk_data] Downloading package stopwords to
[nltk_data]     C:\Users\ADMIN\AppData\Roaming\nltk_data...
[nltk_data]   Unzipping corpora\stopwords.zip.
```

Out[52]: True

In [57]:
```
from nltk.corpus  import  stopwords
stop_words = set(stopwords.words("english"))
print(stop_words)
```

```
{'wasn', 'how', 'herself', 'couldn', 'up', 'during', 'itself', 'than', 't', '
can', 'was', 'mustn', 'yours', 'did', 'didn', 'my', 'at', 'he', 'again', "wou
ldn't", 'myself', "isn't", 'it', "you'll", 'whom', 'any', "you're", "couldn'
t", 'shouldn', 'all', 'its', 'just', "hasn't", 'won', 'o', "mightn't", 'which
', 'hasn', 'that', 'theirs', 'over', 'i', 'such', 'am', 'until', 'on', 'throu
gh', 's', 'about', 'being', "mustn't", 'under', 'same', 'has', "should've", '
each', 'we', 'them', 'were', 'nor', 'here', "shan't", 'does', 'below', 'why',
'her', 'mightn', 'be', "it's", 'of', 'above', 'aren', 'doesn', 'by', 'wouldn
', 'then', 'him', "she's", 'while', 'with', 'for', 'their', 'to', 'out', 'if
', 'don', 'ourselves', 'in', 'themselves', 'ours', 'his', 'off', "wasn't", 't
he', 'very', 'so', 'are', 'what', 'from', 'there', 'will', 'yourselves', "tha
t'll", 'she', 'some', 'between', "aren't", 'shan', 'who', 'few', 'before', 'w
eren', 'this', 'because', 'both', 'd', 'hers', 'll', 'but', "won't", "don't",
'is', 'and', 'where', 'too', "shouldn't", 'ma', 'these', "hadn't", 'you', "yo
u've", 'down', "needn't", 'or', 'have', 'after', 'only', 'ain', 'own', 'once
', "you'd", 've', 'against', 'y', 'as', 'had', 'haven', 'more', "haven't", 'f
urther', 'no', 'those', "weren't", 'should', 'been', 'when', 'your', 'me', 'a
n', 'having', 'isn', 'm', 'doing', "doesn't", 'our', 'do', "didn't", 're', 'h
adn', 'they', 'into', 'not', 'himself', 'needn', 'most', 'other', 'now', 'a',
'yourself'}
```

Scanned with CamScanner

In [60]:
```
filtered_sent=[]
for w in tokenizer_word:
    if w not in stop_words:
        filtered_sent.append(w)

print("Tokenized sentence : ",tokenizer_word)
print("Filtered sentence : ", filtered_sent)
```

```
Tokenized sentence :  ['Good', 'Day', 'everyone', ',', 'how', 'are', 'you', '
all', 'today', '?', 'Its', 'fun', 'learning', 'data', 'analysis', '.', 'Hope
', 'you', 'all', 'are', 'practicing', 'well', '.']
Filtered sentence :  ['Good', 'Day', 'everyone', ',', 'today', '?', 'Its', 'f
un', 'learning', 'data', 'analysis', '.', 'Hope', 'practicing', 'well', '.']
```

In [61]:
```
from nltk.stem import PorterStemmer
from nltk.tokenize import sent_tokenize, word_tokenize
ps = PorterStemmer()
stemmed_words = []
for w in filtered_sent:
    stemmed_words.append(ps.stem(w))
print("Filtered Sentence : ", filtered_sent)
print("Stemmed Sentence : ", stemmed_words)
```

```
Filtered Sentence :  ['Good', 'Day', 'everyone', ',', 'today', '?', 'Its', 'f
un', 'learning', 'data', 'analysis', '.', 'Hope', 'practicing', 'well', '.']
Stemmed Sentence :  ['good', 'day', 'everyon', ',', 'today', '?', 'it', 'fun
', 'learn', 'data', 'analysi', '.', 'hope', 'practic', 'well', '.']
```

In [62]:
```
nltk.download('wordnet')
```

```
[nltk_data] Downloading package wordnet to
[nltk_data]     C:\Users\ADMIN\AppData\Roaming\nltk_data...
[nltk_data]   Unzipping corpora\wordnet.zip.
```

Out[62]:
```
True
```

In [64]:
```
from nltk.stem.wordnet import WordNetLemmatizer
lem = WordNetLemmatizer()
from nltk.stem.porter import PorterStemmer
stem = PorterStemmer()
word = "flying"
print("Lemmatizer Word : ", lem.lemmatize(word, "v"))
print("Stemmed Word : ", stem.stem(word))
```

```
Lemmatizer Word : fly
Stemmed Word :  fli
```

In [65]:
```
sent = "Albert Einstien was born in Ulm, Germany in 1879."
tokens = nltk.word_tokenize(sent)
print(tokens)
```

```
['Albert', 'Einstien', 'was', 'born', 'in', 'Ulm', ',', 'Germany', 'in', '187
9', '.']
```

Scanned with CamScanner

In [66]:
```
nltk.download('averaged_perceptron_tagger')
```

```
[nltk_data] Downloading package averaged_perceptron_tagger to
[nltk_data]     C:\Users\ADMIN\AppData\Roaming\nltk_data...
[nltk_data]   Unzipping taggers\averaged_perceptron_tagger.zip.
```

Out[66]:
```
True
```

In [67]:
```
nltk.pos_tag(tokens)
```

Out[67]:
```
[('Albert', 'NNP'),
 ('Einstien', 'NNP'),
 ('was', 'VBD'),
 ('born', 'VBN'),
 ('in', 'IN'),
 ('Ulm', 'NNP'),
 (',', ','),
 ('Germany', 'NNP'),
 ('in', 'IN'),
 ('1879', 'CD'),
 ('.', '.')]
```

In [68]:
```
from collections import Counter
sentence = "Texas A&M University is located in Texas"
term_frequency = Counter(sentence.split())
```

In [69]:
```
term_frequency
```

Out[69]:
```
Counter({'Texas': 2,
         'A&M': 1,
         'University': 1,
         'is': 1,
         'located': 1,
         'in': 1})
```

Scanned with CamScanner

Assignment No 8 : Data Visualization 1

Import Required Libraries

In [1]:
```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
%matplotlib inline
import seaborn as sns
```

Reading csv into data frame

In [2]:
```
df = pd.read_csv('train.csv')
df
```

Out[2]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500
...	...	...	...	...	...	...	...	...	...	...
886	887	0	2	Montvila, Rev. Juozas	male	27.0	0	0	211536	13.0000
887	888	1	1	Graham, Miss. Margaret Edith	female	19.0	0	0	112053	30.0000

Scanned with CamScanner

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
888	889	0	3	Johnston, Miss. Catherine Helen "Carrie"	female	NaN	1	2	W./C. 660	23.4500
889	890	1	1	Behr, Mr. Karl Howell	male	26.0	0	0	111369	30.0000
890	891	0	3	Dooley, Mr.	male	32.0	0	0	370376	7.7500

Scanned with CamScanner

Data Visualization

In [3]:
```
import seaborn as sns
sns.distplot(df['Pclass'])
```

Out[3]: <matplotlib.axes._subplots.AxesSubplot at 0x4f90eff688>



In [4]:
```
sns.distplot(df['Age'])
```

Out[4]: <matplotlib.axes._subplots.AxesSubplot at 0x4f914a8b08>



In [5]:
```
sns.distplot(df['Age'], bins=40)
```

Out[5]: <matplotlib.axes._subplots.AxesSubplot at 0x4f91918cc8>

Scanned with CamScanner




```
In [6]: sns.distplot(df['Age'], bins=20, kde=False, rug=True)
```

```
Out[6]: <matplotlib.axes._subplots.AxesSubplot at 0x4f914b4b88>
```




```
In [7]: sns.jointplot(x = df['Age'], y = df['Fare'], kind = 'scatter')
```

```
Out[7]: <seaborn.axisgrid.JointGrid at 0x4f91b27388>
```

Scanned with CamScanner




```
In [8]: sns.jointplot(x = df['Age'], y = df['Fare'], kind = 'hex')
```

```
Out[8]: <seaborn.axisgrid.JointGrid at 0x4f91cca788>
```



Scanned with CamScanner

In [9]:
```
sns.pairplot(df)
```

Out[9]: <seaborn.axisgrid.PairGrid at 0x4f91ccff88>



In [10]:
```
sns.barplot(x = df['Sex'], y = df['Fare'])
```

Out[10]: <matplotlib.axes._subplots.AxesSubplot at 0x4f94808a48>



Scanned with CamScanner

In [11]:
```
sns.countplot(df['Pclass'])
```

Out[11]: <matplotlib.axes._subplots.AxesSubplot at 0x4f91514648>



In [24]:
```
sns.distplot(df['Fare'], hist = True)
```

Out[24]: <matplotlib.axes._subplots.AxesSubplot at 0x4f955c6a48>



Scanned with CamScanner

Assignment No 9 : Data Visualization 2

Import required Libraries

In [1]:
```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline
import seaborn as sns
```

Read csv into dataframe

In [2]:
```
df = pd.read_csv('train.csv')
```

In [3]:
```
df
```

Out[3]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500
...	...	...	...	...	...	...	...	...	...	...
886	887	0	2	Montvila, Rev. Juozas	male	27.0	0	0	211536	13.0000

Scanned with CamScanner

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare
887	888	1	1	Graham, Miss. Margaret Edith	female	19.0	0	0	112053	30.0000
888	889	0	3	Johnston, Miss. Catherine Helen "Carrie"	female	NaN	1	2	W./C. 6607	23.4500
889	890	1	1	Behr, Mr. Karl Howell	male	26.0	0	0	111369	30.0000
				Dooley,						

Data preprocessing

In [4]:
```
df.shape
```

Out[4]:
```
(891, 12)
```

In [5]:
```
df.columns
```

Out[5]:
```
Index(['PassengerId', 'Survived', 'Pclass', 'Name', 'Sex', 'Age', 'SibSp',
       'Parch', 'Ticket', 'Fare', 'Cabin', 'Embarked'],
      dtype='object')
```

In [6]:
```
df.dtypes
```

Out[6]:
```
PassengerId      int64
Survived         int64
Pclass           int64
Name            object
Sex             object
Age            float64
SibSp            int64
Parch            int64
Ticket          object
Fare           float64
Cabin           object
Embarked        object
dtype: object
```

In [7]:
```
df.info()
```

Scanned with CamScanner

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 891 entries, 0 to 890
Data columns (total 12 columns):
 #   Column       Non-Null Count  Dtype
---  ------------ --------------- -----
 0   PassengerId  891 non-null    int64
 1   Survived     891 non-null    int64
 2   Pclass       891 non-null    int64
 3   Name         891 non-null    object
```

In [8]:
```
df.isnull()
```

Out[8]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	E
0	False	False	False	False	False	False	False	False	False	False	True	
1	False	False	False	False	False	False	False	False	False	False	False	
2	False	False	False	False	False	False	False	False	False	False	True	
3	False	False	False	False	False	False	False	False	False	False	False	
4	False	False	False	False	False	False	False	False	False	False	True	
...	...	...	...	...	...	...	...	...	...	...	...	
886	False	False	False	False	False	False	False	False	False	False	True	
887	False	False	False	False	False	False	False	False	False	False	False	
888	False	False	False	False	False	True	False	False	False	False	True	
889	False	False	False	False	False	False	False	False	False	False	False	
890	False	False	False	False	False	False	False	False	False	False	True	

891 rows × 12 columns

In [9]:
```
df.isnull().sum()
```

Out[9]:
```
PassengerId      0
Survived         0
Pclass           0
Name             0
Sex              0
Age            177
SibSp            0
Parch            0
Ticket           0
Fare             0
Cabin          687
Embarked         2
dtype: int64
```

In [10]:
```
df.describe()
```

Out[10]:

	PassengerId	Survived	Pclass	Age	SibSp	Parch	Fare
count	891.000000	891.000000	891.000000	714.000000	891.000000	891.000000	891.000000

Scanned with CamScanner

	PassengerId	Survived	Pclass	Age	SibSp	Parch	Fare
mean	446.000000	0.383838	2.308642	29.699118	0.523008	0.381594	32.204208
std	257.353842	0.486592	0.836071	14.526497	1.102743	0.806057	49.693429
min	1.000000	0.000000	1.000000	0.420000	0.000000	0.000000	0.000000
25%	223.500000	0.000000	2.000000	20.125000	0.000000	0.000000	7.910400
50%	446.000000	0.000000	3.000000	28.000000	0.000000	0.000000	14.454200

Data Visualization

In [12]:
```
sns.countplot(df['Sex'])
```

Out[12]:
```
<matplotlib.axes._subplots.AxesSubplot at 0x8345203508>
```



In [13]:
```
sns.countplot(df['Survived'])
```

Out[13]:
```
<matplotlib.axes._subplots.AxesSubplot at 0x8345288b88>
```



Scanned with CamScanner

In [15]:
```
df['Sex'].value_counts().plot(kind = 'pie', autopct = '%.2f')
```
Out[15]: <matplotlib.axes._subplots.AxesSubplot at 0x8345593d08>



In [16]:
```
df['Survived'].value_counts().plot(kind = 'pie', autopct = '%.2f')
```
Out[16]: <matplotlib.axes._subplots.AxesSubplot at 0x83455b8ec8>



In [17]:
```
sns.barplot(df['Survived'], df['Age'])
```
Out[17]: <matplotlib.axes._subplots.AxesSubplot at 0x8345bd2788>



Scanned with CamScanner

In [19]:
```
sns.barplot(df['Sex'], df['Survived'])
```

Out[19]: <matplotlib.axes._subplots.AxesSubplot at 0x8345bcda08>



In [20]:
```
sns.barplot(df['Sex'],df['Age'], hue = df['Survived'])
```

Out[20]: <matplotlib.axes._subplots.AxesSubplot at 0x8345cf55c8>



Scanned with CamScanner

In [21]:
```
sns.boxplot(df['Sex'], df['Age'])
```

Out[21]: <matplotlib.axes._subplots.AxesSubplot at 0x8345d66c48>



In [4]:
```
sns.boxplot(df['Sex'], df['Age'], df['Survived'])
```

Out[4]: <matplotlib.axes._subplots.AxesSubplot at 0x44b8ecf788>



In [24]:
```
pd.crosstab(df['Sex'], df['Survived'])
```

Out[24]:

Survived	0	1
Sex		
female	81	233
male	468	109

In [25]:
```
pd.crosstab(df['Age'], df['Survived'])
```

Out[25]:

Survived	0	1
Age		

Scanned with CamScanner

Survived	0	1
Age		
0.42	0	1
0.67	0	1
0.75	0	2
0.83	0	2
0.92	0	1
...	...	...
70.00	2	0
70.50	1	0
71.00	2	0
74.00	1	0

In [26]:
```
sns.heatmap(pd.crosstab(df['Sex'], df['Survived']))
```

Out[26]:
```
<matplotlib.axes._subplots.AxesSubplot at 0x8345eaa848>
```



Scanned with CamScanner

In [27]:
```
sns.heatmap(pd.crosstab(df['Age'], df['Survived']))
```

Out[27]: <matplotlib.axes._subplots.AxesSubplot at 0x8346973308>



Scanned with CamScanner

In [28]:
```
sns.clustermap(pd.crosstab(df['Sex'], df['Survived']))b
```

Out[28]: <seaborn.matrix.ClusterGrid at 0x8345c8bd48>



Scanned with CamScanner

In [29]:
```
sns.clustermap(pd.crosstab(df['Age'], df['Survived']))
```

Out[29]: <seaborn.matrix.ClusterGrid at 0x83469736c8>



Scanned with CamScanner

Assignment No 10 : Data Visualization 3

Importing Required Libraries

In [1]:
```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline
import seaborn as sns
```

Reading csv into Dataframe

In [2]:
```
df = pd.read_csv('iris.csv')
df
```

Out[2]:

	Id	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm	Species
0	1	5.1	3.5	1.4	0.2	Iris-setosa
1	2	4.9	3.0	1.4	0.2	Iris-setosa
2	3	4.7	3.2	1.3	0.2	Iris-setosa
3	4	4.6	3.1	1.5	0.2	Iris-setosa
4	5	5.0	3.6	1.4	0.2	Iris-setosa
...	...	...	...	...	...	...
145	146	6.7	3.0	5.2	2.3	Iris-virginica
146	147	6.3	2.5	5.0	1.9	Iris-virginica
147	148	6.5	3.0	5.2	2.0	Iris-virginica
148	149	6.2	3.4	5.4	2.3	Iris-virginica
149	150	5.9	3.0	5.1	1.8	Iris-virginica

150 rows × 6 columns

Data preprocessing

In [3]:
```
df.shape
```

Out[3]: (150, 6)

In [4]:
```
df.columns
```

Out[4]:

Scanned with CamScanner

```
Index(['Id', 'SepalLengthCm', 'SepalWidthCm', 'PetalLengthCm', 'PetalWidthCm
',
       'Species'],
```

In [5]:
```
df.dtypes
```

Out[5]:
```
Id                 int64
SepalLengthCm    float64
SepalWidthCm     float64
PetalLengthCm    float64
PetalWidthCm     float64
Species           object
dtype: object
```

In [6]:
```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 150 entries, 0 to 149
Data columns (total 6 columns):
 #   Column         Non-Null Count  Dtype
---  ------         --------------  -----
 0   Id             150 non-null    int64
 1   SepalLengthCm  150 non-null    float64
 2   SepalWidthCm   150 non-null    float64
 3   PetalLengthCm  150 non-null    float64
 4   PetalWidthCm   150 non-null    float64
 5   Species        150 non-null    object
dtypes: float64(4), int64(1), object(1)
memory usage: 7.2+ KB
```

In [7]:
```
df.describe()
```

Out[7]:

	Id	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm
count	150.000000	150.000000	150.000000	150.000000	150.000000
mean	75.500000	5.843333	3.054000	3.758667	1.198667
std	43.445368	0.828066	0.433594	1.764420	0.763161
min	1.000000	4.300000	2.000000	1.000000	0.100000
25%	38.250000	5.100000	2.800000	1.600000	0.300000
50%	75.500000	5.800000	3.000000	4.350000	1.300000
75%	112.750000	6.400000	3.300000	5.100000	1.800000
max	150.000000	7.900000	4.400000	6.900000	2.500000

Data Visualization

Scanned with CamScanner

In [9]:
```
sns.distplot(df['SepalLengthCm'])
```

Out[9]: <matplotlib.axes._subplots.AxesSubplot at 0x491aa5fec8>



In [10]:
```
sns.distplot(df['SepalWidthCm'])
```

Out[10]: <matplotlib.axes._subplots.AxesSubplot at 0x4919d7a808>



Scanned with CamScanner

In [11]:
```
sns.distplot(df['PetalLengthCm'])
```

Out[11]: <matplotlib.axes._subplots.AxesSubplot at 0x491ad8f0c8>



In [18]:
```
sns.distplot(df['PetalWidthCm'])
```

Out[18]: <matplotlib.axes._subplots.AxesSubplot at 0x49203185c8>



Scanned with CamScanner

In [13]:
```
plt.hist(df['SepalLengthCm'])
```

Out[13]:
```
(array([ 9., 23., 14., 27., 16., 26., 18.,  6.,  5.,  6.]),
 array([4.3 , 4.66, 5.02, 5.38, 5.74, 6.1 , 6.46, 6.82, 7.18, 7.54, 7.9 ]),
 <a list of 10 Patch objects>)
```



In [14]:
```
plt.hist(df['SepalWidthCm'])
```

Out[14]:
```
(array([ 4.,  7., 22., 24., 38., 31.,  9., 11.,  2.,  2.]),
 array([2.  , 2.24, 2.48, 2.72, 2.96, 3.2 , 3.44, 3.68, 3.92, 4.16, 4.4 ]),
 <a list of 10 Patch objects>)
```



Scanned with CamScanner

In [15]:
```
plt.hist(df['PetalLengthCm'])
```

Out[15]:
```
(array([37., 13.,  0.,  3.,  8., 26., 29., 18., 11.,  5.]),
 array([1.  , 1.59, 2.18, 2.77, 3.36, 3.95, 4.54, 5.13, 5.72, 6.31, 6.9 ]),
 <a list of 10 Patch objects>)
```



In [16]:
```
plt.hist(df['PetalWidthCm'])
```

Out[16]:
```
(array([41.,  8.,  1.,  7.,  8., 33.,  6., 23.,  9., 14.]),
 array([0.1 , 0.34, 0.58, 0.82, 1.06, 1.3 , 1.54, 1.78, 2.02, 2.26, 2.5 ]),
 <a list of 10 Patch objects>)
```



Scanned with CamScanner

In [19]:
```
sns.boxplot(df['SepalLengthCm'])
```

Out[19]: <matplotlib.axes._subplots.AxesSubplot at 0x492033df88>



In [20]:
```
sns.boxplot(df['SepalWidthCm'])
```

Out[20]: <matplotlib.axes._subplots.AxesSubplot at 0x49203d7d48>



Scanned with CamScanner

In [21]:
```
sns.boxplot(df['PetalLengthCm'])
```

Out[21]: <matplotlib.axes._subplots.AxesSubplot at 0x492043fe88>



In [22]:
```
sns.boxplot(df['PetalWidthCm'])
```

Out[22]: <matplotlib.axes._subplots.AxesSubplot at 0x492047cf88>



Scanned with CamScanner

In [27]:
```
sns.boxplot(data = df, x = df['SepalLengthCm'], y = df['Species'])
```

Out[27]: <matplotlib.axes._subplots.AxesSubplot at 0x49206243c8>



In [28]:
```
sns.boxplot(data = df, x = df['Species'], y = df['SepalWidthCm'])
```

Out[28]: <matplotlib.axes._subplots.AxesSubplot at 0x49206b7688>



Scanned with CamScanner

In [29]:
```
sns.boxplot(data = df, x = df['Species'], y = df['PetalWidthCm'])
```

Out[29]: <matplotlib.axes._subplots.AxesSubplot at 0x49207549c8>



In [30]:
```
sns.boxplot(data = df, x = df['Species'], y = df['PetalLengthCm'])
```

Out[30]: <matplotlib.axes._subplots.AxesSubplot at 0x49207d9ac8>



Scanned with CamScanner

Group B Assignments
Assignment : 01

Program :

```
package org.myorg;
import java.io.IOException;
import java.util.*;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.conf.*;
import org.apache.hadoop.io.*;
import org.apache.hadoop.mapreduce.*;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.input.TextInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;
import org.apache.hadoop.mapreduce.lib.output.TextOutputFormat;
public class WordCount
{
        public static class Map extends Mapper<LongWritable, Text, Text, IntWritable>
        {
            private final static IntWritable one = new IntWritable(1);
            private Text word = new Text();
            public void map(LongWritable key, Text value, Context context) throws IOException,
InterruptedException
            {
                String line = value.toString();
                StringTokenizer tokenizer = new StringTokenizer(line);
                while (tokenizer.hasMoreTokens())
                {
                    word.set(tokenizer.nextToken());
                    context.write(word, one);
                }
            }
}

public static class Reduce extends Reducer<Text, IntWritable, Text, IntWritable>
{
      public void reduce(Text key, Iterable<IntWritable> values, Context context) throws
IOException, InterruptedException
      {
           int sum = 0;
          for (IntWritable val : values)
```

Scanned with CamScanner

```
            {
                sum += val.get();
            }
            context.write(key, new IntWritable(sum));
        }
    }
    public static void main(String[] args) throws Exception
    {
        Configuration conf = new Configuration();
        Job job = new Job(conf, "wordcount");
        job.setOutputKeyClass(Text.class);
        job.setOutputValueClass(IntWritable.class);
        job.setMapperClass(Map.class);
        job.setReducerClass(Reduce.class);
        job.setInputFormatClass(TextInputFormat.class);
        job.setOutputFormatClass(TextOutputFormat.class);
        FileInputFormat.addInputPath(job, new Path(args[0]));
        FileOutputFormat.setOutputPath(job, new Path(args[1]));
        job.waitForCompletion(true);
    }
```

Output :

Compile WordCount.java and create a jar:

```
$ bin/hadoop com.sun.tools.javac.Main WordCount.java

$ jar cf wc.jar WordCount*.class
```

Sample text-files as input:

```
$ bin/hadoop fs -ls /user/wordcount/input/

/user/wordcount/input/file01

/user/wordcount/input/file02



$ bin/hadoop fs -cat /user/wordcount/input/file01

Hello World Bye World
```

Scanned with CamScanner

```
$ bin/hadoop fs -cat /user/wordcount/input/file02

Hello Hadoop Goodbye Hadoop
```

Output:

```
$ bin/hadoop jar wc.jar WordCount /user/wordcount/input /user/wordcount/output

Output:

$ bin/hadoop fs -cat /user/wordcount/output/part-r-00000

Bye 1

Goodbye 1

Hadoop 2

Hello 2

World 2
```

Scanned with CamScanner

Assignment : 02

SalesCountry.java

```
package SalesCountry;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.*;
import org.apache.hadoop.mapred.*;
public class SalesCountryDriver
{
	public static void main(String[] args)
	{
		JobClient my_client = new JobClient();
		// Create a configuration object for the job
		JobConf job_conf = new JobConf(SalesCountryDriver.class);
		// Set a name of the Job
		job_conf.setJobName("SalePerCountry");
		// Specify data type of output key and value
		job_conf.setOutputKeyClass(Text.class);
		job_conf.setOutputValueClass(IntWritable.class);
		// Specify names of Mapper and Reducer Class
		job_conf.setMapperClass(SalesCountry.SalesMapper.class);
		job_conf.setReducerClass(SalesCountry.SalesCountryReducer.class);
		// Specify formats of the data type of Input and output
		job_conf.setInputFormat(TextInputFormat.class);
		job_conf.setOutputFormat(TextOutputFormat.class);
		// Set input and output directories using command line arguments,
		//arg[0] = name of input directory on HDFS, and arg[1] =  name of output
		//directory to be created to store the output file.
		FileInputFormat.setInputPaths(job_conf, new Path(args[0]));
		FileOutputFormat.setOutputPath(job_conf, new Path(args[1]));
		my_client.setConf(job_conf);
		try
		 {
			// Run the job
			JobClient.runJob(job_conf);
		} catch (Exception e) { e.printStackTrace(); }
	}
}
```

SalesCountryReducer.java

```
package SalesCountry;
import java.io.IOException;
import java.util.*;
```

Scanned with CamScanner

```
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapred.*;
public class SalesCountryReducer extends MapReduceBase implements Reducer<Text,
IntWritable, Text, IntWritable>
 {
        public void reduce(Text t_key, Iterator<IntWritable> values, r<Text,IntWritable> output,
Reporter reporter) throws IOException
        {
                Text key = t_key; int frequencyForCountry = 0;
                while (values.hasNext())
                {
                        // replace type of value with the actual type of our value
                        IntWritable value = (IntWritable) values.next(); frequencyForCountry +=
                value.get();
                }
                output.collect(key, new IntWritable(frequencyForCountry));
        }
}
```

SalesMapper.java

```
package SalesCountry;
import java.io.IOException;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.LongWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapred.*;
public class SalesMapper extends MapReduceBase implements Mapper<LongWritable, Text,
Text, IntWritable>
{
        private final static IntWritable one = new IntWritable(1);
        public void map(LongWritable key, Text value, OutputCollector<Text, IntWritable>
output, Reporter reporter) throws IOException
        {
                String valueString = value.toString();
                String[] SingleCountryData = valueString.split(",");
                output.collect(new Text(SingleCountryData[7]), one);
        }
}
```

Scanned with CamScanner

Assignment : 03

```
import java.io.IOException;
import java.util.ArrayList;
import java.util.Iterator;
import java.util.List;
import java.util.StringTokenizer;
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.conf.Configured;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.LongWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapred.FileInputFormat;
import org.apache.hadoop.mapred.FileOutputFormat;
import org.apache.hadoop.mapred.JobClient;
import org.apache.hadoop.mapred.JobConf;
import org.apache.hadoop.mapred.KeyValueTextInputFormat;
import org.apache.hadoop.mapred.MapReduceBase;
import org.apache.hadoop.mapred.Mapper;
import org.apache.hadoop.mapred.OutputCollector;
import org.apache.hadoop.mapred.Reducer;
import org.apache.hadoop.mapred.Reporter;
import org.apache.hadoop.util.Tool;
import org.apache.hadoop.util.ToolRunner;

public class Weather extends Configured implements Tool
{
	final long DEFAULT_SPLIT_SIZE = 128 * 1024 * 1024;
	public static class MapClass extends MapReduceBase implements
Mapper<LongWritable, Text, Text, Text>
	{
		private Text word = new Text();
		private Text values = new Text();
		public void map(LongWritable key, Text value, OutputCollector<Text, Text>
	output, Reporter reporter) throws IOException
		{
			String line = value.toString();
			StringTokenizer itr = new StringTokenizer(line);
			int counter = 0;
			String key_out = null;
			String value_str = null;
			boolean skip = false;
```

Scanned with CamScanner

```
loop:while (itr.hasMoreTokens() && counter<13)
{
        String str = itr.nextToken();
        switch (counter)
         {
                case 0:
                key_out = str;
                if(str.contains("STN"))
                {
                        //Ignoring rows where station id is all 9
                        skip = true;
                        break loop;
                }
                else
                { break;}
                case 2:
                int hour
        =Integer.valueOf(str.substring(str.lastIndexOf("_")+1,
        str.length()));
                str = str.substring(4,str.lastIndexOf("_")-2);
                if(hour>4 && hour<=10)
                { str = str.concat("_section1"); }
                else if(hour>10 && hour<=16)
                { str = str.concat("_section2"); }
                else if(hour>16 && hour<=22)
                { str = str.concat("_section3"); }
                else{ str = str.concat("_section4"); }
                key_out = key_out.concat("_").concat(str);
                break;
                case 3:
                if(str.equals("9999.9"))
                {
                        skip = true;
                        break loop;
                }
                Else
                { value_str = str.concat(" "); break; }
                case 4:
                if(str.equals("9999.9"))
                {
                        skip = true;
                        break loop;
                }
```

Scanned with CamScanner

```
                    else{ value_str = value_str.concat(str).concat(" "); break; }
                    case 12:
                     if(str.equals("999.9"))
                    {
                            skip = true; break loop;
                    }
                    else{ value_str = value_str.concat(str).concat(" "); break; }
                    default: break;
            } counter++;
        }
        if(!skip)
        {
            word.set(key_out);
            values.set(value_str);
            output.collect(word, values);
        }
    }
}
public static class MapClassForJob2 extends MapReduceBase implements Mapper<Text, Text,
Text, Text>
 {
        private Text key_text = new Text();
        private Text value_text = new Text();
        public void map(Text key, Text value, OutputCollector<Text, Text> output, Reporter
reporter) throws IOException
         {
                String str = key.toString();
                String station = str.substring(str.lastIndexOf("_")+1, str.length());
                str = str.substring(0,str.lastIndexOf("_"));
                key_text.set(str);
                StringTokenizer itr = new StringTokenizer(value.toString());
                String str_out = station.concat("<");
                while (itr.hasMoreTokens())
                {
                         String nextToken = itr.nextToken(" ");
                        str_out = str_out.concat(nextToken);
                        str_out = ((itr.hasMoreTokens()) ? str_out.concat(",") :
                str_out.concat(">"));
                }
                value_text.set(str_out); output.collect(key_text,value_text);
        }
}
```

Scanned with CamScanner

```
public static class Reduce extends MapReduceBase implements Reducer<Text, Text, Text,
Text> {
	private Text value_out_text = new Text();
	public void reduce(Text key, Iterator<Text> values, OutputCollector<Text, Text> output,
Reporter reporter) throws IOException
	{
		double sum_temp = 0;
		double sum_dew = 0;
		double sum_wind = 0;
		int count = 0;
		while (values.hasNext())
		{
			String str = values.next().toString();
			StringTokenizer itr = new StringTokenizer(str);
			int count_vector = 0;
			while (itr.hasMoreTokens())
			{
				String nextToken = itr.nextToken(" ");
				if(count_vector==0)
				{
					sum_temp += Double.valueOf(nextToken);
				}
				if(count_vector==1)
				{
					sum_dew += Double.valueOf(nextToken);
				}
				if(count_vector==2)
				{
					sum_wind += Double.valueOf(nextToken);
				}
				count_vector++;
			} count++;
		}
		double avg_tmp = sum_temp / count;
		double avg_dew = sum_dew / count;
		double avg_wind = sum_wind / count;
		System.out.println(key.toString()+" count is "+count+" sum of temp is
"+sum_temp+" sum of dew is "+sum_dew+" sum of wind is "+sum_wind+"\n");
		String value_out =
String.valueOf(avg_tmp).concat("").concat(String.valueOf(avg_dew)).concat("
").concat(String.valueOf(avg_wind));
		value_out_text.set(value_out);
		output.collect(key, value_out_text);
```

Scanned with CamScanner

```
        }
}
public static class ReduceForJob2 extends MapReduceBase implements Reducer<Text, Text,
Text, Text>
 {
        private Text value_out_text = new Text();
        public void reduce(Text key, Iterator<Text> values, OutputCollector<Text, Text> output,
Reporter reporter) throws IOException
        {
                 String value_out = "";
                while (values.hasNext())
                {
                        value_out = value_out.concat(values.next().toString()).concat(" ");
                }
                 value_out_text.set(value_out);
                output.collect(key, value_out_text);
        }
}
static int printUsage()
{
        System.out.println("weather [-m <maps>] [-r <reduces>] <job_1 input> <job_1 output>
<job_2 output>");
        ToolRunner.printGenericCommandUsage(System.out);
        return -1;
}
public int run(String[] args) throws Exception
{
        Configuration config = getConf();
        JobConf conf = new JobConf(config, Weather.class);
        conf.setJobName("Weather Job1");
        conf.setOutputKeyClass(Text.class);
        conf.setOutputValueClass(Text.class);
        conf.setMapOutputKeyClass(Text.class);
        conf.setMapOutputValueClass(Text.class);
        conf.setMapperClass(MapClass.class);
        conf.setReducerClass(Reduce.class);
        List<String> other_args = new ArrayList<String>();
        for(int i=0; i < args.length; ++i)
        {
                try
                { if ("-m".equals(args[i]))
                        { conf.setNumMapTasks(Integer.parseInt(args[++i]));
                        }
```

Scanned with CamScanner

```
            else if ("-r".equals(args[i]))
            {
                conf.setNumReduceTasks(Integer.parseInt(args[++i]));
            }
            else
            {
                other_args.add(args[i]);
            }
        }
        catch (NumberFormatException except)
        {
            System.out.println("ERROR: Integer expected instead of " + args[i]);
            return printUsage();
        }
        catch (ArrayIndexOutOfBoundsException except)
        {
             System.out.println("ERROR: Required parameter missing from " +
        args[i-1]);
            return printUsage();
        }
    }
    FileInputFormat.setInputPaths(conf, other_args.get(0));
    FileOutputFormat.setOutputPath(conf, new Path(other_args.get(1)));
    JobClient.runJob(conf);
    JobConf conf2 = new JobConf(config, Weather.class);
    conf2.setJobName("Weather Job 2");
    conf2.setOutputKeyClass(Text.class);
    conf2.setOutputValueClass(Text.class);
    conf2.setInputFormat(KeyValueTextInputFormat.class);
    conf2.setMapOutputKeyClass(Text.class);
    conf2.setMapOutputValueClass(Text.class);
    conf2.setMapperClass(MapClassForJob2.class);
    conf2.setReducerClass(ReduceForJob2.class);
    FileInputFormat.setInputPaths(conf2, new Path(other_args.get(1)));
    FileOutputFormat.setOutputPath(conf2, new Path(other_args.get(2)));
    JobClient.runJob(conf2);
    return 0;
}
public static void main(String[] args) throws Exception
{
     int res = ToolRunner.run(new Configuration(), new Weather(), args);
    System.exit(res);
}}
```

Scanned with CamScanner