

Project name: \_\_\_\_\_

Fixture type: \_\_\_\_\_

Date: \_\_\_\_\_

# 120V Line Voltage Builder's Track Kits



Kit includes: (4) ET630 Gimbal Ring Fixtures, (1) 6' Track, (1) Floating Canopy

## Features

- Kit includes: (4) ET630 Gimbal Ring Fixtures, (1) 6' Track, (1) Floating Canopy
- Lamp: 120V 75W PAR30/R30.
- This track head comes standard as H Style. J (Juno) and L (Lightolier) styles are available. For J style please order PJTHI (W/B) with the track head.
- For L style please order PLTHI (W/B) with the track head.  
Note these must be factory installed.

## Technical Details

**Construction:** Meticulously manufactured track fixture with a clean powder coated finish for lasting quality.

**Adjustability:** Track head is adjustable 180° vertically with 358° rotation.

**Lamp:** Compatible with LED and non-LED PAR30 lamp (not included).

**Installation:** Effortlessly installed into H-Style track from ELCO or others. Compatible with Single and Double circuit track. Can be special ordered as J-Style (requires PJTLO W/B/) or L-Style (requires PLTLO W/B).

**Socket:** High quality Porcelain socket, jacketed aluminum screw shell, medium-base (E26) socket.

**Dimmability:** Triac and ELV dimmable based on lamp.

## Listings:

- ETL Listed
- RoHS Compliant

## Specifications

Voltage	120V
---------	------

## Options




White



Black

## Dimensions



## Product Numbers

Item	Voltage	Finish
<b>ET705W</b>	120V	All White
<b>ET705B</b>	120V	All Black

# Track Accessories




## Single Circuit




### Single Circuit Track

Track supplied with dead end and mounting hardware




### Live End Connector

Live end connector used for direct wiring



### Flexible Connector

Flexible connector to join two track sections at an angle up to 90°. Can be used as a feed point



### Straight Connector


Power feedable connector to join two track sections

#### CAT NO. SPECIFICATIONS

EP002W	White / 2'
EP004W	White / 4'
EP006W	White / 6'
EP008W	White / 8'
EP012W	White / 12'
EP002B	Black / 2'
EP004B	Black / 4'
EP006B	Black / 6'
EP008B	Black / 8'
EP0012B	Black / 12'
EP002BZ	Bronze / 2'
EP004BZ	Bronze / 4'
EP006BZ	Bronze / 6'
EP008BZ	Bronze / 8'
EP002N	Nickel / 2'
EP004N	Nickel / 4'
EP006N	Nickel / 6'
EP008N	Nickel / 8'


#### CAT NO. SPECIFICATIONS

EP801W	White
EP801B	Black
EP801BZ	Bronze
EP801N	Nickel




### L Connector

Power feedable connector to join two track sections at a 90° angle



### T Connector

Power feedable connector to join three track sections



### X Connector

Power feedable connector to join four track sections

#### CAT NO. SPECIFICATIONS

EP804W	White
EP804B	Black
EP804BZ	Bronze
EP804N	Nickel


#### CAT NO. SPECIFICATIONS

EP805W	White
EP805B	Black
EP805BZ	Bronze
EP805N	Nickel




### Mini Connector

Mini Connector to join two track sections. Cannot be used as a feed point




### Floating Canopy

Can be used anywhere along length of track to supply power. Includes end cap



### End Feed Kit

Kit includes live end feed and canopy to mount on outlet box. 4 1/2" x 4 1/2" x 1/4" thick



### Dead End

Dead end cap for single and double circuit track

#### CAT NO. SPECIFICATIONS

EP808W	White
EP808B	Black
EP808BZ	Bronze
EP808N	Nickel

#### CAT NO. SPECIFICATIONS

EP809W	White
EP809B	Black
EP809BZ	Bronze
EP809N	Nickel

#### CAT NO. SPECIFICATIONS

EP810W	White
EP810B	Black
EP810BZ	Bronze
EP810N	Nickel


#### CAT NO. SPECIFICATIONS

EP812W	White
EP812B	Black
EP812BZ	Bronze
EP812N	Nickel

# Track Accessories




## Single Circuit



### T-Bar Ceiling Feed

Live feed with outlet box for use with T-bar ceilings




### Dead Mini Connector

Dead Mini Connector to join two track sections without passing the power



### T-Bar Ceiling Feed

In-line T-bar ceiling feed



### Cord and Plug Connector


Cord and Plug Connector for single circuit track. 10 Amp MAX or 1200W. 12 ft. long

CAT NO.	SPECIFICATIONS
EP817W	White
EP817B	Black
EP817BZ	Bronze
EP817N	Nickel

CAT NO.	SPECIFICATIONS
EP825W	White
EP825B	Black
EP825BZ	Bronze
EP825N	Nickel


CAT NO.	SPECIFICATIONS
EP827W	White
EP827B	Black

CAT NO.	SPECIFICATIONS
EP850W	White
EP850B	Black
EP850BZ	Bronze
EP850N	Nickel




### Conduit Connector

To start a surface run




### Conduit Continuation Kit

Kit includes: (1) Left and (1) Right feed, to continue around obstructions with 1/2" surface conduit



### Live Feed with Current Limiter

Current Limiter for single circuit track. 1A to 12A available



### In-Line Feed Connector with Current Limiter

Current Limiter for single circuit track. 1A to 12A available

CAT NO.	SPECIFICATIONS
EP880W	White
EP880B	Black
EP880BZ	Bronze
EP880N	Nickel

CAT NO.	SPECIFICATIONS
EP979W	White
EP979B	Black


CAT NO.	SPECIFICATIONS
EP840W-1A	White \ 1 Amp
EP840W-2A	White \ 2.5 Amp
EP840W-5A	White \ 5 Amp
EP840W-7A	White \ 7.5 Amp
EP840W-10A	White \ 10 Amp
EP840W-12A	White \ 12 Amp
EP840B-1A	Black \ 1 Amp
EP840B-2A	Black \ 2.5 Amp
EP840B-5A	Black \ 5 Amp
EP840B-7A	Black \ 7.5 Amp
EP840B-10A	Black \ 10 Amp
EP840B-12A	Black \ 12 Amp
EP840BZ-1A	Bronze \ 1 Amp
EP840BZ-2A	Bronze \ 2.5 Amp
EP840BZ-5A	Bronze \ 5 Amp
EP840BZ-7A	Bronze \ 7.5 Amp
EP840BZ-10A	Bronze \ 10 Amp
EP840BZ-12A	Bronze \ 12 Amp

CAT NO.	SPECIFICATIONS
EP841W-1A	White \ 1 Amp
EP841W-2A	White \ 2.5 Amp
EP841W-5A	White \ 5 Amp
EP841W-7A	White \ 7.5 Amp
EP841W-10A	White \ 10 Amp
EP841W-12A	White \ 12 Amp
EP841B-1A	Black \ 1 Amp
EP841B-2A	Black \ 2.5 Amp
EP841B-5A	Black \ 5 Amp
EP841B-7A	Black \ 7.5 Amp
EP841B-10A	Black \ 10 Amp
EP841B-12A	Black \ 12 Amp

# Track Accessories




## Two Circuit



### Two Circuit Track

Track supplied with dead end and mounting hardware


CAT NO.	SPECIFICATIONS
EC002W	White / 2'
EC004W	White / 4'
EC006W	White / 6'
EC008W	White / 8'
EC012W	White / 12'
EC002B	Black / 2'
EC004B	Black / 4'
EC006B	Black / 6'
EC008B	Black / 8'
EC012B	Black / 12'



### Live End Connector

Two circuit live end connector to start a run


CAT NO.	SPECIFICATIONS
EC801W	White
EC801B	Black



### Flexible Connector

Flexible connector to join two track sections at an angle up to 90°


CAT NO.	SPECIFICATIONS
EC802W	White
EC802B	Black



### Straight Connector

Power feedable connector to join two track sections


CAT NO.	SPECIFICATIONS
EC803W	White
EC803B	Black



### L Connector

Power feedable connector to join two track sections at a 90° angle


CAT NO.	SPECIFICATIONS
EC804W	White
EC804B	Black



### T Connector

Power feedable connector to join three track sections


CAT NO.	SPECIFICATIONS
EC805W	White
EC805B	Black



### X Connector

Power feedable connector to join four track sections

CAT NO.	SPECIFICATIONS
EC806W	White
EC806B	Black



### Mini Connector

Mini Connector to join two track sections. Cannot be used as a feed point


CAT NO.	SPECIFICATIONS
EC808W	White
EC808B	Black



### Floating Canopy

Can be used anywhere along length of track to supply power. Includes end cap

CAT NO.	SPECIFICATIONS
EC809W	White
EC809B	Black



### Dead End

Dead end cap for single and double circuit track


CAT NO.	SPECIFICATIONS
EP812W	White
EP812B	Black



### T-Bar Ceiling Feed

Live feed with outlet box for use with T-bar ceilings

CAT NO.	SPECIFICATIONS
EC817W	White
EC817B	Black




### Conduit Connector

To start a surface run


CAT NO.	SPECIFICATIONS
EC880W	White
EC880B	Black

## Two Circuit



**Two Circuit Live-End Feed Connector  
with Current Limiter**

1A to 12A available. Separate circuit breaker for each circuit.  
Custom current rating available upon request



**Two Circuit In-Line Feed Connector  
with Current Limiter**

1A to 12A available. Separate circuit breaker for each circuit.  
Custom current rating available upon request


CAT NO.	SPECIFICATIONS	CIRCUIT 1		CIRCUIT 2	
EC840W	White	<b>1A</b>	1 Amp	<b>1A</b>	1 Amp
EC840B	Black	<b>2A</b>	2.5 Amp	<b>2A</b>	2.5 Amp
		<b>5A</b>	5 Amp	<b>5A</b>	5 Amp
		<b>7A</b>	7.5 Amp	<b>7A</b>	7.5 Amp
		<b>10A</b>	10 Amp	<b>10A</b>	10 Amp
		<b>12A</b>	12.5 Amp	<b>12A</b>	12.5 Amp

CAT NO.	SPECIFICATIONS	CIRCUIT 1		CIRCUIT 2	
EC841W	White	<b>1A</b>	1 Amp	<b>1A</b>	1 Amp
EC841B	Black	<b>2A</b>	2.5 Amp	<b>2A</b>	2.5 Amp
		<b>5A</b>	5 Amp	<b>5A</b>	5 Amp
		<b>7A</b>	7.5 Amp	<b>7A</b>	7.5 Amp
		<b>10A</b>	10 Amp	<b>10A</b>	10 Amp
		<b>12A</b>	12.5 Amp	<b>12A</b>	12.5 Amp

# Track Accessories




## General




### Track Adapter Trim

For use with standard 6" recessed housings. Allow track lamp holders to be used with recessed installations. Up to 150W Max. 7 1/2" O.D.



### Outlet Box Cover

Outlet box cover. Screws not included. 5" x 5" x 1 1/8" x 1 1/4" Sq



### Monopoint Canopy

Allows any lamp holder (300W MAX.) to be converted to canopy installation. For Line Voltage fixtures



### Sign Hanger


Sign Hanger with hook for single and double circuit track. Holds up to 25 lbs

CAT NO.	SPECIFICATIONS
EP577W	White
EP577B	Black

CAT NO.	SPECIFICATIONS
EP800W	White
EP800B	Black
EP800BZ	Bronze

CAT NO.	SPECIFICATIONS
EP811W	White
EP811B	Black
EP811BZ	Bronze
EP811N	Nickel

CAT NO.	SPECIFICATIONS
EP813W	White
EP813B	Black
EP813BZ	Bronze
EP813N	Nickel



### Outlet Adapter

Outlet Adapter for single circuit and two circuit track




### Pendant Adapter

For single circuit and two circuit track with strain relief connector for cord or chain hung fixtures. Holds up to 35 lbs



### Round Monopoint Canopy

For Line Voltage fixtures. 4 5/8" O.D.



### Straight Channel


Provides support for straight connection points in suspended track system. Track sits inside the channel. 16 1/4" long. Support rails for tracks

CAT NO.	SPECIFICATIONS
EP814W	White
EP814B	Black
EP814BZ	Bronze
EP814N	Nickel

CAT NO.	SPECIFICATIONS
EP815W	White
EP815B	Black
EP815BZ	Bronze
EP815N	Nickel


CAT NO.	SPECIFICATIONS
EP819W	White
EP819B	Black
EP819BZ	Bronze

CAT NO.	SPECIFICATIONS
EP844W	White
EP844B	Black




### L Channel

Support corner connection points in suspended track system. Track sits inside the channel. 16 1/4" long in each side. Support rails for tracks



### Dimmer Switch

Dimmer with ON/OFF switch. For Line Voltage fixtures. 150W MAX. For use with extension wands. Halogen lamps only



### Clamp Cord and Plug

Clamp with 6 ft.cord and plug with female track connector for attaching a Line Voltage fixture



### 48" Steel Stem

For additional pendant length. Includes coupling. Use with EP918, EP924, EP936, and EP948

CAT NO.	SPECIFICATIONS
EP845W	White
EP845B	Black

CAT NO.	SPECIFICATIONS
EP901W	White
EP901B	Black

CAT NO.	SPECIFICATIONS
EP903W	White
EP903B	Black

CAT NO.	SPECIFICATIONS
EP904W	White
EP904B	Black

# Track Accessories



## General



**T-Bar Attachment Clip**

Allows track to be attached to inverted T-Bar ceiling. Order as follow: (2) clips for 2' or 4' track, (3) clips for 6' track, (4) clips for 8' or 12' track




**Slope Ceiling Fixture Adapter**

Allows use of extension wands on slope ceiling. 0°- 90°



**Track Pendant Kit**

Track pendant kit with 60" stainless steel cable.  
1/16" stranded



**Clamp Cord and Track Adapter**


Connects to Line Voltage track.  
Includes female track connector for attaching a Line Voltage fixture

CAT NO.	SPECIFICATIONS
EP989B	Black

CAT NO.	SPECIFICATIONS
EP906W	White
EP906B	Black

CAT NO.	SPECIFICATIONS
EP960W	White
EP960B	Black

CAT NO.	SPECIFICATIONS
EP907W	White
EP907B	Black




**Pendant Assembly**

Suspends track from ceiling.  
Order as follow: (2) kits for 2' or 4' track, (3) kits for 6' track, (4) kits for 8' track, (5) kits for 12', (1) EP807 per feed




**Sloped Ceiling Pendant Adapter**

Sloped Ceiling Pendant adapter for use with EP918, EP924, EP936, and EP948



**Wire Cover**

Wire cover for power feed through with pendant assembly. One per run. For use with EP918 to EP948



**Extension Wand**

Line voltage extension wands.  
Drops head from track

CAT NO.	SPECIFICATIONS
EP918W	White \ 18"
EP924W	White \ 24"
EP936W	White \ 36"
EP948W	White \ 48"
EP918B	Black \ 18"
EP924B	Black \ 24"
EP936B	Black \ 36"
EP948B	Black \ 48"

CAT NO.	SPECIFICATIONS
EP905W	White
EP905B	Black

CAT NO.	SPECIFICATIONS
EP807W	White
EP807B	Black
EP807BZ	Bronze
EP807N	Nickel

CAT NO.	SPECIFICATIONS
EP881W	6"
EP882W	12"
EP818W	18"
EP824W	24"
EP836W	36"
EP848W	48"
EP881B	6"
EP882B	12"
EP818B	18"
EP824B	24"
EP836B	36"
EP848B	48"