

Direct Implementation Guide: Xtime API Extraction for Retell AI Integration

Vault - The Unsealed Depository

1 Core Objective

To bypass the Xtime GUI and programmatically schedule service appointments via a Retell AI Voice Agent. This requires a full mapping of the Xtime REST headers, payload schemas, and state transitions.

2 Postman Collection Mapping: Logic Flow

2.1 Phase 1: Customer Identification (The Fork)

The system must differentiate between a new and returning user to determine the payload structure for the final booking.

- Existing User Path:

```
1 GET /api/v2/dealers/{dealerId}/customers?query={phone_number}
2 // Result: Returns customerId and array of vehicleId
```

- New User Path:

```
1 GET /api/v2/vehicles/years
2 GET /api/v2/vehicles/{year}/makes
3 // Result: Requires full manual construction of Vehicle Object
```

2.2 Phase 2: Availability & Service Mapping

- **Endpoint:** POST /api/v2/dealers/dealerId/availability
- **Payload:** Must include opCodes[] (e.g., "LOF" for Oil Change) and transportationOption.
- **Response:** A flat list of startDateTime strings.

3 Implementation: Next.js + Supabase + Retell

3.1 The Middleware Logic

The Next.js route /api/schedule-xtime performs the following linear actions:

1. Receive transcript or tool_call from Retell.
2. Query Supabase to find the dealerId for the specific phone number the agent is calling for.
3. Execute the Reverse Engineered Xtime sequence:
 - Lookup Customer → Select/Create Vehicle → Fetch Slots → **Final Book.**
4. Confirm the booking to Retell to be spoken to the user.

4 The Reverse Engineering Task List

- **Task 1:** Use a proxy to intercept the `X-AUTH-TOKEN` or `Cookie` patterns used by *mcgovernsubarufacton.com*.
- **Task 2:** Map the JSON payload for `POST /api/v2/appointments`. This is the "God Request" that finalizes the schedule.
- **Task 3:** Build the Postman collection with tests that verify if a `customerId` exists before attempting a `customer/create` call.

5 Final Architecture Formula

$$Appointment = Retell(Voice) \rightarrow NextJS(MappingLogic) \rightarrow Xtime(EndpointInjection)$$