

# Using a Service to Expose Your App

## Overview of Kubernetes Services

Kubernetes [Pods](#) are mortal. Pods in fact have a [lifecycle](#). When a worker node dies, the Pods running on the Node are also lost. A [ReplicaSet](#) might then dynamically drive the cluster back to desired state via creation of new Pods to keep your application running. As another example, consider an image-processing backend with 3 replicas. Those replicas are exchangeable; the front-end system should not care about backend replicas or even if a Pod is lost and recreated. That said, each Pod in a Kubernetes cluster has a unique IP address, even Pods on the same Node, so there needs to be a way of automatically reconciling changes among Pods so that your applications continue to function.

A Service in Kubernetes is an abstraction which defines a logical set of Pods and a policy by which to access them. Services enable a loose coupling between dependent Pods. A Service is defined using YAML ([preferred](#)) or JSON, like all Kubernetes objects. The set of Pods targeted by a Service is usually determined by a *LabelSelector* (see below for why you might want a Service without including selector in the spec).

Although each Pod has a unique IP address, those IPs are not exposed outside the cluster without a Service. Services allow your applications to receive traffic. Services can be exposed in different ways by specifying a type in the ServiceSpec:

- *ClusterIP* (default) - Exposes the Service on an internal IP in the cluster. This type makes the Service only reachable from within the cluster.
- *NodePort* - Exposes the Service on the same port of each selected Node in the cluster using NAT. Makes a Service accessible from outside the cluster using `<NodeIP>:<NodePort>`. Superset of ClusterIP.
- *LoadBalancer* - Creates an external load balancer in the current cloud (if supported) and assigns a fixed, external IP to the Service. Superset of NodePort.
- *ExternalName* - Maps the Service to the contents of the `externalName` field (e.g. `foo.bar.example.com`), by returning a CNAME record with its value. No proxying of any kind is set up. This type requires v1.7 or higher of kube-dns, or CoreDNS version 0.0.8 or higher.

More information about the different types of Services can be found in the [Using Source IP](#) tutorial. Also see [Connecting Applications with Services](#).

Additionally, note that there are some use cases with Services that involve not defining selector in the spec. A Service created without selector will also not create the corresponding Endpoints object. This allows users to manually map a Service to specific endpoints. Another possibility why there may be no selector is you are strictly using type: `ExternalName`.

