



Program No:	1
Roll No :	1545
Title of Program :	MongoDb commands
Objective :	Perform basic operations in MongoDB database

1) Data Definition

Create a database:

Creating a database is dynamic

use command - create new database and switch to that database and if database already exists then existing database is used

cmd: use TeacherDB1

```
> use TeachersDB1
switched to db TeachersDB1
>
> show dbs
EmpDb      0.000GB
RetailDb    0.000GB
SalesDb     0.000GB
StudentDb   0.000GB
admin       0.000GB
config      0.000GB
local       0.000GB
mca         0.000GB
> |
```

Creating a Collection:

Creating a database itself does not allocate the memory you have to create a collection

```
> db.TeacherColl.insert(
... {
... "tid": 101,
... "tname": "Om"
... }
... );
WriteResult({ "nInserted" : 1 })
```



MUMBAI EDUCATIONAL TRUST

MET Institute of Computer Science

THE MET LEAGUE OF COLLEGES
MET
AS SHARP AS YOU CAN GET
Bhujbal Knowledge City

Inserting one document

```
> db.TeacherColl.insertOne(  
... {  
... "tid": 102,  
... "tname": "om1",  
... "salary": 20000  
... });  
{  
    "acknowledged" : true,  
    "insertedId" : ObjectId("686b69b328a22fc429746e47")  
}
```

Inserting many documents

```
> db.TeacherColl.insertMany( [ { "tid": 103, "tname": "ca", "salary": 25000 }, { "tid": 104, "tname": "fg", "salary": 20000, "experience": 20 }, { "tid": 105, "tname": "pg" } ]);  
{  
    "acknowledged" : true,  
    "insertedIds" : [  
        ObjectId("686b6ae128a22fc429746e48"),  
        ObjectId("686b6ae128a22fc429746e49"),  
        ObjectId("686b6ae128a22fc429746e4a")  
    ]  
}
```

To see list of collections

```
> show collections  
TeacherColl
```

To display the records

```
> db.TeacherColl.find();  
{ "_id" : ObjectId("686b686e28a22fc429746e46"), "tid" : 101, "tname" : "Om" }  
{ "_id" : ObjectId("686b69b328a22fc429746e47"), "tid" : 102, "tname" : "om1", "salary" : 20000 }  
{ "_id" : ObjectId("686b6ae128a22fc429746e48"), "tid" : 103, "tname" : "ca", "salary" : 25000 }  
{ "_id" : ObjectId("686b6ae128a22fc429746e49"), "tid" : 104, "tname" : "fg", "salary" : 20000, "experience" : 20 }  
{ "_id" : ObjectId("686b6ae128a22fc429746e4a"), "tid" : 105, "tname" : "pg" }
```



To display the records in json format

```
> db.TeacherColl.find().pretty();
{
    "_id" : ObjectId("686b686e28a22fc429746e46"),
    "tid" : 101,
    "tname" : "Om"
}
{
    "_id" : ObjectId("686b69b328a22fc429746e47"),
    "tid" : 102,
    "tname" : "om1",
    "salary" : 20000
}
{
    "_id" : ObjectId("686b6ae128a22fc429746e48"),
    "tid" : 103,
    "tname" : "ca",
    "salary" : 25000
}
{
    "_id" : ObjectId("686b6ae128a22fc429746e49"),
    "tid" : 104,
    "tname" : "fg",
    "salary" : 20000,
    "experience" : 20
}
{
    "_id" : ObjectId("686b6ae128a22fc429746e4a"),
    "tid" : 105,
    "tname" : "pg"
}
> |
```

Creating a Collection statically



MUMBAI EDUCATIONAL TRUST

MET Institute of Computer Science

THE MET LEAGUE OF COLLEGES
MET
AS SHARP AS YOU CAN GET
Bhujbal Knowledge City

```
> db.createCollection("Students")
{ "ok" : 1 }
> show collections
Students
TeacherColl
```

Gives error when we give same `_id` to two documents

```
> db.Students.insertOne(
... {
...   "_id": 101,
...   "sname": "shivam",
... });
{ "acknowledged" : true, "insertedId" : 101 }
> db.Students.insertOne(
... {
...   "_id": 101,
...   "sname": "ajay",
... });
2025-07-07T12:23:14.602+0530 E QUERY      [js] WriteError: E11000 duplicate key error collection:
TeachersDB1.Students index: _id_ dup key: { : 101.0 } :
WriteError({
  "index" : 0,
  "code" : 11000,
  "errmsg" : "E11000 duplicate key error collection: TeachersDB1.Students index: _id_ dup
key: { : 101.0 }",
  "op" : {
    "_id" : 101,
    "sname" : "ajay"
  }
})
```

```
> db.Students.insertOne( { "sid": 101, "sname": "ajay", });
{
  "acknowledged" : true,
  "insertedId" : ObjectId("686b6f2b28a22fc429746e4b")
}
> db.Students.find().pretty();
{ "_id" : 101, "sname" : "shivam" }
{
  "_id" : ObjectId("686b6f2b28a22fc429746e4b"),
  "sid" : 101,
  "sname" : "ajay"
}
```



2) Data Manipulation

\$gt	greater than
\$lt	less than
\$gte	greater than or equal to
\$lte	less than or equal to
\$eq	equality
\$ne	not equal to

Write a query to find all the teacher earning salary greater than 20000

```
> db.TeacherColl.find(  
... {  
... "salary": {$gt: 20000}  
... });  
{ "_id" : ObjectId("686b6ae128a22fc429746e48"), "tid" : 103, "tname" : "ca", "salary" : 25000 }
```

Write a query to find all the teacher earning salary less than 30000

```
> db.TeacherColl.find( { "salary": {$lt: 30000} } );  
{ "_id" : ObjectId("686b69b328a22fc429746e47"), "tid" : 102, "tname" : "oml", "salary" : 20000  
}  
{ "_id" : ObjectId("686b6ae128a22fc429746e48"), "tid" : 103, "tname" : "ca", "salary" : 25000 }  
{ "_id" : ObjectId("686b6ae128a22fc429746e49"), "tid" : 104, "tname" : "fg", "salary" : 20000,  
"experience" : 20 }
```

Write a query to find all the teacher earning salary 20000

```
> db.TeacherColl.find( { "salary": {$eq: 20000} } );  
{ "_id" : ObjectId("686b69b328a22fc429746e47"), "tid" : 102, "tname" : "oml", "salary" : 20000  
}  
{ "_id" : ObjectId("686b6ae128a22fc429746e49"), "tid" : 104, "tname" : "fg", "salary" : 20000,  
"experience" : 20 }
```



Write a query to find all the teachers who does not have experience of 20

```
> db.TeacherColl.find( { "experience": {$ne: 20} } );
{ "_id" : ObjectId("686b686e28a22fc429746e46"), "tid" : 101, "tname" : "Om" }
{ "_id" : ObjectId("686b69b328a22fc429746e47"), "tid" : 102, "tname" : "om1", "salary" : 20000
}
{ "_id" : ObjectId("686b6ae128a22fc429746e48"), "tid" : 103, "tname" : "ca", "salary" : 25000 }
{ "_id" : ObjectId("686b6ae128a22fc429746e4a"), "tid" : 105, "tname" : "pg" }
```

Find teacher with id 103

```
> db.TeacherColl.find(
... {
...   "tid": 103
... });
{ "_id" : ObjectId("686b6ae128a22fc429746e48"), "tid" : 103, "tname" : "ca", "salary" : 25000 }
```

Display all teacher info except 105

```
> db.TeacherColl.find( { "tid": {$ne: 105} } );
{ "_id" : ObjectId("686b686e28a22fc429746e46"), "tid" : 101, "tname" : "Om" }
{ "_id" : ObjectId("686b69b328a22fc429746e47"), "tid" : 102, "tname" : "om1", "salary" : 20000
}
{ "_id" : ObjectId("686b6ae128a22fc429746e48"), "tid" : 103, "tname" : "ca", "salary" : 25000 }
{ "_id" : ObjectId("686b6ae128a22fc429746e49"), "tid" : 104, "tname" : "fg", "salary" : 20000,
"experience" : 20 }
```

Find all the teacher whose salary is greater than 30000 or experience greater than 15 years

```
> db.TeacherColl.find(
... {
...   $or: [ {"salary": {$gt: 30000}}, {"experience": {$gt: 15}} ]
... });
{ "_id" : ObjectId("686b6ae128a22fc429746e49"), "tid" : 104, "tname" : "fg", "salary" : 20000,
"experience" : 20 }
```

Find all the teacher whose salary is greater than 10000 and experience greater than 15 years

```
> db.TeacherColl.find( { $and: [ {"salary": {$gt: 10000}}, {"experience": {$gt: 15}} ] } );
{ "_id" : ObjectId("686b6ae128a22fc429746e49"), "tid" : 104, "tname" : "fg", "salary" : 20000, "experience" : 20 }
```