



# How do you handle API security in your application ? How can you make your API secure ? What are possible ways to do it in Springboot? Assume you are using Spring security 6.x+ ,then how will you do it ?

To secure APIs in a modern Spring Boot 3 + Spring Security 6.x environment, the standard approach is using **OAuth2 Resource Server** with **JWT** (stateless), combined with **Method Security** (`@PreAuthorize`) for fine-grained control.<sup>[1] [2]</sup>

Here is how I handle it, structured as a clear interview answer:

## 1. Core Security Strategy

"I handle API security by implementing a **stateless, token-based architecture** using **OAuth2** and **JWT**. I use Spring Security 6.x as the framework, configuring it as a **Resource Server**. My strategy includes:

- **Authentication:** Verifying identity via JWT tokens issued by an Identity Provider (like Keycloak, Okta, or a custom Auth Service).
- **Authorization:** Enforcing access control at two levels:
  - **URL Level:** Using `SecurityFilterChain` to protect endpoints globally.
  - **Method Level:** Using `@EnableMethodSecurity` and `@PreAuthorize` for fine-grained business logic access."<sup>[3] [1]</sup>

## 2. How I implement it in Spring Boot 3 (Spring Security 6.x)

### Step A: Dependency

"I add `spring-boot-starter-oauth2-resource-server`. This single starter handles JWT validation, parsing, and context setup automatically."<sup>[1]</sup>

### Step B: Configuration (`SecurityFilterChain`)

"In Spring Security 6, we no longer extend `WebSecurityConfigurerAdapter`. Instead, we define a bean."<sup>[4]</sup>

```
@Configuration
@EnableWebSecurity
@EnableMethodSecurity // Replaces @EnableGlobalMethodSecurity in v6
public class SecurityConfig {
```

```

@Bean
public SecurityFilterChain filterChain(HttpSecurity http) throws Exception {
    return http
        .csrf(csrf -> csrf.disable()) // Disable CSRF for stateless APIs
        .sessionManagement(session -> session.sessionCreationPolicy(SessionCreationPolicy.STATELESS))
        .authorizeHttpRequests(auth -> auth
            .requestMatchers("/public/**").permitAll() // Public endpoints
            .anyRequest().authenticated() // Everything else requires a token
        )
        .oauth2ResourceServer(oauth2 -> oauth2.jwt()) // Enable JWT validation
        .build();
}
}

```

### Step C: Handling Roles (The "Tricky" Part)

"By default, Spring Security 6 maps JWT scopes to authorities (e.g., `SCOPE_read`). To use roles like `ROLE_ADMIN`, I configure a **JwtAuthenticationConverter**." [\[2\]](#) [\[1\]](#)

```

@Bean
public JwtAuthenticationConverter jwtAuthenticationConverter() {
    JwtGrantedAuthoritiesConverter grantedAuthoritiesConverter = new JwtGrantedAuthoritiesConverter();
    grantedAuthoritiesConverter.setAuthorityPrefix("ROLE_"); // Prefixes roles
    grantedAuthoritiesConverter.setAuthoritiesClaimName("roles"); // Reads "roles" claim

    JwtAuthenticationConverter jwtConverter = new JwtAuthenticationConverter();
    jwtConverter.setJwtGrantedAuthoritiesConverter(grantedAuthoritiesConverter);
    return jwtConverter;
}

```

## 3. Making APIs Secure (Best Practices I Follow)

Beyond just "login," I enforce:

- **HTTPS Only:** I enforce TLS (SSL) so tokens aren't intercepted. [\[5\]](#) [\[6\]](#)
- **Fine-Grained Access:** I use `@PreAuthorize` on service methods.
  - *Example:* `@PreAuthorize("hasRole('ADMIN') or #username == authentication.name")` to ensure users can only edit their own profile. [\[7\]](#) [\[3\]](#)
- **Input Validation:** I use `@Valid` and JSR-380 annotations on DTOs to prevent injection attacks before data even reaches business logic. [\[6\]](#)
- **Rate Limiting:** I implement rate limiting (using libraries like Bucket4j or via API Gateway) to prevent DDoS.
- **CORS Configuration:** I strictly configure CORS to allow only trusted frontend domains, preventing unauthorized cross-origin calls. [\[6\]](#)

## 4. Interview Follow-Up: "What if you need Custom Auth?"

"If I can't use an external IDP and need custom auth, I implement a custom `JwtAuthenticationFilter` that intercepts the request, parses the Bearer token, validates it (signature + expiry), and manually populates the `SecurityContextHolder`. But in Spring 6, standard OAuth2 Resource Server is preferred for standard JWTs." [8] [2]

✱

1. <https://devlach.com/blog/java/spring-security-oauth2-resource-server>
2. [https://www.youtube.com/watch?v=cIML\\_jhQcR4](https://www.youtube.com/watch?v=cIML_jhQcR4)
3. <https://www.baeldung.com/spring-enablemethodsecurity>
4. <https://www.tothenew.com/blog/migrating-to-spring-security-6/>
5. <https://moldstud.com/articles/p-securing-restful-apis-with-spring-security-best-practices>
6. <https://escape.tech/blog/security-best-practices-for-spring-boot-applications/>
7. <https://docs.spring.io/spring-security/reference/6.0/servlet/authorization/method-security.html>
8. [https://blog.csdn.net/m0\\_60551898/article/details/130458451](https://blog.csdn.net/m0_60551898/article/details/130458451)
9. <https://ppl-ai-file-upload.s3.amazonaws.com/web/direct-files/attachments/images/81815274/24f18c0a-b56e-4862-a619-e2959036a5c2/image.jpg>
10. <https://ppl-ai-file-upload.s3.amazonaws.com/web/direct-files/attachments/images/81815274/97e9ed86-ed11-4035-a18b-1eb05c1bab4e/image.jpg>
11. <https://ppl-ai-file-upload.s3.amazonaws.com/web/direct-files/attachments/images/81815274/87f62423-96f2-4071-9802-8f6699e0ecd8/image.jpg>
12. <https://spring.io/projects/spring-security>
13. <https://spring.io/guides/gs/securing-web>
14. <https://www.geeksforgeeks.org/advance-java/securing-rest-apis-with-spring-security/>
15. <https://stackoverflow.com/questions/41480102/how-spring-security-filter-chain-works>
16. [https://www.youtube.com/watch?v=oeni\\_9g7too](https://www.youtube.com/watch?v=oeni_9g7too)
17. <https://stevenpg.com/posts/spring-boot-oauth2-multiple-resource-servers/>
18. <https://docs.spring.io/spring-security/reference/servlet/configuration/java.html>
19. <https://docs.spring.io/spring-security/reference/servlet/oauth2/resource-server/index.html>
20. <https://www.geeksforgeeks.org/java/spring-security-filter-chain-with-example/>
21. <https://bootify.io/spring-security/rest-api-spring-security-with-jwt.html>
22. <https://docs.spring.io/spring-security/reference/servlet/authorization/method-security.html>
23. <https://snyk.io/blog/spring-boot-security-best-practices/>
24. <https://ppl-ai-file-upload.s3.amazonaws.com/web/direct-files/attachments/images/81815274/429036f4-3bc3-4a7a-8c6f-90246e73b9b9/image.jpg>