UCLA Samueli School of Engineering

Industrobot4.0

Pick and Place robot for Material Handling

Team #14
Kalra, Nitesh (005528195)
Sanghai, Nikunj (505730005)
Wani, Shubham Kiran (105730007)

Agenda

1. Motivation and Task Definition
2. Literature Review
3. Object Detection and Sorting
4. Computed Feedforward Controller
5. PD controller with Gravity Compensation
6. Inverse Dynamics Control
7. Discussion and Conclusions
8. Q&A

Motivation and Task Definition

Motivation

- Material handling/manipulation is a routine task in every industry, esp. e-commerce and manufacturing due to staffing issues.
- The global pick-n-place robot market was valued at USD 148.1 million in 2020 and it is expected to reach USD 2870.13 million by 2026 [7].

Objectives of controller design (KPI)

- Cycle Time < 10 sec (sort frequency)
- Torque i/p - 75% of Max Torques
- Error (EE position) < 5°
- Velocity of Conveyor = 0.3 m/s

Task Definition

Phase 1 - Object Interception Trajectory

↓

Phase 2 - Trajectory Tracking

↓

Phase 3 - Object Placement Trajectory

Joint N°	1	2	3	4	5	6
τ_{max} (N m)	97.6	186.4	89.4	24.2	20.1	21.3

Figure 1: Max Joint Torques

https://www.mordorintelligence.com/industry-reports/piece-picking-robots-market

Literature Review

Dynamics and Modelling Assumptions

Robot - Unimation Puma 560 [2]

Dynamics Equations - Inertia, Coriolis, Centrifugal, Gravity [3]

The first 3 axis provide position whereas the next 3 provide orientation. Moment of Inertia (M.o.I) is comparatively higher and hence control effort focuses on first 3. [3]

Uses Explicit Dynamics for simulation.



Figure 2: Puma 560

Modified D-H frame notation for a six degrees of freedom PUMA 560 robot manipulator[3]

	Joint 1	Joint 2	Joint 3	Joint 4	Joint 5	Joint 6
Gear Ratio	62.61	107.36	53.69	76.01	71.91	76.73
Maximum Torque (N-m)	97.6	186.4	89.4	24.2	20.1	21.3
Break Away Torque (N-m)	6.3	5.5	2.6	1.3	1.0	1.2

Figure 3: Motor and Drive Parameters [3]

Object Detection and Sorting

Actual Conveyor

Simulated Conveyor

Parameters

Random Parameters:
Shape, Size, Colour

Set Parameters
Speed, Width, Time Step

Single frame



Figure 4: Flowchart

RGB Channel Separation



Figure 5: RGB Layers

MATLAB Image Processing Toolbox

imfindcircles

1

- Circular Hough Transform
- Centre, Radii, No. of Circles

bwlabel

2

- Circularity R= 4*pi*A/P^2
- Blob Perimeter, Area, Location, Circularity

https://www.videvo.net/video/electric-waste-on-conveyor-belt-1/2200/

https://www.mathworks.com/help/images/display-separated-color-channels-of-rgb-image.html

UCLA Samueli School of Engineering

Computed Torque Controller



Decentralized Feedforward action

Centralised Feedforward action

Figure 6: Computed Torque Control

Bruno Siciliano, et al. 2010. Robotics: Modelling, Planning and Control. Springer Publishing

Computed Torque Controller



Figure 7: End Effector - Desired vs Actual Trajectory

- Decentralized controller does not consider dynamic coupling of links.
- The calculation of feedforward compensation is not able to account for couplings between the links thus accounting for very high error.
- The speeds are quite high, and hence the controller failed.

Initial - $K_p = 200 * I_{6x6}$; $K_d = 50 * I_{6x6}$

Final - $K_p = 280 * I_{6x6}$; $K_d = 70 * I_{6x6}$

PD control with Gravity Compensation



Figure 8: PD Control with Gravity Comp.

$$u = g(q) + K_P\tilde{q} - K_D\dot{q},$$

Nonlinear gravity compensation **Linear PD action**

Bruno Siciliano, et al. 2010. Robotics: Modelling, Planning and Control. Springer Publishing

PD control with Gravity Compensation



Video 1: Trajectory Tracking



Figure 9: End Effector - Desired vs Actual Trajectory

PD control with Gravity Compensation

Controller Design

- Assumption: Speeds very low i.e. $\dot{q} \sim 0$ for global asymptotic stability for any Kp & Kd.
- Simulation: $\dot{q} \neq 0$ so errors expected
- Result: Max error ~10 degree, moderate error but not suitable for pick and place.
- Advantages:
  - Computationally inexpensive.
  - Great for low speeds.
  - Will always converge

Initial - $K_p = 200 * I_{6x6}$; $K_d = 40 * I_{6x6}$

Final - $K_p = 150 * I_{6x6}$; $K_d = 30 * I_{6x6}$



Figure 10: Joint Position Errors

PD control with Gravity Compensation



Figure 11: Joint Positions



Figure 12: Joint Velocities

Inverse Dynamics Control



Stabilizing linear control

$$\boldsymbol{r} = \ddot{\boldsymbol{q}}_d + \boldsymbol{K}_D\dot{\boldsymbol{q}}_d + \boldsymbol{K}_P\boldsymbol{q}_d$$



Nonlinear compensation and decoupling

$$\boldsymbol{u} = \boldsymbol{B}(\boldsymbol{q})\boldsymbol{y} + \boldsymbol{n}(\boldsymbol{q}, \dot{\boldsymbol{q}})$$

Figure 13: Inverse Dynamics Control

Bruno Siciliano, et al. 2010. Robotics: Modelling, Planning and Control. Springer Publishing

Inverse Dynamics Controller



Video 2: Trajectory Tracking



Figure 14: End Effector - Desired vs Actual Trajectory

Inverse Dynamics Controller

Controller Design

Trial 1 - $K_p = 150 * I_{6x6}$; $K_d = 25 * I_{6x6}$

Trial 2 - $K_p = 200 * I_{6x6}$; $K_d = 50 * I_{6x6}$

Final Design - $K_p = 200 * I_{6x6}$; $K_d = 40 * I_{6x6}$

Result - Max error < 3.5° (Joint 1)

Challenges

- Accuracy of parameters of the system dynamic model
- Online computation



Figure 15: Joint Position Errors

Inverse Dynamics Controller



Figure 16: Joint Positions



Figure 17: Joint Velocities

Discussion and Conclusion

- **Studied 3 controllers for high speed pick and place operation**
  - Cycle time, t = 9.5 [sec]
  - CTFA = Max error
  - PDGF = Max error < 10° in Joint 1
  - IDC = Max error < 3.5° in Joint 1

- **Error analysis for task at higher speed**
  - To further demonstrate the robustness of Inverse Dynamics Control for these applications, we ran the task with higher speeds
  - Cycle time, t = 7.1 [sec]
  - Max error ~5° in Joint 1



Figure 18: Joint Position Errors

References

1. Bruno Siciliano, Lorenzo Sciavicco, Luigi Villani, and Giuseppe Oriolo. 2010. Robotics: Modelling, Planning and Control. Springer Publishing Company, Incorporated.
2. B. Armstrong, O. Khatib and J. Burdick, "The explicit dynamic model and inertial parameters of the PUMA 560 arm," Proceedings. 1986 IEEE International Conference on Robotics and Automation, 1986, pp. 510-518, doi: 10.1109/ROBOT.1986.1087644.
3. Farzin Piltan, S. Emamzadeh, Z. Hivand, F. Shahriyari & Mina Mirazaei. ” PUMA-560 Robot Manipulator Position Sliding Mode Control Methods Using MATLAB/SIMULINK and Their Integration into Graduate/Undergraduate Nonlinear Control, Robotics and MATLAB Courses” International Journal of Robotics and Automation, 3(3): 2012.
4. P.I. Corke, “Robotics, Vision & Control”, Springer 2017, ISBN 978-3-319-54413-7
5. MATLAB. (2019). 9.7.0.1190202 (R2020b). Natick, Massachusetts: The MathWorks Inc
6. https://manipulation.csail.mit.edu/pick.html
7. https://www.mordorintelligence.com/industry-reports/piece-picking-robots-market

Q&A