


Professional-Cloud-Architect Dumps

Google Certified Professional - Cloud Architect (GCP)

<https://www.certleader.com/Professional-Cloud-Architect-dumps.html>



NEW QUESTION 1

- (Exam Topic 1)

For this question, refer to the Mountkirk Games case study.

Mountkirk Games wants to set up a real-time analytics platform for their new game. The new platform must meet their technical requirements. Which combination of Google technologies will meet all of their requirements?

- A. Container Engine, Cloud Pub/Sub, and Cloud SQL
- B. Cloud Dataflow, Cloud Storage, Cloud Pub/Sub, and BigQuery
- C. Cloud SQL, Cloud Storage, Cloud Pub/Sub, and Cloud Dataflow
- D. Cloud Dataproc, Cloud Pub/Sub, Cloud SQL, and Cloud Dataflow
- E. Cloud Pub/Sub, Compute Engine, Cloud Storage, and Cloud Dataproc

Answer: B

Explanation:

A real time requires Stream / Messaging so Pub/Sub, Analytics by Big Query.

Ingest millions of streaming events per second from anywhere in the world with Cloud Pub/Sub, powered by Google's unique, high-speed private network. Process the streams with Cloud Dataflow to ensure reliable, exactly-once, low-latency data transformation. Stream the transformed data into BigQuery, the cloud-native data warehousing service, for immediate analysis via SQL or popular visualization tools.

From scenario: They plan to deploy the game's backend on Google Compute Engine so they can capture streaming metrics, run intensive analytics.

Requirements for Game Analytics Platform

Dynamically scale up or down based on game activity
Process incoming data on the fly directly from the game servers
Process data that arrives late because of slow mobile networks
Allow SQL queries to access at least 10 TB of historical data
Process files that are regularly uploaded by users' mobile devices
Use only fully managed services
References: <https://cloud.google.com/solutions/big-data/stream-analytics/>

NEW QUESTION 2

- (Exam Topic 2)

For this question, refer to the TerramEarth case study

Your development team has created a structured API to retrieve vehicle data. They want to allow third parties to develop tools for dealerships that use this vehicle event data. You want to support delegated authorization against this data. What should you do?

- A. Build or leverage an OAuth-compatible access control system.
- B. Build SAML 2.0 SSO compatibility into your authentication system.
- C. Restrict data access based on the source IP address of the partner systems.
- D. Create secondary credentials for each dealer that can be given to the trusted third party.

Answer: A

Explanation:

<https://cloud.google.com/appengine/docs/flexible/go/authorizing-apps> https://cloud.google.com/docs/enterprise/best-practices-for-enterprise-organizations#delegate_application_autho Delegate application authorization with OAuth2

Cloud Platform APIs support OAuth 2.0, and scopes provide granular authorization over the methods that are supported. Cloud Platform supports both service-account and user-account OAuth, also called three-legged OAuth.

References:

https://cloud.google.com/docs/enterprise/best-practices-for-enterprise-organizations#delegate_application_autho

<https://cloud.google.com/appengine/docs/flexible/go/authorizing-apps>

NEW QUESTION 3

- (Exam Topic 2)

For this question, refer to the TerramEarth case study.

The TerramEarth development team wants to create an API to meet the company's business requirements. You want the development team to focus their development effort on business value versus creating a custom framework. Which method should they use?

- A. Use Google App Engine with Google Cloud Endpoint
- B. Focus on an API for dealers and partners.
- C. Use Google App Engine with a JAX-RS Jersey Java-based framework
- D. Focus on an API for the public.
- E. Use Google App Engine with the Swagger (open API Specification) framework
- F. Focus on an API for the public.
- G. Use Google Container Engine with a Django Python container
- H. Focus on an API for the public.
- I. Use Google Container Engine with a Tomcat container with the Swagger (Open API Specification) framework
- J. Focus on an API for dealers and partners.

Answer: A

Explanation:

https://cloud.google.com/endpoints/docs/openapi/about-cloud-endpoints?hl=en_US&_ga=2.21787131.-1712523

<https://cloud.google.com/endpoints/docs/openapi/architecture-overview>

<https://cloud.google.com/storage/docs/gsutil/commands/test>

Develop, deploy, protect and monitor your APIs with Google Cloud Endpoints. Using an Open API Specification or one of our API frameworks, Cloud Endpoints gives you the tools you need for every phase of API development.

From scenario: Business Requirements

Decrease unplanned vehicle downtime to less than 1 week, without increasing the cost of carrying surplus inventory

Support the dealer network with more data on how their customers use their equipment to better position new products and services

Have the ability to partner with different companies – especially with seed and fertilizer suppliers in the fast-growing agricultural business – to create compelling joint offerings for their customers.

Reference: <https://cloud.google.com/certification/guides/cloud-architect/casestudy-terramearth>

NEW QUESTION 4

- (Exam Topic 2)

For this question refer to the TerramEarth case study

Operational parameters such as oil pressure are adjustable on each of TerramEarth's vehicles to increase their efficiency, depending on their environmental conditions. Your primary goal is to increase the operating efficiency of all 20 million cellular and unconnected vehicles in the field How can you accomplish this goal?

- A. Have your engineers inspect the data for patterns, and then create an algorithm with rules that make operational adjustments automatically.
- B. Capture all operating data, train machine learning models that identify ideal operations, and run locally to make operational adjustments automatically.
- C. Implement a Google Cloud Dataflow streaming job with a sliding window, and use Google Cloud Messaging (GCM) to make operational adjustments automatically.
- D. Capture all operating data, train machine learning models that identify ideal operations, and host in Google Cloud Machine Learning (ML) Platform to make operational adjustments automatically.

Answer: B

NEW QUESTION 5

- (Exam Topic 4)

The current Dress4win system architecture has high latency to some customers because it is located in one data center.

As of a future evaluation and optimizing for performance in the cloud, Dress4win wants to distribute its system architecture to multiple locations when Google cloud platform. Which approach should they use?

- A. Use regional managed instance groups and a global load balancer to increase performance because the regional managed instance group can grow instances in each region separately based on traffic.
- B. Use a global load balancer with a set of virtual machines that forward the requests to a closer group of virtual machines managed by your operations team.
- C. Use regional managed instance groups and a global load balancer to increase reliability by providing automatic failover between zones in different regions.
- D. Use a global load balancer with a set of virtual machines that forward the requests to a closer group of virtual machines as part of a separate managed instance groups.

Answer: A

NEW QUESTION 6

- (Exam Topic 5)

Your company just finished a rapid lift and shift to Google Compute Engine for your compute needs. You have another 9 months to design and deploy a more cloud-native solution. Specifically, you want a system that is no-ops and auto-scaling. Which two compute products should you choose? Choose 2 answers

- A. Compute Engine with containers
- B. Google Kubernetes Engine with containers
- C. Google App Engine Standard Environment
- D. Compute Engine with custom instance types
- E. Compute Engine with managed instance groups

Answer: BC

Explanation:

B: With Container Engine, Google will automatically deploy your cluster for you, update, patch, secure the nodes.

Kubernetes Engine's cluster autoscaler automatically resizes clusters based on the demands of the workloads you want to run.

C: Solutions like Datastore, BigQuery, AppEngine, etc are truly NoOps.

App Engine by default scales the number of instances running up and down to match the load, thus providing consistent performance for your app at all times while minimizing idle instances and thus reducing cost.

Note: At a high level, NoOps means that there is no infrastructure to build out and manage during usage of the platform. Typically, the compromise you make with

NoOps is that you lose control of the underlying infrastructure.

References:

<https://www.quora.com/How-well-does-Google-Container-Engine-support-Google-Cloud-Platform%E2%80%99>

NEW QUESTION 7

- (Exam Topic 5)

One of your primary business objectives is being able to trust the data stored in your application. You want to log all changes to the application data. How can you design your logging system to verify authenticity of your logs?

- A. Write the log concurrently in the cloud and on premises.
- B. Use a SQL database and limit who can modify the log table.
- C. Digitally sign each timestamp and log entry and store the signature.
- D. Create a JSON dump of each log entry and store it in Google Cloud Storage.

Answer: C

Explanation:

<https://cloud.google.com/storage/docs/access-logs>

References: <https://cloud.google.com/logging/docs/reference/tools/gcloud-logging>

NEW QUESTION 8

- (Exam Topic 5)

You have an application that will run on Compute Engine. You need to design an architecture that takes into account a disaster recovery plan that requires your application to fail over to another region in case of a regional outage. What should you do?

- A. Deploy the application on two Compute Engine instances in the same project but in a different region. Use the first instance to serve traffic, and use the HTTP load balancing service to fail over to the standby instance in case of a disaster.
- B. Deploy the application on a Compute Engine instance
- C. Use the instance to serve traffic, and use the HTTP load balancing service to fail over to an instance on your premises in case of a disaster.
- D. Deploy the application on two Compute Engine instance groups, each in the same project but in a different region
- E. Use the first instance group to serve traffic, and use the HTTP load balancing service to fail over to the standby instance group in case of a disaster.
- F. Deploy the application on two Compute Engine instance groups, each in separate project and a different region
- G. Use the first instance group to serve traffic, and use the HTTP load balancing service to fail over to the standby instance in case of a disaster.

Answer: C

NEW QUESTION 9

- (Exam Topic 5)

Your customer runs a web service used by e-commerce sites to offer product recommendations to users. The company has begun experimenting with a machine learning model on Google Cloud Platform to improve the quality of results.

What should the customer do to improve their model's results over time?

- A. Export Cloud Machine Learning Engine performance metrics from Stackdriver to BigQuery, to be used to analyze the efficiency of the model.
- B. Build a roadmap to move the machine learning model training from Cloud GPUs to Cloud TPUs, which offer better results.
- C. Monitor Compute Engine announcements for availability of newer CPU architectures, and deploy the model to them as soon as they are available for additional performance.
- D. Save a history of recommendations and results of the recommendations in BigQuery, to be used as training data.

Answer: D

Explanation:

<https://cloud.google.com/solutions/building-a-serverless-ml-model>

NEW QUESTION 10

- (Exam Topic 5)

You want to make a copy of a production Linux virtual machine in the US-Central region. You want to manage and replace the copy easily if there are changes on the production virtual machine. You will deploy the copy as a new instances in a different project in the US-East region. What steps must you take?

- A. Use the Linux dd and netcat command to copy and stream the root disk contents to a new virtual machine instance in the US-East region.
- B. Create a snapshot of the root disk and select the snapshot as the root disk when you create a new virtual machine instance in the US-East region.
- C. Create an image file from the root disk with Linux dd command, create a new disk from the image file, and use it to create a new virtual machine instance in the US-East region
- D. Create a snapshot of the root disk, create an image file in Google Cloud Storage from the snapshot, and create a new virtual machine instance in the US-East region using the image file for the root disk.

Answer: D

Explanation:

<https://stackoverflow.com/questions/36441423/migrate-google-compute-engine-instance-to-a-different-region>

NEW QUESTION 10

- (Exam Topic 5)

Your organization requires that metrics from all applications be retained for 5 years for future analysis in possible legal proceedings. Which approach should you use?

- A. Grant the security team access to the logs in each Project.
- B. Configure Stackdriver Monitoring for all Projects, and export to BigQuery.
- C. Configure Stackdriver Monitoring for all Projects with the default retention policies.

D. Configure Stackdriver Monitoring for all Projects, and export to Google Cloud Storage.

Answer: D

Explanation:

Overview of storage classes, price, and use cases <https://cloud.google.com/storage/docs/storage-classes> Why export logs?

<https://cloud.google.com/logging/docs/export/>

StackDriver Quotas and Limits for Monitoring <https://cloud.google.com/monitoring/quotas> The BigQuery pricing. <https://cloud.google.com/bigquery/pricing>

NEW QUESTION 11

- (Exam Topic 5)

You are helping the QA team to roll out a new load-testing tool to test the scalability of your primary cloud services that run on Google Compute Engine with Cloud Bigtable. Which three requirements should they include? Choose 3 answers

- A. Ensure that the load tests validate the performance of Cloud Bigtable.
- B. Create a separate Google Cloud project to use for the load-testing environment.
- C. Schedule the load-testing tool to regularly run against the production environment.
- D. Ensure all third-party systems your services use are capable of handling high load.
- E. Instrument the production services to record every transaction for replay by the load-testing tool.
- F. Instrument the load-testing tool and the target services with detailed logging and metrics collection.

Answer: ABF

NEW QUESTION 14

- (Exam Topic 5)

Your company is using BigQuery as its enterprise data warehouse. Data is distributed over several Google Cloud projects. All queries on BigQuery need to be billed on a single project. You want to make sure that no query costs are incurred on the projects that contain the data. Users should be able to query the datasets, but not edit them.

How should you configure users' access roles?

- A. Add all users to a group
- B. Grant the group the role of BigQuery user on the billing project and BigQuery dataViewer on the projects that contain the data.
- C. Add all users to a group
- D. Grant the group the roles of BigQuery dataViewer on the billing project and BigQuery user on the projects that contain the data.
- E. Add all users to a group
- F. Grant the group the roles of BigQuery jobUser on the billing project and BigQuery dataViewer on the projects that contain the data.
- G. Add all users to a group
- H. Grant the group the roles of BigQuery dataViewer on the billing project and BigQuery jobUser on the projects that contain the data.

Answer: A

Explanation:

Reference: <https://cloud.google.com/bigquery/docs/running-queries>

NEW QUESTION 17

- (Exam Topic 5)

You want your Google Kubernetes Engine cluster to automatically add or remove nodes based on CPUload. What should you do?

- A. Configure a HorizontalPodAutoscaler with a target CPU usage
- B. Enable the Cluster Autoscaler from the GCP Console.
- C. Configure a HorizontalPodAutoscaler with a target CPU usage
- D. Enable autoscaling on the managed instance group for the cluster using the gcloud command.
- E. Create a deployment and set the maxUnavailable and maxSurge properties
- F. Enable the Cluster Autoscaler using the gcloud command.
- G. Create a deployment and set the maxUnavailable and maxSurge properties
- H. Enable autoscaling on the cluster managed instance group from the GCP Console.

Answer: B

NEW QUESTION 19

- (Exam Topic 5)

You created a pipeline that can deploy your source code changes to your infrastructure in instance groups for self healing.

One of the changes negatively affects your key performance indicator. You are not sure how to fix it and investigation could take up to a week. What should you do

- A. Log in to a server, and iterate a fix locally
- B. Change the instance group template to the previous one, and delete all instances.
- C. Revert the source code change and rerun the deployment pipeline
- D. Log into the servers with the bad code change, and swap in the previous code

Answer: C

NEW QUESTION 22

- (Exam Topic 5)

Your customer is moving their corporate applications to Google Cloud Platform. The security team wants detailed visibility of all projects in the organization. You provision the Google Cloud Resource Manager and set up yourself as the org admin. What Google Cloud Identity and Access Management (Cloud IAM) roles should you give to the security team?

- A. Org viewer, project owner

- B. Org viewer, project viewer
- C. Org admin, project browser
- D. Project owner, network admin

Answer: B

Explanation:

<https://cloud.google.com/iam/docs/using-iam-securely>

NEW QUESTION 24

- (Exam Topic 5)

The application reliability team at your company has added a debug feature to their backend service to send all server events to Google Cloud Storage for eventual analysis. The event records are at least 50 KB and at most 15 MB and are expected to peak at 3,000 events per second. You want to minimize data loss. Which process should you implement?

- A. • Append metadata to file body. • Compress individual files. • Name files with serverName-Timestamp. • Create a new bucket if bucket is older than 1 hour and save individual files to the new bucket
- B. Otherwise, save files to existing bucket
- C. • Batch every 10,000 events with a single manifest file for metadata. • Compress event files and manifest file into a single archive file. • Name files using serverName-EventSequence. • Create a new bucket if bucket is older than 1 day and save the single archive file to the new bucket
- D. Otherwise, save the single archive file to existing bucket.
- E. • Compress individual files. • Name files with serverName-EventSequence. • Save files to one bucket • Set custom metadata headers for each object after saving.
- F. • Append metadata to file body. • Compress individual files. • Name files with a random prefix pattern. • Save files to one bucket

Answer: D

Explanation:

In order to maintain a high request rate, avoid using sequential names. Using completely random object names will give you the best load distribution. Randomness after a common prefix is effective under the prefix <https://cloud.google.com/storage/docs/request-rate>

NEW QUESTION 26

- (Exam Topic 5)

You want to establish a Compute Engine application in a single VPC across two regions. The application must communicate over VPN to an on-premises network. How should you deploy the VPN?

- A. Use VPC Network Peering between the VPC and the on-premises network.
- B. Expose the VPC to the on-premises network using IAM and VPC Sharing.
- C. Create a global Cloud VPN Gateway with VPN tunnels from each region to the on-premises peer gateway.
- D. Deploy Cloud VPN Gateway in each region
- E. Ensure that each region has at least one VPN tunnel to the on-premises peer gateway.

Answer: C

Explanation:

<https://cloud.google.com/vpn/docs/how-to/creating-static-vpns>

NEW QUESTION 31

- (Exam Topic 5)

You want to enable your running Google Container Engine cluster to scale as demand for your application changes. What should you do?

- A. Add additional nodes to your Container Engine cluster using the following command: `gcloud container clusters resize CLUSTER_NAME --size 10`
- B. Add a tag to the instances in the cluster with the following command: `gcloud compute instances add-tags INSTANCE --tags enable --autoscaling max-nodes=10`
- C. Update the existing Container Engine cluster with the following command: `gcloud alpha container clusters update mycluster --enable-autoscaling --min-nodes=1 --max-nodes=10`
- D. Create a new Container Engine cluster with the following command: `gcloud alpha container clusters create mycluster --enable-autocaling --min-nodes=1 --max-nodes=10` and redeploy your application.

Answer: B

Explanation:

<https://cloud.google.com/kubernetes-engine/docs/concepts/cluster-autoscaler> Cluster autoscaling

`--enable-autoscaling`

Enables autoscaling for a node pool.

Enables autoscaling in the node pool specified by `--node-pool` or the default node pool if `--node-pool` is not provided.

Where:

`--max-nodes=MAX_NODES`

Maximum number of nodes in the node pool.

Maximum number of nodes to which the node pool specified by `--node-pool` (or default node pool if unspecified) can scale.

NEW QUESTION 33

- (Exam Topic 5)

A development manager is building a new application He asks you to review his requirements and identify what cloud technologies he can use to meet them. The application must

- * 1. Be based on open-source technology for cloud portability
- * 2. Dynamically scale compute capacity based on demand
- * 3. Support continuous software delivery
- * 4. Run multiple segregated copies of the same application stack

- * 5. Deploy application bundles using dynamic templates
 - * 6. Route network traffic to specific services based on URL
- Which combination of technologies will meet all of his requirements?

- A. Google Container Engine, Jenkins, and Helm
- B. Google Container Engine and Cloud Load Balancing
- C. Google Compute Engine and Cloud Deployment Manager
- D. Google Compute Engine, Jenkins, and Cloud Load Balancing

Answer: A

Explanation:

Helm for managing Kubernetes

Kubernetes can base on the URL to route traffic to different location (path) <https://cloud.google.com/kubernetes-engine/docs/tutorials/http-balancer> eg. apiVersion: networking.k8s.io/v1beta1

kind: Ingress metadata:

name: fanout-ingress spec:

rules:

- http: paths:

- path: /* backend: serviceName: web servicePort: 8080

- path: /v2/* backend: serviceName: web2 servicePort: 8080

NEW QUESTION 34

- (Exam Topic 5)

Your organization has a 3-tier web application deployed in the same network on Google Cloud Platform. Each tier (web, API, and database) scales independently of the others. Network traffic should flow through the web to the API tier and then on to the database tier. Traffic should not flow between the web and the database tier. How should you configure the network?

- A. Add each tier to a different subnetwork.
- B. Set up software based firewalls on individual VMs.
- C. Add tags to each tier and set up routes to allow the desired traffic flow.
- D. Add tags to each tier and set up firewall rules to allow the desired traffic flow.

Answer: D

Explanation:

<https://aws.amazon.com/blogs/aws/building-three-tier-architectures-with-security-groups/>

Google Cloud Platform(GCP) enforces firewall rules through rules and tags. GCP rules and tags can be defined once and used across all regions.

References: <https://cloud.google.com/docs/compare/openstack/> <https://aws.amazon.com/it/blogs/aws/building-three-tier-architectures-with-security-groups/>

NEW QUESTION 36

- (Exam Topic 5)

Your company creates rendering software which users can download from the company website. Your company has customers all over the world. You want to minimize latency for all your customers. You want to follow Google-recommended practices. How should you store the files?

- A. Save the files in a Multi-Regional Cloud Storage bucket.
- B. Save the files in a Regional Cloud Storage bucket, one bucket per zone of the region.
- C. Save the files in multiple Regional Cloud Storage buckets, one bucket per zone per region.
- D. Save the files in multiple Multi-Regional Cloud Storage buckets, one bucket per multi-region.

Answer: A

Explanation:

<https://cloud.google.com/storage/docs/locations#location-mr>

NEW QUESTION 41

- (Exam Topic 5)

Your company is migrating its on-premises data center into the cloud. As part of the migration, you want to integrate Kubernetes Engine for workload orchestration. Parts of your architecture must also be PCI DSS compliant. Which of the following is most accurate?

- A. App Engine is the only compute platform on GCP that is certified for PCI DSS hosting.
- B. Kubernetes Engine cannot be used under PCI DSS because it is considered shared hosting.
- C. Kubernetes Engine and GCP provide the tools you need to build a PCI DSS-compliant environment.
- D. All Google Cloud services are usable because Google Cloud Platform is certified PCI-compliant.

Answer: D

Explanation:

<https://cloud.google.com/security/compliance/pci-dss>

NEW QUESTION 46

- (Exam Topic 5)

You are developing a globally scaled frontend for a legacy streaming backend data API. This API expects events in strict chronological order with no repeat data for proper processing.

Which products should you deploy to ensure guaranteed-once FIFO (first-in, first-out) delivery of data?

- A. Cloud Pub/Sub alone

- B. Cloud Pub/Sub to Cloud DataFlow
- C. Cloud Pub/Sub to Stackdriver
- D. Cloud Pub/Sub to Cloud SQL

Answer: B

Explanation:

Reference <https://cloud.google.com/pubsub/docs/ordering>

NEW QUESTION 48

- (Exam Topic 5)

A news feed web service has the following code running on Google App Engine. During peak load, users report that they can see news articles they already viewed. What is the most likely cause of this problem?

- A. The session variable is local to just a single instance.
- B. The session variable is being overwritten in Cloud Datastore.
- C. The URL of the API needs to be modified to prevent caching.
- D. The HTTP Expires header needs to be set to -1 to stop caching.

Answer: A

Explanation:

<https://stackoverflow.com/questions/3164280/google-app-engine-cache-list-in-session-variable?rq=1>

NEW QUESTION 53

- (Exam Topic 5)

Your web application has several VM instances running within a VPC. You want to restrict communications between instances to only the paths and ports you authorize, but you don't want to rely on static IP addresses or subnets because the app can autoscale. How should you restrict communications?

- A. Use separate VPCs to restrict traffic
- B. Use firewall rules based on network tags attached to the compute instances
- C. Use Cloud DNS and only allow connections from authorized hostnames
- D. Use service accounts and configure the web application particular service accounts to have access

Answer: B

NEW QUESTION 57

- (Exam Topic 5)

Your organization wants to control IAM policies for different departments independently, but centrally. Which approach should you take?

- A. Multiple Organizations with multiple Folders
- B. Multiple Organizations, one for each department
- C. A single Organization with Folder for each department
- D. A single Organization with multiple projects, each with a central owner

Answer: C

Explanation:

Folders are nodes in the Cloud Platform Resource Hierarchy. A folder can contain projects, other folders, or a combination of both. You can use folders to group projects under an organization in a hierarchy. For example, your organization might contain multiple departments, each with its own set of GCP resources. Folders allow you to group these resources on a per-department basis. Folders are used to group resources that share common IAM policies. While a folder can contain multiple folders or resources, a given folder or resource can have exactly one parent.

References: <https://cloud.google.com/resource-manager/docs/creating-managing-folders>

NEW QUESTION 59

- (Exam Topic 5)

You are analyzing and defining business processes to support your startup's trial usage of GCP, and you don't yet know what consumer demand for your product will be. Your manager requires you to minimize GCP service costs and adhere to Google best practices. What should you do?

- A. Utilize free tier and sustained use discount
- B. Provision a staff position for service cost management.
- C. Utilize free tier and sustained use discount
- D. Provide training to the team about service cost management.
- E. Utilize free tier and committed use discount
- F. Provision a staff position for service cost management.
- G. Utilize free tier and committed use discount
- H. Provide training to the team about service cost management.

Answer: D

Explanation:

https://cloud.google.com/docs/enterprise/best-practices-for-enterprise-organizations#billing_and_management

NEW QUESTION 63

- (Exam Topic 5)

You are using Cloud SQL as the database backend for a large CRM deployment. You want to scale as usage increases and ensure that you don't run out of storage, maintain 75% CPU usage cores, and keep replication lag below 60 seconds. What are the correct steps to meet your requirements?

- A. 1) Enable automatic storage increase for the instance.2) Create a Stackdriver alert when CPU usage exceeds 75%, and change the instance type to reduce CPU usage.3) Create a Stackdriver alert for replication lag, and shard the database to reduce replication time.
- B. 1) Enable automatic storage increase for the instance.2) Change the instance type to a 32-core machine type to keep CPU usage below 75%.3) Create a Stackdriver alert for replication lag, and shard the database to reduce replication time.
- C. 1) Create a Stackdriver alert when storage exceeds 75%, and increase the available storage on the instance to create more space.2) Deploy memcached to reduce CPU load.3) Change the instance type to a 32-core machine type to reduce replication lag.
- D. 1) Create a Stackdriver alert when storage exceeds 75%, and increase the available storage on the instance to create more space.2) Deploy memcached to reduce CPU load.3) Create a Stackdriver alert for replication lag, and change the instance type to a 32-core machine type to reduce replication lag.

Answer: A

NEW QUESTION 64

- (Exam Topic 5)

You are running a cluster on Kubernetes Engine to serve a web application. Users are reporting that a specific part of the application is not responding anymore. You notice that all pods of your deployment keep restarting after 2 seconds. The application writes logs to standard output. You want to inspect the logs to find the cause of the issue. Which approach can you take?

- A. Review the Stackdriver logs for each Compute Engine instance that is serving as a node in the cluster.
- B. Review the Stackdriver logs for the specific Kubernetes Engine container that is serving the unresponsive part of the application.
- C. Connect to the cluster using gcloud credentials and connect to a container in one of the pods to read the logs.
- D. Review the Serial Port logs for each Compute Engine instance that is serving as a node in the cluster.

Answer: B

NEW QUESTION 69

- (Exam Topic 5)

You write a Python script to connect to Google BigQuery from a Google Compute Engine virtual machine. The script is printing errors that it cannot connect to BigQuery. What should you do to fix the script?

- A. Install the latest BigQuery API client library for Python
- B. Run your script on a new virtual machine with the BigQuery access scope enabled
- C. Create a new service account with BigQuery access and execute your script with that user
- D. Install the bq component for gcloud with the command `gcloud components install bq`.

Answer: B

Explanation:

The error is most likely caused by the access scope issue. When create new instance, you have the default Compute engine default service account but most serves access including BigQuery is not enable. Create an instance Most access are not enabled by default You have default service account but don't have the permission (scope) you can stop the instance, edit, change scope and restart it to enable the scope access. Of course, if you Run your script on a new virtual machine with the BigQuery access scope enabled, it also works

<https://cloud.google.com/compute/docs/access/service-accounts>

NEW QUESTION 72

- (Exam Topic 5)

As part of implementing their disaster recovery plan, your company is trying to replicate their production MySQL database from their private data center to their GCP project using a Google Cloud VPN connection. They are experiencing latency issues and a small amount of packet loss that is disrupting the replication. What should they do?

- A. Configure their replication to use UDP.
- B. Configure a Google Cloud Dedicated Interconnect.
- C. Restore their database daily using Google Cloud SQL.
- D. Add additional VPN connections and load balance them.
- E. Send the replicated transaction to Google Cloud Pub/Sub.

Answer: B

NEW QUESTION 73

- (Exam Topic 5)

You have an outage in your Compute Engine managed instance group: all instance keep restarting after 5 seconds. You have a health check configured, but autoscaling is disabled. Your colleague, who is a Linux expert, offered to look into the issue. You need to make sure that he can access the VMs. What should you do?

- A. Grant your colleague the IAM role of project Viewer
- B. Perform a rolling restart on the instance group
- C. Disable the health check for the instance group
- D. Add his SSH key to the project-wide SSH keys
- E. Disable autoscaling for the instance group
- F. Add his SSH key to the project-wide SSH Keys

Answer: C

Explanation:

<https://cloud.google.com/compute/docs/instance-groups/autohealing-instances-in-migs>

Health checks used for autohealing should be conservative so they don't preemptively delete and recreate your instances. When an autohealer health check is too aggressive, the autohealer might mistake busy instances for failed instances and unnecessarily restart them, reducing availability

NEW QUESTION 76

- (Exam Topic 5)

You need to set up Microsoft SQL Server on GCP. Management requires that there's no downtime in case of a data center outage in any of the zones within a GCP region. What should you do?

- A. Configure a Cloud SQL instance with high availability enabled.
- B. Configure a Cloud Spanner instance with a regional instance configuration.
- C. Set up SQL Server on Compute Engine, using Always On Availability Groups using Windows Failover Cluster in
- D. Place nodes in different subnets.
- E. Set up SQL Server Always On Availability Groups using Windows Failover Cluster in
- F. Place nodes in different zones.

Answer: D

Explanation:

<https://cloud.google.com/sql/docs/sqlserver/configure-ha>

NEW QUESTION 77

- (Exam Topic 5)

You have been engaged by your client to lead the migration of their application infrastructure to GCP. One of their current problems is that the on-premises high performance SAN is requiring frequent and expensive upgrades to keep up with the variety of workloads that are identified as follows: 20TB of log archives retained for legal reasons; 500 GB of VM boot/data volumes and templates; 500 GB of image thumbnails; 200 GB of customer session state data that allows customers to restart sessions even if off-line for several days.

Which of the following best reflects your recommendations for a cost-effective storage allocation?

- A. Local SSD for customer session state data
- B. Lifecycle-managed Cloud Storage for log archives, thumbnails, and VM boot/data volumes.
- C. Memcache backed by Cloud Datastore for the customer session state data
- D. Lifecycle-managed Cloud Storage for log archives, thumbnails, and VM boot/data volumes.
- E. Memcache backed by Cloud SQL for customer session state data
- F. Assorted local SSD-backed instances for VM boot/data volume
- G. Cloud Storage for log archives and thumbnails.
- H. Memcache backed by Persistent Disk SSD storage for customer session state data
- I. Assorted local SSD-backed instances for VM boot/data volume
- J. Cloud Storage for log archives and thumbnails.

Answer: D

Explanation:

<https://cloud.google.com/compute/docs/disks>

NEW QUESTION 79

- (Exam Topic 5)

You deploy your custom Java application to Google App Engine. It fails to deploy and gives you the following stack trace:

- A. Recompile the CLoakedServlet class using and MD5 hash instead of SHA1
- B. Digitally sign all of your JAR files and redeploy your application.
- C. Upload missing JAR files and redeploy your application

Answer: B

NEW QUESTION 80

- (Exam Topic 5)

You need to reduce the number of unplanned rollbacks of erroneous production deployments in your company's web hosting platform. Improvement to the QA/Test processes accomplished an 80% reduction. Which additional two approaches can you take to further reduce the rollbacks? Choose 2 answers

- A. Introduce a green-blue deployment model.
- B. Replace the QA environment with canary releases.
- C. Fragment the monolithic platform into microservices.
- D. Reduce the platform's dependency on relational database systems.
- E. Replace the platform's relational database systems with a NoSQL database.

Answer: AC

NEW QUESTION 85

- (Exam Topic 5)

A development team at your company has created a dockerized HTTPS web application. You need to deploy the application on Google Kubernetes Engine (GKE) and make sure that the application scales automatically.

How should you deploy to GKE?

- A. Use the Horizontal Pod Autoscaler and enable cluster autoscalin
- B. Use an Ingress resource to loadbalance the HTTPS traffic.
- C. Use the Horizontal Pod Autoscaler and enable cluster autoscaling on the Kubernetes cluste
- D. Use a Service resource of type LoadBalancer to load-balance the HTTPS traffic.
- E. Enable autoscaling on the Compute Engine instance grou
- F. Use an Ingress resource to load balance the HTTPS traffic.
- G. Enable autoscaling on the Compute Engine instance grou
- H. Use a Service resource of type LoadBalancer to load-balance the HTTPS traffic.

Answer: B

Explanation:

<https://cloud.google.com/kubernetes-engine/docs/tutorials/http-balancer> <https://cloud.google.com/kubernetes-engine/docs/concepts/network-overview#ext-lb>

NEW QUESTION 87

- (Exam Topic 5)

Your company has decided to build a backup replica of their on-premises user authentication PostgreSQL database on Google Cloud Platform. The database is 4 TB, and large updates are frequent. Replication requires private address space communication. Which networking approach should you use?

- A. Google Cloud Dedicated Interconnect
- B. Google Cloud VPN connected to the data center network
- C. A NAT and TLS translation gateway installed on-premises
- D. A Google Compute Engine instance with a VPN server installed connected to the data center network

Answer: A

Explanation:

<https://cloud.google.com/docs/enterprise/best-practices-for-enterprise-organizations>

Google Cloud Dedicated Interconnect provides direct physical connections and RFC 1918 communication between your on-premises network and Google's network. Dedicated Interconnect enables you to transfer large amounts of data between networks, which can be more cost effective than purchasing additional bandwidth over the public Internet or using VPN tunnels.

Benefits:

Traffic between your on-premises network and your VPC network doesn't traverse the public Internet.

Traffic traverses a dedicated connection with fewer hops, meaning there are less points of failure where traffic might get dropped or disrupted.

Your VPC network's internal (RFC 1918) IP addresses are directly accessible from your on-premises network. You don't need to use a NAT device or VPN tunnel to reach internal IP addresses. Currently, you can only reach internal IP addresses over a dedicated connection. To reach Google external IP addresses, you must use a separate connection.

You can scale your connection to Google based on your needs. Connection capacity is delivered over one or more 10 Gbps Ethernet connections, with a maximum of eight connections (80 Gbps total per interconnect).

The cost of egress traffic from your VPC network to your on-premises network is reduced. A dedicated connection is generally the least expensive method if you have a high-volume of traffic to and from Google's network.

References: <https://cloud.google.com/interconnect/docs/details/dedicated>

NEW QUESTION 88

- (Exam Topic 5)

Your company operates nationally and plans to use GCP for multiple batch workloads, including some that are not time-critical. You also need to use GCP services that are HIPAA-certified and manage service costs.

How should you design to meet Google best practices?

- A. Provisioning preemptible VMs to reduce cos
- B. Discontinue use of all GCP services and APIs that are not HIPAA-compliant.
- C. Provisioning preemptible VMs to reduce cos
- D. Disable and then discontinue use of all GCP and APIs that are not HIPAA-compliant.
- E. Provision standard VMs in the same region to reduce cos

- F. Discontinue use of all GCP services and APIs that are not HIPAA-compliant.
- G. Provision standard VMs to the same region to reduce cos
- H. Disable and then discontinue use of all GCP services and APIs that are not HIPAA-compliant.

Answer: B

Explanation:

<https://cloud.google.com/security/compliance/hipaa/>

NEW QUESTION 89

- (Exam Topic 5)

You are deploying an application on App Engine that needs to integrate with an on-premises database. For security purposes, your on-premises database must not be accessible through the public Internet. What should you do?

- A. Deploy your application on App Engine standard environment and use App Engine firewall rules to limit access to the open on-premises database.
- B. Deploy your application on App Engine standard environment and use Cloud VPN to limit access to the onpremises database.
- C. Deploy your application on App Engine flexible environment and use App Engine firewall rules to limit access to the on-premises database.
- D. Deploy your application on App Engine flexible environment and use Cloud VPN to limit access to the on-premises database.

Answer: D

Explanation:

<https://cloud.google.com/appengine/docs/flexible/python/using-third-party-databases>

NEW QUESTION 94

- (Exam Topic 5)

You have created several preemptible Linux virtual machine instances using Google Compute Engine. You want to properly shut down your application before the virtual machines are preempted. What should you do?

- A. Create a shutdown script named k99.shutdown in the /etc/rc.6.d/ directory.
- B. Create a shutdown script registered as a xinetd service in Linux and configure a Stackdriver endpoint check to call the service.
- C. Create a shutdown script and use it as the value for a new metadata entry with the key shutdown-script in the Cloud Platform Console when you create the new virtual machine instance.
- D. Create a shutdown script, registered as a xinetd service in Linux, and use the gcloud compute instances add-metadata command to specify the service URL as the value for a new metadata entry with the key shutdown-script-url

Answer: C

NEW QUESTION 99

- (Exam Topic 5)

Your company pushes batches of sensitive transaction data from its application server VMs to Cloud Pub/Sub for processing and storage. What is the Google-recommended way for your application to authenticate to the required Google Cloud services?

- A. Ensure that VM service accounts are granted the appropriate Cloud Pub/Sub IAM roles.
- B. Ensure that VM service accounts do not have access to Cloud Pub/Sub, and use VM access scopes to grant the appropriate Cloud Pub/Sub IAM roles.
- C. Generate an OAuth2 access token for accessing Cloud Pub/Sub, encrypt it, and store it in Cloud Storage for access from each VM.
- D. Create a gateway to Cloud Pub/Sub using a Cloud Function, and grant the Cloud Function service account the appropriate Cloud Pub/Sub IAM roles.

Answer: A

NEW QUESTION 100

- (Exam Topic 5)

The development team has provided you with a Kubernetes Deployment file. You have no infrastructure yet and need to deploy the application. What should you do?

- A. Use gcloud to create a Kubernetes cluste
- B. Use Deployment Manager to create the deployment.
- C. Use gcloud to create a Kubernetes cluste
- D. Use kubect1 to create the deployment.
- E. Use kubect1 to create a Kubernetes cluste
- F. Use Deployment Manager to create the deployment.
- G. Use kubect1 to create a Kubernetes cluste
- H. Use kubect1 to create the deployment.

Answer: B

Explanation:

<https://cloud.google.com/kubernetes-engine/docs/how-to/creating-a-cluster>

NEW QUESTION 104

- (Exam Topic 5)

You want to optimize the performance of an accurate, real-time, weather-charting application. The data comes from 50,000 sensors sending 10 readings a second, in the format of a timestamp and sensor reading. Where should you store the data?

- A. Google BigQuery
- B. Google Cloud SQL
- C. Google Cloud Bigtable

D. Google Cloud Storage

Answer: C

Explanation:

It is time-series data, So Big Table. <https://cloud.google.com/bigtable/docs/schema-design-time-series>

Google Cloud Bigtable is a scalable, fully-managed NoSQL wide-column database that is suitable for both real-time access and analytics workloads.

Good for:

Low-latency read/write access

High-throughput analytics

Native time series support

Common workloads:

IoT, finance, adtech

Personalization, recommendations

Monitoring

Geospatial datasets

Graphs

References: <https://cloud.google.com/storage-options/>

NEW QUESTION 106

- (Exam Topic 5)

Your customer wants to do resilience testing of their authentication layer. This consists of a regional managed instance group serving a public REST API that reads from and writes to a Cloud SQL instance.

What should you do?

A. Engage with a security company to run web scrapes that look your users' authentication data on malicious websites and notify you if any is found.

B. Deploy intrusion detection software to your virtual machines to detect and log unauthorized access.

C. Schedule a disaster simulation exercise during which you can shut off all VMs in a zone to see how your application behaves.

D. Configure a read replica for your Cloud SQL instance in a different zone than the master, and then manually trigger a failover while monitoring KPIs for our REST API.

Answer: C

NEW QUESTION 111

- (Exam Topic 5)

You want to automate the creation of a managed instance group and a startup script to install the OS package dependencies. You want to minimize the startup time for VMs in the instance group.

What should you do?

A. Use Terraform to create the managed instance group and a startup script to install the OS package dependencies.

B. Create a custom VM image with all OS package dependencies

- C. Use Deployment Manager to create the managed instance group with the VM image.
- D. Use Puppet to create the managed instance group and install the OS package dependencies.
- E. Use Deployment Manager to create the managed instance group and Ansible to install the OS package dependencies.

Answer: B

Explanation:

"Custom images are more deterministic and start more quickly than instances with startup scripts. However, startup scripts are more flexible and let you update the apps and settings in your instances more easily." https://cloud.google.com/compute/docs/instance-templates/create-instance-templates#using_custom_or_public_i

NEW QUESTION 115

- (Exam Topic 5)

You are deploying a PHP App Engine Standard service with SQL as the backend. You want to minimize the number of queries to the database. What should you do?

- A. Set the memcache service level to dedicate
- B. Create a key from the hash of the query, and return database values from memcache before issuing a query to Cloud SQL.
- C. Set the memcache service level to dedicate
- D. Create a cron task that runs every minute to populate the cache with keys containing query results.
- E. Set the memcache service level to share
- F. Create a cron task that runs every minute to save all expected queries to a key called "cached-queries".
- G. Set the memcache service level to share
- H. Create a key called "cached-queries", and return database values from the key before using a query to Cloud SQL.

Answer: A

Explanation:

<https://cloud.google.com/appengine/docs/standard/php/memcache/using>

NEW QUESTION 120

- (Exam Topic 5)

During a high traffic portion of the day, one of your relational databases crashes, but the replica is never promoted to a master. You want to avoid this in the future. What should you do?

- A. Use a different database.
- B. Choose larger instances for your database.
- C. Create snapshots of your database more regularly.
- D. Implement routinely scheduled failovers of your databases.

Answer: D

Explanation:

<https://cloud.google.com/solutions/dr-scenarios-planning-guide>

NEW QUESTION 121

- (Exam Topic 5)

You are designing an application for use only during business hours. For the minimum viable product release, you'd like to use a managed product that automatically "scales to zero" so you don't incur costs when there is no activity. Which primary compute resource should you choose?

- A. Cloud Functions
- B. Compute Engine
- C. Kubernetes Engine
- D. AppEngine flexible environment

Answer: A

Explanation:

<https://cloud.google.com/serverless-options>

NEW QUESTION 125

- (Exam Topic 5)

Your development team has installed a new Linux kernel module on the batch servers in Google Compute Engine (GCE) virtual machines (VMs) to speed up the nightly batch process. Two days after the installation, 50% of web application deployed in the same nightly batch run. You want to collect details on the failure to pass back to the development team. Which three actions should you take? Choose 3 answers

- A. Use Stackdriver Logging to search for the module log entries.
- B. Read the debug GCE Activity log using the API or Cloud Console.
- C. Use gcloud or Cloud Console to connect to the serial console and observe the logs.
- D. Identify whether a live migration event of the failed server occurred, using in the activity log.
- E. Adjust the Google Stackdriver timeline to match the failure time, and observe the batch server metrics.
- F. Export a debug VM into an image, and run the image on a local server where kernel log messages will be displayed on the native screen.

Answer: ACE

Explanation:

<https://www.flexera.com/blog/cloud/2013/12/google-compute-engine-live-migration-passes-the-test/> "With live migration, the virtual machines are moved without any downtime or noticeable service

degradation"

NEW QUESTION 126

- (Exam Topic 5)

Your company is building a new architecture to support its data-centric business focus. You are responsible for setting up the network. Your company's mobile and web-facing applications will be deployed on-premises, and all data analysis will be conducted in GCP. The plan is to process and load 7 years of archived .csv files totaling 900 TB of data and then continue loading 10 TB of data daily. You currently have an existing 100-MB internet connection.

What actions will meet your company's needs?

- A. Compress and upload both archived files and files uploaded daily using the `gsutil -m` option.
- B. Lease a Transfer Appliance, upload archived files to it, and send it, and send it to Google to transfer archived data to Cloud Storage
- C. Establish a connection with Google using a Dedicated Interconnect or Direct Peering connection and use it to upload files daily.
- D. Lease a Transfer Appliance, upload archived files to it, and send it, and send it to Google to transfer archived data to Cloud Storage
- E. Establish one Cloud VPN Tunnel to VPC networks over the public internet, and compress and upload files daily using the `gsutil -m` option.
- F. Lease a Transfer Appliance, upload archived files to it, and send it to Google to transfer archived data to Cloud Storage
- G. Establish a Cloud VPN Tunnel to VPC networks over the public internet, and compress and upload files daily.

Answer: B

Explanation:

<https://cloud.google.com/interconnect/docs/how-to/direct-peering>

NEW QUESTION 128

- (Exam Topic 5)

You are migrating your on-premises solution to Google Cloud in several phases. You will use Cloud VPN to maintain a connection between your on-premises systems and Google Cloud until the migration is completed.

You want to make sure all your on-premises systems remain reachable during this period. How should you organize your networking in Google Cloud?

- A. Use the same IP range on Google Cloud as you use on-premises
- B. Use the same IP range on Google Cloud as you use on-premises for your primary IP range and use a secondary range that does not overlap with the range you use on-premises
- C. Use an IP range on Google Cloud that does not overlap with the range you use on-premises
- D. Use an IP range on Google Cloud that does not overlap with the range you use on-premises for your primary IP range and use a secondary range with the same IP range as you use on-premises

Answer: C

NEW QUESTION 133

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your Professional-Cloud-Architect Exam with Our Prep Materials Via below:

<https://www.certleader.com/Professional-Cloud-Architect-dumps.html>