

Importing Libraries

```
In [1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import warnings
warnings.filterwarnings('ignore')
```


Importing Data

```
In [2]: df=pd.read_csv(r"C:\Users\Shubham\Desktop\Data Science\Data Science Class\Stats a
df.head()
```

Out[2]:

	meanfreq	sd	median	Q25	Q75	IQR	skew	kurt	sp.ent	
0	0.059781	0.064241	0.032027	0.015071	0.090193	0.075122	12.863462	274.402906	0.893369	0
1	0.066009	0.067310	0.040229	0.019414	0.092666	0.073252	22.423285	634.613855	0.892193	0
2	0.077316	0.083829	0.036718	0.008701	0.131908	0.123207	30.757155	1024.927705	0.846389	0
3	0.151228	0.072111	0.158011	0.096582	0.207955	0.111374	1.232831	4.177296	0.963322	0
4	0.135120	0.079146	0.124656	0.078720	0.206045	0.127325	1.101174	4.333713	0.971955	0

5 rows × 21 columns



Describing Data

```
In [3]: df.columns
```

```
Out[3]: Index(['meanfreq', 'sd', 'median', 'Q25', 'Q75', 'IQR', 'skew', 'kurt',
'sp.ent', 'sfm', 'mode', 'centroid', 'meanfun', 'minfun', 'maxfun',
'meandom', 'mindom', 'maxdom', 'dfrange', 'modindx', 'label'],
dtype='object')
```

In [4]: df.info()

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 3168 entries, 0 to 3167
Data columns (total 21 columns):
#   Column      Non-Null Count  Dtype
---  -
0   meanfreq    3168 non-null   float64
1   sd          3168 non-null   float64
2   median      3168 non-null   float64
3   Q25         3168 non-null   float64
4   Q75         3168 non-null   float64
5   IQR         3168 non-null   float64
6   skew        3168 non-null   float64
7   kurt        3168 non-null   float64
8   sp.ent      3168 non-null   float64
9   sfm         3168 non-null   float64
10  mode        3168 non-null   float64
11  centroid    3168 non-null   float64
12  meanfun     3168 non-null   float64
13  minfun      3168 non-null   float64
14  maxfun      3168 non-null   float64
15  meandom     3168 non-null   float64
16  mindom      3168 non-null   float64
17  maxdom      3168 non-null   float64
18  dfrange     3168 non-null   float64
19  modindx     3168 non-null   float64
20  label       3168 non-null   object
dtypes: float64(20), object(1)
memory usage: 519.9+ KB
```

Checking Null Values


```
In [5]: df.isna().sum()
```

```
Out[5]: meanfreq    0
sd              0
median         0
Q25            0
Q75            0
IQR            0
skew           0
kurt           0
sp.ent         0
sfm            0
mode           0
centroid       0
meanfun        0
minfun         0
maxfun         0
meandom        0
mindom         0
maxdom         0
dfrange        0
modindx        0
label          0
dtype: int64
```

Checking Outliers

```
In [6]: def boxplots(col):
sns.boxplot(df[col])
plt.show()

for i in list(df.select_dtypes(exclude=['object']).columns)[0:]:
    boxplots(i)
```



As a natural part of the population we won't remove outliers

Encoding Concept

```
In [7]: df.label=df.label.astype('category')
df.label=df.label.cat.codes
```

```
In [8]: x=df.drop(["label"],axis=1)
y=df['label']
```

```
In [9]: x.head()
```

```
Out[9]:
```

	meanfreq	sd	median	Q25	Q75	IQR	skew	kurt	sp.ent
0	0.059781	0.064241	0.032027	0.015071	0.090193	0.075122	12.863462	274.402906	0.893369
1	0.066009	0.067310	0.040229	0.019414	0.092666	0.073252	22.423285	634.613855	0.892193
2	0.077316	0.083829	0.036718	0.008701	0.131908	0.123207	30.757155	1024.927705	0.846389
3	0.151228	0.072111	0.158011	0.096582	0.207955	0.111374	1.232831	4.177296	0.963322
4	0.135120	0.079146	0.124656	0.078720	0.206045	0.127325	1.101174	4.333713	0.971955

```
In [10]: y.head()
```

```
Out[10]: 0    1
1    1
2    1
3    1
4    1
Name: label, dtype: int8
```


Checking if the data is balanced

```
In [11]: y.value_counts()
```

```
Out[11]: 1    1584
0    1584
Name: label, dtype: int64
```

Checking Colinearity

```
In [12]: plt.figure(figsize=(20,15))
sns.heatmap(df.corr(),annot=True, cmap='rainbow')
plt.show()
```



split the training data into train and test

```
In [13]: from sklearn.model_selection import train_test_split
x_train, x_test, y_train, y_test = train_test_split(x,y, test_size=0.2, random_st
```

Support Vector Machine Model

```
In [14]: from sklearn.svm import SVC
```

kernel - linear

In [16]:

```
svm_linear=SVC(kernel='linear',probability = True)
svm_linear.fit(x_train,y_train)
y_pred_train_linear=svm_linear.predict(x_train)
y_pred_test_linear=svm_linear.predict(x_test)
```

kernel - sigmoid

In [17]:

```
svm_sigmoid=SVC(kernel='sigmoid')
svm_sigmoid.fit(x_train,y_train)
y_pred_train_sigmoid=svm_sigmoid.predict(x_train)
y_pred_test_sigmoid=svm_sigmoid.predict(x_test)
```

kernel - poly

In [18]:

```
svm_poly=SVC(kernel='poly')
svm_poly.fit(x_train,y_train)
y_pred_train_poly=svm_poly.predict(x_train)
y_pred_test_poly=svm_poly.predict(x_test)
```

kernel - rbf

In [19]:

```
svm_rbf=SVC(kernel='rbf')
svm_rbf.fit(x_train,y_train)
y_pred_train_rbf=svm_rbf.predict(x_train)
y_pred_test_rbf=svm_rbf.predict(x_test)
```

Evaluating the Data

In [20]:

```
from sklearn.metrics import confusion_matrix, classification_report, accuracy_score
```

```
In [21]: print("Training Accuracy - Linear :", accuracy_score(y_train, y_pred_train_linear))
print("*****"*5)
print("Test Accuracy - Linear :", accuracy_score(y_test, y_pred_test_linear))
print("*****"*5)
print("Training Accuracy - sigmoid :", accuracy_score(y_train, y_pred_train_sigmoid))
print("*****"*5)
print("Test Accuracy - sigmoid :", accuracy_score(y_test, y_pred_test_sigmoid))
print("*****"*5)
print("Training Accuracy - poly :", accuracy_score(y_train, y_pred_train_poly))
print("*****"*5)
print("Test Accuracy - poly :", accuracy_score(y_test, y_pred_test_poly))
print("*****"*5)
print("Training Accuracy - rbf :", accuracy_score(y_train, y_pred_train_rbf))
print("*****"*5)
print("Test Accuracy - rbf :", accuracy_score(y_test, y_pred_test_rbf))
```

Training Accuracy - Linear : 0.9222573007103394

Test Accuracy - Linear : 0.9148264984227129

Training Accuracy - sigmoid : 0.3701657458563536

Test Accuracy - sigmoid : 0.3722397476340694

Training Accuracy - poly : 0.5197316495659037

Test Accuracy - poly : 0.5031545741324921

Training Accuracy - rbf : 0.6764009471191792

Test Accuracy - rbf : 0.6829652996845426

Since Linear SVM gives higher accuracy we will continue with that

```
In [22]: print("Training Accuracy - Linear :", classification_report(y_train, y_pred_train))
print("*****"*5)
print("Test Accuracy - Linear :", classification_report(y_test, y_pred_test_linear))
```

Training Accuracy - Linear :		precision	recall	f1-score	support
------------------------------	--	-----------	--------	----------	---------

0	0.98	0.86	0.92	1273
1	0.88	0.98	0.93	1261

accuracy			0.92	2534
macro avg	0.93	0.92	0.92	2534
weighted avg	0.93	0.92	0.92	2534

Test Accuracy - Linear :		precision	recall	f1-score	support
--------------------------	--	-----------	--------	----------	---------

0	0.97	0.85	0.91	311
1	0.87	0.98	0.92	323

accuracy			0.91	634
macro avg	0.92	0.91	0.91	634
weighted avg	0.92	0.91	0.91	634

cross validation method

```
In [23]: from sklearn.model_selection import cross_val_score
train_accuracy = cross_val_score(svm_linear, x_train, y_train, cv=10)
test_accuracy = cross_val_score(svm_linear, x_test, y_test, cv=10)
print("Training accuracy :", train_accuracy)
print("*****"*5)
print("Training Mean Accuracy :", train_accuracy.mean())
print("*****"*5)
print("Training Max Accuracy :", train_accuracy.max())

print("Test accuracy :", test_accuracy)
print("*****"*5)
print("Test Mean Accuracy :", test_accuracy.mean())
print("*****"*5)
print("Test Max Accuracy :", test_accuracy.max())
```

Training accuracy : [0.94488189 0.9015748 0.92519685 0.9015748 0.92490119 0.90513834 0.8972332 0.9486166 0.93280632 0.92094862]

 Training Mean Accuracy : 0.9202872615231398

 Training Max Accuracy : 0.9486166007905138
 Test accuracy : [0.890625 0.890625 0.9375 0.828125 0.87301587 0.80952381 0.92063492 0.87301587 0.88888889 0.87301587]

 Test Mean Accuracy : 0.8784970238095239

 Test Max Accuracy : 0.9375

Grid Search CV(Hyperparameter Tuning)

```
In [24]: from sklearn.model_selection import GridSearchCV
```

```
In [25]: SVC()
```

```
Out[25]: SVC()
```

```
In [26]: param_grid = {'C':[0,1,2,10,100], 'gamma':[1,0.1,0.001,0.01]}
grid = GridSearchCV(SVC(), param_grid, refit=True)
grid.fit(x_train, y_train)
grid_predict = grid.predict(x_test)
print(accuracy_score(y_test, grid_predict))
```

0.9211356466876972

In []:

Building Voting Class Model- It combines various models and produce higer accuarcy

In []:

LogisticRegression

```
In [27]: from sklearn.linear_model import LogisticRegression
logit = LogisticRegression()
logit.fit(x_train, y_train)
```

Out[27]: LogisticRegression()

```
In [28]: y_pred_logit_train = logit.predict(x_train)
y_pred_logit_test = logit.predict(x_test)
```

```
In [29]: print("Training Accuracy - Logistic :", accuracy_score(y_train, y_pred_logit_train))
print("*****"*5)
print("Test Accuracy - Logistic :", accuracy_score(y_test, y_pred_logit_test))
```

```
Training Accuracy - Logistic : 0.9048934490923441
*****
Test Accuracy - Logistic : 0.8943217665615142
```

DecisionTreeClassifier

```
In [30]: from sklearn.tree import DecisionTreeClassifier
dtree = DecisionTreeClassifier()
dtree.fit(x_train, y_train)
```

Out[30]: DecisionTreeClassifier()

```
In [31]: y_pred_dtree_train = dtree.predict(x_train)
y_pred_dtree_test = dtree.predict(x_test)
```

```
In [32]: print("Training Accuracy - Dtree :", accuracy_score(y_train, y_pred_dtree_train))
print("*****"*5)
print("Test Accuracy - dtree :", accuracy_score(y_test, y_pred_dtree_test))
```

```
Training Accuracy - Dtree : 1.0
*****
Test Accuracy - dtree : 0.9747634069400631
```

KNN

```
In [33]: from sklearn.neighbors import KNeighborsClassifier
knn = KNeighborsClassifier()
knn.fit(x_train, y_train)
```

Out[33]: KNeighborsClassifier()

```
In [34]: y_pred_knn_train = knn.predict(x_train)
y_pred_knn_test = knn.predict(x_test)
```

```
In [35]: print("Training Accuracy - knn :", accuracy_score(y_train, y_pred_knn_train))
print("*****" * 5)
print("Test Accuracy - knn :", accuracy_score(y_test, y_pred_knn_test))
```

```
Training Accuracy - knn : 0.8113654301499605
*****
Test Accuracy - knn : 0.722397476340694
```

Using Voting Method

```
In [36]: estimators = [('SVM_Linear', svm_linear), ('SVM_Sigmoid', svm_sigmoid), ('SVM_Poly',
('SVM_RBF' , svm_rbf), ('Logistic', logit), ('Dtree', dtree), ('KNN', knn)]
```

```
In [37]: from sklearn.ensemble import VotingClassifier
```

Hard Voting

```
In [38]: voting_hard = VotingClassifier(estimators = estimators, voting='hard')
v_train_accuracy = cross_val_score(voting_hard, x_train, y_train, cv=10, scoring='accuracy')
v_test_accuracy = cross_val_score(voting_hard, x_test, y_test, cv=10, scoring='accuracy')
print(np.round(np.mean(v_train_accuracy),2))
print()
print(np.round(np.mean(v_test_accuracy),2))
```

0.9

0.79

Since there a big diiference in the accuracy in train and test data we have overfitting problem

So we will only take linear SVM and try

```
In [39]: estimators1 = [('SVM_Linear', svm_linear), ('Logistic', logit), ('Dtree', dtree), ('KNN', KNeighborsClassifier())]
```

```
In [40]: voting_hard1 = VotingClassifier(estimators = estimators1, voting='hard')
voting_hard1.fit(x_train, y_train)
```

```
Out[40]: VotingClassifier(estimators=[('SVM_Linear',
                                       SVC(kernel='linear', probability=True)),
                                      ('Logistic', LogisticRegression()),
                                      ('Dtree', DecisionTreeClassifier()),
                                      ('KNN', KNeighborsClassifier())])
```

```
In [41]: y_pred_train_voting = voting_hard1.predict(x_train)
y_pred_test_voting = voting_hard1.predict(x_test)
```

```
In [42]: print("Training Accuracy - voting_hard :", accuracy_score(y_train, y_pred_train_voting))
print("*****"*5)
print("Test Accuracy - voting_hard :", accuracy_score(y_test, y_pred_test_voting))
```

```
Training Accuracy - voting_hard : 0.9593528018942383
*****
Test Accuracy - voting_hard : 0.9258675078864353
```

```
In [ ]:
```

Soft Voting

```
In [44]: voting_soft = VotingClassifier(estimators = estimators1, voting='soft')
v_train_accuracy1 = cross_val_score(voting_soft, x_train, y_train, cv=10, scoring='accuracy')
v_test_accuracy1 = cross_val_score(voting_soft, x_test, y_test, cv=10, scoring='accuracy')
print("Training Accuracy - voting_soft :", np.round(np.mean(v_train_accuracy1),2))
print("*****"*5)
print("Test Accuracy - voting_soft :", np.round(np.mean(v_test_accuracy1),2))
```

```
Training Accuracy - voting_soft : 0.94
*****
Test Accuracy - voting_soft : 0.91
```

```
In [ ]:
```

