Pump P-101 Datasheet (fictional)

Service: cooling water transfer from tank T-201 to header H-7.
Design pressure 16 bar g at 80 °C; test pressure 24 bar g.
Rated flow 125 m3/h, differential head 42 m, NPSH available 6.5 m.
Casing material ASTM A216 WCB; impeller 316 stainless steel.
Shaft seal: single mechanical seal, plan 11, tolerance ±0.05 mm.
Motor 22 kW, 2950 rpm, IE3, 400 V 50 Hz, IP55 enclosure.
Nozzles: suction DN150 PN16, discharge DN100 PN16, drain 1/2 in.
Notes: spare impeller supplied; coupling guard per EN 953.

Pump P-101 Datasheet (fictional)

Service: cooling water transfer from tank T-201 to header H-7.

Design pressure 16 bar g at 80 °C; test pressure 24 bar g.

Rated flow 125 m3/h, differential head 42 m, NPSH available 6.5 m.

Casing material ASTM A216 WCB; impeller 316 stainless steel.

Shaft seal: single mechanical seal, plan 11, tolerance ±0.05 mm.

Motor 22 kW, 2950 rpm, IE3, 400 V 50 Hz, IP55 enclosure.

Nozzles: suction DN150 PN16, discharge DN100 PN16, drain 1/2 in.

Notes: spare impeller supplied; coupling guard per EN 953.

Pump P-101 Datasheet (fictional)

Service: cooling water transfer from tank T-201 to header H-7.
Design pressure 16 bar g at 80 °C; test pressure 24 bar g.
Rated flow 125 m3/h, differential head 42 m, NPSH available 6.5 m.
Casing material ASTM A216 WCB; impeller 316 stainless steel.
Shaft seal: single mechanical seal, plan 11, tolerance ±0.05 mm.
Motor 22 kW, 2950 rpm, IE3, 400 V 50 Hz, IP55 enclosure.
Nozzles: suction DN150 PN16, discharge DN100 PN16, drain 1/2 in.
Notes: spare impeller supplied; coupling guard per EN 953.

This page already has a text layer.