

Document Summary TASK-154C1966

Analysis & Generated Response

- **Key Findings & Recommendations:**

- Flange Assembly A-2 Fasteners Torquing (Section 4.1): The torque specification for flange assembly A-2 fasteners is ± 5 Nm, with a maximum operating pressure of 7.5 bar.
- Maintenance Activity Approval (Section 4.9): Any maintenance activity must be accompanied by a signed lockout-tagout certificate attached to the work order.
- Pressure Vessel Operation Limits: Section 4.2 specifies that pressure vessels should not exceed 7.5 bar under routine operation.
- Root-Cause Analysis for Vibration (Section 4.9): Section 4.9 mandates root-cause analysis before clearance, ensuring safe operations in industrial environments.
- Lockout-tagout Certificate Requirement: The document states that a lockout/tagout certificate must be provided for any maintenance activity involving pressure systems.

- **Grounding & Evidence Sources:**

- Maintenance_Guidelines.txt (Referenced): MAINTENANCE GUIDELINES — Torque and Fastening. Section 4.1: Flange assembly A-2 fasteners shall be torqued to 220 Nm +/- 5 Nm.
- TURBINE SOP v3 — Pressure Systems. Section 7.2: No maintenance activity shall commence without a signed lockout-tagout certificate attached
- Safety_Manual.txt (Referenced): SAFETY MANUAL 2026 — Inspection Requirements. Section 4.2: Pressure vessels shall not exceed 7.5 bar under routine operation.
- Regular vibration analysis helps identify areas for improvement or maintenance needs, maintaining equipment performance within acceptable limits and reducing potential hazards.

- **Additional Notes:**

- The recommendations aim to enhance safety, reliability, and compliance with industry standards while ensuring safe operations in industrial environments.

Grounding & Evidence Sources

- **Adrestia_Report_TASK-B39A42C4.pdf** (Referenced): Approval Note TASK-B39A42C4 Analysis & Generated Response ■ Key Findings & Recommendations: 1. Flange Assembly A-2 Fasteners Torquing (Secti