

Lithium Battery

ST-Li-24105



Features Of LiFePO4 Battery

- Long cycle life
- High integration, small size, high energy density
- Intelligent management of product usage status with high security
- Environmental protection
- Capable of 1C fast charging

Application scenarios

- Forklift
- Lead-acid battery to lithium battery vehicles
- Industrial control products
- Rescue vehicles such as scissor forklifts

Specification

Nom inal Voltage	25.6V
Working Voltage	20-29.2V
Nom inal Capacity	105Ah
Energy	2688Wh
Self Dis charge	≤3% Per Month
IP Grade	IP65
Pos itive m aterial	Lithium iron phosphate
Cell type	Prismatic
Com bination m ethod	105Ah, 1P8S
Weight	ABOUT 20.0KG
Dim ension LxWxH	L306W206H240mm
Fixed size	NO
Term inal Type	M8 Term inal Bolts, 12±2Nm
Shell type	Powder Coated Steel
Handle	YES
Storage Temp .s hort term	-20-45°C
Storage Temp .p. long term	-20-35°C
Cycle Life	5000 cycles (80%DOD)
Heating function	No
Cooling type	No
Insulation	20MΩ/1000VDC, @25±5°C, RH50%



Charging

Recom . Charging Current	50A
Upper lim it voltage	29.2V
Charging Temp . Range	0~55°C

DisCharging

Max Continuous Discharge	100A
Max Dis charge current	210A@1S
Lower lim it voltage	20.0V
BMS Voltage Recovery	22.4V
Dis charge Temp . Range	-20-55°C

Function (optional)

(CAN/RS485), Bluetooth, 4G, Screen, Charger

Physical Dimension-mm

