

Lithium Battery

ST-Li-2450



Features Of LiFePO4 Battery

- Long cycle life
- High integration, small size, high energy density
- Intelligent management of product usage status with high security
- Environmental protection
- Capable of 1C fast charging

Application scenarios

- Forklift
- Lead-acid battery to lithium battery vehicles
- Industrial control products
- Rescue vehicles such as scissor forklifts

Specification

Nominal Voltage	25.6V
Working Voltage	20-29.2V
Nominal Capacity	50Ah
Energy	1280Wh
Self Dis charge	≤2% Per Month
IP Grade	IP65
Positive material	Lithium iron phosphate
Cell type	Prismatic
Combination method	50Ah, 1P8S
Weight	ABOUT 23.0KG
Dimension LxWxH	L240W310H190mm
Fixed size	NO
Terminal Type	M8 Terminal Bolts, 12±2Nm
Shell type	Powder Coated Steel
Handle	YES
Storage Temp.s hortterm	-20-45°C
Storage Temp.p.long term	-20-35°C
Cycle Life	5000 cycles (80%DOD)
Heating function	No
Cooling type	No
Insulation	20MΩ/1000VDC, @25±5°C, RH50%
Bluetooth	YES



Charging

Recom. Charging Current	25A
Upper limit voltage	28.8V
Charging Temp. Range	0~45°C

DisCharging

Max Continuous Discharge	50A
Max Dis charge current	100A@10S
Lower limit voltage	20.0V
BMS Voltage Recovery	22.4V
Dis charge Temp. Range	-20-60°C

Function (optional)

(CAN/RS485), Bluetooth, Charger

Physical Dimension-mm

