

Lithium Battery

ST-Li-2465



Features Of LiFePO4 Battery

- Long cycle life
- High integration, small size, high energy density
- Intelligent management of product usage status with high security
- Environmental protection

Application scenarios

- sanitation vehicle
- Lead-acid battery to lithium battery vehicles
- Industrial control products
- Rescue vehicles such as scissor forklifts

Specification

Nom inal Voltage	25.6V
Working Voltage	20-28.8V
Nom inal Capacity	65Ah
Energy	1664Wh
Self Dis charge	≤3% Per Month
IP Grade	IP65
Pos itive m aterial	Lithium iron phosphate
Cell type	Square LFP 65AH
Com bination m ethod	65Ah, 1P8S
Weight	ABOUT 20KG
Dim ension LxWxH	L320W300H200mm
Fixed size	NO
Term inal Type	M8 Term inal Bolts, 12±2Nm
Shell type	Powder Coated Steel
Handle	YES
Storage Temp .s hortterm	-20-45℃
Storage Temp .long term	-20-35℃
Cycle Life	5000 cycles(80%DOD)
Heating function	No
Cooling type	No
Insulation	20MΩ/1000VDC, @25±5℃, RH50%



Charging

Recom . Charging Current	30A
Upper lim it voltage	28.8V
Charging Temp .Range	0~45℃

DisCharging

Max Continuous Discharge	65A
Max Dis charge current	130A@10S
Lower lim it voltage	20.0V
BMS Voltage Recovery	22.4V
Dis charge Temp .Range	-20-60℃

Function (optional)

(CAN), Bluetooth, Screen, Charger

Physical Dimension-mm

