

Lithium Battery

ST-Li-36200



Features Of LiFePO4 Battery

- Long cycle life
- High integration, small size, high energy density
- Intelligent management of product usage status with high security
- Environmental protection

Application scenarios

- sanitation vehicle
- Lead-acid battery to lithium battery vehicles
- Industrial control products
- Rescue vehicles such as scissor forklifts



Specification

Nom inal Voltage	35.2V
Working Voltage	27.5-40V
Nom inal Capacity	200Ah
Energy	7.04KWh
Self Dis charge	≤3% Per Month
IP Grade	IP65
Pos itive m aterial	Lithium iron phosphate
Cell type	Prismatic
Com bination m ethod	100Ah, 2P8S
Weight	ABOUT 55KG
Dim ension L×W×H	L540W360H250mm
Fixed size	NO
Term inal Type	M8 Term inal Bolts ,12±2Nm
Shell type	Powder Coated Steel
Handle	YES
Storage Tem p.s hortterm	-20-45°C
Storage Tem p.long term	-20-35°C
Cycle Life	5000 cycles(80%DOD)
Heating function	No
Cooling type	No
Insulation	20MΩ/1000VDC, @25±5°C,RH50%

Charging

Recom .Charging Current	30A
Upper lim it voltage	40V
Charging Tem p. Range	0~55°C

DisCharging

Max Continuous Discharge	200A
Max Dis charge current	250A@2S
Lower lim it voltage	27.5V
BMS Voltage Recovery	30.25V
Dis charge Tem p. Range	-20-60°C

Function (optional)

CAN, Bluetooth, Screen

Physical Dimension-mm

