

Lithium Battery -Forklift Series

ST-Li-SP72300 (72V300Ah)



Features Of LiFePO4 Battery

- Long cycle life
- High integration, small size, high energy density
- Intelligent management of product usage status with high security
- Environmental protection

Application scenarios

- Sightseeing vehicle



Specification

Nominal Voltage	76.8V
Working Voltage	60-87.6V
Nominal Capacity	300Ah
Energy	23.04KWh
Self Discharge	≤2% Per Month
IP Grade	IP65
Positive material	Lithium ironphosphate
Cell type	Prismatic
Combination method	300Ah, 24S1P
Weight	180±2KG
Dimension LxWxH	L860W260H280mm
Fixed size	NO
Terminal Type	M8 Terminal Bolts,12±2Nm
Shell type	Powder Coated Steel
Handle	YES
Storage Temp. short term	0-60°C
Storage Temp. long term	0-60°C
Cycle Life	3000 cycles
Heating function	No
Cooling type	No

Charging

Recom. Charging Current	100A
Max charging current	150A
Upper limit voltage	87.6V
Charging Temp. Range	0~55°C

DisCharging

Max Continuous Discharge	250A
Max Discharge current	400A@5S
Lower limit voltage	60.0V
BMS Voltage Recovery	66V
Discharge Temp. Range	-20-65°C

Function (optional)

(CAN/RS485), Bluetooth, 4G, Screen, Charger

Physical Dimension-mm

