

Cross-Domain Preservation of State Partitions: An Information-Theoretic Bound via the Situs Conditional Mutual Information

Anonymous Author(s)

June 29, 2026

Abstract

We study the robustness of state-space partitions under distribution shift. Starting from the Situs conditional mutual information $I(Y; P \mid S)$, which quantifies how much a partition P of the state space $\mathcal{X}$ reveals about an output variable Y conditional on auxiliary state S , we derive a tight upper bound on the information loss incurred when transferring the partition from a source domain $\mathcal{D}_s$ to a target domain $\mathcal{D}_t$:

$$\Delta I \leq \sum_{k=1}^K \left[L_k \cdot \text{diam}(\Omega_k) \cdot W_1(P_s, P_t) + \delta_k + \varepsilon_k \right],$$

where L_k is the Lipschitz constant of the per-cell output-conditional density, $\text{diam}(\Omega_k)$ is the diameter of the k -th partition cell in the state space, $W_1(P_s, P_t)$ is the 1-Wasserstein distance between source and target marginals, δ_k is the discretization error from finite partition granularity, and ε_k is the irreducible approximation error. The bound is asymptotically tight: we construct a sequence of domain shifts for which the inequality holds with equality in the limit of fine partitions. The theorem provides a principled robustness guarantee for state-partition-based representations under covariate shift, with direct applications to domain adaptation, transfer learning, and cross-domain causal inference.

1 Introduction

State-space partitioning is a fundamental operation in representation learning, reinforcement learning, and causal inference. By discretizing a continuous state space into a finite set of cells $\mathcal{P} = \{P_1, \dots, P_K\}$, one obtains a compressed representation that preserves the information most relevant to predicting or controlling an output variable Y . The quality of a partition is measured by how much information it retains: given a partition P (as a random variable taking values in $\{1, \dots, K\}$ indicating which cell contains the state X), the conditional mutual information $I(Y; P \mid S)$ quantifies the predictive value of the partition for Y beyond what is already captured by auxiliary context S .

A partition optimized on a source domain $\mathcal{D}_s$ will, in general, *degrade* when deployed on a target domain $\mathcal{D}_t$ where the distribution over states differs. This is the **cross-domain partition preservation problem**: given a partition P that is ε -optimal on $\mathcal{D}_s$, how much information is lost on $\mathcal{D}_t$? We answer this question with a non-asymptotic upper bound that depends on geometric properties of the partition, the smoothness of the data-generating process, and the statistical distance between domains.

Motivation from SCX. The Situs operator, introduced in the SCX axiomatic framework (?), formalizes optimal state partitioning as the maximizer of $I(Y; P \mid S)$ over a class of admissible partitions. Situs provides existence and characterization results for optimal partitions under a fixed data distribution. The present work extends Situs to the cross-domain setting, providing the perturbation theory: how does the optimal partition — and the information it preserves — change when the underlying distribution changes? Our bound is the Situs sensitivity theorem.

Contributions.

- (1) We formalize the cross-domain partition preservation problem and define the information loss $\Delta I = I_s(Y; P \mid S) - I_t(Y; P \mid S)$ (Section ??).
- (2) We prove the main upper bound $\Delta I \leq \sum_k [L_k \cdot \text{diam}(\Omega_k) \cdot W_1(P_s, P_t) + \delta_k + \varepsilon_k]$ (Theorem ??).
- (3) We provide a matching lower-bound construction, establishing asymptotic tightness (Theorem ??).
- (4) We decompose the bound into interpretable components — geometric, statistical, and irreducible — and discuss implications for each (Section ??).

- (5) We discuss applications to domain adaptation and cross-domain generalization (Section ??).

2 Preliminaries

2.1 Notation and Setup

Let $(\mathcal{X}, d_{\mathcal{X}})$ be a complete separable metric space (the state space) and $\mathcal{Y} \subseteq \mathbb{R}$ the output space. Let S be an auxiliary random variable taking values in a measurable space $\mathcal{S}$, representing contextual information (e.g., domain identity, environment conditions). The joint distribution over $(\mathcal{X} \times \mathcal{Y} \times \mathcal{S})$ on domain $d \in \{s, t\}$ is $P_{XYS}^{(d)}$, with marginal $P_X^{(d)}$ on $\mathcal{X}$.

Definition 2.1 (State Partition). *A state partition of size K is a measurable mapping $\pi : \mathcal{X} \rightarrow \{1, \dots, K\}$ with cells $\Omega_k = \pi^{-1}(k) = \{x \in \mathcal{X} : \pi(x) = k\}$ for $k = 1, \dots, K$. The cells are disjoint ($\Omega_k \cap \Omega_{k'} = \emptyset$ for $k \neq k'$) and cover $\mathcal{X}$ ($\bigcup_k \Omega_k = \mathcal{X}$). We identify the partition with the random variable $P = \pi(X) \in \{1, \dots, K\}$.*

Definition 2.2 (Situs Conditional Mutual Information). *For a partition π and domain d , the Situs conditional mutual information is*

$$I^{(d)}(Y; P \mid S) = \mathbb{E}_{P_{XYS}^{(d)}} \left[\log \frac{p^{(d)}(Y \mid P, S)}{p^{(d)}(Y \mid S)} \right], \quad (1)$$

where $p^{(d)}(Y \mid P, S)$ is the conditional density of Y given the partition cell P and context S , and $p^{(d)}(Y \mid S)$ is the conditional density given S alone.

Equivalently, $I^{(d)}(Y; P \mid S) = H^{(d)}(Y \mid S) - H^{(d)}(Y \mid P, S)$, the reduction in conditional entropy achieved by knowing the partition cell.

2.2 Domain Discrepancy Measures

Definition 2.3 (1-Wasserstein Distance). *For two probability measures μ, ν on $(\mathcal{X}, d_{\mathcal{X}})$ with finite first moments, the 1-Wasserstein distance is*

$$W_1(\mu, \nu) = \inf_{\gamma \in \Gamma(\mu, \nu)} \int_{\mathcal{X} \times \mathcal{X}} d_{\mathcal{X}}(x, x') \, d\gamma(x, x'), \quad (2)$$

where $\Gamma(\mu, \nu)$ is the set of all couplings of μ and ν .

Definition 2.4 (Cell Diameter). *The diameter of cell Ω_k is $\text{diam}(\Omega_k) = \sup_{x, x' \in \Omega_k} d_{\mathcal{X}}(x, x')$.*

Definition 2.5 (Lipschitz Constant of Cell-Conditional Density). *For cell k , the function $f_k(x, s) = \mathbb{E}[Y \mid X = x, S = s, \pi(X) = k]$ is the expected output given the exact state and context within that cell. Its Lipschitz constant is*

$$L_k = \sup_{\substack{x, x' \in \Omega_k \\ s \in \mathcal{S} \\ x \neq x'}} \frac{|f_k(x, s) - f_k(x', s)|}{d_{\mathcal{X}}(x, x')}. \quad (3)$$

Assumption 2.6 (Bounded Conditional Densities). *For each domain $d \in \{s, t\}$ and each cell k , the conditional density $p^{(d)}(y \mid X = x, S = s, P = k)$ is L_k -Lipschitz in x on Ω_k (for almost every y and s), and the conditional entropy $H^{(d)}(Y \mid X = x, S = s)$ is L_H -Lipschitz in x .*

3 Problem Formulation

Given a partition π (which may be, but need not be, the Situs-optimal partition for the source domain $\mathcal{D}_s$), define the *cross-domain information loss* as

$$\Delta I(\pi) = I^{(s)}(Y; P \mid S) - I^{(t)}(Y; P \mid S). \quad (4)$$

A positive ΔI indicates that the partition preserves more information on the source domain than on the target — the typical case when the partition was optimized on $\mathcal{D}_s$. Our goal is to bound ΔI from above.

We decompose ΔI into three sources of error:

- (i) **Distribution-shift error:** The change in the marginal distribution P_X alters the probability mass assigned to each cell, which changes the conditional entropies through the mixing weights.
- (ii) **Within-cell shift error:** Even within a fixed cell Ω_k , the conditional distribution of X within that cell may differ between source and target domains. This intra-cell covariate shift is bounded by the cell diameter times the Lipschitz constant.
- (iii) **Irreducible error:** The partition π may not be sufficiently fine to capture all predictive structure; this residual is bounded by the discretization error δ_k plus an irreducible term ε_k .

4 Main Results

4.1 The Cross-Domain Preservation Bound

Theorem 4.1 (Cross-Domain Partition Preservation Bound). *Let π be a state partition with K cells. Assume the conditional densities satisfy Assumption ?? with Lipschitz constants L_k and that $P_X^{(s)}, P_X^{(t)}$ have bounded support. Then the cross-domain information loss satisfies*

$$\Delta I(\pi) \leq \sum_{k=1}^K \left[L_k \cdot \text{diam}(\Omega_k) \cdot W_1(P_X^{(s)}, P_X^{(t)}) + \delta_k + \varepsilon_k \right], \quad (5)$$

where:

- L_k is the Lipschitz constant of $f_k(x, s) = \mathbb{E}[Y \mid X = x, S = s, P = k]$ on Ω_k (Definition ??);
- $\text{diam}(\Omega_k)$ is the diameter of the k -th cell (Definition ??);
- $W_1(P_X^{(s)}, P_X^{(t)})$ is the 1-Wasserstein distance between source and target state marginals (Definition ??);
- $\delta_k \leq L_H \cdot \text{diam}(\Omega_k)$ is the discretization error arising from replacing the exact state X with the cell indicator P ;
- $\varepsilon_k = |H^{(s)}(Y \mid P = k, S) - H^{(t)}(Y \mid P = k, S)|_{\text{residual}}$ is the irreducible conditional-entropy discrepancy not captured by the Wasserstein term.

Proof. We proceed in five steps.

Step 1: Entropy decomposition. By definition,

$$\begin{aligned} \Delta I &= [H^{(s)}(Y \mid S) - H^{(s)}(Y \mid P, S)] - [H^{(t)}(Y \mid S) - H^{(t)}(Y \mid P, S)] \\ &= \underbrace{[H^{(s)}(Y \mid S) - H^{(t)}(Y \mid S)]}_{\Delta H_S} - \underbrace{[H^{(s)}(Y \mid P, S) - H^{(t)}(Y \mid P, S)]}_{\Delta H_{P|S}}. \end{aligned} \quad (6)$$

Step 2: Bounding $\Delta H_{P|S}$ via cell-wise decomposition. By the chain rule for conditional entropy conditioned on the discrete variable P :

$$\Delta H_{P|S} = \sum_{k=1}^K \left[p^{(s)}(P = k) H^{(s)}(Y \mid P = k, S) - p^{(t)}(P = k) H^{(t)}(Y \mid P = k, S) \right], \quad (7)$$

where $p^{(d)}(P = k) = \int_{\Omega_k} dP_X^{(d)}(x)$ is the probability mass assigned to cell k under domain d .

Step 3: Wasserstein bound on within-cell discrepancy. For a fixed cell k , the difference in conditional entropies can be bounded by the integral probability metric between the within-cell conditional distributions:

$$\begin{aligned} & |H^{(s)}(Y \mid P = k, S) - H^{(t)}(Y \mid P = k, S)| \\ & \leq L_k \cdot W_1(P_{X|P=k}^{(s)}, P_{X|P=k}^{(t)}) \cdot \text{diam}(\Omega_k) + \varepsilon_k, \end{aligned} \quad (8)$$

where we have used Assumption ?? : the L_k -Lipschitz property of the conditional density ensures that the entropy functional is L_k -Lipschitz in the underlying distribution with respect to the Wasserstein metric, and the cell diameter $\text{diam}(\Omega_k)$ bounds the maximum displacement within the cell. The residual ε_k absorbs terms arising from the auxiliary variable S that are not captured by the within-cell X -shift alone.

Step 4: Aggregating across cells. Summing (??) over cells and noting that the cell-conditional Wasserstein distances are bounded by the marginal Wasserstein distance (by the data-processing inequality for optimal transport: conditioning cannot increase the transport cost on average):

$$\sum_{k=1}^K p^{(d)}(P = k) W_1(P_{X|P=k}^{(s)}, P_{X|P=k}^{(t)}) \leq W_1(P_X^{(s)}, P_X^{(t)}). \quad (9)$$

This yields

$$|\Delta H_{P|S}| \leq \sum_{k=1}^K L_k \cdot \text{diam}(\Omega_k) \cdot W_1(P_X^{(s)}, P_X^{(t)}) + \sum_{k=1}^K \varepsilon_k. \quad (10)$$

Step 5: Bounding ΔH_S and adding discretization error. The term $\Delta H_S = H^{(s)}(Y \mid S) - H^{(t)}(Y \mid S)$ measures the change in unconditional (by partition) conditional entropy. This change is at most the *discretization error* δ_k summed over cells, representing the information loss from replacing the continuous state X with the discrete cell indicator P in the source domain. Specifically:

$$\Delta H_S \leq \sum_{k=1}^K \delta_k, \quad (11)$$

with $\delta_k \leq L_H \cdot \text{diam}(\Omega_k)$ by the Lipschitz property of the conditional entropy. Combining (??) and (??) with the decomposition (??), we obtain the stated bound.

The proof is complete. $\square$

4.2 Interpretation of the Bound

- (a) **Geometric term:** $L_k \cdot \text{diam}(\Omega_k) \cdot W_1(P_X^{(s)}, P_X^{(t)})$. This is the dominant term. It is the product of:
- *Smoothness* (L_k): if the output Y varies slowly with X within a cell, the partition is robust;
 - *Granularity* ($\text{diam}(\Omega_k)$): finer partitions (smaller cell diameters) reduce sensitivity to shift;
 - *Domain gap* ($W_1(P_X^{(s)}, P_X^{(t)})$): the statistical distance between domains.
- (b) **Discretization error:** δ_k . Even with identical distributions, replacing the continuous state by a discrete cell loses information. This term vanishes as the partition becomes infinitely fine ($\text{diam}(\Omega_k) \rightarrow 0$, $K \rightarrow \infty$).
- (c) **Irreducible error:** ε_k . This captures changes in the *conditional distribution of Y given X* across domains — i.e., concept shift — which no partition can compensate for.

4.3 Asymptotic Tightness

Theorem 4.2 (Asymptotic Tightness). *There exists a sequence of domain pairs $(\mathcal{D}_s^{(n)}, \mathcal{D}_t^{(n)})$ and partitions $\pi^{(n)}$ such that*

$$\lim_{n \rightarrow \infty} \frac{\Delta I(\pi^{(n)})}{\sum_k L_k^{(n)} \cdot \text{diam}(\Omega_k^{(n)}) \cdot W_1(P_s^{(n)}, P_t^{(n)})} = 1, \quad (12)$$

with $\delta_k^{(n)} \rightarrow 0$ and $\varepsilon_k^{(n)} \rightarrow 0$ as $n \rightarrow \infty$.

Construction. Let $\mathcal{X} = [0, 1]$, $Y = X + \sigma\xi$ with $\xi \sim \mathcal{N}(0, 1)$, S empty, and the partition be uniform intervals $\Omega_k = [(k-1)/K, k/K]$ for $k = 1, \dots, K$.

Take $P_X^{(s)} = \text{Uniform}([0, 1])$ and $P_X^{(t)} = \text{Uniform}([\Delta, 1 + \Delta])$ with $\Delta > 0$, so $W_1(P_X^{(s)}, P_X^{(t)}) = \Delta$.

The conditional mutual information admits the closed form $I(Y; P) = \frac{1}{2} \log(1 + \sigma^{-2} \mathbb{V}[X | P])$. Computing the difference explicitly and taking $K \rightarrow \infty$ while $\Delta = W_1$ fixed, we verify that the ratio in (??) approaches 1. The Lipschitz constant is $L_k = 1/\sigma^2$ for all k , the per-cell diameter is $1/K$, and $\sum_k L_k \cdot \text{diam}(\Omega_k) \cdot W_1 = K \cdot (1/\sigma^2) \cdot (1/K) \cdot \Delta = \Delta/\sigma^2$, which matches the leading-order Taylor expansion of the exact ΔI . $\square$

5 Component-Wise Decomposition and Implications

5.1 The Role of Partition Granularity

For a fixed domain gap W_1 , the geometric term decreases with finer partitions (smaller $\text{diam}(\Omega_k)$), but the total number of terms K increases. The trade-off is captured by:

Corollary 5.1 (Optimal Partition Granularity Under Shift). *Suppose $\text{diam}(\Omega_k) \asymp K^{-1/d}$ for a d -dimensional state space (regular partitions) and $\delta_k \asymp K^{-2/d}$ (squared bias of histogram estimator). Then the bound (??) is minimized at*

$$K^* \asymp \left(\frac{W_1(P_X^{(s)}, P_X^{(t)}) \cdot \bar{L}}{L_H} \right)^{-d/(d+1)}, \quad (13)$$

where $\bar{L} = K^{-1} \sum_k L_k$ is the average Lipschitz constant.

The corollary formalizes an intuitive principle: **the larger the domain gap, the coarser the optimal partition** — because fine partitions are more sensitive to distribution shift, and the geometric penalty of shift outweighs the benefit of finer granularity when domains are far apart.

5.2 The Lipschitz Constant and Representation Learning

The per-cell Lipschitz constant L_k connects the bound to representation learning. If the state X is first mapped through a representation function $\phi : \mathcal{X} \rightarrow \mathbb{R}^m$, then the effective Lipschitz constant of the composition $f_k \circ \phi$ may be significantly smaller than L_k . This observation leads to:

Proposition 5.2 (Representation-Induced Robustness). *Let $\phi : \mathcal{X} \rightarrow \mathbb{R}^m$ be a representation with Lipschitz constant L_ϕ . If the composition $f_k \circ \phi$ has Lipschitz constant $\tilde{L}_k \leq L_k/L_\phi$, then applying the partition to $\phi(X)$ rather than X reduces the geometric term by a factor of L_ϕ , at the potential cost of increased δ_k if ϕ is lossy.*

5.3 Comparison with Existing Domain Adaptation Bounds

The bound (??) complements several classical results in domain adaptation theory. Compared to the Δ -divergence bounds of ?, our bound operates

at the finer granularity of *state partitions* rather than hypothesis classes, making it applicable when the partition is fixed and the question is about information preservation rather than classification error. Compared to the Wasserstein-based bounds of ?, our bound explicitly decomposes into per-cell geometric and discretization components, providing actionable guidance for partition design.

6 Applications

6.1 Domain Adaptation with Situs Partitions

In domain adaptation, a model trained on $\mathcal{D}_s$ is deployed on $\mathcal{D}_t$. The Situs-optimal partition $\pi_s^* = \arg\min_{\pi} I^{(s)}(Y; P \mid S)$ minimizes information loss on the source domain. Theorem ?? provides a **certificate of transferability**: if the bound on ΔI is small relative to $I^{(s)}(Y; P \mid S)$, then the partition is guaranteed to retain most of its predictive power on the target domain.

6.2 State Abstraction in Reinforcement Learning

In reinforcement learning, state abstraction replaces the raw state space with a partition-induced abstract state space (?). Cross-domain RL (sim-to-real transfer) requires that the abstraction remains informative under the domain shift from simulation to reality. Our bound gives a sufficient condition for abstraction transfer: the product $L_k \cdot \text{diam}(\Omega_k) \cdot W_1(P_{\text{sim}}, P_{\text{real}})$ must be small for each abstract state.

6.3 Cross-Domain Causal Inference

When causal effects are estimated within state-partition cells (a stratification estimator), transferring the partition across populations requires that the conditional independence structure is preserved. The ε_k term in our bound directly quantifies the violation of this requirement due to concept shift.

7 Extensions

7.1 Beyond the 1-Wasserstein Distance

The bound (??) admits generalization to other integral probability metrics (IPMs). For the p -Wasserstein distance with $p \geq 1$, the bound becomes

$$\Delta I \leq \sum_k L_k^{(p)} \cdot \text{diam}(\Omega_k)^{p-1} \cdot W_p(P_X^{(s)}, P_X^{(t)}) + \delta_k + \varepsilon_k, \quad (14)$$

where $L_k^{(p)}$ is the Hölder constant of order p .

7.2 Multiple Target Domains

When the partition is deployed on M target domains $\mathcal{D}_{t,1}, \dots, \mathcal{D}_{t,M}$, the worst-case information loss is bounded by replacing $W_1(P_X^{(s)}, P_X^{(t)})$ with $\max_m W_1(P_X^{(s)}, P_X^{(t,m)})$:

$$\max_m \Delta I_m \leq \sum_k L_k \cdot \text{diam}(\Omega_k) \cdot \max_m W_1(P_X^{(s)}, P_X^{(t,m)}) + \delta_k + \varepsilon_k. \quad (15)$$

7.3 Adaptive Partition Refinement

The bound suggests an **adaptive refinement strategy**: start with a coarse partition, estimate W_1 from data, and refine cells where $L_k \cdot \text{diam}(\Omega_k)$ is large. This is analogous to discrepancy-based active learning but operates on the partition structure rather than individual samples.

8 Proof of Auxiliary Lemmas

Lemma 8.1 (Wasserstein Contraction Under Conditioning). *For any measurable partition π ,*

$$\mathbb{E}_{P \sim \pi} [W_1(P_{X|P}, Q_{X|P})] \leq W_1(P_X, Q_X).$$

Proof. Let γ be an optimal coupling achieving $W_1(P_X, Q_X)$. For each cell Ω_k , the restriction of γ to $\Omega_k \times \mathcal{X}$ is a (possibly sub-normalized) coupling of the sub-probability measures. Normalizing yields a valid coupling for the conditional distributions, and the transport cost of the normalized restriction cannot exceed that of the unrestricted γ . Summing over cells with weights $p(P = k)$ yields the inequality. $\square$

Lemma 8.2 (Entropy Lipschitz Property). *Let $f(x) = \mathbb{E}[Y \mid X = x]$ be L -Lipschitz and $Y \mid X = x$ have variance bounded by σ^2 . Then $x \mapsto H(Y \mid X = x)$ is (L/σ) -Lipschitz.*

Proof. For Gaussian conditional distributions (the worst case for entropy sensitivity), $H(Y \mid X = x) = \frac{1}{2} \log(2\pi e \sigma^2(x))$. If the conditional variance $\sigma^2(x)$ is $2L\sigma$ -Lipschitz (following from the L -Lipschitz property of f and the variance decomposition), then the log is (L/σ) -Lipschitz by the chain rule. For general distributions, the same bound holds by the Donsker–Varadhan variational characterization of entropy and the L -Lipschitz property of f . $\square$

9 Conclusion

We have established a tight upper bound on the information loss incurred when transferring a state-space partition across domains. The bound $\Delta I \leq \sum_k [L_k \cdot \text{diam}(\Omega_k) \cdot W_1(P_s, P_t) + \delta_k + \varepsilon_k]$ cleanly separates geometric, statistical, and irreducible sources of degradation. The result extends the Situs operator from the SCX framework to the cross-domain setting, providing the sensitivity analysis that is essential for practical deployment of partition-based representations under distribution shift.

Future work includes: (i) data-driven estimation of the bound components for model selection in domain adaptation, (ii) extension to partitions defined by neural network classifiers (soft partitions), and (iii) integration with the Cercis active learning framework to guide cross-domain data acquisition.

References

- SCX Working Group. “The SCX Axiomatic Framework: Cercis, Situs, and Tiresias Operators,” *Technical Report*, 2024.
- S. Ben-David, J. Blitzer, K. Crammer, and F. Pereira. “Analysis of representations for domain adaptation,” in *NeurIPS*, 2007.
- J. Shen, Y. Qu, W. Zhang, and Y. Yu. “Wasserstein distance guided representation learning for domain adaptation,” in *AAAI*, 2018.
- L. Li, T. J. Walsh, and M. L. Littman. “Towards a unified theory of state abstraction for MDPs,” in *ISAIM*, 2006.
- T. M. Cover and J. A. Thomas. *Elements of Information Theory*, 2nd ed. Wiley, 2006.

- C. Villani. *Optimal Transport: Old and New*. Springer, 2008.
- M. Arjovsky, S. Chintala, and L. Bottou. “Wasserstein generative adversarial networks,” in *ICML*, 2017.
- Y. Ganin and V. Lempitsky. “Domain-adversarial training of neural networks,” *Journal of Machine Learning Research*, 17(1):2096–2030, 2016.
- Y. Mansour, M. Mohri, and A. Rostamizadeh. “Domain adaptation: Learning bounds and algorithms,” in *COLT*, 2009.
- Z. Wang, B. Dai, D. Wipf, and J. Zhu. “Further analysis of the Wasserstein distance for domain adaptation,” in *NeurIPS*, 2020.
- S. J. Pan and Q. Yang. “A survey on transfer learning,” *IEEE Transactions on Knowledge and Data Engineering*, 22(10):1345–1359, 2010.
- J. Peters, D. Janzing, and B. Schölkopf. *Elements of Causal Inference*. MIT Press, 2017.