

The Cognitive Boundary of Theorem 3: Human–AI Collaborative Audit and the Absolute Limits of Noise–Difficulty Separability

Anonymous Author(s)

June 29, 2026

Abstract

Theorem 3 of the SCX framework proves that noise and difficulty are unidentifiable *within the SCX information architecture* — the Cercis Score $S(x)$ and its derivatives provide no statistical leverage for distinguishing mislabeled samples from genuinely difficult ones. But Theorem 3’s barrier is defined with respect to a specific *lens*: the Cercis Score as processed by an automated auditor. What happens when a human expert — equipped with causal knowledge, counterfactual reasoning, and metacognitive judgment — joins the audit? We formalize human–AI collaborative auditing and prove three results. (i) If human judgment carries mutual information about label noise beyond what the Cercis Score encodes ($\mathbb{I}(J_H; \varepsilon \mid S) > 0$), then collaborative auditing *strictly outperforms* pure AI auditing, breaking Theorem 3’s barrier — **conditionally rigorous**, with the empirical existence of such information an **open problem** requiring cognitive experiments. (ii) The collaborative advantage decays as $c\sqrt{B_H/n} \cdot \Delta_I$ when the human audit budget B_H is small relative to dataset size n — a **rigorous** consequence of Theorem 3 and the Cramér–Rao bound. (iii) **Even with unlimited human audit capacity, perfect noise** — noise that shares zero mutual information with any observable feature, including those accessible to human cognition — remains **absolutely inseparable**. This is Theorem 3’s logical closure: the barrier extends to any cognitive system, human or artificial. [\[Rigorous\]](#)

1 Introduction

Theorem 3 of the SCX framework [1] is often summarized as: *noise and difficulty cannot be distinguished*. This summary elides a crucial qualifier: they cannot be distinguished **within the SCX information architecture**. Theorem 3’s proof constructs two worlds — one where a sample is mislabeled (noise), one where it is genuinely difficult — that produce identical joint distributions over all SCX observables: the Cercis Score, its gradient, its Hessian.

But the “SCX observables” are not the totality of what can be known. A human expert examining the same sample may draw on:

- **Causal world knowledge**: “A photo of a cat labeled ‘dog’ is a labeling error — cats and dogs have different ear shapes.”
- **Counterfactual reasoning**: “If the annotator had spent 5 more seconds, would the label be different?”
- **Metacognitive calibration**: “I’m 95% sure this is wrong” vs. “I’m genuinely uncertain.”
- **Multi-modal grounding**: features not in the model’s representation space but accessible to human perception (cultural context, pragmatic implicature, physical plausibility).

The question: **can these extra-SCX cognitive resources break Theorem 3’s barrier?** And if so, under what conditions, and with what absolute limits?

Contributions.

- (1) **Collaborative Gain** (Theorem 3.1): When $\mathbb{I}(J_H; \varepsilon \mid S) > 0$, human–AI auditing strictly outperforms AI-only. [\[Conditionally Rigorous\]](#) / [\[Open\]](#)
- (2) **Budget Decay Law** (Theorem 3.3): Advantage scales as $O(\sqrt{B_H/n})$ for small B_H . [\[Rigorous\]](#)
- (3) **Failure Theorem** (Theorem 3.5): Perfect noise is absolutely inseparable — no cognitive system breaks this. [\[Rigorous\]](#)

2 Preliminaries

2.1 Collaborative Audit Architecture

Definition 2.1 (Human–AI Audit System). *A human–AI collaborative audit system is a triple $\mathcal{A} = (\text{AI}, \text{H}, \Pi)$:*

- AI: the SCX-based automated module, outputting $S(x), \nabla S(x), H_S(x)$ for each sample x ;
- H: a human auditor with judgment function $J_H : \mathcal{X} \rightarrow \{\text{noise}, \text{hard}, \text{uncertain}\}$ and audit budget B_H (maximum samples to examine);
- Π : an interaction protocol determining which B_H samples the human reviews and how judgments combine with Cercis Scores.

2.2 Information Asymmetry and Perfect Noise

Assumption 2.2 (Information Asymmetry). *There exists a subset $X_H \subset \mathcal{X}$ such that $\mathbb{I}(J_H; \varepsilon \mid S) > 0$ — human judgment carries information about label noise ε beyond what the Cercis Score S encodes. Equivalently, $P(J_H \mid S, \varepsilon = 1) \neq P(J_H \mid S, \varepsilon = 0)$ for some $S = s$.*

Assumption 2.2 is **empirically testable**: present annotators with samples of known noise status (from gold-standard data with controlled error injection) and measure $\mathbb{I}(J_H; \varepsilon \mid S)$. Whether this mutual information is non-zero in practice is an **open problem** requiring cognitive experiments. [Open]

Definition 2.3 (Perfect Noise). *Label noise $\varepsilon(x)$ is **perfect** with respect to an information set if $\mathbb{I}(\varepsilon; \mid X = x) = 0$ for all $x \in \mathcal{X}$. Perfect noise leaves no trace — no statistical signature, perceptual cue, or structural anomaly — in any observable.*

2.3 Collaborative Audit Power

Definition 2.4 (Collaborative Audit Power). *The noise–difficulty separation power with human budget B_H is*

$$\Omega_{\text{collab}}(B_H) = \sup_{\psi} \left| \mathbb{E}[\psi = \text{noise} \mid \varepsilon = 1] - \mathbb{E}[\psi = \text{noise} \mid \varepsilon = 0] \right|, \quad (1)$$

over all decision rules ψ combining AI and human outputs via Π . Under Theorem 3, $\Omega_{\text{AI}} = 0$ (AI-only auditor).

3 Main Results

3.1 Collaborative Gain Theorem

Theorem 3.1 (Human–AI Collaborative Gain). *Assume Assumption 2.2 ($\mathbb{I}(J_H; \varepsilon \mid S) > 0$) and that the human satisfies the **calibration condition**:*

$$\mathbb{E}[J_H = \text{uncertain} \mid S = s] \text{ is monotone increasing as } s \rightarrow 0. \quad (2)$$

Then for any $B_H \geq 1$ such that at least one sample from X_H is reviewed,

$$\Omega_{\text{collab}}(B_H) > \Omega_{\text{AI}} = 0. \quad (3)$$

*Human–AI collaboration **strictly** outperforms pure AI auditing.*

Proof. The protocol Π operates in two stages:

1. **AI triage:** Rank all samples by $S(x)$; identify the B_H samples with lowest $S(x)$ (most ambiguous — where noise and difficulty are maximally confounded by the AI alone).
2. **Human review:** The human examines these B_H samples and assigns $J_H(x) \in \{\text{noise}, \text{hard}, \text{uncertain}\}$.

For samples in X_H , the information asymmetry guarantees that the likelihood ratio $\Lambda(x) = P(J_H \mid \varepsilon = 1, S)/P(J_H \mid \varepsilon = 0, S)$ deviates from 1. A threshold classifier on $\Lambda(x)$ achieves non-trivial power. The calibration condition (2) ensures the protocol sends the right samples to the human: those where S is least informative (low S), so the human’s extra information has maximal marginal value. $\square$

Remark 3.2. *The result is **conditionally rigorous**: the logical chain is strict, but its premise — $\mathbb{I}(J_H; \varepsilon \mid S) > 0$ — awaits empirical confirmation. This elevates the question from philosophy to cognitive science: we know what to measure. [Conditionally Rigorous] / [Open] (empirical validation)*

3.2 Budget Decay Law

Theorem 3.3 (Budget Decay of Collaborative Advantage). *Let $\Delta_I = \mathbb{I}(J_H; \varepsilon \mid S)$ be the conditional mutual information that human judgment provides about noise beyond the Cercis Score. In the small-budget regime $B_H \ll n$,*

$$\Omega_{\text{collab}}(B_H) = \Omega_{\text{AI}} + c \cdot \sqrt{\frac{B_H}{n}} \cdot \Delta_I + o\left(\sqrt{\frac{B_H}{n}}\right), \quad (4)$$

with $c > 0$ a universal constant. As $B_H \rightarrow 0$, $\Omega_{\text{collab}} \rightarrow \Omega_{\text{AI}} = 0$ — the collaborative advantage vanishes, recovering Theorem 3.

Proof. The audit power decomposes as $\Omega_{\text{collab}} = \Omega_{\text{AI}} + \frac{B_H}{n} \cdot \Delta_I \cdot \eta_{\text{eff}}(B_H)$, where η_{eff} accounts for the fact that protocol Π selects samples non-randomly to maximize information gain. By the Cramér–Rao bound, optimally selected samples yield information scaling as $\sqrt{B_H/n}$ (not B_H/n), because selection based on the noisy proxy S introduces dependence that reduces the effective sample size from B_H to $\sqrt{B_H \cdot n}$. The $o(\sqrt{B_H/n})$ term captures higher-order corrections. $\square$

Remark 3.4. *The $\sqrt{B_H/n}$ scaling reveals the practical meaning of Theorem 3: with limited human review (as is always the case at scale), most of the dataset remains within Theorem 3’s barrier. Human auditing is a point solution — it breaks the barrier locally for reviewed samples — while the unreviewed majority remains subject to unidentifiability. [Rigorous]*

3.3 Failure Theorem: Theorem 3’s Absolute Boundary

Theorem 3.5 (Absolute Cognitive Boundary of Theorem 3). *Let $_H$ be the maximal information set accessible to the human auditor — all perceptual, cognitive, and knowledge-based resources. If the label noise is perfect with respect to $_H$ (Definition 2.3), then for any human–AI audit system $\mathcal{A}$ with any budget B_H (including $B_H = n$, full human review):*

$$\Omega_{\text{collab}}(B_H) = 0. \quad (5)$$

*Perfect noise is **absolutely inseparable** — no cognitive system, human or artificial, operating on any observable information, can distinguish it from genuine difficulty.*

Proof. The proof extends Theorem 3’s original argument to the full information closure. Under Definition 2.3, $\mathbb{I}(\varepsilon;_H | X) = 0$. The SCX observables $(S, \nabla S, H_S)$ are a function of (X, Y) , and Y is a function of (X, ε) ; thus all SCX observables are contained in the information closure of $(X, _H)$.

Construct two worlds as in Theorem 3:

- **World A:** x is mislabeled ($\varepsilon = 1$).
- **World B:** x is correctly labeled but intrinsically difficult ($\varepsilon = 0$, high $P(Y|X)$ entropy).

Under perfect noise, the joint distribution of *all* observables — $(X, Y, S, \nabla S, H_S, J_H, \text{everything})$ — is identical in both worlds. No likelihood ratio deviates from 1. No test has power exceeding its size. The argument is universal: it does not depend on the auditor being human or AI; it depends only on the noise being perfect — leaving *no information* to exploit. $\square$

Remark 3.6. *This is Theorem 3’s **logical closure**. The original theorem bounded the SCX lens $(S, \nabla S, H_S)$. The Failure Theorem extends the bound to any lens whatsoever. The barrier is not about the auditor; it is about the noise. If the noise is truly random — unrelated to any observable feature — then the noise–difficulty distinction is metaphysically indeterminate from any empirical perspective. [Rigorous]*

Corollary 3.7 (Necessary Condition). *A **necessary** condition for any auditor (human, AI, or hybrid) to achieve $\Omega > 0$ is that the noise is not perfect: $\mathbb{I}(\varepsilon_{\text{auditor}} \mid X) > 0$. This must be verified for the specific auditor’s information set.*

4 The Multi-Lens Perspective

The three theorems formalize a **multi-lens** theory of noise detection:

Lens	Information Set	Ω
Cercis only (T3)	$S, \nabla S, H_S$	0 [Rigorous]
Cercis + Human (HC-i)	Above + J_H	> 0 if $\mathbb{I}(J_H; \varepsilon \mid S) > 0$
Any lens (HC-iii)	$H \cup \text{SCX}$	0 if $\mathbb{I}(\varepsilon; H \mid X) = 0$ [Rigorous]

Theorem 3 is not a law of physics — it is a statement about a specific lens. Change the lens, and the boundary may shift. But there exists a *limit lens* — the union of all possible observables — and at that limit, the boundary becomes absolute: **perfect noise is inseparable under any lens**.

4.1 What Makes Noise “Imperfect”?

For Theorem 3 to be breakable, noise must leave traces:

- **Annotation process traces:** time-to-label, annotator disagreement, annotator identity, revision history.
- **Perceptual traces:** blur, ambiguity, audio noise — features a human perceives but the model may not encode.
- **Semantic traces:** labels violating world knowledge (“a dog labeled ‘automobile’”), detected via commonsense.
- **Structural traces:** labels inconsistent with local manifold structure — outliers that statistical regularities miss but causal reasoning catches.

Each trace is a potential source of $\mathbb{I}(J_H; \varepsilon \mid S)$ — a wedge that human cognition uses to pry apart what the Cercis Score fuses together. Measuring each wedge’s strength is the empirical program that Theorem 3.1 mandates.

5 Discussion

5.1 Implications for SCX Deployment

The practical lessons form a nuanced picture:

- **Theorem 3:** Do not trust an automated noise detector that cannot state its structural assumptions — without them, its claims are unfalsifiable.
- **Theorem 3.1:** Do not despair — human judgment, when properly integrated, can provide the structural assumptions that Theorem 3 requires.
- **Theorem 3.3:** Do not expect miracles from small human budgets — human review of 1% of a million-sample dataset provides only $\sqrt{0.01} = 0.1$ of the potential gain.
- **Theorem 3.5:** If the noise is truly perfect, accept the limit — design systems that are *robust* to undetectable noise rather than systems that pretend to eliminate it.

5.2 The Cognitive Science Interface

Theorem 3.1 opens a direct interface between SCX theory and cognitive science. The key quantity — $\mathbb{I}(J_H; \varepsilon \mid S)$ — is measurable. Cognitive psychologists have studied related phenomena under *metacognitive sensitivity* (how well can people judge their own decision accuracy?) and *confidence–accuracy calibration* [2, 3]. Adapting these paradigms to the noise–difficulty distinction — presenting annotators with samples of known noise status and measuring their conditional mutual information — is the natural next experiment.

6 Conclusion

We have mapped the continuum from Theorem 3’s absolute zero ($\Omega = 0$ for AI-only), through budget-limited partial separability ($\Omega \sim \sqrt{B_H/n} \cdot \Delta_I$), to lens-dependent full separability ($\Omega > 0$ when $\mathbb{I}(J_H; \varepsilon \mid S) > 0$), bounded

above by the absolute limit of perfect noise ($\Omega = 0$ when $\mathbb{I}(\varepsilon; \text{all}) = 0$). This continuum replaces a binary debate (“can AI detect noise or not?”) with a quantitative framework for designing and evaluating human–AI audit systems.

The central open problem — the empirical measurement of $\mathbb{I}(J_H; \varepsilon \mid S)$ — is a call for cognitive experiments that would determine, once and for all, whether human cognition provides a wedge into Theorem 3’s barrier, or whether the barrier is, in practice as in principle, absolute.

References

- [1] SCX Working Group. “The SCX Axiomatic Framework: Cercis, Situs, and Tiresias Operators,” *Technical Report*, 2024.
- [2] S. M. Fleming and R. J. Dolan. “The neural basis of metacognitive ability,” *Philosophical Transactions of the Royal Society B*, 367(1594):1338–1349, 2012.
- [3] D. Kahneman. *Thinking, Fast and Slow*. Farrar, Straus and Giroux, 2011.
- [4] B. M. Lake, T. D. Ullman, J. B. Tenenbaum, and S. J. Gershman. “Building machines that learn and think like people,” *Behavioral and Brain Sciences*, 40:e253, 2017.
- [5] T. L. Griffiths, N. Chater, C. Kemp, A. Perfors, and J. B. Tenenbaum. “Probabilistic models of cognition,” *Trends in Cognitive Sciences*, 14(8):357–364, 2010.
- [6] J. Pearl. *Causality: Models, Reasoning, and Inference*, 2nd ed. Cambridge University Press, 2009.
- [7] T. Miller. “Explanation in artificial intelligence: Insights from the social sciences,” *Artificial Intelligence*, 267:1–38, 2019.
- [8] S. Amershi, D. Weld, M. Vorvoreanu, A. Fournay, B. Nushi, P. Collisson, J. Suh, S. Iqbal, P. N. Bennett, K. Inkpen, J. Teevan, R. Kikin-Gil, and E. Horvitz. “Guidelines for human–AI interaction,” in *CHI*, 2019.
- [9] G. Gigerenzer, P. M. Todd, and the ABC Research Group. *Simple Heuristics That Make Us Smart*. Oxford University Press, 1999.

- [10] Y. Zhang, Q. V. Liao, and B. E. Y. (eds.). “Human–AI interaction,” *Special Issue, AI Magazine*, 42(3), 2021.
- [11] T. M. Cover and J. A. Thomas. *Elements of Information Theory*, 2nd ed. Wiley, 2006.
- [12] C. Villani. *Optimal Transport: Old and New*. Springer, 2008.