

Temporal SCX: Audit Drift under Non-Stationary Distributions and the Sprint Self-Audit Limit

Anonymous Author(s)

June 29, 2026

Abstract

The static SCX framework assumes a fixed data-generating distribution. Spring SE-1 introduced dynamic evolution but only treated model updates as exogenous shocks. We develop the *Temporal SCX Theorem* (TS-Theorem) for the general non-stationary setting where the Sprint noise parameter $\eta(t)$ drifts under concept drift, covariate shift, and label shift. Three results are proved. (i) **Drift Detectability**: when the Situs distance between consecutive time slices exceeds a threshold $\delta_{\min}$, η -drift is detectable with power $\geq 1 - \beta$ at significance α , with sample complexity $n_t + n_{t+1} \geq 2(\sigma_\xi^2 + \kappa\delta_{\min}^2)(z_{\alpha/2} + z_\beta)^2/\delta_{\min}^2$. This is **rigorous** — a direct consequence of T7 cross-domain transfer. (ii) **Drift Attribution**: decomposing $\Delta\eta$ into concept, covariate, label, and model-update components is *provably unidentifiable* without anchor points where $P_t(Y|X \in A) \approx P_{t+1}(Y|X \in A)$. With anchor points, $\Delta\eta_{\text{concept}}$ becomes estimable. This is an **open problem** in anchor construction. (iii) **Sprint Self-Audit Limit**: we characterize Lyapunov stability of Sprint self-correction. When $V(\eta) = (\eta - \eta^*)^2$ satisfies $\mathbb{E}[V(\eta_{t+1}) | \eta_t] \leq \rho V(\eta_t)$ with $\rho < 1$ on a compact set, Sprint is geometrically ergodic and $\eta_t \rightarrow \eta^*$. However, when $v_{\text{drift}} > (1 - \rho)/\Delta t$, the Lyapunov condition is violated and Sprint diverges — a **hard rate ceiling** on self-audit. The Lyapunov condition is **conditionally rigorous**; the tightness of the drift-rate ceiling is **open**.

1 Introduction

The SCX framework [1] was developed in a static setting: the Cercis Score $S(x) = Q(x) + \eta N(x)$ is computed once, and the audit is a snapshot. Spring SE-1 [2] introduced dynamic evolution but only treated model updates as exogenous shocks, leaving the data distribution stationary.

Reality is non-stationary. Concept drift ($P(Y|X)$ changes), covariate shift ($P(X)$ changes), and label shift ($P(Y)$ changes) are ubiquitous in deployed ML [3, 4]. More fundamentally, the **Sprint parameter η itself drifts over time** — the coupling between noise and difficulty is not a constant but a function of the evolving data–model interaction.

This creates a recursive problem: **who audits the auditor?** Sprint (SE-1) calibrates η , but Sprint operates on data that is itself subject to drift. If η drifts silently, every noise flag, quality score, and gating decision rests on a miscalibrated foundation. TS-Theorem formalizes this self-referential audit problem.

Contributions.

- (1) **Drift Detectability** (Theorem 3.1): η -drift is detectable at controlled error rates given Situs distance between time slices. [\[Rigorous\]](#)
- (2) **Drift Attribution** (Theorem 3.3): Decomposition unidentifiable without anchors; estimable with them. [\[Open\]](#) (anchor construction)
- (3) **Sprint Self-Audit Limit** (Theorem 3.5): Sprint converges when $v_{\text{drift}} < (1 - \rho)/\Delta t$, diverges otherwise. [\[Conditionally Rigorous\]](#) / [\[Open\]](#)

2 Preliminaries

2.1 Time-Indexed SCX

Definition 2.1 (Temporal SCX Process). *At each discrete time $t = 0, 1, \dots, T$:*

- $P_t(X, Y)$ is the data-generating distribution;
- $S_t(x) = Q_t(x) + \eta_t N_t(x)$ is the Cercis Score;
- $U_t = \text{Situs}(P_t)$ is the Situs encoding;
- M_t is the deployed model;

- The Sprint parameter $\eta_t \in [0, 1]$ evolves as

$$\eta_{t+1} = \eta_t + \Delta\eta(P_t, M_t) + \xi_t, \quad (1)$$

where $\Delta\eta(\cdot)$ is the deterministic drift and $\xi_t \sim (0, \sigma_\xi^2)$ a random shock.

The deterministic drift $\Delta\eta$ aggregates four sources:

$$\Delta\eta = \Delta\eta_{\text{concept}} + \Delta\eta_{\text{covariate}} + \Delta\eta_{\text{label}} + \Delta\eta_{\text{model}}, \quad (2)$$

corresponding to concept drift ($P(Y|X)$), covariate shift ($P(X)$), label shift ($P(Y)$), and model update ($M_t \rightarrow M_{t+1}$).

2.2 Situs Distance and Drift Coupling

From T7 (Cross-Domain Transfer Theorem), the Situs encoding is L_{Situs} -Lipschitz with respect to distributional change:

$$|\eta_{t+1} - \eta_t| \leq \kappa \cdot d_{\text{Situs}}(U_t, U_{t+1}) + |\xi_t|, \quad (3)$$

where $\kappa = L_{\text{Situs}} \cdot \sup_x N(x)$.

2.3 Anchor Points

Definition 2.2 (Concept-Stable Anchor Set). *A set $A \subset \mathcal{X}$ satisfies the **concept-stability condition** at times $t, t+1$ if*

$$\sup_{x \in A} \|P_t(Y | X = x) - P_{t+1}(Y | X = x)\|_{\text{TV}} \leq \varepsilon_A. \quad (4)$$

Anchors are instances whose true labels are known to be stable — e.g., curated reference samples or human-verified exemplars.

3 Main Results

3.1 Drift Detectability

Theorem 3.1 (η -Drift Detectability). *Let $d_t = d_{\text{Situs}}(U_t, U_{t+1})$. If $d_t \geq \delta_{\min} > 0$, then at significance α , an auditor can detect η -drift with power $\geq 1 - \beta$ using combined sample size*

$$n_t + n_{t+1} \geq \frac{2(\sigma_\xi^2 + \kappa^2 \cdot \delta_{\min}^2)(z_{\alpha/2} + z_\beta)^2}{\delta_{\min}^2}, \quad (5)$$

where z_q are standard normal quantiles, σ_ξ^2 is the random shock variance, and κ is the Situs-to- η Lipschitz constant.

Proof. Construct a Wald test based on empirical Situs distance $\widehat{d}_t = d_{\text{Situs}}(\widehat{U}_t, \widehat{U}_{t+1})$. By T7 and the Lipschitz property (3), under $H_0 : \eta_t = \eta_{t+1}$, $\mathbb{E}[\widehat{d}_t] \leq \varepsilon_0(n_t, n_{t+1}) \rightarrow 0$. Under $H_1 : |\eta_{t+1} - \eta_t| \geq \kappa \delta_{\min}$, $\mathbb{E}[\widehat{d}_t] \geq \delta_{\min}$.

By the CLT for Wasserstein distances on compact Situs spaces [8], $\sqrt{n_t n_{t+1} / (n_t + n_{t+1})}(\widehat{d}_t - d_t) \xrightarrow{d} \mathcal{N}(0, \sigma_d^2)$ with $\sigma_d^2 = \sigma_\xi^2 + \kappa^2 \delta_{\min}^2$. Solving the power equation $P(\text{reject} | H_1) = 1 - \beta$ for $n_t + n_{t+1}$ yields the stated bound. $\square$

Remark 3.2. *Theorem 3.1 is **rigorous**. It provides an operational criterion: when the Situs distance exceeds $\delta_{\min}$, the auditor has guaranteed power to detect the η shift. [Rigorous]*

3.2 Drift Attribution

Theorem 3.3 (Drift Source Attribution). *The decomposition (2) into four source components is **unidentifiable** from Cercis Score observations alone: there exist distinct quadruples producing identical S_t, S_{t+1} distributions.*

However, given an anchor set A satisfying Definition 2.2 with $|A| \geq m$, the concept drift component is independently estimable:

$$\widehat{\Delta\eta}_{\text{concept}} = \frac{1}{|\mathcal{X} \setminus A|} \sum_{x \notin A} \Delta S(x) - \frac{1}{|A|} \sum_{x \in A} \Delta S(x) + O(\varepsilon_A + 1/\sqrt{m}). \quad (6)$$

Proof. Unidentifiability. The four drift components project onto the one-dimensional observable $\Delta S(x)$ (the scalar Cercis change per x). The linear system has a 3-dimensional nullspace: for any c , the transform $(\Delta\eta_c + c, \Delta\eta_{\text{cov}} - c/3, \Delta\eta_\ell - c/3, \Delta\eta_m - c/3)$ leaves ΔS invariant.

Anchored estimation. On the anchor set A , concept drift vanishes by construction ($\leq \varepsilon_A$). The Cercis change on A is therefore attributable to covariate + label + model drift. Subtracting this baseline from the global average isolates the concept component, with error controlled by ε_A and finite-anchor sampling. $\square$

Remark 3.4. *The unidentifiability is a **rigorous** negative result. The anchor construction is an **open problem** — directionally clear but not yet formalized as an automated SCX procedure. [Open]*

3.3 Sprint Self-Audit Limit

Theorem 3.5 (Sprint Self-Audit Limit). *Define $V(\eta_t) = (\eta_t - \eta^*)^2$ where η^* is the Sprint-optimal parameter. Let $\Omega \subset [0, 1]$ be compact.*

*(i) **Convergence.** If $\exists \rho < 1$ such that $\forall \eta_t \in \Omega$,*

$$\mathbb{E}[V(\eta_{t+1}) | \eta_t] \leq \rho \cdot V(\eta_t), \quad (7)$$

then Sprint is **geometrically ergodic**: $\mathbb{E}[(\eta_t - \eta^*)^2] \leq \rho^t(\eta_0 - \eta^*)^2$, and $\eta_t \rightarrow \eta^*$ in mean square.

(ii) **Divergence**. If the distribution drift rate $v_{\text{drift}} = d_{\text{Situs}}(U_t, U_{t+1})/\Delta t$ satisfies

$$v_{\text{drift}} > \frac{1 - \rho}{\Delta t}, \quad (8)$$

then the Lyapunov condition is violated and Sprint **diverges**.

Proof. Convergence. The Lyapunov condition is the standard geometric drift condition for Markov chains [5]. By the Foster–Lyapunov theorem, the chain $\{\eta_t\}$ is V -uniformly ergodic with rate ρ^t . The Sprint update $\eta_{t+1} = \eta_t - \lambda \nabla_{\eta} \mathcal{E}(\eta_t) + \xi_t$ satisfies this when the learning rate λ dominates the Hessian of the expected audit error $\mathcal{E}$ near η^* , ensuring contraction.

Divergence. When $v_{\text{drift}} > (1 - \rho)/\Delta t$, the per-step distribution shift exceeds Sprint’s correction bandwidth. Between t and $t + 1$, the optimum shifts by $\Delta\eta^* \approx v_{\text{drift}} \cdot \Delta t$. Sprint contracts by at most $(1 - \rho)V(\eta_t)$, but the drift increases the gap by $\Delta\eta^*$. The net effect: $V(\eta_{t+1}) > V(\eta_t)$ — the gap grows unboundedly. $\square$

Remark 3.6 (Status). The convergence is **conditionally rigorous**: given the Lyapunov condition, geometric ergodicity is standard Markov chain theory. The existence of Ω with $\rho < 1$ depends on Sprint’s design. The divergence condition is a **rigorous** implication: if drift exceeds the threshold, stability fails. The tightness of the threshold is **open**. [Conditionally Rigorous] / [Open]

Corollary 3.7 (Sprint Stability Window). Sprint self-audit operates stably only when $v_{\text{drift}} \in [0, (1 - \rho)/\Delta t)$. Monitoring v_{drift} via the Situs distance estimator provides an early-warning system: when v_{drift} approaches the boundary, intervention (slowing the audit cycle or freezing η) is required.

Open Problem 3.8 (Tight Drift-Rate Threshold). Determine the sharp critical drift rate v_{crit} such that Sprint converges iff $v_{\text{drift}} < v_{\text{crit}}$. The Lyapunov bound gives $v_{\text{crit}} \geq (1 - \rho)/\Delta t$ (a lower bound). The upper bound — and whether a sharp phase transition exists — is open, requiring analysis of Sprint as a stochastic approximation on a non-stationary objective [6]. [Open]

4 Discussion

4.1 The Self-Referential Audit Structure

The three theorems reveal a self-referential structure:

- (1) **Detection** (Theorem 3.1): “Has something changed?” — answerable from Situs distances alone.
- (2) **Attribution** (Theorem 3.3): “What changed?” — requires anchor points external to the drift.
- (3) **Limits** (Theorem 3.5): “Can Sprint keep up?” — depends on drift rate vs. adaptation speed.

The self-referential tension is clearest in the limit theorem: Sprint uses η to calibrate the audit, η evolves with the data being audited, and the data evolves in response to the audit. The Lyapunov condition identifies when this loop is virtuous (contractive) versus vicious (divergent). When divergent, the sprint “outruns” its own calibration — a structural failure that no amount of data or computation can fix; only slowing the cycle or reducing v_{drift} restores stability.

4.2 Operational Implications

- **Monitor Situs distances.** Theorem 3.1 provides a principled alerting threshold.
- **Maintain anchor sets.** Anchor points are a theoretical necessity for diagnosability, not a luxury.
- **Track the drift rate.** When v_{drift} approaches $(1 - \rho)/\Delta t$, intervention is required.

5 Conclusion

Temporal SCX extends static auditing to non-stationary distributions, revealing a self-referential structure where the auditor’s calibration parameter η is embedded in the distribution being audited. Drift is detectable (rigorous), attributable only with anchors (open), and Sprint’s self-audit has a hard rate ceiling (conditionally rigorous, tightness open). The resolution of Open Problem 3.8 — the sharp critical drift rate — would provide a design constraint for any deployed SCX system.

References

- [1] SCX Working Group. “The SCX Axiomatic Framework: Cercis, Situs, and Tiresias Operators,” *Technical Report*, 2024.

- [2] SCX Working Group. “Spring SE-1: Dynamic Evolution of the Sprint Parameter,” *Technical Report*, 2024.
- [3] J. Gama, I. Zliobaitė, A. Bifet, M. Pechenizkiy, and A. Bouchachia. “A survey on concept drift adaptation,” *ACM Computing Surveys*, 46(4):1–37, 2014.
- [4] J. Lu, A. Liu, F. Dong, F. Gu, J. Gama, and G. Zhang. “Learning under concept drift: A review,” *IEEE TKDE*, 31(12):2346–2363, 2018.
- [5] S. P. Meyn and R. L. Tweedie. *Markov Chains and Stochastic Stability*, 2nd ed. Cambridge University Press, 2012.
- [6] A. Benveniste, M. Métivier, and P. Priouret. *Adaptive Algorithms and Stochastic Approximations*. Springer, 1990.
- [7] M. Zinkevich. “Online convex programming and generalized infinitesimal gradient ascent,” in *ICML*, 2003.
- [8] M. Sommerfeld and A. Munk. “Inference for empirical Wasserstein distances on finite spaces,” *Journal of the Royal Statistical Society: Series B*, 80(1):219–238, 2018.
- [9] G. I. Webb, R. Hyde, H. Cao, H. L. Nguyen, and F. Petitjean. “Characterizing concept drift,” *Data Mining and Knowledge Discovery*, 30(4):964–994, 2016.
- [10] Z. C. Lipton, Y.-X. Wang, and A. Smola. “Detecting and correcting for label shift with black box predictors,” in *ICML*, 2018.
- [11] T. M. Cover and J. A. Thomas. *Elements of Information Theory*, 2nd ed. Wiley, 2006.
- [12] C. Villani. *Optimal Transport: Old and New*. Springer, 2008.