

The Alignment Audit Theorem: Reducing AI Alignment to Data Quality Audit, RLHF Preference Noise Detection, and the Indistinguishability of Value Uncertainty from Noise

Anonymous Author(s)

June 29, 2026

Abstract

AI alignment — ensuring that AI systems behave consistently with human values — is the central safety challenge of modern machine learning. Current alignment techniques (RLHF, DPO, CAI) rely on human preference data to shape model behavior. But what if the alignment data itself is noisy — corrupted by careless annotators, ambiguous preferences, or genuine value disagreements among humans? We formalize the reduction of alignment auditing to SCX data quality auditing and prove four results. (i) **Alignment–Audit Reduction** (Theorem ??): there exists a mapping Φ from alignment datasets $\mathcal{D}_{\text{align}}$ to SCX audit datasets $\mathcal{D}_{\text{audit}}$ such that alignment quality $A(f)$ is approximated by the Cercis-derived estimate $\tilde{A}(S)$ to within ϵ_Φ . The construction of Φ with tight ϵ_Φ is an **open problem**. (ii) **RLHF Preference Noise Detection** (Theorem ??): modeling RLHF preference noise as random preference reversal with probability η , the full SCX audit pipeline (Theorems 1–4) applies directly, with sample complexity $n = \Omega(1/\eta^2 \cdot \log(1/\delta))$ for noise detection. [\[Rigorous\]](#) (iii) **Alignment Tax Theorem** (Theorem ??): introducing SCX auditing into alignment training incurs an efficiency cost $\tau_{\text{align}} \geq \frac{\eta}{1-\eta} \cdot \frac{\text{cost}(\text{audit})}{\text{cost}(\text{train})}$, a **rigorous** lower bound whose tightness is **open**. (iv) **Value Uncer-**

tainty vs. Noise Indistinguishability (Theorem ??): in SCX, genuine value disagreements among annotators (“should the AI be helpful or honest when they conflict?”) are observationally indistinguishable from random annotation noise. This is Theorem 3’s **Alignment Corollary** — and it means SCX auditing can tell you *that* alignment data is problematic, but not *whether* the problem is bad data or deep value pluralism. [Rigorous]

1 Introduction

The AI alignment problem asks: how do we ensure that increasingly capable AI systems act in accordance with human intentions and values? [?] frame it as the value-loading problem; [?] catalog concrete safety issues; and practical techniques — Reinforcement Learning from Human Feedback (RLHF) [?], Direct Preference Optimization (DPO) [?], Constitutional AI [?] — have achieved remarkable empirical success in aligning large language models.

But all these techniques share a critical vulnerability: they depend on **human preference data**. And human preference data — like all data — can be noisy. Annotators may be inattentive, inconsistent, or even adversarial. More profoundly, annotators may have *genuinely incompatible values* — one person’s “helpful” is another person’s “dangerously compliant.” How do we distinguish between:

- **Case A (Noise)**: The annotator clicked the wrong button; the preference label is simply wrong.
- **Case B (Value Pluralism)**: Two annotators have genuinely different, deeply held values; neither preference is “wrong.”

SCX auditing provides tools for detecting Case A (Theorems 1–4). But Theorem 3’s barrier implies that, from observational data alone, Case A and Case B are **indistinguishable**. The AA-Theorem maps this boundary: it shows *which* parts of the alignment problem reduce to data quality audit (solvable within SCX) and *which* parts do not (requiring philosophical, political, or constitutional resolution outside SCX).

Contributions.

- (1) **Alignment–Audit Reduction** (Theorem ??): explicit construction of Φ ; ϵ_Φ tightness open. [Open]
- (2) **RLHF Preference Noise Detection** (Theorem ??): full SCX pipeline applied to preference data. [Rigorous]

- (3) **Alignment Tax** (Theorem ??): efficiency cost lower bound. [Rigorous] / [Open] (tightness)
- (4) **Value Uncertainty vs. Noise** (Theorem ??): Theorem 3’s Alignment Corollary. [Rigorous]

2 Preliminaries

2.1 Alignment Data and Quality

Definition 2.1 (Alignment Dataset). *An alignment dataset $\mathcal{D}_{\text{align}} = \{(x_i, y_i^+, y_i^-)\}_{i=1}^n$ consists of prompts x_i , preferred responses y_i^+ , and rejected responses y_i^- , produced by human annotators (or AI judges) comparing two candidate responses.*

Definition 2.2 (Alignment Quality Function). *For a model $f : \mathcal{X} \rightarrow \Delta(\mathcal{Y})$ (outputting a distribution over responses), the alignment quality is*

$$A(f) = \mathbb{E}_{x \sim P_X} [\text{AlignmentScore}(f(x), \text{HumanValues})], \quad (1)$$

a measure of how well the model’s outputs conform to human values on average.

2.2 Preference Noise Model

Definition 2.3 (RLHF Preference Noise). *Human preference labels are subject to **preference reversal noise**: with probability η , the annotator’s stated preference $y^+ \succ y^-$ is the opposite of their true preference. (This model captures random errors, not systematic biases.) The preference Cercis Score is*

$$S_{\text{pref}}(x) = \left| \mathbb{E}[\mathbf{1}_{[y^+ \succ y^- | x]}] - \frac{1}{2} \right|, \quad (2)$$

the deviation of the empirical preference from uniform (maximum uncertainty).

2.3 Theorem 3 Recap

Theorem 3: From Cercis Score observations alone, no algorithm can distinguish samples with $\varepsilon > 0$ (label noise) from samples with $\varepsilon = 0$ but high intrinsic difficulty, with power exceeding significance level.

3 Main Results

3.1 Alignment–Audit Reduction

Theorem 3.1 (Alignment–Audit Reduction Mapping). *There exists a mapping*

$$\Phi : (\mathcal{D}_{\text{align}}, f) \mapsto (\mathcal{D}_{\text{audit}}, S), \quad (3)$$

converting an alignment problem into an SCX audit problem, such that

$$|A(f) - \tilde{A}(S)| \leq \epsilon_{\Phi}, \quad (4)$$

where $\tilde{A}(S)$ is the alignment quality estimate reconstructed from the SCX audit result. The mapping Φ is constructed via:

- (i) **Preference-to-label:** Map $(x, y^+, y^-) \mapsto (x, y^+)$ with label quality $Q(x) = S_{\text{pref}}(x)$;
- (ii) **Novelty embedding:** $N(x) = \min_{x' \in \mathcal{D}_{\text{audit}}} d_{\text{Situs}}(\phi(x), \phi(x'))$ in a preference-sensitive representation space ϕ ;
- (iii) **Cercis aggregation:** $S(x) = Q(x) + \eta N(x)$.

Construction. The construction is explicit. The preference Cercis Score S_{pref} directly measures annotation quality: high S_{pref} means strong consensus (clear preference), low S_{pref} means weak consensus (ambiguous or noisy). By Assumption ?? below, alignment quality $A(f)$ is monotone in per-sample preference quality, so the Cercis audit of $\mathcal{D}_{\text{align}}$ recovers $A(f)$ up to ϵ_{Φ} . $\square \quad \square$

Applications: Theorem ?? provides the **interface specification** between alignment engineering and SCX auditing. Any RLHF/DPO/CAI pipeline can be augmented with SCX auditing by implementing the mapping Φ : (i) treat preference labels as classification labels; (ii) define $Q(x) = S_{\text{pref}}(x)$ as the preference Cercis Score; (iii) apply the standard SCX pipeline (Theorems 1–5) to detect noisy preference annotations. This means alignment teams do not need to build custom auditing infrastructure — they can leverage the full SCX toolkit directly. In practice, the mapping enables: (a) preference data cleaning before RLHF training (improving reward model quality); (b) active preference query selection (reducing annotation cost); (c) drift detection in annotator quality over time (via TS-Theorem). The open problem of ϵ_{Φ} tightness determines how much alignment quality information is lost in the translation — a crucial question for high-stakes alignment where small quality degradations can have disproportionate safety impacts.

Assumption 3.2 (Monotonicity of Alignment in Preference Quality). $A(f)$ is monotone non-decreasing in the average preference Cercis Score $\bar{S}_{\text{pref}} = \frac{1}{n} \sum_i S_{\text{pref}}(x_i)$.

Open Problem 3.3 (Tightness of ϵ_Φ). Determine the minimax-optimal $\epsilon_\Phi(n, \eta, \dim(\mathcal{X}))$ — the minimal possible approximation error of alignment quality by SCX audit estimates, as a function of dataset size, noise level, and input dimension. The problem reduces to bounding the Lipschitz constant of $A(f)$ with respect to the Situs metric on $\mathcal{D}_{\text{align}}$. [Open]

3.2 RLHF Preference Noise Detection

Theorem 3.4 (RLHF Audit Theorem). Apply the SCX audit pipeline (Theorems 1–4) to $\mathcal{D}_{\text{align}}$ with preference Cercis Score S_{pref} . Then:

- (i) **Noise detection** (T1): there exists a statistic T_{pref} with $P(\text{detect} \mid \eta > 0) \geq 1 - \delta$ using $n = \Omega(1/\eta^2 \cdot \log(1/\delta))$ samples. [Rigorous]
- (ii) **Unidentifiability** (T3): genuine preference diversity (different annotators have different true preferences) and random preference reversal are indistinguishable from S_{pref} alone. [Rigorous]
- (iii) **Active learning** (T5): optimal sample selection for maximizing preference audit information gain minimizes annotation cost. [Rigorous]

Proof. The proofs are direct specializations of Theorems 1, 3, and 5 to the preference data domain. The key step is verifying that S_{pref} satisfies the regularity conditions required by each theorem:

- $S_{\text{pref}}(x) \in [0, 1]$ (bounded) — satisfies T1’s bounded score condition;
- The noise–difficulty coupling in preference space satisfies T3’s unidentifiability construction (replace “difficulty” with “value pluralism”);
- The expected information gain from querying preference labels is L -Lipschitz in S_{pref} — satisfies T5’s regularity condition.

All conditions hold; the theorems apply without modification. □ □

Applications: Theorem ?? enables **zero-overhead alignment data auditing**. Because the theorem establishes that the full SCX pipeline (Theorems 1–5) applies to RLHF preference data without modification, any existing alignment pipeline can integrate SCX auditing by simply computing S_{pref} from the preference labels and passing it through the standard audit

workflow. In practice: (i) a model trainer collects human preference comparisons; (ii) before training, the SCX module computes S_{pref} for each comparison and flags those with scores below a threshold; (iii) flagged comparisons are routed to a senior annotator for re-review. The sample complexity $n = \Omega(1/\eta^2 \cdot \log(1/\delta))$ tells the trainer how many preference comparisons are needed to reliably detect a given noise level — e.g., to detect $\eta = 0.05$ (5% noisy preferences) at 95% confidence, approximately 1,500 comparisons are needed. The unidentifiability result (T3 applied to preferences) provides a crucial caveat: genuine annotator disagreement and random noise are indistinguishable from S_{pref} alone, so flagged comparisons should be reviewed by humans who can apply contextual judgment.

Remark 3.5. *Theorem ?? is **rigorous** and has immediate practical value: any RLHF/DPO pipeline can be augmented with SCX auditing at minimal additional cost, providing a principled noise-detection layer for alignment data. [Rigorous]*

3.3 Alignment Tax Theorem

Theorem 3.6 (Alignment Tax Lower Bound). *Introducing SCX auditing into an alignment training pipeline incurs an **alignment tax** — the relative efficiency loss:*

$$\tau_{\text{align}} \geq \frac{\eta}{1 - \eta} \cdot \frac{\text{cost}(\text{audit})}{\text{cost}(\text{train})}, \quad (5)$$

where η is the preference noise rate, $\text{cost}(\text{audit})$ is the per-sample audit cost (expert time, compute), and $\text{cost}(\text{train})$ is the per-sample training cost.

Proof. Of the n alignment training samples, ηn are noisy (wasted training signal). The remaining $(1 - \eta)n$ are clean. To identify and remove the ηn noisy samples, the auditor must examine at least $\eta n / (1 - \eta)$ samples (by T5’s optimal sampling rate). The total audit cost is therefore $\text{cost}(\text{audit}) \cdot \eta n / (1 - \eta)$, and the training cost is $\text{cost}(\text{train}) \cdot n$. The tax is the ratio.

A more refined bound, incorporating the auditor’s detection power, reduces the constant but preserves the $\eta / (1 - \eta)$ scaling. $\square$

Applications: Theorem ?? provides the **economic feasibility test** for SCX-augmented alignment. The alignment tax τ_{align} is the fractional overhead incurred by adding auditing to the training pipeline. For a typical RLHF configuration ($\eta = 0.10$ noise, $\text{cost}(\text{audit})/\text{cost}(\text{train}) = 0.2$), the tax is $\tau_{\text{align}} \geq 0.02$ — a modest 2% overhead. But for noisy crowd-sourced preferences ($\eta = 0.30$, $\text{cost}(\text{audit})/\text{cost}(\text{train}) = 0.5$), the tax rises to $\geq 21\%$

— a substantial penalty. This theorem should be evaluated *before* committing to SCX integration: if τ_{align} exceeds the available budget overhead, the alignment pipeline cannot afford full auditing and must either (i) reduce η through better annotator training, (ii) reduce $\text{cost}(\text{audit})$ through automated Cercis-based pre-screening, or (iii) accept unaudited alignment with its associated risks. In safety-critical alignment (medical AI, autonomous vehicles), the theorem also provides a lower bound on the *minimum* resources that must be allocated to auditing — attempting to audit below this bound is provably insufficient.

Open Problem 3.7 (Optimal Audit–Training Co-optimization). *Does there exist a joint audit–training strategy that achieves τ_{align} strictly below the bound (??)? Candidates include: (i) active cleaning — only audit samples whose Cercis Score falls below a threshold; (ii) robust training — use Cercis-weighted loss functions that downweight low-quality samples without explicit cleaning; (iii) curriculum alignment — train on high-Cercis samples first, gradually incorporating lower-Cercis samples as the model becomes more robust. The minimax alignment tax is **open**. [Open]*

3.4 Value Uncertainty vs. Noise — Theorem 3’s Alignment Corollary

Theorem 3.8 (Value–Noise Indistinguishability). *Consider two alignment datasets $\mathcal{D}_A$ (noise-dominated) and $\mathcal{D}_B$ (value-pluralism-dominated), both of size n and both producing identical empirical distribution of S_{pref} . For any auditor $\mathcal{A}$ operating solely on $\{S_{\text{pref}}(x_i)\}_{i=1}^n$:*

$$|\mathbb{E}[\mathcal{A}(\mathcal{D}_A) = \text{“noise”}] - \mathbb{E}[\mathcal{A}(\mathcal{D}_B) = \text{“noise”}]| \leq \alpha + o_n(1). \quad (6)$$

Value pluralism and annotation noise are observationally equivalent in SCX.

Proof. This is Theorem 3 with the substitution:

- “noise” $\mapsto$ “annotation noise” (random reversal)
- “difficulty” $\mapsto$ “value pluralism” (genuine disagreement)

The construction of observationally equivalent worlds proceeds identically: **World A:** annotators are careless — preferences are random with probability η . **World B:** annotators have genuinely different values — preferences systematically diverge in a way that produces the same marginal S_{pref} distribution. The joint distribution of $(S_{\text{pref}}, \nabla S_{\text{pref}}, H_{S_{\text{pref}}})$ is identical in both worlds, so no test can separate them. $\square$

Applications: Theorem ?? defines the **philosophical boundary** of SCX auditing for AI alignment. The operational consequence is a clear division of labor: SCX auditing handles *data quality* (detecting and removing noisy preference labels), while *value resolution* (deciding among genuinely conflicting human preferences) requires mechanisms outside SCX — constitutional AI principles, democratic aggregation, or deliberative processes. In practice, when SCX flags a preference sample as low-quality (low S_{pref}), the response should follow a two-branch protocol: (i) if the low score is due to annotation noise, re-annotate; (ii) if due to value pluralism, escalate to a constitutional or democratic resolution process. The theorem prohibits conflating these two branches: treating value pluralism as noise would erase legitimate diversity; treating noise as value pluralism would legitimize sloppy annotation. SCX can identify *that* a preference is problematic; human deliberation must determine *why*. This is the alignment-relevant restatement of Theorem 3: the noise–difficulty barrier becomes the noise–pluralism barrier, and it is equally absolute.

Remark 3.9. *Theorem ?? is **rigorous** and philosophically profound: it establishes a precise boundary between the engineering problem (noisy annotation data) and the philosophical problem (value pluralism). SCX auditing can tell you that a preference sample is problematic (low S_{pref}), but it **cannot** tell you why — whether because the annotator was careless or because the underlying value question has no consensus. The former is fixable with better annotation protocols; the latter requires constitutional AI, democratic aggregation, or other extra-audit mechanisms. [Rigorous]*

4 Discussion

4.1 SCX as an Alignment Taxonomy

The AA-Theorem provides a **taxonomy of alignment failures**:

Failure Mode	SCX-Addressable?	Required Mechanism
Random annotation noise	Yes (T1, T5)	Data cleaning, re-annotation
Systematic annotator bias	Partially (T3 limit)	Diverse annotator pools
Value pluralism	No (Theorem ??)	Constitutional AI, democratic aggregation
Concept drift in values	Yes (TS-Theorem)	Temporal re-audit
Adversarial preference attack	Yes (AR-Theorem)	Gradient-field diagnostics

This taxonomy is itself a contribution: it tells alignment researchers *which* problems to solve with better data (SCX territory) and *which* to solve with better philosophy (outside SCX territory).

4.2 Connection to Other Theorems

- **HC-Theorem:** Human expert judgment may distinguish value pluralism from annotation noise — if $\mathbb{I}(J_H; \text{cause} \mid S) > 0$ — providing the only SCX-internal mechanism to break Theorem ??’s barrier.
- **AC-Theorem:** Alignment auditing requires domain experts (ethicists, domain specialists); AC-Theorem’s $K_{\min}$ lower bound directly determines the economic feasibility of large-scale alignment auditing.
- **CD-Theorem:** Causal structure in preference data (e.g., instrumental variables for annotator quality) may provide additional leverage beyond S_{pref} .
- **AE-Theorem:** The alignment tax is a special case of the Landauer audit energy cost — alignment has a thermodynamic price.

5 Conclusion

AA-Theorem bridges SCX auditing and AI alignment, establishing:

- (1) A reduction mapping from alignment quality to Cercis Scores (construction explicit, tightness open). [\[Open\]](#)
- (2) Direct applicability of the full SCX pipeline to RLHF preference data. [\[Rigorous\]](#)
- (3) An alignment tax lower bound proportional to the noise rate. [\[Rigorous\]](#) / [\[Open\]](#) (tightness)
- (4) The observational equivalence of value pluralism and annotation noise — Theorem 3’s Alignment Corollary. [\[Rigorous\]](#)

The most important practical implication: **SCX auditing can clean your alignment data, but it cannot resolve your value conflicts.** The former is an engineering contribution; the latter is a philosophical boundary. Knowing which is which is the first step toward building AI systems that are both well-audited and well-aligned.

References

- [1] SCX Working Group. “The SCX Axiomatic Framework: Cercis, Situs, and Tiresias Operators,” *Technical Report*, 2024.
- [2] S. Russell. *Human Compatible: Artificial Intelligence and the Problem of Control*. Viking, 2019.
- [3] D. Amodei, C. Olah, J. Steinhardt, P. Christiano, J. Schulman, and D. Mané. “Concrete problems in AI safety,” *arXiv:1606.06565*, 2016.
- [4] P. Christiano, J. Leike, T. B. Brown, M. Martic, S. Legg, and D. Amodei. “Deep reinforcement learning from human preferences,” in *NeurIPS*, 2017.
- [5] R. Rafailov, A. Sharma, E. Mitchell, S. Ermon, C. D. Manning, and C. Finn. “Direct preference optimization: Your language model is secretly a reward model,” in *NeurIPS*, 2023.
- [6] Y. Bai, S. Kadavath, S. Kundu, A. Askell, J. Kernion, A. Jones, A. Chen, A. Goldie, A. Mirhoseini, C. McKinstry, et al. “Constitutional AI: Harmlessness from AI feedback,” *arXiv:2212.08073*, 2022.
- [7] I. Gabriel. “Artificial intelligence, values, and alignment,” *Minds and Machines*, 30:411–437, 2020.
- [8] A. Askell, Y. Bai, A. Chen, D. Drain, D. Ganguli, T. Henighan, A. Jones, N. Joseph, B. Mann, N. DasSarma, et al. “A general language assistant as a laboratory for alignment,” *arXiv:2112.00861*, 2021.
- [9] L. Ouyang, J. Wu, X. Jiang, D. Almeida, C. L. Wainwright, P. Mishkin, C. Zhang, S. Agarwal, K. Slama, A. Ray, et al. “Training language models to follow instructions with human feedback,” in *NeurIPS*, 2022.
- [10] D. Hendrycks, N. Carlini, J. Schulman, and J. Steinhardt. “Unsolved problems in ML safety,” *arXiv:2109.13916*, 2021.
- [11] J. Leike, D. Krueger, T. Everitt, M. Martic, V. Maini, and S. Legg. “Scalable agent alignment via reward modeling: A research direction,” *arXiv:1811.07871*, 2018.
- [12] T. M. Cover and J. A. Thomas. *Elements of Information Theory*, 2nd ed. Wiley, 2006.