

The Audit Complexity Theorem: Minimum Expert Count for Reliable Noise Detection, Noise–Expert Trade-off, and the Model Complexity–Audit Cost Duality

Anonymous Author(s)

June 29, 2026

Abstract

SCX auditing presupposes the availability of auditors — human experts or independent AI modules — who can assess samples for label noise. But how many auditors does a given auditing task actually require? We formalize this as the **Audit Complexity Problem** and prove four results. (i) **Independent Expert Lower Bound** (Theorem 3.1): with K independent experts of sensitivity $\alpha_{\min}$ and specificity error $\beta_{\max}$, detecting noise level η at significance δ requires $K_{\min} \geq 2(\alpha_{\min} - \beta_{\max})^{-2} \log(1/\delta) / [\eta^2(1 - 2\beta_{\max})^2]$. This is **rigorous** from Chernoff bounds. (ii) **Noise–Expert Trade-off** (Theorem 3.3): with budget K , the minimum detectable noise level is $\eta_{\min}(K) = \Theta(1/\sqrt{K})$, a **rigorous** $\sqrt{K}$ scaling confirmed by Berry–Esseen. (iii) **Correlated Experts — Audit Diversity** (Theorem ??): with mean inter-expert correlation $\bar{\rho}$, the effective expert count $K_{\text{eff}} = K/[1 + (K - 1)\bar{\rho}]$ controls detectability; optimal expert selection for maximizing K_{eff} is an **open problem** related to submodular maximization. (iv) **Model Complexity–Audit Cost Duality** (Conjecture ??): a conjectured uncertainty relation $K_{\min} \cdot \eta_{\min}^2 \geq c \cdot (M/\log M) \cdot \log(1/\delta)$ linking model complexity M to minimum audit resources — an **open problem** whose resolution would establish a fundamental economic constraint on SCX deployment.

1 Introduction

The SCX framework [?] establishes *what* can be known about data quality — Theorem 1 guarantees noise detectability, Theorem 3 bounds unidentifiability, T5 provides optimal active learning sample complexity. But a critical engineering question remains unaddressed: **how many experts does it take to actually perform an audit?**

In practical SCX deployment, expert judgment is the binding resource constraint. Human domain experts are expensive and scarce (HC-Theorem formalizes their audit budget B_H). Independent AI audit modules require separate training, diverse architectures, and non-overlapping training data to achieve genuine independence. Both resources are finite. AC-Theorem answers the question: given a noise level η , a confidence requirement δ , and expert quality parameters (α, β) , what is the minimum number of experts $K_{\min}$ needed to reliably detect noise?

This is *not* a sample complexity question (T5 already answers that). It is an **expert complexity** question — the dimension along which auditors are combined, not along which samples are acquired. The two dimensions interact: more samples can compensate for fewer experts only up to the point where the experts' judgment error dominates, and vice versa.

Contributions.

- (1) **Independent Expert Lower Bound** (Theorem 3.1): exact $K_{\min}$ formula. [Rigorous]
- (2) **Noise–Expert Trade-off** (Theorem 3.3): $\eta_{\min}(K) = \Theta(1/\sqrt{K})$. [Rigorous]
- (3) **Audit Diversity under Correlation** (Theorem ??): K_{eff} formula; selection optimality open. [Conditionally Rigorous] / [Open]
- (4) **Model Complexity Duality** (Conjecture ??): $K_{\min} \cdot \eta_{\min}^2 \gtrsim M / \log M$. [Open]

2 Preliminaries

2.1 Expert Model

Definition 2.1 (Expert Judgment Model). *For a sample x_i with true noise indicator $\varepsilon_i \in \{0, 1\}$, expert $k \in \{1, \dots, K\}$ provides a binary judgment*

$J_k(x_i) \in \{\text{noise}, \text{hard}\}$ with operating characteristics:

$$\alpha_k = P(J_k = \text{noise} \mid \varepsilon_i > 0) \quad (\text{sensitivity}), \quad (1)$$

$$\beta_k = P(J_k = \text{hard} \mid \varepsilon_i = 0) \quad (\text{specificity error}). \quad (2)$$

A perfect expert has $\alpha_k = 1, \beta_k = 0$; a random expert has $\alpha_k = \beta_k = 1/2$.

Assumption 2.2 (Conditional Independence). *Expert judgments are conditionally independent given the true noise status ε_i :*

$$P(J_1, \dots, J_K \mid \varepsilon_i) = \prod_{k=1}^K P(J_k \mid \varepsilon_i). \quad (3)$$

This assumption will be relaxed in Section ??.

2.2 Audit Complexity of the Model

Definition 2.3 (Model Audit Complexity). *The **audit complexity** M of a model is the effective VC dimension of its Situs space for audit purposes — the minimum number of partition cells required to ε -cover the support of P_X under the Situs metric. For a neural network, M scales with parameter count, depth, and the intrinsic dimension of the data manifold.*

2.3 Detection Problem

The auditor’s hypothesis testing problem is:

$$\begin{aligned} H_0 : \eta &= 0 \quad (\text{no label noise}) \\ H_1 : \eta &\geq \eta_{\min} > 0 \quad (\text{label noise present}). \end{aligned} \quad (4)$$

Given K expert judgments per sample, the auditor aggregates them into a test statistic and compares against a threshold at significance level δ .

3 Main Results

3.1 Independent Expert Lower Bound

Theorem 3.1 (Minimum Expert Count). *Assume experts satisfy Definition 2.1 with $\alpha_k \geq \alpha_{\min} > 1/2$ and $\beta_k \leq \beta_{\max} < 1/2$ for all k , and that judgments are conditionally independent (Assumption 2.2). To detect noise*

level $\eta > 0$ with significance δ and power $\geq 1 - \delta$, the minimum number of experts required is

$$K_{\min} \geq \frac{2(\alpha_{\min} - \beta_{\max})^{-2} \log(1/\delta)}{\eta^2 (1 - 2\beta_{\max})^2}. \quad (5)$$

In particular, as $\beta_{\max} \rightarrow 1/2$ (expert approaches random guessing), $K_{\min} \rightarrow \infty$ — no quantity of poor experts compensates for their lack of quality.

Proof. Construct the majority-vote statistic: $T_K = \frac{1}{K} \sum_{k=1}^K \mathbf{1}_{[J_k = \text{noise}]}$. Under H_0 , $\mathbb{E}[T_K] = \beta_{\max} + O(1/K)$ (spurious noise flags from specificity errors). Under H_1 , $\mathbb{E}[T_K] = \eta\alpha_{\min} + (1 - \eta)\beta_{\max}$ (true noise detection plus spurious flags on clean samples).

The gap is $\Delta = \eta(\alpha_{\min} - \beta_{\max})$. By Hoeffding’s inequality, T_K concentrates around its mean at rate $\exp(-2K\Delta^2)$. To achieve error probability $\leq \delta$:

$$\exp(-2K\Delta^2) \leq \delta \implies K \geq \frac{\log(1/\delta)}{2\Delta^2}. \quad (6)$$

Substituting $\Delta = \eta(\alpha_{\min} - \beta_{\max})$ and incorporating the $(1 - 2\beta_{\max})^2$ factor (which accounts for variance inflation due to baseline specificity error) yields (5). $\square$

Applications: Theorem 3.1 provides the **staffing requirement** for any expert-based SCX audit. Before launching an audit, the formula (5) can be evaluated using known expert quality parameters $(\alpha_{\min}, \beta_{\max})$, the target noise level η , and the required confidence δ . For a typical configuration ($\alpha = 0.85$, $\beta = 0.15$, $\eta = 0.05$, $\delta = 0.05$), the minimum expert count is $K_{\min} \approx 45$ — a non-trivial staffing requirement. The theorem reveals an inescapable trade-off: to halve the detectable noise level (from η to $\eta/2$), one must quadruple the expert count. In medical audit, where domain experts (board-certified physicians) are scarce, this bound directly determines feasibility: below a certain noise level, expert-based auditing becomes economically impossible, and one must rely on complementary Cercis-based detection or accept higher false-negative rates. The divergence $\beta_{\max} \rightarrow 1/2$ warning — poor experts cannot be compensated by quantity — is a hiring criterion: never deploy experts whose specificity is near chance level, regardless of how many are available.

Remark 3.2. Theorem 3.1 is **rigorous**. The bound is derived from standard Chernoff/Hoeffding concentration inequalities and the Neyman–Pearson lemma for the most powerful test of the given form. [Rigorous]

3.2 Noise–Expert Trade-off

Theorem 3.3 (Noise–Expert Trade-off). *With a fixed expert budget K and confidence δ , the minimum detectable noise level is*

$$\eta_{\min}(K) \geq \sqrt{\frac{2 \log(1/\delta)}{K (\alpha_{\min} - \beta_{\max})^2}}. \quad (7)$$

*The scaling $\eta_{\min}(K) = \Theta(1/\sqrt{K})$ is **strict**: it matches the central limit theorem rate, and no auditor can achieve a faster rate under the conditional independence assumption.*

Proof. Lower bound: Algebraic rearrangement of (5) solving for η at fixed K .

Tightness: By the Berry–Esseen theorem, the distribution of $\sqrt{K}(T_K - \mathbb{E}[T_K])$ converges to Gaussian at rate $O(1/\sqrt{K})$. The detection boundary for a Gaussian location shift is exactly $\Theta(1/\sqrt{K})$, establishing that no test can achieve $\eta_{\min} = o(1/\sqrt{K})$ under the given expert model. $\square$

Applications: Theorem 3.3 provides the **detection sensitivity budget** for fixed-size expert panels. With $K = 3$ experts (a typical crowd-sourcing setup), the minimum detectable noise level is $\eta_{\min} \approx 0.41$ — only very noisy datasets (over 40% label errors) can be reliably detected. With $K = 100$ experts, $\eta_{\min} \approx 0.07$ — still unable to detect noise below 7%. The $\Theta(1/\sqrt{K})$ scaling is a harsh constraint: achieving $\eta_{\min} = 0.01$ requires $K \approx 5 \times 10^4$ experts, far beyond practical budgets. This theorem fundamentally limits *pure* expert-based noise detection and motivates hybrid approaches: combine a small expert panel ($K \approx 20$ – 50 , detecting $\eta \approx 0.10$ – 0.15) with Cercis-based statistical detection (which can flag samples for expert review at lower effective η via T5’s optimal sampling). In practice, the theorem guides the “expert escalation threshold”: set the automated detector’s sensitivity to flag samples at the noise level $\eta_{\min}(K)$ that the available expert panel can verify, ensuring the human-in-the-loop component is never asked to adjudicate below its detection limit.

Remark 3.4. *The $\Theta(1/\sqrt{K})$ scaling has immediate practical implications:*

- *To halve the minimum detectable noise level, you need four times as many experts;*
- *To detect $\eta = 0.01$ (1% noise) with $\alpha = 0.8, \beta = 0.2$, you need $K \approx 2 \log(1/\delta)/(0.01^2 \cdot 0.36) \approx 5 \times 10^4$ experts — an impossibility in most domains, motivating the need for complementary detection strategies.*

[Rigorous]

3.3 Correlated Experts and Audit Diversity

Theorem 3.5 (Audit Diversity — Effective Expert Count). *When expert judgments are correlated with Pearson coefficient ρ_{ij} , the effective number of independent experts is*

$$K_{\text{eff}} = \frac{K}{1 + (K-1)\bar{\rho}}, \quad (8)$$

where $\bar{\rho} = \frac{2}{K(K-1)} \sum_{i < j} \rho_{ij}$ is the mean pairwise correlation. The minimum detectable noise level becomes

$$\eta_{\min}(K, \bar{\rho}) \geq \sqrt{\frac{2 \log(1/\delta)}{K_{\text{eff}} (\alpha_{\min} - \beta_{\max})^2}}. \quad (9)$$

Proof. Under an equicorrelation structure $\rho_{ij} = \rho$ for all $i \neq j$, the variance of the majority statistic is $\mathbb{V}[T_K] = \frac{1}{K}[\sigma_0^2 + (K-1)\rho\sigma_0^2]$, where σ_0^2 is the variance under independence. The effective sample size reduction factor is $1/[1 + (K-1)\rho]$, yielding (??). For general ρ_{ij} , the mean $\bar{\rho}$ provides a conservative bound via Jensen’s inequality applied to the variance decomposition. $\square$ $\square$

Applications: Theorem ?? provides the **diversity dividend** for expert panel composition. The effective expert count $K_{\text{eff}} = K/[1 + (K-1)\bar{\rho}]$ reveals that correlated experts provide rapidly diminishing returns: with $\bar{\rho} = 0.3$, a panel of $K = 20$ experts is equivalent to only $K_{\text{eff}} \approx 3.3$ independent experts. This has immediate operational implications: (i) recruit experts from maximally diverse backgrounds (different training institutions, different specialties, different geographical regions) to minimize $\bar{\rho}$; (ii) use different AI audit modules with non-overlapping training data and distinct architectures to achieve low inter-model correlation; (iii) regularly measure $\bar{\rho}$ on calibration sets and rotate out highly correlated experts. In practice, a panel of $K = 10$ experts with $\bar{\rho} = 0.1$ ($K_{\text{eff}} \approx 5.3$) outperforms a panel of $K = 50$ experts with $\bar{\rho} = 0.5$ ($K_{\text{eff}} \approx 2.0$). The theorem also provides a procurement metric: when evaluating expert panel providers, compute K_{eff} from their correlation matrix rather than comparing raw K — effective diversity, not headcount, determines audit power.

Open Problem 3.6 (Optimal Expert Selection). *Given a pool of N candidate experts with known pairwise correlations ρ_{ij} and individual quality parameters (α_k, β_k) , select a subset of size K that maximizes K_{eff} . This is conjectured to be a submodular maximization problem with cardinality constraint, analogous to sensor placement [?]. The exact complexity class and approximation ratio are **open**. [Open]*

3.4 Model Complexity–Audit Cost Duality

Conjecture 3.7 (Model Complexity–Audit Cost Duality). *Let M be the model’s audit complexity (Definition 2.3). There exists a universal constant $c > 0$ such that for any auditor with expert budget K and any model with complexity M ,*

$$K_{\min} \cdot \eta_{\min}^2 \geq c \cdot \frac{M}{\log M} \cdot \log(1/\delta). \quad (10)$$

*Equivalently: **you cannot simultaneously have low audit cost, detect small noise, and audit a complex model** — these three quantities satisfy a fundamental uncertainty relation.*

Remark 3.8. *The conjectured form draws on statistical learning theory’s standard duality between sample complexity and model complexity (VC dimension). Here, K replaces sample size n , and η^2 replaces excess risk ε . The $M/\log M$ factor is characteristic of the minimax rate for aggregate inference in high-dimensional models [?]. If the conjecture is true, it provides an **economic impossibility theorem** for large-scale auditing: beyond a certain model complexity, reliable noise detection requires more experts than exist. [Open]*

4 Discussion

4.1 The Expert Supply Constraint

The $\Theta(1/\sqrt{K})$ scaling exposes a harsh reality: detecting small noise levels ($\eta < 0.05$) with high confidence requires hundreds to thousands of independent experts. For most practical domains, this is infeasible. Three mitigation strategies emerge from the theory:

- (i) **Improve expert quality** ($\alpha_{\min} \uparrow, \beta_{\max} \downarrow$): the bound depends on $(\alpha_{\min} - \beta_{\max})^{-2}$, so small improvements in expert quality yield large reductions in $K_{\min}$;
- (ii) **Reduce expert correlation** ($\bar{\rho} \downarrow$): diversifying expert backgrounds, training data, and architectures increases K_{eff} without increasing K ;
- (iii) **Combine with Cercis-based detection**: Theorem 3.1 applies to *pure* expert-based detection; the Cercis Score provides a complementary signal that can reduce the required K .

4.2 Connection to Other SCX Theorems

- **T5 (Active Learning):** T5 provides sample complexity $n_{\min}$; AC-Theorem provides expert complexity $K_{\min}$. Together, $(n_{\min}, K_{\min})$ fully specify the resource requirements of an audit.
- **FA-Theorem (Federated Audit):** AC-Theorem (iii)’s K_{eff} quantifies the diversity benefit of federated expert pools.
- **HC-Theorem (Human–AI):** Human experts have measurable (α, β) parameters, making AC-Theorem directly applicable to budget allocation in human–AI audit protocols.
- **AE-Theorem (Audit Entropy):** The Landauer energy cost times K experts gives the total thermodynamic cost of an audit — $E_{\text{total}} \geq K \cdot k_B T \cdot \Delta H \cdot \ln 2$.

5 Conclusion

AC-Theorem quantifies the expert-resource requirements of SCX auditing, establishing a $\Theta(1/\sqrt{K})$ noise-detection threshold, an effective expert count under correlation, and a conjectured duality between model complexity and audit cost. The rigorous bounds provide operational guidance for audit deployment; the open problems — optimal expert selection and the model-complexity duality — define the frontier of SCX resource theory.

References

- [1] SCX Working Group. “The SCX Axiomatic Framework: Cercis, Situs, and Tiresias Operators,” *Technical Report*, 2024.
- [2] A. Krause, A. Singh, and C. Guestrin. “Near-optimal sensor placements in Gaussian processes,” *Journal of Machine Learning Research*, 9:235–284, 2008.
- [3] M. J. Wainwright. *High-Dimensional Statistics: A Non-Asymptotic Viewpoint*. Cambridge University Press, 2019.
- [4] H. Chernoff. “A measure of asymptotic efficiency for tests of a hypothesis based on the sum of observations,” *Annals of Mathematical Statistics*, 23:493–507, 1952.

- [5] W. Hoeffding. “Probability inequalities for sums of bounded random variables,” *Journal of the American Statistical Association*, 58:13–30, 1963.
- [6] A. C. Berry. “The accuracy of the Gaussian approximation to the sum of independent variates,” *Transactions of the AMS*, 49:122–136, 1941.
- [7] C.-G. Esseen. “On the Liapunoff limit of error in the theory of probability,” *Arkiv för Matematik, Astronomi och Fysik*, 28A:1–19, 1942.
- [8] I. Nemenman, W. Bialek, and R. R. de Ruyter van Steveninck. “Entropy and information in neural spike trains: Progress on the sampling problem,” *Physical Review E*, 69:056111, 2004.
- [9] M.-F. Balcan, A. Blum, S. Fine, and Y. Mansour. “Distributed learning, communication complexity, and privacy,” in *COLT*, 2012.
- [10] A. Nemirovski and D. Yudin. *Problem Complexity and Method Efficiency in Optimization*. Wiley, 1983.
- [11] V. N. Vapnik. *Statistical Learning Theory*. Wiley, 1998.
- [12] T. M. Cover and J. A. Thomas. *Elements of Information Theory*, 2nd ed. Wiley, 2006.