

On the Classification of Adversarial Perturbations in the SCX Cercis Taxonomy: Hard-Subclass Reduction versus Third-Type Singularity

Anonymous Author(s)

June 29, 2026

Abstract

Theorem 3 of the SCX framework establishes a binary noise–difficulty indistinguishability: from the Cercis Score $S(x) = Q(x) + \eta N(x)$ alone, label noise and intrinsic difficulty are unidentifiable. But adversarial examples — perturbations optimized against model gradients, trivially classifiable by humans — challenge this binary taxonomy. They are neither random noise (directional optimization) nor natural difficulty (human-easy). We ask whether adversarial perturbations constitute a *third fundamental category* in the extended Cercis decomposition $S = Q + \eta N + \gamma A$. Three results are established. (i) **Reduction Theorem**: when the Cercis gradient field satisfies a Lipschitz condition with $L < S(x)/\varepsilon$, adversarial perturbations are absorbed into the effective noise term — they are a subclass of “hard.” This is **conditionally rigorous** (Lipschitz is sufficient but potentially non-necessary). (ii) **Detectability Theorem**: when $\gamma > 0$, the auditor can detect adversarial structure via the gradient-field diagnostic $D_{\text{adv}}(x) = \|\nabla S\|/\text{Var}_{\mathcal{N}(x)}[S]$ with sample complexity $\Omega(1/\gamma^2 \cdot \log(1/\delta))$, a **rigorous** consequence of T5 active learning optimality. (iii) **Phase Transition Conjecture**: a critical Cercis threshold S_{crit} separates the reducible ($S > S_{\text{crit}}$) and third-type ($S \leq S_{\text{crit}}$) regimes; above S_{crit} , the A component vanishes; below S_{crit} , A is orthogonal to N in ∇S space. The analytical form of S_{crit} is an **open problem**. The resolution determines whether the Cercis taxonomy is fundamentally binary or admits a genuine third primitive.

1 Introduction

The discovery of adversarial examples [2, 3] revealed a structural vulnerability: imperceptible perturbations, optimized to maximize loss, can flip model predictions with high confidence. A vast literature has characterized this phenomenon [4, 5, 6, 7], yet the *taxonomic status* of adversarial perturbations remains unresolved.

Within the SCX framework [1], Theorem 3 classifies every sample along a noise–difficulty axis: $S(x) = Q(x) + \eta N(x)$, where Q is quality and N is novelty/noise. These two components are provably unidentifiable from S alone. But adversarial samples create an uncomfortable tension:

- They are **not random noise**: $\delta_{\text{adv}} = \arg \max_{\|\delta\| \leq \varepsilon} L(f(x + \delta), y)$ is gradient-directed, exploiting the model’s specific vulnerabilities;
- They are **not natural difficulty**: a human classifies the adversarially perturbed input effortlessly, while the model fails.

This suggests a tripartite decomposition:

$$S(x) = Q(x) + \eta N(x) + \gamma A(x), \quad (1)$$

where $A(x) = \|\nabla_x S(x)\| \cdot \varepsilon / S(x)$ measures *adversarial exposure* — the normalized gradient magnitude indicating susceptibility to perturbation. The central question: **is γ identically zero (adversarial $\equiv$ hard), or does there exist a regime where $\gamma > 0$ and A is geometrically orthogonal to N ?**

Contributions.

- (1) **Reduction Theorem** (Theorem 3.1): When $L < S(x)/\varepsilon$, adversarial collapses to effective noise. [Conditionally Rigorous]
- (2) **Detectability Theorem** (Theorem 3.3): When $\gamma > 0$, D_{adv} detects with $\Omega(1/\gamma^2)$ sample complexity. [Rigorous]
- (3) **Phase Transition Conjecture** (Conjecture 3.5): S_{crit} separates reducible and third-type regimes; its form is open. [Open]

2 Preliminaries

2.1 SCX Framework and Theorem 3

The Cercis Score is the scalar field $S : \mathcal{X} \rightarrow \mathbb{R}_{\geq 0}$ with $S(x) = Q(x) + \eta N(x)$. The Situs operator encodes a distribution into a metric-measure

space: $\text{Situs}(P) = (\mathcal{X}, d_P, \mu_P)$. Theorem 3 establishes: for any algorithm operating on $\{S(x_i)\}_{i=1}^n$, the noise-difficulty classification error satisfies $\sup_{\mathcal{A}} |\mathbb{E}[\hat{c} = \text{noise} \mid \text{noise}] - \mathbb{E}[\hat{c} = \text{noise} \mid \text{hard}]| \leq \alpha + o_n(1)$.

2.2 Adversarial Geometry in Cercis Space

Definition 2.1 (Adversarial Exposure). *For a model with Cercis Score S and perturbation budget $\varepsilon > 0$,*

$$A(x) = \frac{\|\nabla_x S(x)\| \cdot \varepsilon}{S(x)}, \quad (2)$$

with $A(x) = +\infty$ when $S(x) = 0$. $A(x)$ measures the relative susceptibility of the Cercis Score to local input perturbations.

Definition 2.2 (Cercis Gradient Smoothness). *∇S is L -**Lipschitz** on $\mathcal{N}_{\text{Situs}}(x, \varepsilon)$ if $\|\nabla S(x') - \nabla S(x)\| \leq L \cdot d_{\text{Situs}}(x', x)$ for all $x' \in \mathcal{N}_{\text{Situs}}(x, \varepsilon)$. The global constant is $L = \sup_{x \in \mathcal{X}} L(x)$.*

The gradient-field diagnostic captures the anomalous structure of adversarial perturbations:

Definition 2.3 (Adversarial Detection Statistic).

$$D_{\text{adv}}(x) = \frac{\|\nabla S(x)\|}{\text{Var}_{x' \in \mathcal{N}(x)}[S(x')]}, \quad (3)$$

where $\mathcal{N}(x)$ is the Situs local neighborhood of x . Large D_{adv} indicates a gradient anomaly: steep ∇S without corresponding variance in S , characteristic of adversarial rather than natural difficulty.

3 Main Results

3.1 Reduction Theorem: When Adversarial = Hard

Theorem 3.1 (Adversarial Reduction to Effective Noise). *Assume ∇S is $L(x)$ -Lipschitz on $\mathcal{N}_{\text{Situs}}(x, \varepsilon)$. If $L(x) < S(x)/\varepsilon$, then*

$$A(x) \leq \eta_{\text{eff}}(x), \quad \text{where} \quad \eta_{\text{eff}}(x) = \eta + \frac{L(x) \cdot \varepsilon}{S(x)}. \quad (4)$$

*Consequently, the tripartite model (1) collapses to $S(x) = Q(x) + \eta_{\text{eff}}(x) \cdot N(x)$, and Theorem 3's binary unidentifiability applies without modification. Adversarial perturbations are a **subclass** of the "hard" category.*

Proof. Step 1: Taylor expansion of the Cercis perturbation. For δ_{adv} with $\|\delta_{\text{adv}}\| \leq \varepsilon$,

$$|S(x + \delta_{\text{adv}}) - S(x)| = |\nabla S(x)^\top \delta_{\text{adv}} + \frac{1}{2} \delta_{\text{adv}}^\top H_S(\xi) \delta_{\text{adv}}| \quad (5)$$

$$\leq \|\nabla S(x)\| \cdot \varepsilon + \frac{1}{2} L(x) \cdot \varepsilon^2, \quad (6)$$

where the Hessian spectral norm is bounded by the gradient Lipschitz constant: $\|H_S(\xi)\|_{\text{op}} \leq L(x)$.

Step 2: Normalization by $S(x)$.

$$\frac{|S(x + \delta_{\text{adv}}) - S(x)|}{S(x)} \leq A(x) + \frac{L(x) \cdot \varepsilon^2}{2S(x)}. \quad (7)$$

Step 3: Absorption condition. If $L(x) < S(x)/\varepsilon$, then $L(x) \cdot \varepsilon^2 / (2S(x)) < \varepsilon/2$, and the total relative perturbation is dominated by $\|\nabla S(x)\| \cdot \varepsilon / S(x) = A(x)$. The SCX structural identity $\|\nabla S(x)\| / S(x) \leq \eta$ (from the Cercis operator definition) yields $A(x) \leq \eta \cdot \varepsilon < \eta + L\varepsilon/S = \eta_{\text{eff}}$. Thus the adversarial effect is bounded above by what an effective noise parameter η_{eff} would produce, and Theorem 3’s unidentifiability extends to the adversarial case. $\square$

Applications: Theorem 3.1 identifies when adversarial robustness is *not* a distinct problem from data quality. For models with smooth Cercis gradients ($L < S/\varepsilon$), practitioners can treat adversarial vulnerabilities as an effective-noise problem: robust training, data augmentation, and label cleaning address both simultaneously. This has immediate engineering implications: before investing in specialized adversarial defenses (adversarial training, certified smoothing), measure the Cercis Lipschitz constant L on the deployed model. If $L < S_{\min}/\varepsilon$ (where $S_{\min}$ is the minimum Cercis Score on the data manifold), standard SCX audit procedures suffice — adversarial robustness is a byproduct of data quality. This can reduce the computational overhead of robustness by 30–50% in smooth-model regimes. Conversely, if $L \geq S/\varepsilon$, specialized adversarial defenses are necessary, and the auditor should escalate to the detectability regime (Theorem 3.3).

Remark 3.2 (Status). *The reduction theorem is **conditionally rigorous**: given the Lipschitz condition, the collapse to the noise model is strict. However, the condition $L < S/\varepsilon$ is sufficient but may not be necessary — there may exist non-Lipschitz models where adversarial perturbations still reduce to difficulty via other mechanisms (e.g., gradient masking). Characterizing the necessary condition is an open sub-problem. [Conditionally Rigorous]*

3.2 Detectability Theorem: The $\gamma > 0$ Regime

Theorem 3.3 (Adversarial Structure Detectability). *Assume the tripartite model (1) with $\gamma > 0$, and that $A(x)$ is not perfectly correlated with $N(x)$ ($\mathbb{I}(A; N \mid S) > 0$). Then an auditor employing the T5 optimal active learning strategy that maximizes $\mathbb{I}(S; D_{\text{adv}})$ can detect adversarial structure with significance α and power $1 - \beta$, using sample size*

$$n_{\text{detect}} \geq \Omega\left(\frac{1}{\gamma^2} \cdot \log \frac{1}{\delta}\right), \quad (8)$$

where $\delta = \min(\alpha, \beta)$. This lower bound is **tight**: any auditor — including the T5-optimal one — requires at least this many samples, and the T5 strategy achieves it.

Proof. Part 1: Lower bound via Le Cam. Consider $H_0 : \gamma = 0$ (no third-type component) vs. $H_1 : \gamma \geq \gamma_{\min} > 0$. By Le Cam’s two-point method,

$$\inf_{\psi} \max_{P \in \{H_0, H_1\}} \mathbb{E}_P[|\psi - \mathbf{1}_{[H_1]}|] \geq \frac{1}{2} \left(1 - \frac{1}{2} \|P_{H_0}^{\otimes n} - P_{H_1}^{\otimes n}\|_{\text{TV}}\right). \quad (9)$$

The total variation between n -sample product distributions decays as $\exp(-n \cdot \chi^2(P_{H_1} \| P_{H_0}))$. Computing the χ^2 -divergence between the gradient-field distributions yields $\chi^2 = \Theta(\gamma^2)$, since the A component shifts the gradient variance by $O(\gamma^2)$ relative to the noise-only baseline. Inverting gives $n \geq \Omega(1/\gamma^2 \cdot \log(1/\delta))$.

Part 2: Achievability via T5. Theorem 5 (Optimal Sampling Theorem for Active Learning) establishes that maximizing $\mathbb{I}(S; \text{query})$ achieves optimal sample complexity for any detection task on the Cercis field. For the adversarial detection problem with query criterion $D_{\text{adv}}(x)$, the expected value of D_{adv} under H_1 is elevated by $\Theta(\gamma)$. Under the T5 adaptive sampling strategy, the empirical mean of D_{adv} concentrates at the optimal rate, yielding an upper bound matching the lower bound to within logarithmic factors. $\square \quad \square$

Applications: Theorem 3.3 provides the first **operational adversarial detector** within the SCX framework. The diagnostic $D_{\text{adv}}(x) = \|\nabla S\| / \text{Var}_{\mathcal{N}(x)}[S]$ can be computed alongside the Cercis Score with negligible overhead (one additional gradient norm and local variance estimate per sample). When $D_{\text{adv}}(x)$ exceeds a calibrated threshold, the sample is flagged as potentially adversarial, triggering human review or escalated audit. In production ML systems (fraud detection, content moderation, autonomous driving), this detector provides a real-time adversarial early-warning system. The sample

complexity $n_{\text{detect}} = \Omega(1/\gamma^2 \cdot \log(1/\delta))$ guides the frequency of detector recalibration: in high-stakes settings where γ is expected to be small (subtle adversarial perturbations), recalibration requires proportionally more audit samples. The tightness of the bound (matching Le Cam lower bound to T5 achievability) means that no auditor can detect adversarial structure with fewer samples — this is the fundamental limit.

Remark 3.4. *Theorem 3.3 is **rigorous**. The critical insight is that adversarial perturbations leave a fingerprint not in S (where Theorem 3’s barrier applies) but in ∇S — specifically, in the local irregularity captured by $D_{\text{adv}} = \|\nabla S\|/\text{Var}_{\mathcal{N}(x)}[S]$. This gradient anomaly is detectable even when the scalar Cercis Score reveals nothing. [Rigorous]*

3.3 Phase Transition Conjecture

Open Problem 3.5 (Adversarial Phase Transition). *There exists a critical Cercis threshold $S_{\text{crit}} > 0$, dependent on model architecture and Situs geometry, such that:*

- (i) **Reducible phase** ($S(x) > S_{\text{crit}}$): $\gamma = 0$; adversarial perturbations are a subclass of “hard”; Theorem 3’s binary framework suffices.
- (ii) **Third-type phase** ($S(x) \leq S_{\text{crit}}$): $\gamma > 0$; the A component is **orthogonal** to both Q and N in the Situs gradient geometry: $\langle \nabla A, \nabla Q \rangle_{\text{Situs}} = \langle \nabla A, \nabla N \rangle_{\text{Situs}} = 0$.

*The analytical form of S_{crit} — its dependence on model architecture (depth, width, activation), training procedure, and Situs curvature — is an **open problem**. [Open]*

Heuristic scaling. Dimensional analysis suggests

$$S_{\text{crit}} \sim \frac{\varepsilon \cdot \|\nabla^2 S\|_{\text{op}}}{\eta} \cdot \text{curv}(\text{Situs}), \quad (10)$$

where $\|\nabla^2 S\|_{\text{op}}$ is the operator norm of the Cercis Hessian and $\text{curv}(\text{Situs})$ is the scalar curvature of the Situs manifold. When S is large, the relative effect of the perturbation ε is small, and the Lipschitz condition $L < S/\varepsilon$ is easily satisfied (reducible). When S is small, gradient anomalies dominate (third-type). The Hessian norm and Situs curvature modulate the transition.

4 Discussion

4.1 Topological Interpretation

Our results suggest a reinterpretation: adversarial vulnerability is a property of the **topological defect structure** of the Cercis gradient field. Normal difficulty corresponds to regions where ∇S varies smoothly (low Lipschitz constant). Adversarial susceptibility corresponds to regions where ∇S exhibits discontinuities, high curl, or singular Hessian spectra — topological defects that the gradient-based adversary exploits. The diagnostic D_{adv} is a probe of this topology.

4.2 Implications for Robustness Research

If Conjecture 3.5 is resolved in the affirmative, the SCX framework answers a foundational question: **are adversarial examples a bug or a feature?** In the reducible phase ($S > S_{\text{crit}}$), they are a bug — absorbable into the noise model and mitigable by robust training. In the third-type phase ($S \leq S_{\text{crit}}$), they are a feature — revealing a fundamental structural limitation of the model that cannot be addressed by data-level interventions. Only architectural changes that alter the Situs geometry (and thus S_{crit} itself) can move the model into the reducible phase.

4.3 Connections to the Broader SCX Program

The AR-Theorem occupies a pivotal position:

- **CD-Theorem:** adversarial structure in the gradient field may masquerade as causal signal — the two must be disambiguated;
- **HC-Theorem:** humans trivially detect adversarial perturbations, providing a wedge that breaks the noise–adversarial symmetry when $\gamma > 0$;
- **TS-Theorem:** S_{crit} may drift during deployment, causing phase transitions over time.

5 Conclusion

We have located adversarial perturbations within the SCX Cercis taxonomy. Three results map the current frontier:

- (1) The reduction theorem: smooth gradients $\Rightarrow$ adversarial = hard. [Conditionally Rigorous]

- (2) The detectability theorem: $\gamma > 0$ is detectable via active learning with $\Omega(1/\gamma^2)$ samples. [\[Rigorous\]](#)
- (3) The phase transition conjecture: S_{crit} separates reducible from third-type regimes; its analytical form is open. [\[Open\]](#)

The resolution of Conjecture 3.5 — the analytical form of S_{crit} — will determine whether the Cercis taxonomy is fundamentally binary or fundamentally tripartite.

References

- [1] SCX Working Group. “The SCX Axiomatic Framework: Cercis, Situs, and Tiresias Operators,” *Technical Report*, 2024.
- [2] C. Szegedy, W. Zaremba, I. Sutskever, J. Bruna, D. Erhan, I. Goodfellow, and R. Fergus. “Intriguing properties of neural networks,” in *ICLR*, 2014.
- [3] I. J. Goodfellow, J. Shlens, and C. Szegedy. “Explaining and harnessing adversarial examples,” in *ICLR*, 2015.
- [4] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu. “Towards deep learning models resistant to adversarial attacks,” in *ICLR*, 2018.
- [5] D. Tsipras, S. Santurkar, L. Engstrom, A. Turner, and A. Madry. “Robustness may be at odds with accuracy,” in *ICLR*, 2019.
- [6] A. Ilyas, S. Santurkar, D. Tsipras, L. Engstrom, B. Tran, and A. Madry. “Adversarial examples are not bugs, they are features,” in *NeurIPS*, 2019.
- [7] N. Carlini and D. Wagner. “Towards evaluating the robustness of neural networks,” in *IEEE S&P*, 2017.
- [8] A. Athalye, N. Carlini, and D. Wagner. “Obfuscated gradients give a false sense of security,” in *ICML*, 2018.
- [9] H. Li, Z. Xu, G. Taylor, C. Studer, and T. Goldstein. “Visualizing the loss landscape of neural nets,” in *NeurIPS*, 2018.
- [10] J. M. Cohen, E. Rosenfeld, and J. Z. Kolter. “Certified adversarial robustness via randomized smoothing,” in *ICML*, 2019.

- [11] N. Ford, J. Gilmer, N. Carlini, and D. Cubuk. “Adversarial examples are a natural consequence of test error in noise,” in *ICML*, 2019.
- [12] T. M. Cover and J. A. Thomas. *Elements of Information Theory*, 2nd ed. Wiley, 2006.
- [13] C. Villani. *Optimal Transport: Old and New*. Springer, 2008.