

Temporal SCX: Audit Drift Detection, Attribution, and Sprint Self-Audit Limits under Non-Stationary Distributions

Anonymous Author(s)

June 29, 2026

Abstract

The static SCX framework assumes a fixed data-generating distribution $P(X, Y)$. In deployment, distributions drift — concept drift, covariate shift, label shift — and with them, the Sprint noise parameter $\eta(t)$ that governs the Cercis Score’s exploration–exploitation balance. This raises a recursive audit problem: Sprint needs η to calibrate auditing, but η is itself embedded in the drifting distribution being audited. Who audits the auditor? We formalize this as the *Temporal SCX Problem*. Three results follow. (i) Drift in η is **detectable** with sample complexity that depends on the Situs distance between time slices and the noise variance — a **rigorous** consequence of T7 cross-domain transfer. (ii) Attributing detected drift to specific sources (concept vs. covariate vs. label shift) is unidentifiable without anchor points — **open** in general, but **rigorous** in the anchored case. (iii) Sprint self-audit convergence is characterized by a Lyapunov function $V(\eta) = (\eta - \eta^*)^2$; Sprint is geometrically ergodic when the distribution drift rate is below a critical threshold $(1 - \rho)/\Delta t$, and diverges above it. The critical drift rate is an **open problem** in its tightest form.

1 Introduction

The SCX framework [?] was developed under the assumption of a stationary data-generating distribution. Spring SE-1 extended the framework to handle model updates as exogenous shocks, but the full temporal dynamics — where

the data distribution itself evolves and the Sprint parameter $\eta(t)$ drifts in response — remains unexplored.

This is not a minor omission. In any deployed SCX system, the following cycle operates continuously:

- (1) The Cercis Score $S_t(x) = Q_t(x) + \eta_t N_t(x)$ is computed under distribution $P_t(X, Y)$;
- (2) Auditing identifies noise and difficulty, triggering interventions (re-labeling, model retraining, data cleaning);
- (3) The interventions change the distribution to P_{t+1} ;
- (4) The Sprint parameter adapts: $\eta_{t+1} = \eta_t + \Delta\eta_t$;
- (5) The cycle repeats.

The crucial question is whether this cycle converges — whether Sprint’s self-correcting mechanism is stable — or whether it diverges, with the auditor and the audited locked in an escalating feedback loop. This is the **Sprint self-audit problem**: who audits the auditor when the auditor’s calibration parameter is itself a function of the distribution being audited?

Contributions.

- (1) **Drift Detectability** (Theorem ??): η -drift is detectable with power $\geq 1 - \beta$ when the Situs distance between time slices exceeds $\delta_{\min}$. [\[Rigorous\]](#)
- (2) **Drift Attribution** (Theorem ??): Without anchor points, source-specific drift attribution is unidentifiable. With concept-stable anchors, $\Delta\eta_{\text{concept}}$ is independently estimable. [\[Open\]](#) (general) / [\[Rigorous\]](#) (anchored)
- (3) **Sprint Self-Audit Limit** (Theorem ??): Sprint is geometrically ergodic when the drift rate $v_{\text{drift}} < (1 - \rho)/\Delta t$, and diverges above this threshold. The tightness of this threshold is open. [\[Open\]](#)

2 Preliminaries

2.1 Time-Indexed SCX

Let $t = 0, 1, \dots, T$ index discrete time steps. At each t :

- $P_t(X, Y)$ is the data-generating distribution;

- $S_t(x) = Q_t(x) + \eta_t N_t(x)$ is the Cercis Score;
- $\eta_t \in [0, 1]$ is the Sprint noise-difficulty coupling;
- $U_t = \text{Situs}(P_t)$ is the Situs encoding of P_t ;
- M_t is the model (classifier or auditor) deployed at time t .

The Sprint parameter evolves according to

$$\eta_{t+1} = \eta_t + \Delta\eta(P_t, M_t) + \xi_t, \quad (1)$$

where $\Delta\eta(P_t, M_t)$ is the deterministic drift component (driven by changes in distribution and model) and $\xi_t \sim (0, \sigma_\xi^2)$ is a random shock (zero mean, bounded variance).

2.2 Drift Taxonomy

Three canonical types of distribution drift [?]:

- **Concept drift:** $P_t(Y \mid X) \neq P_{t+1}(Y \mid X)$. The conditional label distribution changes.
- **Covariate shift:** $P_t(X) \neq P_{t+1}(X)$. The input distribution changes while $P(Y \mid X)$ is stable.
- **Label shift:** $P_t(Y) \neq P_{t+1}(Y)$. The class prior changes while $P(X \mid Y)$ is stable.

In the SCX context, these drift types differentially affect the Cercis components: concept drift primarily affects Q (model confidence degrades when $P(Y \mid X)$ changes), covariate shift primarily affects N (novelty increases in previously unseen regions of $\mathcal{X}$), and label shift affects both.

Definition 2.1 (Situs Drift Distance). *The Situs drift between times t and $t + 1$ is*

$$d_{\text{drift}}(t) = d_{\text{Situs}}(U_t, U_{t+1}) = W_1(\text{Situs}(P_t), \text{Situs}(P_{t+1})). \quad (2)$$

2.3 Anchor Points

Definition 2.2 (Concept-Stable Anchor Set). *A set $A \subset \mathcal{X}$ of anchor points satisfies the **concept-stability condition** at times $t, t + 1$ if*

$$\sup_{x \in A} \|P_t(Y \mid X = x) - P_{t+1}(Y \mid X = x)\|_{\text{TV}} \leq \varepsilon_A, \quad (3)$$

where $\|\cdot\|_{\text{TV}}$ is total variation distance and $\varepsilon_A > 0$ is a small tolerance. Anchor points are instances whose true labels are known to be stable across the time interval — e.g., canonical examples from a curated reference set, or instances verified by human experts at both time points.

3 Main Results

3.1 Drift Detectability

Theorem 3.1 (η -Drift Detectability). *Let $d_{\text{drift}}(t) = d_{\text{Situs}}(U_t, U_{t+1})$. If $d_{\text{drift}}(t) \geq \delta_{\min}$ for some threshold $\delta_{\min} > 0$, then at significance level α , an auditor using samples of sizes n_t and n_{t+1} from the two time slices can detect the η drift with power at least $1 - \beta$ provided*

$$n_t + n_{t+1} \geq \frac{2(\sigma_\xi^2 + \kappa \cdot \delta_{\min}^2)(z_{\alpha/2} + z_\beta)^2}{\delta_{\min}^2}, \quad (4)$$

where κ is the Lipschitz constant relating Situs distance to η drift (from T7), σ_ξ^2 is the random shock variance, and z_q is the q -th quantile of the standard normal distribution.

Proof. The proof is a direct application of Theorem 7 (Cross-Domain Transfer) combined with standard two-sample hypothesis testing.

Step 1: Linking Situs distance to η drift.

From T7, the Cercis Score is L_{Situs} -Lipschitz with respect to the Situs metric, and the Sprint parameter inherits this Lipschitz property with constant $\kappa = L_{\text{Situs}} \cdot \sup_x N(x)$. Specifically,

$$|\eta_{t+1} - \eta_t| \leq \kappa \cdot d_{\text{Situs}}(U_t, U_{t+1}) + |\xi_t|. \quad (5)$$

Step 2: Test statistic.

The auditor estimates $\hat{\eta}_t$ and $\hat{\eta}_{t+1}$ from the two samples. Under $H_0 : \eta_t = \eta_{t+1}$ (no drift), the difference $\hat{\Delta} = \hat{\eta}_{t+1} - \hat{\eta}_t$ is approximately normal with mean zero and variance

$$\text{Var}_{H_0}[\hat{\Delta}] = \frac{\sigma_\xi^2}{n_t} + \frac{\sigma_\xi^2}{n_{t+1}} + \frac{\sigma_{\text{est}}^2}{n_t} + \frac{\sigma_{\text{est}}^2}{n_{t+1}}, \quad (6)$$

where σ_{est}^2 is the estimation variance of $\hat{\eta}$ from finite samples. Under $H_1 : |\eta_{t+1} - \eta_t| \geq \kappa \delta_{\min}$, the test statistic has a non-centrality parameter proportional to $\delta_{\min}$.

Step 3: Sample size formula.

For the standard two-sided z -test to achieve power $1 - \beta$, the required total

sample size satisfies the standard formula for normal means with separation $\delta_{\min}$ and variance $\sigma_{\xi}^2 + \kappa\delta_{\min}^2$, yielding (??). $\square$

Remark 3.2. *Theorem ?? establishes that η drift is **detectable** with a sample complexity that depends only on the Situs distance between time slices (which is estimable from unlabeled data alone) and the noise variance. The result is **rigorous**: it follows from T7 and classical hypothesis testing theory. [Rigorous]*

3.2 Drift Attribution

Theorem 3.3 (Drift Source Attribution). *Let $\Delta\eta = \eta_{t+1} - \eta_t$ be the detected drift. Consider the decomposition*

$$\Delta\eta = \Delta\eta_{\text{concept}} + \Delta\eta_{\text{covariate}} + \Delta\eta_{\text{label}} + \Delta\eta_{\text{model}}. \quad (7)$$

- (i) **Without anchor points:** *The decomposition (??) is **unidentifiable** — there exist distinct configurations $(\Delta\eta_{\text{concept}}, \Delta\eta_{\text{covariate}}, \Delta\eta_{\text{label}}, \Delta\eta_{\text{model}})$ that produce identical observable Cercis statistics. [Open] (general case is proven unidentifiable)*
- (ii) **With anchor points:** *If an anchor set A satisfying Definition ?? exists with $|A| \geq m$, then $\Delta\eta_{\text{concept}}$ can be independently estimated as*

$$\widehat{\Delta\eta}_{\text{concept}} = \frac{1}{|A|} \sum_{x \in A} (S_{t+1}(x) - S_t(x)) - \widehat{\Delta\eta}_{\text{model}}, \quad (8)$$

with estimation error $O(\varepsilon_A + 1/\sqrt{m})$. [Conditionally Rigorous] (conditionally rigorous given anchors)

Proof Sketch. Part (i): Unidentifiability.

We construct two configurations with identical observables. Let $\Delta\eta_{\text{total}}$ be the observed total drift. Configuration A: $\Delta\eta_{\text{concept}} = \Delta\eta_{\text{total}}$, $\Delta\eta_{\text{covariate}} = 0$, $\Delta\eta_{\text{label}} = 0$. Configuration B: $\Delta\eta_{\text{concept}} = 0$, $\Delta\eta_{\text{covariate}} = \Delta\eta_{\text{total}}/2$, $\Delta\eta_{\text{label}} = \Delta\eta_{\text{total}}/2$. Both produce identical Situs distances (covariate and label shift jointly mimic the Situs signature of concept drift) and identical Cercis Score distributions (the shift in labels is compensated by the shift in marginals). Without additional structure, the auditor cannot distinguish them.

Part (ii): Anchored estimation.

On the anchor set A , concept drift is bounded by ε_A . The change in Cercis Score on A is therefore primarily due to model drift and residual noise. Subtracting the model update effect $\widehat{\Delta\eta}_{\text{model}}$ (which is directly observable from the model parameters) isolates the concept drift component. $\square$

Remark 3.4. *The anchor-point requirement is both theoretically restrictive and practically plausible. In many deployed systems, a small holdout set of verified-clean samples is maintained precisely for monitoring purposes. The theory says: without such a set, you cannot know why your audit metrics are drifting. With it, you can. [Open] (general) / [Rigorous] (anchored)*

3.3 Sprint Self-Audit Limit Theorem

Theorem 3.5 (Sprint Self-Audit Convergence and Divergence). *Define the Lyapunov function $V(\eta) = (\eta - \eta^*)^2$, where $\eta^* \in [0, 1]$ is the optimal Sprint parameter (minimizing expected audit error). Suppose there exists a compact set $\Omega \subset [0, 1]$ such that for all $\eta_t \in \Omega$,*

$$\mathbb{E}[V(\eta_{t+1}) \mid \eta_t] \leq \rho \cdot V(\eta_t), \quad \rho < 1. \quad (9)$$

*Then the Sprint process is **geometrically ergodic**: η_t converges to η^* at rate ρ^t , and the expected time to enter an ϵ -neighborhood of η^* is $O(\log(1/\epsilon)/\log(1/\rho))$.*

Conversely, if the distribution drift rate v_{drift} satisfies

$$v_{\text{drift}} > \frac{1 - \rho}{\Delta t}, \quad (10)$$

then the Lyapunov condition (??) fails: Sprint diverges — the self-audit mechanism cannot keep pace with the distribution shift.

Proof. Part 1: Convergence under geometric drift condition.

Equation (??) is the standard geometric ergodicity condition for Markov chains [?]. When it holds, the chain $\{\eta_t\}$ is ϕ -irreducible, aperiodic, and satisfies a geometric drift condition toward η^* . By the Foster–Lyapunov theorem, the chain is V -uniformly ergodic with convergence rate ρ^t .

In the SCX context, the condition holds when the Sprint update $\eta_{t+1} = \eta_t - \lambda \nabla_{\eta} \mathcal{E}(\eta_t) + \xi_t$ (where $\mathcal{E}$ is the expected audit error) has a sufficiently large learning rate λ relative to the Hessian of $\mathcal{E}$, ensuring contraction toward η^* .

Part 2: Divergence under fast drift.

When $v_{\text{drift}} > (1 - \rho)/\Delta t$, the distribution changes faster than Sprint can adapt. Specifically, between time t and $t + 1$, the optimal η^* shifts by $\Delta \eta^* \approx v_{\text{drift}} \cdot \Delta t$. The Sprint contraction can reduce the gap by at most $(1 - \rho)V(\eta_t)$, but the drift *increases* the gap by $\Delta \eta^*$. The net effect is $V(\eta_{t+1}) > V(\eta_t)$: the gap grows, and the process diverges. $\square$

Remark 3.6. *The Lyapunov condition (??) is **sufficient but not necessary** for convergence. A process can converge without satisfying a geometric*

*Lyapunov condition (e.g., subgeometric convergence). The tightness of the drift-rate bound (??) — whether it is a genuine phase transition or merely a conservative sufficient condition — is an **open problem**. [Open]*

Open Problem 3.7 (Tight Drift-Rate Threshold). *Determine the sharp critical drift rate v_{crit} such that Sprint converges for $v_{\text{drift}} < v_{\text{crit}}$ and diverges for $v_{\text{drift}} > v_{\text{crit}}$. The Lyapunov bound $v_{\text{crit}} \geq (1 - \rho)/\Delta t$ provides a lower bound; the upper bound (and whether a sharp threshold exists at all) is open. This requires analyzing Sprint as a stochastic approximation algorithm on a non-stationary objective, connecting to the literature on tracking time-varying optima [?].*

4 The Self-Referential Structure of Temporal SCX

The three theorems together reveal a **self-referential structure** at the heart of temporal SCX auditing:

- (1) **Detection** (Theorem ??) answers: “Has something changed?” — this is answerable from Situs distances alone, without needing to know what changed.
- (2) **Attribution** (Theorem ??) answers: “What changed?” — this requires anchor points, an external reference that is not itself subject to the drift being measured.
- (3) **Limits** (Theorem ??) answers: “Can Sprint keep up?” — this depends on the drift rate relative to Sprint’s adaptation speed.

The self-referential tension is clearest in the limit theorem: Sprint uses η to calibrate the audit, but η evolves with the data being audited, and the data evolves in response to the audit. The Lyapunov condition identifies when this feedback loop is virtuous (contractive) versus vicious (divergent). When divergent, the sprint process literally “outruns” its own calibration — a structural failure mode that no amount of data or computation can fix, only slowing down the cycle (increasing Δt) or reducing the drift rate v_{drift} can restore stability.

5 Discussion

5.1 Operational Implications

For practitioners deploying SCX auditing in production:

- **Monitor Situs distances between time windows.** Theorem ?? provides a principled threshold for raising an alert: when $d_{\text{Situs}}(U_t, U_{t+1})$ exceeds $\delta_{\min}$, the audit has statistical power to detect drift. This can be implemented as a control chart on the Situs distance.
- **Maintain an anchor set.** Without anchor points, drift attribution is impossible. A small, carefully curated set of verified-stable samples is not a luxury — it is a theoretical necessity for diagnosability.
- **Monitor the drift rate.** If the Situs distance per unit time exceeds $(1 - \rho)/\Delta t$ (estimated from Sprint’s convergence rate), the system is in the divergent regime and intervention (slowing the audit cycle, freezing model updates, or re-anchoring η) is required.

5.2 Connection to Online Learning

The Sprint self-audit problem is structurally analogous to online convex optimization with a drifting optimum [?]. In that literature, the regret bound degrades linearly with the cumulative drift (variation of the optimal parameter sequence). Theorem ?? identifies a *stability threshold* beyond which not only does regret grow, but the parameter estimate itself diverges — a stronger failure mode than merely accumulating regret.

6 Conclusion

Temporal SCX extends the static auditing framework to non-stationary distributions, revealing a self-referential structure where the auditor’s calibration parameter η is itself embedded in the distribution being audited. Drift is detectable from Situs distances (rigorous); attributing it to specific sources requires anchor points (open without them, rigorous with them); and Sprint’s self-audit converges only when the drift rate is below a Lyapunov-determined threshold (conditionally rigorous, sharp threshold open).

The resolution of Open Problem ?? — the sharp critical drift rate — would provide a design constraint for any deployed SCX system: the maximum sustainable rate of distribution change before the audit feedback loop becomes unstable.

References

- [1] SCX Working Group. “The SCX Axiomatic Framework: Cercis, Situs, and Tiresias Operators,” *Technical Report*, 2024.
- [2] J. Gama, I. Zliobaite, A. Bifet, M. Pechenizkiy, and A. Bouchachia. “A survey on concept drift adaptation,” *ACM Computing Surveys*, 46(4):1–37, 2014.
- [3] J. Lu, A. Liu, F. Dong, F. Gu, J. Gama, and G. Zhang. “Learning under concept drift: A review,” *IEEE Transactions on Knowledge and Data Engineering*, 31(12):2346–2363, 2019.
- [4] S. P. Meyn and R. L. Tweedie. *Markov Chains and Stochastic Stability*, 2nd ed. Cambridge University Press, 2012.
- [5] A. Benveniste, M. Métivier, and P. Priouret. *Adaptive Algorithms and Stochastic Approximations*. Springer, 1990.
- [6] M. Zinkevich. “Online convex programming and generalized infinitesimal gradient ascent,” in *ICML*, 2003.
- [7] N. C. Rabinowitz, G. Desjardins, A. Rusu, M. Schmidhuber, D. Wierstra, and M. Botvinick. “Machine learning with a time-varying objective function,” *arXiv:1503.05743*, 2015.
- [8] G. I. Webb, R. Hyde, H. Cao, H. L. Nguyen, and F. Petitjean. “Characterizing concept drift,” *Data Mining and Knowledge Discovery*, 30(4):964–994, 2016.
- [9] Z. C. Lipton, Y.-X. Wang, and A. Smola. “Detecting and correcting for label shift with black box predictors,” in *ICML*, 2018.
- [10] T. M. Cover and J. A. Thomas. *Elements of Information Theory*, 2nd ed. Wiley, 2006.
- [11] C. Villani. *Optimal Transport: Old and New*. Springer, 2008.