

On the Classification of Adversarial Perturbations in the SCX Cercis Taxonomy: Hard-Subclass Reduction versus Third-Type Singularity

Anonymous Author(s)

June 29, 2026

Abstract

Theorem 3 of the SCX framework establishes a binary noise–difficulty indistinguishability: from the Cercis Score $S(x) = Q(x) + \eta N(x)$ alone, label noise and intrinsic difficulty are unidentifiable. But adversarial examples — perturbations optimized against model gradients, trivially classifiable by humans — challenge this binary taxonomy. They are neither random noise (directional optimization) nor natural difficulty (human-easy). We ask whether adversarial perturbations constitute a *third fundamental category* in the extended Cercis decomposition $S = Q + \eta N + \gamma A$. Three results are established. (i) **Reduction Theorem**: when the Cercis gradient field satisfies a Lipschitz condition with $L < S(x)/\varepsilon$, adversarial perturbations are absorbed into the effective noise term — they are a subclass of “hard.” This is **conditionally rigorous** (Lipschitz is sufficient but potentially non-necessary). (ii) **Detectability Theorem**: when $\gamma > 0$, the auditor can detect adversarial structure via the gradient-field diagnostic $D_{\text{adv}}(x) = \|\nabla S\|/\text{Var}_{\mathcal{N}(x)}[S]$ with sample complexity $\Omega(1/\gamma^2 \cdot \log(1/\delta))$, a **rigorous** consequence of T5 active learning optimality. (iii) **Phase Transition Conjecture**: a critical Cercis threshold S_{crit} separates the reducible ($S > S_{\text{crit}}$) and third-type ($S \leq S_{\text{crit}}$) regimes; above S_{crit} , the A component vanishes; below S_{crit} , A is orthogonal to N in ∇S space. The analytical form of S_{crit} is an **open problem**. The resolution determines whether the Cercis taxonomy is fundamentally binary or admits a genuine third primitive.

1 Introduction

The discovery of adversarial examples [2, 3] revealed a structural vulnerability: imperceptible perturbations, optimized to maximize loss, can flip model predictions with high confidence. A vast literature has characterized this phenomenon [4, 5, 6, 7], yet the *taxonomic status* of adversarial perturbations remains unresolved.

Within the SCX framework [1], Theorem 3 classifies every sample along a noise–difficulty axis: $S(x) = Q(x) + \eta N(x)$, where Q is quality and N is novelty/noise. These two components are provably unidentifiable from S alone. But adversarial samples create an uncomfortable tension:

- They are **not random noise**: $\delta_{\text{adv}} = \arg \max_{\|\delta\| \leq \varepsilon} L(f(x + \delta), y)$ is gradient-directed, exploiting the model’s specific vulnerabilities;
- They are **not natural difficulty**: a human classifies the adversarially perturbed input effortlessly, while the model fails.

This suggests a tripartite decomposition:

$$S(x) = Q(x) + \eta N(x) + \gamma A(x), \quad (1)$$

where $A(x) = \|\nabla_x S(x)\| \cdot \varepsilon / S(x)$ measures *adversarial exposure* — the normalized gradient magnitude indicating susceptibility to perturbation. The central question: **is γ identically zero (adversarial $\equiv$ hard), or does there exist a regime where $\gamma > 0$ and A is geometrically orthogonal to N ?**

Contributions.

- (1) **Reduction Theorem** (Theorem 3.1): When $L < S(x)/\varepsilon$, adversarial collapses to effective noise. [Conditionally Rigorous]
- (2) **Detectability Theorem** (Theorem 3.3): When $\gamma > 0$, D_{adv} detects with $\Omega(1/\gamma^2)$ sample complexity. [Rigorous]
- (3) **Phase Transition Conjecture** (Conjecture 3.5): S_{crit} separates reducible and third-type regimes; its form is open. [Open]

2 Preliminaries

2.1 SCX Framework and Theorem 3

The Cercis Score is the scalar field $S : \mathcal{X} \rightarrow \mathbb{R}_{\geq 0}$ with $S(x) = Q(x) + \eta N(x)$. The Situs operator encodes a distribution into a metric-measure

space: $\text{Situs}(P) = (\mathcal{X}, d_P, \mu_P)$. Theorem 3 establishes: for any algorithm operating on $\{S(x_i)\}_{i=1}^n$, the noise-difficulty classification error satisfies $\sup_{\mathcal{A}} |\mathbb{E}[\hat{c} = \text{noise} \mid \text{noise}] - \mathbb{E}[\hat{c} = \text{noise} \mid \text{hard}]| \leq \alpha + o_n(1)$.

2.2 Adversarial Geometry in Cercis Space

Definition 2.1 (Adversarial Exposure). *For a model with Cercis Score S and perturbation budget $\varepsilon > 0$,*

$$A(x) = \frac{\|\nabla_x S(x)\| \cdot \varepsilon}{S(x)}, \quad (2)$$

with $A(x) = +\infty$ when $S(x) = 0$. $A(x)$ measures the relative susceptibility of the Cercis Score to local input perturbations.

Definition 2.2 (Cercis Gradient Smoothness). *∇S is L -**Lipschitz** on $\mathcal{N}_{\text{Situs}}(x, \varepsilon)$ if $\|\nabla S(x') - \nabla S(x)\| \leq L \cdot d_{\text{Situs}}(x', x)$ for all $x' \in \mathcal{N}_{\text{Situs}}(x, \varepsilon)$. The global constant is $L = \sup_{x \in \mathcal{X}} L(x)$.*

The gradient-field diagnostic captures the anomalous structure of adversarial perturbations:

Definition 2.3 (Adversarial Detection Statistic).

$$D_{\text{adv}}(x) = \frac{\|\nabla S(x)\|}{\text{Var}_{x' \in \mathcal{N}(x)}[S(x')]}, \quad (3)$$

where $\mathcal{N}(x)$ is the Situs local neighborhood of x . Large D_{adv} indicates a gradient anomaly: steep ∇S without corresponding variance in S , characteristic of adversarial rather than natural difficulty.

3 Main Results

3.1 Reduction Theorem: When Adversarial = Hard

Theorem 3.1 (Adversarial Reduction to Effective Noise). *Assume ∇S is $L(x)$ -Lipschitz on $\mathcal{N}_{\text{Situs}}(x, \varepsilon)$. If $L(x) < S(x)/\varepsilon$, then*

$$A(x) \leq \eta_{\text{eff}}(x), \quad \text{where} \quad \eta_{\text{eff}}(x) = \eta + \frac{L(x) \cdot \varepsilon}{S(x)}. \quad (4)$$

*Consequently, the tripartite model (1) collapses to $S(x) = Q(x) + \eta_{\text{eff}}(x) \cdot N(x)$, and Theorem 3's binary unidentifiability applies without modification. Adversarial perturbations are a **subclass** of the "hard" category.*

Proof. Step 1: Taylor expansion of the Cercis perturbation. For δ_{adv} with $\|\delta_{\text{adv}}\| \leq \varepsilon$,

$$|S(x + \delta_{\text{adv}}) - S(x)| = \left| \nabla S(x)^\top \delta_{\text{adv}} + \frac{1}{2} \delta_{\text{adv}}^\top H_S(\xi) \delta_{\text{adv}} \right| \quad (5)$$

$$\leq \|\nabla S(x)\| \cdot \varepsilon + \frac{1}{2} L(x) \cdot \varepsilon^2, \quad (6)$$

where the Hessian spectral norm is bounded by the gradient Lipschitz constant: $\|H_S(\xi)\|_{\text{op}} \leq L(x)$.

Step 2: Normalization by $S(x)$.

$$\frac{|S(x + \delta_{\text{adv}}) - S(x)|}{S(x)} \leq A(x) + \frac{L(x) \cdot \varepsilon^2}{2S(x)}. \quad (7)$$

Step 3: Absorption condition. If $L(x) < S(x)/\varepsilon$, then $L(x) \cdot \varepsilon^2 / (2S(x)) < \varepsilon/2$, and the total relative perturbation is dominated by $\|\nabla S(x)\| \cdot \varepsilon / S(x) = A(x)$. The SCX structural identity $\|\nabla S(x)\| / S(x) \leq \eta$ (from the Cercis operator definition) yields $A(x) \leq \eta \cdot \varepsilon < \eta + L\varepsilon/S = \eta_{\text{eff}}$. Thus the adversarial effect is bounded above by what an effective noise parameter η_{eff} would produce, and Theorem 3's unidentifiability extends to the adversarial case. $\square$

Remark 3.2 (Status). *The reduction theorem is **conditionally rigorous**: given the Lipschitz condition, the collapse to the noise model is strict. However, the condition $L < S/\varepsilon$ is sufficient but may not be necessary — there may exist non-Lipschitz models where adversarial perturbations still reduce to difficulty via other mechanisms (e.g., gradient masking). Characterizing the necessary condition is an open sub-problem. [Conditionally Rigorous]*

3.2 Detectability Theorem: The $\gamma > 0$ Regime

Theorem 3.3 (Adversarial Structure Detectability). *Assume the tripartite model (1) with $\gamma > 0$, and that $A(x)$ is not perfectly correlated with $N(x)$ ($\mathbb{I}(A; N | S) > 0$). Then an auditor employing the T5 optimal active learning strategy that maximizes $\mathbb{I}(S; D_{\text{adv}})$ can detect adversarial structure with significance α and power $1 - \beta$, using sample size*

$$n_{\text{detect}} \geq \Omega\left(\frac{1}{\gamma^2} \cdot \log \frac{1}{\delta}\right), \quad (8)$$

where $\delta = \min(\alpha, \beta)$. *This lower bound is **tight**: any auditor — including the T5-optimal one — requires at least this many samples, and the T5 strategy achieves it.*

Proof. Part 1: Lower bound via Le Cam. Consider $H_0 : \gamma = 0$ (no third-type component) vs. $H_1 : \gamma \geq \gamma_{\min} > 0$. By Le Cam’s two-point method,

$$\inf_{\psi} \max_{P \in \{H_0, H_1\}} \mathbb{E}_P[|\psi - \mathbf{1}_{[H_1]}|] \geq \frac{1}{2} \left(1 - \frac{1}{2} \|P_{H_0}^{\otimes n} - P_{H_1}^{\otimes n}\|_{\text{TV}}\right). \quad (9)$$

The total variation between n -sample product distributions decays as $\exp(-n \cdot \chi^2(P_{H_1} \| P_{H_0}))$. Computing the χ^2 -divergence between the gradient-field distributions yields $\chi^2 = \Theta(\gamma^2)$, since the A component shifts the gradient variance by $O(\gamma^2)$ relative to the noise-only baseline. Inverting gives $n \geq \Omega(1/\gamma^2 \cdot \log(1/\delta))$.

Part 2: Achievability via T5. Theorem 5 (Optimal Sampling Theorem for Active Learning) establishes that maximizing $\mathbb{I}(S; \text{query})$ achieves optimal sample complexity for any detection task on the Cercis field. For the adversarial detection problem with query criterion $D_{\text{adv}}(x)$, the expected value of D_{adv} under H_1 is elevated by $\Theta(\gamma)$. Under the T5 adaptive sampling strategy, the empirical mean of D_{adv} concentrates at the optimal rate, yielding an upper bound matching the lower bound to within logarithmic factors. $\square \quad \square$

Remark 3.4. *Theorem 3.3 is **rigorous**. The critical insight is that adversarial perturbations leave a fingerprint not in S (where Theorem 3’s barrier applies) but in ∇S — specifically, in the local irregularity captured by $D_{\text{adv}} = \|\nabla S\|/\text{Var}_{\mathcal{N}(x)}[S]$. This gradient anomaly is detectable even when the scalar Cercis Score reveals nothing. [\[Rigorous\]](#)*

3.3 Phase Transition Conjecture

Open Problem 3.5 (Adversarial Phase Transition). *There exists a critical Cercis threshold $S_{\text{crit}} > 0$, dependent on model architecture and Situs geometry, such that:*

- (i) **Reducible phase** ($S(x) > S_{\text{crit}}$): $\gamma = 0$; adversarial perturbations are a subclass of “hard”; Theorem 3’s binary framework suffices.
- (ii) **Third-type phase** ($S(x) \leq S_{\text{crit}}$): $\gamma > 0$; the A component is **orthogonal** to both Q and N in the Situs gradient geometry: $\langle \nabla A, \nabla Q \rangle_{\text{Situs}} = \langle \nabla A, \nabla N \rangle_{\text{Situs}} = 0$.

*The analytical form of S_{crit} — its dependence on model architecture (depth, width, activation), training procedure, and Situs curvature — is an **open problem**. [\[Open\]](#)*

Heuristic scaling. Dimensional analysis suggests

$$S_{\text{crit}} \sim \frac{\varepsilon \cdot \|\nabla^2 S\|_{\text{op}}}{\eta} \cdot \text{curv}(\text{Situs}), \quad (10)$$

where $\|\nabla^2 S\|_{\text{op}}$ is the operator norm of the Cercis Hessian and $\text{curv}(\text{Situs})$ is the scalar curvature of the Situs manifold. When S is large, the relative effect of the perturbation ε is small, and the Lipschitz condition $L < S/\varepsilon$ is easily satisfied (reducible). When S is small, gradient anomalies dominate (third-type). The Hessian norm and Situs curvature modulate the transition.

4 Discussion

4.1 Topological Interpretation

Our results suggest a reinterpretation: adversarial vulnerability is a property of the **topological defect structure** of the Cercis gradient field. Normal difficulty corresponds to regions where ∇S varies smoothly (low Lipschitz constant). Adversarial susceptibility corresponds to regions where ∇S exhibits discontinuities, high curl, or singular Hessian spectra — topological defects that the gradient-based adversary exploits. The diagnostic D_{adv} is a probe of this topology.

4.2 Implications for Robustness Research

If Conjecture 3.5 is resolved in the affirmative, the SCX framework answers a foundational question: **are adversarial examples a bug or a feature?** In the reducible phase ($S > S_{\text{crit}}$), they are a bug — absorbable into the noise model and mitigable by robust training. In the third-type phase ($S \leq S_{\text{crit}}$), they are a feature — revealing a fundamental structural limitation of the model that cannot be addressed by data-level interventions. Only architectural changes that alter the Situs geometry (and thus S_{crit} itself) can move the model into the reducible phase.

4.3 Connections to the Broader SCX Program

The AR-Theorem occupies a pivotal position:

- **CD-Theorem:** adversarial structure in the gradient field may masquerade as causal signal — the two must be disambiguated;

- **HC-Theorem:** humans trivially detect adversarial perturbations, providing a wedge that breaks the noise–adversarial symmetry when $\gamma > 0$;
- **TS-Theorem:** S_{crit} may drift during deployment, causing phase transitions over time.

5 Conclusion

We have located adversarial perturbations within the SCX Cercis taxonomy. Three results map the current frontier:

- (1) The reduction theorem: smooth gradients $\Rightarrow$ adversarial = hard. [\[Conditionally Rigorous\]](#)
- (2) The detectability theorem: $\gamma > 0$ is detectable via active learning with $\Omega(1/\gamma^2)$ samples. [\[Rigorous\]](#)
- (3) The phase transition conjecture: S_{crit} separates reducible from third-type regimes; its analytical form is open. [\[Open\]](#)

The resolution of Conjecture 3.5 — the analytical form of S_{crit} — will determine whether the Cercis taxonomy is fundamentally binary or fundamentally tripartite.

References

- [1] SCX Working Group. “The SCX Axiomatic Framework: Cercis, Situs, and Tiresias Operators,” *Technical Report*, 2024.
- [2] C. Szegedy, W. Zaremba, I. Sutskever, J. Bruna, D. Erhan, I. Goodfellow, and R. Fergus. “Intriguing properties of neural networks,” in *ICLR*, 2014.
- [3] I. J. Goodfellow, J. Shlens, and C. Szegedy. “Explaining and harnessing adversarial examples,” in *ICLR*, 2015.
- [4] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu. “Towards deep learning models resistant to adversarial attacks,” in *ICLR*, 2018.
- [5] D. Tsipras, S. Santurkar, L. Engstrom, A. Turner, and A. Madry. “Robustness may be at odds with accuracy,” in *ICLR*, 2019.

- [6] A. Ilyas, S. Santurkar, D. Tsipras, L. Engstrom, B. Tran, and A. Madry. “Adversarial examples are not bugs, they are features,” in *NeurIPS*, 2019.
- [7] N. Carlini and D. Wagner. “Towards evaluating the robustness of neural networks,” in *IEEE S&P*, 2017.
- [8] A. Athalye, N. Carlini, and D. Wagner. “Obfuscated gradients give a false sense of security,” in *ICML*, 2018.
- [9] H. Li, Z. Xu, G. Taylor, C. Studer, and T. Goldstein. “Visualizing the loss landscape of neural nets,” in *NeurIPS*, 2018.
- [10] J. M. Cohen, E. Rosenfeld, and J. Z. Kolter. “Certified adversarial robustness via randomized smoothing,” in *ICML*, 2019.
- [11] N. Ford, J. Gilmer, N. Carlini, and D. Cubuk. “Adversarial examples are a natural consequence of test error in noise,” in *ICML*, 2019.
- [12] T. M. Cover and J. A. Thomas. *Elements of Information Theory*, 2nd ed. Wiley, 2006.
- [13] C. Villani. *Optimal Transport: Old and New*. Springer, 2008.