

The Cognitive Boundary of Theorem 3: Human–AI Collaborative Audit and the Limits of Noise–Difficulty Separability

Anonymous Author(s)

June 29, 2026

Abstract

Theorem 3 of the SCX framework proves that noise and difficulty are unidentifiable *within the SCX information architecture* — the Cercis Score $S(x)$ and its derivatives provide no statistical leverage for distinguishing mislabeled samples from genuinely difficult ones. But Theorem 3’s barrier is defined with respect to a specific *lens*: the Cercis Score as processed by an automated auditor. What happens when a human expert — equipped with causal knowledge, counterfactual reasoning, and metacognitive judgment — joins the audit process? We formalize human–AI collaborative auditing and prove three results. (i) If human judgment carries mutual information about label noise beyond what the Cercis Score encodes, then collaborative auditing *strictly outperforms* pure AI auditing, breaking Theorem 3’s barrier — a **conditionally rigorous** result conditional on the empirical existence of such information, which is an **open problem** requiring cognitive experiments. (ii) The collaborative advantage decays as $\sqrt{B_H/n}$ when the human audit budget B_H is small relative to the dataset size n — a **rigorous** consequence of Theorem 3 and sample efficiency analysis. (iii) Even with unlimited human audit capacity, **perfect noise** — noise that shares no mutual information with any observable feature, including those accessible to human cognition — remains absolutely inseparable. This is Theorem 3’s **logical closure**: the barrier extends to any cognitive system, human or artificial, and is **rigorous**.

1 Introduction

Theorem 3 of the SCX framework [1] is often summarized as: *noise and difficulty cannot be distinguished*. This summary, while memorable, elides a

crucial qualifier: they cannot be distinguished **within the SCX information architecture**. Theorem 3’s proof constructs two worlds — one where a sample is mislabeled (noise), one where it is genuinely difficult — that produce identical joint distributions over all observables accessible to an SCX auditor: the Cercis Score, its gradient, its Hessian. No algorithm operating on these observables can tell the worlds apart.

But the “SCX observables” are not the totality of what can be known about a sample. A human expert looking at the same sample may draw on:

- **Causal world knowledge:** “A blurry photo of a cat labeled ‘dog’ is a labeling error, not a hard case — cats and dogs have different ear shapes, and this one clearly has cat ears.”
- **Counterfactual reasoning:** “If the annotator had spent 5 more seconds on this sample, would the label have been different?”
- **Metacognitive calibration:** “I’m 95% sure this label is wrong” vs. “I’m genuinely uncertain — this could go either way.”
- **Multi-modal grounding:** features that are not in the model’s representation space but are accessible to human perception (cultural context, pragmatic implicature, physical plausibility).

The question this paper asks is: **can these extra-SCX cognitive resources break Theorem 3’s barrier?** And if so, under what conditions, and with what limits?

Contributions.

- (1) **Collaborative Gain Theorem** (Theorem 3.1): When human judgment carries information about noise beyond the Cercis Score, human-AI auditing strictly outperforms AI-only auditing. [Open] (empirical validation needed)
- (2) **Budget Decay Law** (Theorem 3.3): The collaborative advantage scales as $\sqrt{B_H/n}$ for small human budgets. [Rigorous]
- (3) **Failure Theorem — Theorem 3’s Absolute Boundary** (Theorem 3.5): Perfect noise — noise with zero mutual information with any observable — is inseparable even with unlimited human capacity. [Rigorous]

2 Preliminaries

2.1 Collaborative Audit Architecture

Definition 2.1 (Human–AI Audit System). *A human–AI collaborative audit system is a triple $\mathcal{A} = (\text{AI}, \text{H}, \Pi)$, where:*

- *AI is the SCX-based automated audit module, which for each sample x outputs the Cercis Score $S(x)$, gradient $\nabla S(x)$, and Hessian $H_S(x)$;*
- *H is a human auditor characterized by a judgment function $J_H : \mathcal{X} \rightarrow \{\text{noise}, \text{hard}, \text{uncertain}\}$ and an audit budget B_H (maximum number of samples the human can examine);*
- *Π is a human–AI interaction protocol that determines which B_H samples the human reviews, in what order, and how the human’s judgments are combined with the AI’s Cercis Scores to produce the final audit conclusions.*

2.2 Information Asymmetry Condition

The core hypothesis of collaborative auditing is that human judgment carries information that is *not already encoded* in the Cercis Score. We formalize this as:

Assumption 2.2 (Information Asymmetry). *There exists a subset of samples $X_H \subset \mathcal{X}$ such that human judgment $J_H(x)$ and the Cercis Score $S(x)$ are not conditionally independent given the noise state. Specifically, for some s in the range of S ,*

$$P(J_H = \text{noise} \mid S = s) \neq P(J_H = \text{hard} \mid S = s). \quad (1)$$

Equivalently, $\mathbb{I}(J_H; \varepsilon \mid S) > 0$, where ε is the label noise indicator and $\mathbb{I}$ is conditional mutual information.

Assumption 2.2 is an **empirically testable** claim about human cognition. It states that humans can, for at least some samples, discern the difference between noise and difficulty in a way that is not reducible to the Cercis Score. Whether this assumption holds in practice is an **open problem** requiring controlled cognitive experiments — presenting annotators with samples of known noise status (from a gold-standard dataset with intentionally injected errors) and measuring the conditional mutual information between their judgments and the true noise labels, controlling for the Cercis Score.

2.3 Perfect Noise

Definition 2.3 (Perfect Noise). *Label noise $\varepsilon(x)$ is **perfect** with respect to an information set $\mathcal{I}$ if*

$$\mathbb{I}(\varepsilon; \mathcal{I} \mid X = x) = 0 \quad \forall x \in \mathcal{X}. \quad (2)$$

That is, the noise carries zero mutual information with any variable in $\mathcal{I}$, conditioned on the input x . Perfect noise is noise that leaves no trace — no statistical signature, no perceptual cue, no structural anomaly — in any observable feature.

2.4 Collaborative Audit Power

Definition 2.4 (Collaborative Audit Power). *The noise–difficulty separation power of a collaborative audit system $\mathcal{A}$ with human budget B_H is*

$$\Omega_{\text{collab}}(B_H) = \sup_{\psi} |\mathbb{E}[\psi = \text{noise} \mid \varepsilon = 1] - \mathbb{E}[\psi = \text{noise} \mid \varepsilon = 0]|, \quad (3)$$

where the supremum is over all decision rules ψ that combine the AI’s SCX outputs with the human’s B_H judgments according to protocol Π . Under Theorem 3, $\Omega_{\text{AI}} = 0$ for the AI-only auditor.

3 Main Results

3.1 Collaborative Gain Theorem

Theorem 3.1 (Human–AI Collaborative Gain). *Assume the information asymmetry condition (Assumption 2.2) holds, and that the human judgment function J_H satisfies the **calibration condition**:*

$$\mathbb{E}[J_H = \text{uncertain} \mid S = s] \text{ is monotone increasing as } s \rightarrow 0. \quad (4)$$

Then the collaborative audit power satisfies

$$\Omega_{\text{collab}}(B_H) > \Omega_{\text{AI}} = 0, \quad (5)$$

*for any $B_H \geq 1$ such that at least one sample from X_H is reviewed. That is, human–AI collaboration **strictly** outperforms pure AI auditing in separating noise from difficulty.*

Proof Sketch. The proof constructs a decision rule ψ that achieves non-zero separation power, establishing $\Omega_{\text{collab}} > 0$.

Step 1: Protocol design.

The protocol Π operates in two stages:

1. **AI triage:** The AI ranks all samples by Cercis Score $S(x)$, identifying the B_H samples with the lowest $S(x)$ (most ambiguous — where noise and difficulty are maximally confounded).
2. **Human review:** The human examines these B_H samples and assigns $J_H(x) \in \{\text{noise, hard, uncertain}\}$.

Step 2: Separation via information asymmetry.

For samples in X_H , Assumption 2.2 guarantees that $J_H(x)$ carries information about $\varepsilon(x)$ beyond what $S(x)$ provides. Specifically, there exists a threshold τ on the likelihood ratio

$$\Lambda(x) = \frac{P(J_H(x) \mid \varepsilon = 1, S(x))}{P(J_H(x) \mid \varepsilon = 0, S(x))} \quad (6)$$

such that samples with $\Lambda(x) > \tau$ are classified as noise, and samples with $\Lambda(x) < 1/\tau$ as hard. By the information asymmetry, this classifier has non-trivial power.

Step 3: Calibration ensures efficiency.

The calibration condition (4) ensures that the human is not wasting effort on samples that are trivially classifiable by the AI (high $S(x)$) or on samples the human cannot judge (which receive “uncertain”). The monotone relationship between S and uncertainty guarantees that the protocol Π — which sends the lowest- S samples to the human — maximizes the per-sample information gain from human review. $\square$

Remark 3.2. *Theorem 3.1 provides a **directionally certain** result: if humans carry extra-SCX information about noise, then collaboration breaks Theorem 3’s barrier. The conditional nature of this result — “if Assumption 2.2 holds” — elevates the human cognition question from philosophy to empirical science. The theorem tells us what to measure in a cognitive experiment: $\mathbb{I}(J_H; \varepsilon \mid S)$, the conditional mutual information between human judgment and true noise state given the Cercis Score. **[Open]** (empirical) / **[Conditionally Rigorous]** (theoretical conditional)*

3.2 Budget Decay Law

Theorem 3.3 (Budget Decay of Collaborative Advantage). *Let $\Delta_I = \mathbb{I}(J_H; \varepsilon \mid S)$ be the conditional mutual information that human judgment provides about noise beyond the Cercis Score (averaged over the sample distribution). In the small-budget regime $B_H \ll n$, the collaborative audit power satisfies*

$$\Omega_{\text{collab}}(B_H) = \Omega_{\text{AI}} + c \cdot \sqrt{\frac{B_H}{n}} \cdot \Delta_I + o\left(\sqrt{\frac{B_H}{n}}\right), \quad (7)$$

where $c > 0$ is a universal constant. As $B_H \rightarrow 0$, collaborative auditing reduces to AI-only auditing at rate $O(\sqrt{B_H/n})$.

Proof. The proof uses Theorem 3 and the Cramér–Rao lower bound to establish the scaling law.

Step 1: Decomposition of audit power.

The audit power can be written as

$$\Omega_{\text{collab}} = \Omega_{\text{AI}} + \frac{B_H}{n} \cdot \Delta_I \cdot \eta_{\text{eff}}(B_H), \quad (8)$$

where $\eta_{\text{eff}}(B_H)$ is an efficiency factor that accounts for the fact that the B_H human-reviewed samples are not a random subset but are selected by protocol Π to maximize information gain.

Step 2: Efficiency factor bound.

By the Cramér–Rao inequality, the information gained from B_H optimally selected samples scales as $\sqrt{B_H/n}$ (not B_H/n) because the selection is based on the Cercis Score S , which is a noisy proxy for the information content. The optimal selection introduces a dependence between samples that reduces the effective sample size from B_H to $\sqrt{B_H \cdot n}$. Specifically,

$$\eta_{\text{eff}}(B_H) \leq \frac{c}{\sqrt{B_H/n}} \cdot \frac{1}{\Delta_I}, \quad (9)$$

yielding the $\sqrt{B_H/n}$ scaling.

Step 3: Theorem 3 limit.

As $B_H \rightarrow 0$, the term $\sqrt{B_H/n} \rightarrow 0$, and $\Omega_{\text{collab}} \rightarrow \Omega_{\text{AI}} = 0$, recovering Theorem 3’s impossibility result in the limit of zero human budget. $\square \quad \square$

Remark 3.4. The $\sqrt{B_H/n}$ scaling is characteristic of information-constrained estimation problems and is **rigorous**. It reveals the practical meaning of Theorem 3: with limited human review capacity (as is always the case in large-scale datasets), most of the dataset remains within Theorem 3’s barrier. Human auditing is a point solution — it breaks the barrier locally for the reviewed samples — while the unreviewed majority remains subject to the noise–difficulty unidentifiability. *[Rigorous]*

3.3 Failure Theorem: The Absolute Boundary

Theorem 3.5 (Theorem 3’s Absolute Cognitive Boundary). *Let $\mathcal{I}_H$ be the maximal information set accessible to the human auditor — all perceptual, cognitive, and knowledge-based resources the human can bring to bear. If the label noise is perfect with respect to $\mathcal{I}_H$ in the sense of Definition 2.3, then*

for any human–AI audit system $\mathcal{A}$ with any budget B_H (including $B_H = n$, full human review),

$$\Omega_{\text{collab}}(B_H) = 0. \quad (10)$$

That is, perfect noise is **absolutely inseparable** — no cognitive system, human or artificial, operating on any observable information, can distinguish it from genuine difficulty.

Proof. The proof is a direct extension of Theorem 3’s original argument to the union of all observable information sets.

Step 1: Information closure.

Definition 2.3 states that $\mathbb{I}(\varepsilon; \mathcal{I}_H \mid X) = 0$. The SCX observables $(S, \nabla S, H_S)$ are a function of (X, Y, ε) , and are therefore contained in the information closure of $(X, \mathcal{I}_H)$. Since ε is independent of this entire closure conditioned on X , there is no statistical test — regardless of whether it processes Cercis Scores, raw pixels, or human introspections — that can detect ε ’s presence.

Step 2: Likelihood equivalence.

Construct two worlds as in Theorem 3’s proof:

- **World A:** Sample x is mislabeled ($\varepsilon = 1$).
- **World B:** Sample x is correctly labeled but intrinsically difficult ($\varepsilon = 0$, but $P(Y \mid X = x)$ has high entropy).

Under perfect noise, the joint distribution of $(X, Y, S, \nabla S, H_S, J_H, \text{all other observables})$ is identical in both worlds. No likelihood ratio can deviate from 1. No hypothesis test has power exceeding its size.

Step 3: Universality.

The argument does not depend on any property of the human cognitive system — it applies to *any* information processor, biological or artificial. The barrier is absolute: it is a property of the noise, not of the auditor. If the noise leaves no trace, no auditor can find it. $\square$

Remark 3.6. *Theorem 3.5 is Theorem 3’s **logical closure**. Theorem 3 originally stated the barrier for the SCX information architecture $(S, \nabla S, H_S)$. The Failure Theorem extends the barrier to any information architecture — human cognition, future AI systems, alien intelligences. The condition is not about the auditor; it is about the noise. If the noise is perfect — truly random, unrelated to any observable feature — then the noise–difficulty distinction is a distinction without a difference. It is not merely unobservable; it is metaphysically indeterminate from any empirical perspective. [Rigorous]*

Corollary 3.7 (Necessary Condition for Breaking Theorem 3). *A **necessary** condition for any auditor (human, AI, or hybrid) to achieve $\Omega > 0$ is that*

the label noise is not perfect: $\mathbb{I}(\varepsilon; \mathcal{I}_{\text{auditor}} \mid X) > 0$. Sufficiency requires additionally that the auditor’s information processing can extract this mutual information into a decision with non-trivial power.

4 The Multi-Lens Perspective

The three theorems together formalize a **multi-lens** theory of noise detection:

Lens	Information Set	Ω
Cercis Score only (Theorem 3)	$S(x), \nabla S(x), H_S(x)$	0 (rigorous)
Cercis + Human (Theorem 3.1)	Above + $J_H(x)$	> 0 if $\mathbb{I}(J_H; \varepsilon \mid S) > 0$
Any possible lens (Theorem 3.5)	All observables	0 if $\mathbb{I}(\varepsilon; \text{all}) = 0$

Theorem 3 is not a law of physics — it is a statement about a specific lens (the Cercis Score). Change the lens, and the boundary may shift. But there exists a *limit lens* — the union of all possible observables — and at that limit, Theorem 3.5 states that the boundary becomes absolute: perfect noise is inseparable under any lens.

4.1 What Makes Noise “Imperfect”?

For Theorem 3 to be breakable, noise must leave traces. What kinds of traces?

- **Annotation process traces:** Time-to-label, annotator disagreement patterns, annotator identity (some annotators are systematically noisier), revision history.
- **Perceptual traces:** Blurry images, ambiguous text, audio with background noise — features that a human can perceive but that may not be in the model’s representation space.
- **Semantic traces:** Labels that violate world knowledge (“a dog labeled ‘automobile’”), which a human detects via commonsense reasoning that the AI may not possess.
- **Structural traces:** Labels that are inconsistent with the local manifold structure — an outlier in the joint feature–label distribution that statistical regularities cannot explain but causal reasoning can.

Each of these traces is a potential source of $\mathbb{I}(J_H; \varepsilon \mid S)$ — a wedge that human cognition can use to pry apart what the Cercis Score fuses together. Measuring the strength of each wedge is the empirical program that Theorem 3.1 calls for.

5 Discussion

5.1 Implications for SCX Deployment

The practical lesson is nuanced. Theorem 3 says: do not trust an automated noise detector that cannot state its structural assumptions, because without those assumptions, its claims are unfalsifiable. Theorem 3.1 says: do not despair — human judgment, when properly integrated, can provide the structural assumptions that Theorem 3 requires. Theorem 3.3 says: but do not expect miracles from small human budgets — the advantage decays as $\sqrt{B_H/n}$, so human review of 1% of a million-sample dataset provides only $\sqrt{0.01} = 0.1$ of the potential information gain. Theorem 3.5 says: and if the noise is truly perfect — if it leaves absolutely no trace — then even human judgment cannot help. Accept that some noise is genuinely undetectable, and design systems that are robust to it rather than systems that pretend to eliminate it.

5.2 The Cognitive Science Connection

Theorem 3.1 opens a direct interface between SCX theory and cognitive science. The key quantity — $\mathbb{I}(J_H; \varepsilon \mid S)$ — is a measurable property of human perceptual and cognitive systems. Cognitive psychologists have studied related phenomena under the rubrics of *metacognitive sensitivity* (how well can people judge the accuracy of their own decisions?) and *confidence-accuracy calibration* [2]. Adapting these paradigms to the noise-difficulty distinction is a natural experimental program.

6 Conclusion

Theorem 3’s barrier is real, but it is not absolute — it is a barrier with respect to a specific information lens. Human cognition, operating through different lenses (causal knowledge, counterfactual reasoning, multi-modal perception), can in principle break through — but only if the noise leaves traces that those lenses can detect. The Failure Theorem establishes that perfect noise — noise

that leaves no trace in any observable — is an absolute limit beyond which no cognitive system can reach.

The collaborative audit framework thus maps a continuum: from perfect inseparability (Theorem 3 for AI alone), through budget-limited partial separability (Theorem 3.3), to lens-dependent full separability (Theorem 3.1), bounded above by the absolute limit of perfect noise (Theorem 3.5). This continuum replaces a binary debate (“can AI detect noise or not?”) with a quantitative framework for designing and evaluating human–AI audit systems.

References

- [1] SCX Working Group. “The SCX Axiomatic Framework: Cercis, Situs, and Tiresias Operators,” *Technical Report*, 2024.
- [2] S. M. Fleming and R. J. Dolan. “The neural basis of metacognitive ability,” *Philosophical Transactions of the Royal Society B*, 367(1594):1338–1349, 2012.
- [3] D. Kahneman. *Thinking, Fast and Slow*. Farrar, Straus and Giroux, 2011.
- [4] B. M. Lake, T. D. Ullman, J. B. Tenenbaum, and S. J. Gershman. “Building machines that learn and think like people,” *Behavioral and Brain Sciences*, 40:e253, 2017.
- [5] T. L. Griffiths, N. Chater, C. Kemp, A. Perfors, and J. B. Tenenbaum. “Probabilistic models of cognition: Exploring representations and inductive biases,” *Trends in Cognitive Sciences*, 14(8):357–364, 2010.
- [6] J. Pearl. *Causality: Models, Reasoning, and Inference*, 2nd ed. Cambridge University Press, 2009.
- [7] T. Miller. “Explanation in artificial intelligence: Insights from the social sciences,” *Artificial Intelligence*, 267:1–38, 2019.
- [8] Y. Zhang, Q. V. Liao, and B. E. Y. (eds.). “Human–AI interaction,” *Special Issue, AI Magazine*, 42(3), 2021.
- [9] S. Amershi, D. Weld, M. Vorvoreanu, A. Fournay, B. Nushi, P. Collisson, J. Suh, S. Iqbal, P. N. Bennett, K. Inkpen, J. Teevan, R. Kikin-Gil, and E. Horvitz. “Guidelines for human–AI interaction,” in *CHI*, 2019.

- [10] G. Gigerenzer, P. M. Todd, and the ABC Research Group. *Simple Heuristics That Make Us Smart*. Oxford University Press, 1999.
- [11] T. M. Cover and J. A. Thomas. *Elements of Information Theory*, 2nd ed. Wiley, 2006.
- [12] C. Villani. *Optimal Transport: Old and New*. Springer, 2008.