

Getting started

Clone the repository, start your agent in it, and ask.

1 Clone it

```
git clone  
https://github.com/shuds13/AgentLab
```

2 Start your agent in it

```
cd AgentLab && claude
```

3 Say

"Help me set up."

What you need

- Claude Agent SDK, and an LLM service it can reach
- Python 3.10+, and the claude CLI on PATH and authenticated
- Access to a compute system, and a project to charge

Where to run

- Preferably a shared persistent node, so the team reaches the same campaigns
- Inside tmux. A campaign runs for hours or days, and closing the terminal kills it with jobs still in flight

AGENTS.md in the repository root is the onboarding script — the agent reads it and walks you through the rest.

Tutorial

Three things.

- 1 Install and run the simple example
- 2 Run with Globus Compute
- 3 Add Slack integration

1 Install and run the simple example

Start your agent harness and say “Help me set up.”

The agent installs what's missing

`claude-agent-sdk`, `globus-compute-sdk`

Then run it, with a watch

```
cd campaigns/example-quick-optimum/  
WATCH=true AGENT_MODEL=haiku ./run.sh
```

Click on the watch URL to get an interactive view of the workspace

*If you do not specify AGENT_MODEL it uses your default Claude Code model.
This is a toy example — the smartest model is not needed.*

User and campaign directories

What you keep once, and what each campaign holds.

`users/<user_id>`

- For each remote system — Endpoint UUID / Account / Work-dir

Campaign dir files

<code>prompt.md</code>	The overall challenge / campaign.
<code>method.md</code>	Describes research cycles (defaults to <code>methods/standard.md</code>).
<code>user_prompt.md</code>	Instructions and goal for this run of the agent.
<code>task.py</code>	Task or tasks to run locally or on remote system.
<code>campaign.json</code>	task run settings.
<code>run.sh</code>	Setting and starts agent.

user_prompt.md is most likely to be modified between agent runs in an ongoing campaign.

2(a) Run with Globus Compute

Set the endpoint up on the remote node.

Use a remote endpoint on a GCE node

- no scheduler / no queue
- You will need to ssh to the node — check it is not too busy
- FQDN (e.g. compute-386-03.cels.anl.gov)

On compute-386-03:

```
python3 -m venv ~/gc_env
source ~/gc_env/bin/activate
pip install globus-compute-endpoint
globus-compute-endpoint configure agentlab
```

Laptop — copy the endpoint:

```
scp systems/endpoints/no_scheduler/user_config_template.yaml.j2 compute-386-03.cels.anl.gov:.globus_compute/agentlab/
```

The agent can do this for you, once it has the FQDN.

2(b) Run with Globus Compute

Start the endpoint, then start the campaign.

You start it and authenticate with Globus Compute (interactive)

On compute-386-03:

```
globus-compute-endpoint start agentlab --detach  
globus-compute-endpoint list
```

list gives you the endpoint UUID

Once the detached endpoint is running, the ssh connection is no longer needed.

Then on your own machine

- Agent uses the UUID and puts your personal config under users/<user_id>

On the laptop, users/<you>/gce.json:

```
{"endpoint": "<uuid from list>",  
  "work_dir": "/home/<you>/agentlab-work"}
```

Note the work_dir field is required for remote machines, but not used in this case as no files created.

Laptop:

```
WATCH=true AGENT_MODEL=haiku ./run_remote.sh
```

The quick test does not produce files on the remote machine.

3 Add Slack integration

Notifications one way, or talk to the agents.

Please join the AgentLab Slack workspace.

https://join.slack.com/t/agentlab-co/shared_invite/zt-47fcg5wpv-PnypDIKMB3TYBUZNJitwqA

- Create a new channel in the workspace — you will point your app at this channel

link expires...

Ask your agent (in AgentLab repo) to help setup slack.

- It will take you through the process
- Choose: setting up new lab
- You can set up notifications only, or 2-way comms.

Create a slack app for any workspace — some may require approval.

- Approval request happens in the process.

Note to allow messaging Agent from slack:

OAuth scopes: channels:history → public channel, groups:history → private channel.

Your agent should set up a lab.yaml. You can then start the slack bridge with

```
bin/lab.sh start
```