shuert®


LEADERS IN RESUABLE TRANSPORT PACKAGING


uni-pak II











Uni-Pak® II

70” x 48.5” | Space Saver

As the original sleeve-pack system introduced to the market—setting the standard for many of today’s designs—Uni-Pak is a reusable, collapsible container system designed for storage and transport in closed-loop systems. Engineered for operations where space constraints, return efficiency, and product protection are critical, it provides a systems-based alternative to wood pallets, corrugated boxes, fiber drums, nylon bags, and other limited-life returnable packaging.

Type	Construction	Market	Interior Demensions		Pallet Weight	Cover Weight	Outbound		Return		Ratio	
			L	W			2 High	3 High	2 High	3 High	2 High	3 High
Uni-Pak	Twinsheet	North American	67.315”	46.29”	35.75lbs	23.8lbs	36	54	296	296	1:8.2	1:5.5

* Tolerances are available upon request **Load capacity may vary +/- depending on the nature of the load, stacking confi guration, and handling method

Multiple Footprints
A design that is available in multiple footprint sizes, accommodating varying product dimensions and handling requirements.

Nestable
A design that allows units to partially fit within one another when empty, reducing storage volume and improving warehouse utilization and return ratio.

Locators
An interlocking feature in which female details on the pallet engage corresponding male features on the cover, enabling two containers to stack securely while maintaining alignment and load stability.

Collapsible
A structure capable of folding down quickly for efficient return and storage without full disassembly, improving warehouse utilization and increasing return ratio.

Slidelock (and Uni-Klip)
A locking mechanism that enables fast, tool-free assembly and disassembly—one container, one person, one minute—by securing the sleeve within the track of the pallet and cover.

Tube-cut (straight sleeve)
A sleeve design with a straight-cut bottom edge that interfaces directly with the pallet track.

The contents of this publication are presented for general informational purposes only. Technical data are guideline values based on experience and tests under defined conditions. The data may vary based on intended use, product features, raw materials used and environmental influences. Nothing in this document shall be construed as warranties or guarantees, express or implied, regarding the products or their use, application, performance or otherwise. Upon request our sales team will confirm the data requiredfor your individual application.